
Classes et membres de la référence

ACCESS

Microsoft Access X.X Object Library

GUID : {4AFFC9A0-5F99-101B-AF4E-00AA003F0F07}

Source : **Projet collaboratif d'étude des références de Microsoft ACCESS**

Origine : WWW.DEVELOPPEZ.COM

Forum : ACCESS -> Contribuez

Auteur : [PhilBen]

Membres : [Kikof], [Dolphy35], [Starec],
[Jean-Paul LePetit], [Boulap]

Remerciements : [Cafeine], [Papy Turbo], [Tofalu]

Version PDF : 1.0

Les versions étudiées de la référence ACCESS

Fichier : **MSACC9.OLB**
Version ext. : **9.0** *Version int.* : **9.0**
Fichier d'Aide : **ACMAIN9.CHM**
Version Office : **2000 [00]**

Nb de classes : **99** *Nb de Membres* : **3040**

Fichier : **MSACC.OLB**
Version ext. : **10.0** *Version int.* : **9.0**
Fichier d'Aide : **VBAAC10.CHM**
Version Office : **2002 [02]**

Nb de classes : **119** *Nb de Membres* : **3530**

Fichier : **MSACC.OLB**
Version ext. : **11.0** *Version int.* : **9.0**
Fichier d'Aide : **VBAAC10.CHM**
Version Office : **2003 [03]**

Nb de classes : **128** *Nb de Membres* : **3515**

Fichier : **MSACC.OLB**
Versions ext. : **12.0** *Versions int.* : **9.0**
Fichier d'Aide : **VBAAC10.CHM**
Version Office : **2007 [07]**

Nb de classes : **152** *Nb de Membres* : **4241**

Classes et membres de la référence ACCESS

Classe de membres : AccessField (Type : Classe) 00 02 03 07 *

- Property Get/Let Value As Variant	Non		Non	
-------------------------------------	-----	--	-----	--

Classe de membres : AccessObject (Type : Dispatch) 00 02 03 07 *

- Property Get CurrentView As AcCurrentView	Non			
- Property Get DateCreated As Date	Non			
- Property Get DateModified As Date	Non			
- Property Get FullName As String		Non	Non	Non
- Property Get/Let FullName As String	Non			
- Function GetDependencyInfo () As DependencyInfo	Non	Non		
- Function IsDependentUpon (ObjectType As AcObjectType, ObjectName As String) As Boolean	Non	Non		
- Property Get IsLoaded As Boolean				
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get Properties As AccessObjectProperties				
- Property Get Type As Long		Non	Non	Non
- Property Get Type As AcObjectType	Non			

Classe de membres : AccessObjectProperties (Type : Dispatch) 00 02 03 07 *

- Sub Add (PropertyName As String, Value As Variant)				
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As AccessObjectProperty				
- Property Get Parent As Object				
- Sub Remove (Item As Variant)				

Classe de membres : AccessObjectProperty (Type : Dispatch) 00 02 03 07 *

- Property Get Name As String				
- Property Get/Let Value As Variant				

Classe de membres : AcCloseSave (Type : Enum) 00 02 03 07 *

- Const acSaveNo = 2 (&H2) As Long				
- Const acSavePrompt = 0 (&H0) As Long				
- Const acSaveYes = 1 (&H1) As Long				

Classe de membres : AcColorIndex (Type : Enum) 00 02 03 07 *

- Const acColorIndexAqua = 14 (&HE) As Long				
- Const acColorIndexBlack = 0 (&H0) As Long				
- Const acColorIndexBlue = 12 (&HC) As Long				
- Const acColorIndexBrightGreen = 10 (&HA) As Long				
- Const acColorIndexDarkBlue = 4 (&H4) As Long				
- Const acColorIndexFuschia = 13 (&HD) As Long				
- Const acColorIndexGray = 7 (&H7) As Long				
- Const acColorIndexGreen = 2 (&H2) As Long				
- Const acColorIndexMaroon = 1 (&H1) As Long				
- Const acColorIndexOlive = 3 (&H3) As Long				
- Const acColorIndexRed = 9 (&H9) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcColorIndex (Type : Enum)</i>	00	02	03	07 *
- Const acColorIndexSilver = 8 (&H8) As Long				
- Const acColorIndexTeal = 6 (&H6) As Long				
- Const acColorIndexViolet = 5 (&H5) As Long				
- Const acColorIndexWhite = 15 (&HF) As Long				
- Const acColorIndexYellow = 11 (&HB) As Long				

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdAboutMicrosoftAccess = 35 (&H23) As Long				
- Const acCmdAddFromOutlook = 583 (&H247) As Long	Non	Non	Non	
- Const acCmdAddInManager = 526 (&H20E) As Long	Non			
- Const acCmdAddToNewGroup = 494 (&H1EE) As Long	Non			
- Const acCmdAddWatch = 201 (&HC9) As Long				
- Const acCmdAdvancedFilterSort = 99 (&H63) As Long				
- Const acCmdAlignBottom = 46 (&H2E) As Long				
- Const acCmdAlignCenter = 477 (&H1DD) As Long	Non			
- Const acCmdAlignLeft = 43 (&H2B) As Long				
- Const acCmdAlignmentAndSizing = 478 (&H1DE) As Long	Non			
- Const acCmdAlignMiddle = 476 (&H1DC) As Long	Non			
- Const acCmdAlignRight = 44 (&H2C) As Long				
- Const acCmdAlignToGrid = 47 (&H2F) As Long				
- Const acCmdAlignTop = 45 (&H2D) As Long				
- Const acCmdAlignToShortest = 153 (&H99) As Long				
- Const acCmdAlignToTallest = 154 (&H9A) As Long				
- Const acCmdAnalyzePerformance = 283 (&H11B) As Long				
- Const acCmdAnalyzeTable = 284 (&H11C) As Long				
- Const acCmdAnchorBottomLeft = 616 (&H268) As Long	Non	Non	Non	
- Const acCmdAnchorBottomRight = 618 (&H26A) As Long	Non	Non	Non	
- Const acCmdAnchorBottomStretchAcross = 617 (&H269) As Long	Non	Non	Non	
- Const acCmdAnchorStretchAcross = 611 (&H263) As Long	Non	Non	Non	
- Const acCmdAnchorStretchDown = 613 (&H265) As Long	Non	Non	Non	
- Const acCmdAnchorStretchDownAcross = 614 (&H266) As Long	Non	Non	Non	
- Const acCmdAnchorStretchDownRight = 615 (&H267) As Long	Non	Non	Non	
- Const acCmdAnchorTopLeft = 610 (&H262) As Long	Non	Non	Non	
- Const acCmdAnchorTopRight = 612 (&H264) As Long	Non	Non	Non	
- Const acCmdAnswerWizard = 235 (&HEB) As Long				
- Const acCmdApplyAutoFormat1 = 648 (&H288) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat10 = 657 (&H291) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat11 = 658 (&H292) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat12 = 659 (&H293) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat13 = 660 (&H294) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat14 = 661 (&H295) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat15 = 662 (&H296) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat16 = 663 (&H297) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat17 = 664 (&H298) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat18 = 665 (&H299) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat19 = 666 (&H29A) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdApplyAutoFormat2 = 649 (&H289) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat20 = 667 (&H29B) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat21 = 668 (&H29C) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat22 = 669 (&H29D) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat23 = 670 (&H29E) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat24 = 671 (&H29F) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat25 = 672 (&H2A0) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat3 = 650 (&H28A) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat4 = 651 (&H28B) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat5 = 652 (&H28C) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat6 = 653 (&H28D) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat7 = 654 (&H28E) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat8 = 655 (&H28F) As Long	Non	Non	Non	
- Const acCmdApplyAutoFormat9 = 656 (&H290) As Long	Non	Non	Non	
- Const acCmdApplyDefault = 55 (&H37) As Long				
- Const acCmdApplyFilterSort = 93 (&H5D) As Long				
- Const acCmdAppMaximize = 10 (&HA) As Long				
- Const acCmdAppMinimize = 11 (&HB) As Long				
- Const acCmdAppMove = 12 (&HC) As Long				
- Const acCmdAppRestore = 9 (&H9) As Long				
- Const acCmdAppSize = 13 (&HD) As Long				
- Const acCmdArrangelconsAuto = 218 (&HDA) As Long				
- Const acCmdArrangelconsByCreated = 216 (&HD8) As Long				
- Const acCmdArrangelconsByModified = 217 (&HD9) As Long				
- Const acCmdArrangelconsByName = 214 (&HD6) As Long				
- Const acCmdArrangelconsByType = 215 (&HD7) As Long				
- Const acCmdAutoCorrect = 261 (&H105) As Long				
- Const acCmdAutoDial = 192 (&HC0) As Long				
- Const acCmdAutoFormat = 270 (&H10E) As Long				
- Const acCmdBackgroundPicture = 474 (&H1DA) As Long	Non			
- Const acCmdBackgroundSound = 475 (&H1DB) As Long	Non			
- Const acCmdBackup = 513 (&H201) As Long	Non			
- Const acCmdBookmarksClearAll = 310 (&H136) As Long				
- Const acCmdBookmarksNext = 308 (&H134) As Long				
- Const acCmdBookmarksPrevious = 309 (&H135) As Long				
- Const acCmdBookmarksToggle = 307 (&H133) As Long				
- Const acCmdBringToFront = 52 (&H34) As Long				
- Const acCmdBrowseSharePointList = 621 (&H26D) As Long	Non	Non	Non	
- Const acCmdCallStack = 172 (&HAC) As Long				
- Const acCmdChangeToCheckBox = 231 (&HE7) As Long				
- Const acCmdChangeToComboBox = 230 (&HE6) As Long				
- Const acCmdChangeToCommandButton = 501 (&H1F5) As Long	Non			
- Const acCmdChangeToImage = 234 (&HEA) As Long				
- Const acCmdChangeToLabel = 228 (&HE4) As Long				
- Const acCmdChangeToListBox = 229 (&HE5) As Long				

Classes et membres de la référence ACCESS

Classe de membres : AcCommand (Type : Enum)

	00	02	03	07 *
- Const acCmdChangeToOptionButton = 233 (&HE9) As Long				
- Const acCmdChangeToTextBox = 227 (&HE3) As Long				
- Const acCmdChangeToToggleButton = 232 (&HE8) As Long				
- Const acCmdClearAll = 146 (&H92) As Long				
- Const acCmdClearAllBreakpoints = 132 (&H84) As Long				
- Const acCmdClearGrid = 71 (&H47) As Long				
- Const acCmdClearHyperlink = 343 (&H157) As Long				
- Const acCmdClearItemDefaults = 237 (&HED) As Long				
- Const acCmdClose = 58 (&H3A) As Long				
- Const acCmdCloseAll = 646 (&H286) As Long	Non	Non	Non	
- Const acCmdCloseDatabase = 538 (&H21A) As Long	Non	Non	Non	
- Const acCmdCloseWindow = 186 (&HBA) As Long				
- Const acCmdCollectDataViaEmail = 608 (&H260) As Long	Non	Non	Non	
- Const acCmdColumnWidth = 117 (&H75) As Long				
- Const acCmdCompactDatabase = 4 (&H4) As Long				
- Const acCmdCompileAllModules = 125 (&H7D) As Long				
- Const acCmdCompileAndSaveAllModules = 126 (&H7E) As Long				
- Const acCmdCompileLoadedModules = 290 (&H122) As Long				
- Const acCmdCompleteWord = 306 (&H132) As Long				
- Const acCmdConditionalFormatting = 500 (&H1F4) As Long	Non			
- Const acCmdConnection = 383 (&H17F) As Long				
- Const acCmdControlMarginsMedium = 630 (&H276) As Long	Non	Non	Non	
- Const acCmdControlMarginsNarrow = 629 (&H275) As Long	Non	Non	Non	
- Const acCmdControlMarginsNone = 628 (&H274) As Long	Non	Non	Non	
- Const acCmdControlMarginsWide = 631 (&H277) As Long	Non	Non	Non	
- Const acCmdControlPaddingMedium = 634 (&H27A) As Long	Non	Non	Non	
- Const acCmdControlPaddingNarrow = 633 (&H279) As Long	Non	Non	Non	
- Const acCmdControlPaddingNone = 632 (&H278) As Long	Non	Non	Non	
- Const acCmdControlPaddingWide = 635 (&H27B) As Long	Non	Non	Non	
- Const acCmdControlWizardsToggle = 197 (&HC5) As Long				
- Const acCmdConvertDatabase = 171 (&HAB) As Long				
- Const acCmdConvertMacrosToVisualBasic = 279 (&H117) As Long				
- Const acCmdCopy = 190 (&HBE) As Long				
- Const acCmdCopyDatabaseFile = 516 (&H204) As Long	Non			
- Const acCmdCopyHyperlink = 328 (&H148) As Long				
- Const acCmdCreateMenuFromMacro = 334 (&H14E) As Long				
- Const acCmdCreateRelationship = 150 (&H96) As Long				
- Const acCmdCreateReplica = 263 (&H107) As Long				
- Const acCmdCreateShortcut = 219 (&HDB) As Long				
- Const acCmdCreateShortcutMenuFromMacro = 336 (&H150) As Long				
- Const acCmdCreateToolbarFromMacro = 335 (&H14F) As Long				
- Const acCmdCut = 189 (&HBD) As Long				
- Const acCmdDataAccessPageAddToPage = 480 (&H1E0) As Long	Non			Non
- Const acCmdDataAccessPageBrowse = 344 (&H158) As Long				Non
- Const acCmdDataAccessPageDesignView = 385 (&H181) As Long				Non

Classes et membres de la référence ACCESS

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdDataAccessPageFieldListRefresh = 479 (&H1DF) As Long	Non			Non
- Const acCmdDatabaseProperties = 256 (&H100) As Long				
- Const acCmdDatabaseSplitter = 520 (&H208) As Long	Non			
- Const acCmdDataEntry = 78 (&H4E) As Long				
- Const acCmdDataOutline = 468 (&H1D4) As Long	Non			
- Const acCmdDatasheetView = 282 (&H11A) As Long				
- Const acCmdDateAndTime = 226 (&HE2) As Long				
- Const acCmdDebugWindow = 123 (&H7B) As Long				
- Const acCmdDelete = 337 (&H151) As Long				
- Const acCmdDeleteGroup = 493 (&H1ED) As Long	Non			
- Const acCmdDeletePage = 332 (&H14C) As Long				
- Const acCmdDeleteQueryColumn = 81 (&H51) As Long				
- Const acCmdDeleteRecord = 223 (&HDF) As Long				
- Const acCmdDeleteRows = 188 (&HBC) As Long				
- Const acCmdDeleteSharePointList = 627 (&H273) As Long	Non	Non	Non	
- Const acCmdDeleteTab = 255 (&HFF) As Long				
- Const acCmdDeleteTable = 489 (&H1E9) As Long	Non			
- Const acCmdDeleteTableColumn = 271 (&H10F) As Long				
- Const acCmdDeleteWatch = 267 (&H10B) As Long				
- Const acCmdDemote = 388 (&H184) As Long				Non
- Const acCmdDesignView = 183 (&HB7) As Long				
- Const acCmdDiagramAddRelatedTables = 373 (&H175) As Long				
- Const acCmdDiagramAutosizeSelectedTables = 378 (&H17A) As Long				
- Const acCmdDiagramDeleteRelationship = 382 (&H17E) As Long				
- Const acCmdDiagramLayoutDiagram = 380 (&H17C) As Long				
- Const acCmdDiagramLayoutSelection = 379 (&H17B) As Long				
- Const acCmdDiagramModifyUserDefinedView = 375 (&H177) As Long				
- Const acCmdDiagramNewLabel = 372 (&H174) As Long				
- Const acCmdDiagramNewTable = 381 (&H17D) As Long				
- Const acCmdDiagramRecalculatePageBreaks = 377 (&H179) As Long				
- Const acCmdDiagramShowRelationshipLabels = 374 (&H176) As Long				
- Const acCmdDiagramViewPageBreaks = 376 (&H178) As Long				
- Const acCmdDiscardChanges = 639 (&H27F) As Long	Non	Non	Non	
- Const acCmdDiscardChangesAndRefresh = 640 (&H280) As Long	Non	Non	Non	
- Const acCmdDocMaximize = 15 (&HF) As Long				
- Const acCmdDocMinimize = 60 (&H3C) As Long				
- Const acCmdDocMove = 16 (&H10) As Long				
- Const acCmdDocRestore = 14 (&HE) As Long				
- Const acCmdDocSize = 17 (&H11) As Long				
- Const acCmdDocumenter = 285 (&H11D) As Long				
- Const acCmdDropSQLDatabase = 517 (&H205) As Long	Non			
- Const acCmdDuplicate = 34 (&H22) As Long				
- Const acCmdEditHyperlink = 325 (&H145) As Long				
- Const acCmdEditingAllowed = 70 (&H46) As Long				
- Const acCmdEditListItems = 607 (&H25F) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : **AcCommand** (Type : Enum)

	00	02	03	07 *
- Const acCmdEditRelationship = 151 (&H97) As Long				
- Const acCmdEditTriggers = 384 (&H180) As Long				
- Const acCmdEditWatch = 202 (&HCA) As Long				
- Const acCmdEncryptDecryptDatabase = 5 (&H5) As Long				
- Const acCmdEnd = 198 (&HC6) As Long				
- Const acCmdExit = 3 (&H3) As Long				
- Const acCmdExport = 487 (&H1E7) As Long	Non			Non
- Const acCmdExportAccess = 559 (&H22F) As Long	Non	Non	Non	
- Const acCmdExportdBase = 565 (&H235) As Long	Non	Non	Non	
- Const acCmdExportExcel = 556 (&H22C) As Long	Non	Non	Non	
- Const acCmdExportFixedFormat = 592 (&H250) As Long	Non	Non	Non	
- Const acCmdExportHTML = 564 (&H234) As Long	Non	Non	Non	
- Const acCmdExportLotus = 567 (&H237) As Long	Non	Non	Non	
- Const acCmdExportODBC = 562 (&H232) As Long	Non	Non	Non	
- Const acCmdExportParadox = 566 (&H236) As Long	Non	Non	Non	
- Const acCmdExportRTF = 558 (&H22E) As Long	Non	Non	Non	
- Const acCmdExportSharePointList = 557 (&H22D) As Long	Non	Non	Non	
- Const acCmdExportSnapShot = 563 (&H233) As Long	Non	Non	Non	
- Const acCmdExportText = 560 (&H230) As Long	Non	Non	Non	
- Const acCmdExportXML = 561 (&H231) As Long	Non	Non	Non	
- Const acCmdFavoritesAddTo = 299 (&H12B) As Long				
- Const acCmdFavoritesOpen = 298 (&H12A) As Long				
- Const acCmdFieldList = 42 (&H2A) As Long				
- Const acCmdFieldTemplates = 647 (&H287) As Long	Non	Non	Non	
- Const acCmdFilterByForm = 207 (&HCF) As Long				
- Const acCmdFilterBySelection = 208 (&HD0) As Long				
- Const acCmdFilterExcludingSelection = 277 (&H115) As Long				
- Const acCmdFilterMenu = 619 (&H26B) As Long	Non	Non	Non	
- Const acCmdFind = 30 (&H1E) As Long				
- Const acCmdFindNext = 341 (&H155) As Long				
- Const acCmdFindNextWordUnderCursor = 313 (&H139) As Long				
- Const acCmdFindPrevious = 120 (&H78) As Long				
- Const acCmdFindPrevWordUnderCursor = 312 (&H138) As Long				
- Const acCmdFitToWindow = 245 (&HF5) As Long				
- Const acCmdFont = 19 (&H13) As Long				
- Const acCmdFormatCells = 77 (&H4D) As Long				
- Const acCmdFormHdrFtr = 36 (&H24) As Long				
- Const acCmdFormView = 281 (&H119) As Long				
- Const acCmdFreezeColumn = 105 (&H69) As Long				
- Const acCmdGoBack = 294 (&H126) As Long				
- Const acCmdGoContinue = 127 (&H7F) As Long				
- Const acCmdGoForward = 295 (&H127) As Long				
- Const acCmdGroupByTable = 387 (&H183) As Long				
- Const acCmdGroupControls = 484 (&H1E4) As Long	Non			
- Const acCmdHideColumns = 79 (&H4F) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdHideMessageBar = 677 (&H2A5) As Long	Non	Non	Non	
- Const acCmdHidePane = 365 (&H16D) As Long				
- Const acCmdHideTable = 147 (&H93) As Long				
- Const acCmdHorizontalSpacingDecrease = 158 (&H9E) As Long				
- Const acCmdHorizontalSpacingIncrease = 159 (&H9F) As Long				
- Const acCmdHorizontalSpacingMakeEqual = 157 (&H9D) As Long				
- Const acCmdHyperlinkDisplayText = 329 (&H149) As Long				
- Const acCmdImport = 257 (&H101) As Long				Non
- Const acCmdImportAttachAccess = 544 (&H220) As Long	Non	Non	Non	
- Const acCmdImportAttachdBase = 552 (&H228) As Long	Non	Non	Non	
- Const acCmdImportAttachExcel = 545 (&H221) As Long	Non	Non	Non	
- Const acCmdImportAttachHTML = 550 (&H226) As Long	Non	Non	Non	
- Const acCmdImportAttachLotus = 554 (&H22A) As Long	Non	Non	Non	
- Const acCmdImportAttachODBC = 549 (&H225) As Long	Non	Non	Non	
- Const acCmdImportAttachOutlook = 551 (&H227) As Long	Non	Non	Non	
- Const acCmdImportAttachParadox = 553 (&H229) As Long	Non	Non	Non	
- Const acCmdImportAttachSharePointList = 547 (&H223) As Long	Non	Non	Non	
- Const acCmdImportAttachText = 546 (&H222) As Long	Non	Non	Non	
- Const acCmdImportAttachXML = 548 (&H224) As Long	Non	Non	Non	
- Const acCmdIndent = 205 (&HCD) As Long				
- Const acCmdIndexes = 152 (&H98) As Long				
- Const acCmdInsertActiveXControl = 258 (&H102) As Long				
- Const acCmdInsertChart = 293 (&H125) As Long				
- Const acCmdInsertFile = 39 (&H27) As Long				
- Const acCmdInsertFileIntoModule = 118 (&H76) As Long				
- Const acCmdInsertHyperlink = 259 (&H103) As Long				
- Const acCmdInsertLogo = 585 (&H249) As Long	Non	Non	Non	
- Const acCmdInsertLookupColumn = 273 (&H111) As Long				
- Const acCmdInsertLookupField = 291 (&H123) As Long				
- Const acCmdInsertMovieFromFile = 469 (&H1D5) As Long	Non			
- Const acCmdInsertObject = 33 (&H21) As Long				
- Const acCmdInsertPage = 331 (&H14B) As Long				
- Const acCmdInsertPicture = 222 (&HDE) As Long				
- Const acCmdInsertPivotTable = 470 (&H1D6) As Long	Non			
- Const acCmdInsertProcedure = 262 (&H106) As Long				
- Const acCmdInsertQueryColumn = 82 (&H52) As Long				
- Const acCmdInsertRows = 187 (&HBB) As Long				
- Const acCmdInsertSpreadsheet = 471 (&H1D7) As Long	Non			
- Const acCmdInsertSubdatasheet = 499 (&H1F3) As Long	Non			
- Const acCmdInsertTableColumn = 272 (&H110) As Long				
- Const acCmdInsertTitle = 586 (&H24A) As Long	Non	Non	Non	
- Const acCmdInsertUnboundSection = 472 (&H1D8) As Long	Non			
- Const acCmdInvokeBuilder = 178 (&HB2) As Long				
- Const acCmdJoinProperties = 72 (&H48) As Long				
- Const acCmdLastPosition = 339 (&H153) As Long				

Classes et membres de la référence ACCESS

Classe de membres : **AcCommand (Type : Enum)**

	00	02	03	07 *
- Const acCmdLayoutGridlinesBoth = 574 (&H23E) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesBottom = 580 (&H244) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesCrossHatch = 578 (&H242) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesHorizontal = 576 (&H240) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesNone = 577 (&H241) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesOutline = 581 (&H245) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesTop = 579 (&H243) As Long	Non	Non	Non	
- Const acCmdLayoutGridlinesVertical = 575 (&H23F) As Long	Non	Non	Non	
- Const acCmdLayoutPreview = 141 (&H8D) As Long				
- Const acCmdLayoutView = 593 (&H251) As Long	Non	Non	Non	
- Const acCmdLineUplcons = 213 (&HD5) As Long				
- Const acCmdLinkedTableManager = 519 (&H207) As Long	Non			
- Const acCmdLinkTables = 102 (&H66) As Long				
- Const acCmdListConstants = 303 (&H12F) As Long				
- Const acCmdLoadFromQuery = 95 (&H5F) As Long				
- Const acCmdMacroAllActions = 589 (&H24D) As Long	Non	Non	Non	
- Const acCmdMacroArguments = 588 (&H24C) As Long	Non	Non	Non	
- Const acCmdMacroConditions = 87 (&H57) As Long				
- Const acCmdMacroNames = 86 (&H56) As Long				
- Const acCmdMakeMDEFile = 7 (&H7) As Long				
- Const acCmdManageAttachments = 673 (&H2A1) As Long	Non	Non	Non	
- Const acCmdManageReplies = 609 (&H261) As Long	Non	Non	Non	
- Const acCmdMaximiumRecords = 508 (&H1FC) As Long	Non			
- Const acCmdMicrosoftAccessHelpTopics = 100 (&H64) As Long				
- Const acCmdMicrosoftOnTheWeb = 236 (&HEC) As Long				
- Const acCmdMicrosoftScriptEditor = 390 (&H186) As Long				Non
- Const acCmdModifySharePointList = 622 (&H26E) As Long	Non	Non	Non	
- Const acCmdModifySharePointListAlerts = 623 (&H26F) As Long	Non	Non	Non	
- Const acCmdModifySharePointListPermissions = 625 (&H271) As Long	Non	Non	Non	
- Const acCmdModifySharePointListWorkflow = 624 (&H270) As Long	Non	Non	Non	
- Const acCmdMoreWindows = 8 (&H8) As Long				
- Const acCmdMoveColumnCellDown = 573 (&H23D) As Long	Non	Non	Non	
- Const acCmdMoveColumnCellUp = 572 (&H23C) As Long	Non	Non	Non	
- Const acCmdNewDatabase = 26 (&H1A) As Long				
- Const acCmdNewGroup = 491 (&H1EB) As Long	Non			
- Const acCmdNewObjectAutoForm = 193 (&HC1) As Long				
- Const acCmdNewObjectAutoReport = 194 (&HC2) As Long				
- Const acCmdNewObjectBlankForm = 600 (&H258) As Long	Non	Non	Non	
- Const acCmdNewObjectBlankReport = 602 (&H25A) As Long	Non	Non	Non	
- Const acCmdNewObjectClassModule = 140 (&H8C) As Long				
- Const acCmdNewObjectContinuousForm = 594 (&H252) As Long	Non	Non	Non	
- Const acCmdNewObjectDataAccessPage = 346 (&H15A) As Long				Non
- Const acCmdNewObjectDatasheetForm = 598 (&H256) As Long	Non	Non	Non	
- Const acCmdNewObjectDesignForm = 604 (&H25C) As Long	Non	Non	Non	
- Const acCmdNewObjectDesignQuery = 603 (&H25B) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdNewObjectDesignReport = 605 (&H25D) As Long	Non	Non	Non	
- Const acCmdNewObjectDesignTable = 606 (&H25E) As Long	Non	Non	Non	
- Const acCmdNewObjectDiagram = 352 (&H160) As Long				
- Const acCmdNewObjectForm = 136 (&H88) As Long				
- Const acCmdNewObjectFunction = 394 (&H18A) As Long	Non			
- Const acCmdNewObjectLabelsReport = 601 (&H259) As Long	Non	Non	Non	
- Const acCmdNewObjectMacro = 138 (&H8A) As Long				
- Const acCmdNewObjectModalForm = 599 (&H257) As Long	Non	Non	Non	
- Const acCmdNewObjectModule = 139 (&H8B) As Long				
- Const acCmdNewObjectPivotChart = 596 (&H254) As Long	Non	Non	Non	
- Const acCmdNewObjectPivotTable = 597 (&H255) As Long	Non	Non	Non	
- Const acCmdNewObjectQuery = 135 (&H87) As Long				
- Const acCmdNewObjectReport = 137 (&H89) As Long				
- Const acCmdNewObjectSplitForm = 595 (&H253) As Long	Non	Non	Non	
- Const acCmdNewObjectStoredProcedure = 351 (&H15F) As Long				
- Const acCmdNewObjectTable = 134 (&H86) As Long				
- Const acCmdNewObjectView = 350 (&H15E) As Long				
- Const acCmdObjBrwFindWholeWordOnly = 314 (&H13A) As Long				
- Const acCmdObjBrwGroupMembers = 318 (&H13E) As Long				
- Const acCmdObjBrwHelp = 316 (&H13C) As Long				
- Const acCmdObjBrwShowHiddenMembers = 315 (&H13B) As Long				
- Const acCmdObjBrwViewDefinition = 317 (&H13D) As Long				
- Const acCmdObjectBrowser = 200 (&HC8) As Long				
- Const acCmdOfficeClipboard = 488 (&H1E8) As Long	Non			
- Const acCmdOLEDELinks = 27 (&H1B) As Long				
- Const acCmdOLEObjectConvert = 167 (&HA7) As Long				
- Const acCmdOLEObjectDefaultVerb = 57 (&H39) As Long				
- Const acCmdOpenDatabase = 25 (&H19) As Long				
- Const acCmdOpenHyperlink = 326 (&H146) As Long				
- Const acCmdOpenNewHyperlink = 327 (&H147) As Long				
- Const acCmdOpenSearchPage = 253 (&HFD) As Long				
- Const acCmdOpenStartPage = 252 (&HFC) As Long				
- Const acCmdOpenTable = 221 (&HDD) As Long				
- Const acCmdOpenURL = 251 (&HFB) As Long				
- Const acCmdOptions = 49 (&H31) As Long				
- Const acCmdOutdent = 206 (&HCE) As Long				
- Const acCmdOutputToExcel = 175 (&HAF) As Long				
- Const acCmdOutputToRTF = 176 (&HB0) As Long				
- Const acCmdOutputToText = 177 (&HB1) As Long				
- Const acCmdPageHdrFtr = 182 (&HB6) As Long				
- Const acCmdPageNumber = 225 (&HE1) As Long				
- Const acCmdPageProperties = 467 (&H1D3) As Long	Non			
- Const acCmdPageSetup = 32 (&H20) As Long				
- Const acCmdParameterInfo = 305 (&H131) As Long				
- Const acCmdPartialReplicaWizard = 524 (&H20C) As Long	Non			

Classes et membres de la référence ACCESS

Classe de membres : **AcCommand (Type : Enum)**

	00	02	03	07 *
- Const acCmdPaste = 191 (&HBF) As Long				
- Const acCmdPasteAppend = 38 (&H26) As Long				
- Const acCmdPasteAsHyperlink = 490 (&H1EA) As Long	Non			
- Const acCmdPasteFormatting = 587 (&H24B) As Long	Non	Non	Non	
- Const acCmdPasteSpecial = 64 (&H40) As Long				
- Const acCmdPivotAutoAverage = 416 (&H1A0) As Long	Non			
- Const acCmdPivotAutoCount = 413 (&H19D) As Long	Non			
- Const acCmdPivotAutoFilter = 398 (&H18E) As Long	Non			
- Const acCmdPivotAutoMax = 415 (&H19F) As Long	Non			
- Const acCmdPivotAutoMin = 414 (&H19E) As Long	Non			
- Const acCmdPivotAutoStdDev = 417 (&H1A1) As Long	Non			
- Const acCmdPivotAutoStdDevP = 419 (&H1A3) As Long	Non			
- Const acCmdPivotAutoSum = 412 (&H19C) As Long	Non			
- Const acCmdPivotAutoVar = 418 (&H1A2) As Long	Non			
- Const acCmdPivotAutoVarP = 420 (&H1A4) As Long	Non			
- Const acCmdPivotChartByRowByColumn = 456 (&H1C8) As Long	Non			
- Const acCmdPivotChartDrillInto = 457 (&H1C9) As Long	Non			
- Const acCmdPivotChartDrillOut = 532 (&H214) As Long	Non			
- Const acCmdPivotChartMultiplePlots = 458 (&H1CA) As Long	Non			
- Const acCmdPivotChartMultiplePlotsUnifiedScale = 459 (&H1CB) As Long	Non			
- Const acCmdPivotChartShowLegend = 455 (&H1C7) As Long	Non			
- Const acCmdPivotChartSortAscByTotal = 534 (&H216) As Long	Non			
- Const acCmdPivotChartSortDescByTotal = 535 (&H217) As Long	Non			
- Const acCmdPivotChartType = 453 (&H1C5) As Long	Non			
- Const acCmdPivotChartUndo = 460 (&H1CC) As Long	Non			
- Const acCmdPivotChartView = 397 (&H18D) As Long	Non			
- Const acCmdPivotCollapse = 400 (&H190) As Long	Non			
- Const acCmdPivotDelete = 454 (&H1C6) As Long	Non			
- Const acCmdPivotDropAreas = 452 (&H1C4) As Long	Non			
- Const acCmdPivotExpand = 401 (&H191) As Long	Non			
- Const acCmdPivotRefresh = 404 (&H194) As Long	Non			
- Const acCmdPivotShowAll = 461 (&H1CD) As Long	Non			
- Const acCmdPivotShowBottom1 = 432 (&H1B0) As Long	Non			
- Const acCmdPivotShowBottom10 = 435 (&H1B3) As Long	Non			
- Const acCmdPivotShowBottom10Percent = 440 (&H1B8) As Long	Non			
- Const acCmdPivotShowBottom1Percent = 437 (&H1B5) As Long	Non			
- Const acCmdPivotShowBottom2 = 433 (&H1B1) As Long	Non			
- Const acCmdPivotShowBottom25 = 436 (&H1B4) As Long	Non			
- Const acCmdPivotShowBottom25Percent = 441 (&H1B9) As Long	Non			
- Const acCmdPivotShowBottom2Percent = 438 (&H1B6) As Long	Non			
- Const acCmdPivotShowBottom5 = 434 (&H1B2) As Long	Non			
- Const acCmdPivotShowBottom5Percent = 439 (&H1B7) As Long	Non			
- Const acCmdPivotShowBottomOther = 442 (&H1BA) As Long	Non			
- Const acCmdPivotShowTop1 = 421 (&H1A5) As Long	Non			
- Const acCmdPivotShowTop10 = 424 (&H1A8) As Long	Non			

Classes et membres de la référence ACCESS

Classe de membres : AcCommand (Type : Enum)	00	02	03	07 *
- Const acCmdPivotShowTop10Percent = 429 (&H1AD) As Long	Non			
- Const acCmdPivotShowTop1Percent = 426 (&H1AA) As Long	Non			
- Const acCmdPivotShowTop2 = 422 (&H1A6) As Long	Non			
- Const acCmdPivotShowTop25 = 425 (&H1A9) As Long	Non			
- Const acCmdPivotShowTop25Percent = 430 (&H1AE) As Long	Non			
- Const acCmdPivotShowTop2Percent = 427 (&H1AB) As Long	Non			
- Const acCmdPivotShowTop5 = 423 (&H1A7) As Long	Non			
- Const acCmdPivotShowTop5Percent = 428 (&H1AC) As Long	Non			
- Const acCmdPivotShowTopOther = 431 (&H1AF) As Long	Non			
- Const acCmdPivotTableClearCustomOrdering = 527 (&H20F) As Long	Non			
- Const acCmdPivotTableCreateCalcField = 444 (&H1BC) As Long	Non			
- Const acCmdPivotTableCreateCalcTotal = 443 (&H1BB) As Long	Non			
- Const acCmdPivotTableDemote = 411 (&H19B) As Long	Non			
- Const acCmdPivotTableExpandIndicators = 451 (&H1C3) As Long	Non			
- Const acCmdPivotTableExportToExcel = 405 (&H195) As Long	Non			
- Const acCmdPivotTableFilterBySelection = 528 (&H210) As Long	Non			
- Const acCmdPivotTableGroupItems = 530 (&H212) As Long	Non			
- Const acCmdPivotTableHideDetails = 402 (&H192) As Long	Non			
- Const acCmdPivotTableMoveToColumnArea = 407 (&H197) As Long	Non			
- Const acCmdPivotTableMoveToDetailArea = 409 (&H199) As Long	Non			
- Const acCmdPivotTableMoveToFilterArea = 408 (&H198) As Long	Non			
- Const acCmdPivotTableMoveToRowArea = 406 (&H196) As Long	Non			
- Const acCmdPivotTablePercentColumnTotal = 447 (&H1BF) As Long	Non			
- Const acCmdPivotTablePercentGrandTotal = 450 (&H1C2) As Long	Non			
- Const acCmdPivotTablePercentParentColumnItem = 449 (&H1C1) As Long	Non			
- Const acCmdPivotTablePercentParentRowItem = 448 (&H1C0) As Long	Non			
- Const acCmdPivotTablePercentRowTotal = 446 (&H1BE) As Long	Non			
- Const acCmdPivotTablePromote = 410 (&H19A) As Long	Non			
- Const acCmdPivotTableRemove = 529 (&H211) As Long	Non			
- Const acCmdPivotTableShowAsNormal = 445 (&H1BD) As Long	Non			
- Const acCmdPivotTableShowDetails = 403 (&H193) As Long	Non			
- Const acCmdPivotTableSubtotal = 399 (&H18F) As Long	Non			
- Const acCmdPivotTableUngroupItems = 531 (&H213) As Long	Non			
- Const acCmdPivotTableView = 396 (&H18C) As Long	Non			
- Const acCmdPreviewEightPages = 249 (&HF9) As Long				
- Const acCmdPreviewFourPages = 248 (&HF8) As Long				
- Const acCmdPreviewOnePage = 246 (&HF6) As Long				
- Const acCmdPreviewTwelvePages = 250 (&HFA) As Long				
- Const acCmdPreviewTwoPages = 247 (&HF7) As Long				
- Const acCmdPrimaryKey = 107 (&H6B) As Long				
- Const acCmdPrint = 340 (&H154) As Long				
- Const acCmdPrintPreview = 54 (&H36) As Long				
- Const acCmdPrintRelationships = 483 (&H1E3) As Long	Non			
- Const acCmdPrintSelection = 590 (&H24E) As Long	Non	Non	Non	
- Const acCmdProcedureDefinition = 122 (&H7A) As Long				

Classes et membres de la référence ACCESS

Classe de membres : **AcCommand (Type : Enum)**

	00	02	03	07 *
- Const acCmdPromote = 386 (&H182) As Long				Non
- Const acCmdProperties = 287 (&H11F) As Long				
- Const acCmdPublish = 320 (&H140) As Long			Non	Non
- Const acCmdPublishDatabase = 537 (&H219) As Long	Non	Non	Non	
- Const acCmdPublishDefaults = 324 (&H144) As Long				
- Const acCmdPublishFixedFormat = 591 (&H24F) As Long	Non	Non	Non	
- Const acCmdQueryAddToOutput = 362 (&H16A) As Long				
- Const acCmdQueryGroupBy = 361 (&H169) As Long				
- Const acCmdQueryParameters = 76 (&H4C) As Long				
- Const acCmdQueryTotals = 73 (&H49) As Long				
- Const acCmdQueryTypeAppend = 91 (&H5B) As Long				
- Const acCmdQueryTypeCrosstab = 74 (&H4A) As Long				
- Const acCmdQueryTypeDelete = 92 (&H5C) As Long				
- Const acCmdQueryTypeMakeTable = 94 (&H5E) As Long				
- Const acCmdQueryTypeSelect = 89 (&H59) As Long				
- Const acCmdQueryTypeSQLDataDefinition = 168 (&HA8) As Long				
- Const acCmdQueryTypeSQLPassThrough = 169 (&HA9) As Long				
- Const acCmdQueryTypeSQLUnion = 180 (&HB4) As Long				
- Const acCmdQueryTypeUpdate = 90 (&H5A) As Long				
- Const acCmdQuickInfo = 304 (&H130) As Long				
- Const acCmdQuickPrint = 278 (&H116) As Long				
- Const acCmdQuickWatch = 203 (&HCB) As Long				
- Const acCmdRecordsGoToFirst = 67 (&H43) As Long				
- Const acCmdRecordsGoToLast = 68 (&H44) As Long				
- Const acCmdRecordsGoToNew = 28 (&H1C) As Long				
- Const acCmdRecordsGoToNext = 65 (&H41) As Long				
- Const acCmdRecordsGoToPrevious = 66 (&H42) As Long				
- Const acCmdRecoverDesignMaster = 265 (&H109) As Long				
- Const acCmdRedo = 199 (&HC7) As Long				
- Const acCmdReferences = 260 (&H104) As Long				
- Const acCmdRefresh = 18 (&H12) As Long				
- Const acCmdRefreshData = 541 (&H21D) As Long	Non	Non	Non	
- Const acCmdRefreshPage = 297 (&H129) As Long				
- Const acCmdRefreshSharePointList = 626 (&H272) As Long	Non	Non	Non	
- Const acCmdRegisterActiveXControls = 254 (&HFE) As Long				
- Const acCmdRelationships = 133 (&H85) As Long				
- Const acCmdRemove = 366 (&H16E) As Long				
- Const acCmdRemoveAllFilters = 644 (&H284) As Long	Non	Non	Non	
- Const acCmdRemoveAllSorts = 645 (&H285) As Long	Non	Non	Non	
- Const acCmdRemoveFilterFromCurrentColumn = 643 (&H283) As Long	Non	Non	Non	
- Const acCmdRemoveFilterSort = 144 (&H90) As Long				
- Const acCmdRemoveFromLayout = 582 (&H246) As Long	Non	Non	Non	
- Const acCmdRemoveTable = 84 (&H54) As Long				
- Const acCmdRename = 143 (&H8F) As Long				
- Const acCmdRenameColumn = 274 (&H112) As Long				

Classes et membres de la référence ACCESS

Classe de membres : AcCommand (Type : Enum)	00	02	03	07 *
- Const acCmdRenameGroup = 492 (&H1EC) As Long	Non			
- Const acCmdRepairDatabase = 6 (&H6) As Long				
- Const acCmdReplace = 29 (&H1D) As Long				
- Const acCmdReportHdrFtr = 37 (&H25) As Long				
- Const acCmdReportView = 539 (&H21B) As Long	Non	Non	Non	
- Const acCmdReset = 124 (&H7C) As Long				
- Const acCmdResolveConflicts = 266 (&H10A) As Long				
- Const acCmdRestore = 514 (&H202) As Long	Non			
- Const acCmdRowHeight = 116 (&H74) As Long				
- Const acCmdRun = 181 (&HB5) As Long				
- Const acCmdRunMacro = 31 (&H1F) As Long				
- Const acCmdRunOpenMacro = 338 (&H152) As Long				
- Const acCmdSave = 20 (&H14) As Long				
- Const acCmdSaveAllModules = 280 (&H118) As Long				
- Const acCmdSaveAs = 21 (&H15) As Long				
- Const acCmdSaveAsASP = 323 (&H143) As Long				Non
- Const acCmdSaveAsDataAccessPage = 389 (&H185) As Long				Non
- Const acCmdSaveAsHTML = 321 (&H141) As Long				
- Const acCmdSaveAsIDC = 322 (&H142) As Long				Non
- Const acCmdSaveAsOutlookContact = 584 (&H248) As Long	Non	Non	Non	
- Const acCmdSaveAsQuery = 96 (&H60) As Long				
- Const acCmdSaveAsReport = 142 (&H8E) As Long				
- Const acCmdSavedExports = 555 (&H22B) As Long	Non	Non	Non	
- Const acCmdSavedImports = 543 (&H21F) As Long	Non	Non	Non	
- Const acCmdSaveLayout = 145 (&H91) As Long				
- Const acCmdSaveModuleAsText = 119 (&H77) As Long				
- Const acCmdSaveRecord = 97 (&H61) As Long				
- Const acCmdSelectAll = 333 (&H14D) As Long				
- Const acCmdSelectAllRecords = 109 (&H6D) As Long				
- Const acCmdSelectDataAccessPage = 347 (&H15B) As Long				Non
- Const acCmdSelectEntireColumn = 571 (&H23B) As Long	Non	Non	Non	
- Const acCmdSelectEntireRow = 570 (&H23A) As Long	Non	Non	Non	
- Const acCmdSelectForm = 40 (&H28) As Long				
- Const acCmdSelectRecord = 50 (&H32) As Long				
- Const acCmdSelectReport = 319 (&H13F) As Long				
- Const acCmdSend = 173 (&HAD) As Long				
- Const acCmdSendToBack = 53 (&H35) As Long				
- Const acCmdServerFilterByForm = 507 (&H1FB) As Long	Non			
- Const acCmdServerProperties = 496 (&H1F0) As Long	Non			
- Const acCmdSetCaption = 637 (&H27D) As Long	Non	Non	Non	
- Const acCmdSetControlDefaults = 56 (&H38) As Long				
- Const acCmdSetDatabasePassword = 275 (&H113) As Long				
- Const acCmdSetNextStatement = 129 (&H81) As Long				
- Const acCmdShareOnSharePoint = 542 (&H21E) As Long	Non	Non	Non	
- Const acCmdSharePointSiteRecycleBin = 641 (&H281) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : AcCommand (Type : Enum)	00	02	03	07 *
- Const acCmdShowAllRelationships = 149 (&H95) As Long				
- Const acCmdShowColumnHistory = 620 (&H26C) As Long	Non	Non	Non	
- Const acCmdShowDatePicker = 636 (&H27C) As Long	Non	Non	Non	
- Const acCmdShowDirectRelationships = 148 (&H94) As Long				
- Const acCmdShowEnvelope = 533 (&H215) As Long	Non			
- Const acCmdShowMembers = 302 (&H12E) As Long				
- Const acCmdShowMessageBar = 676 (&H2A4) As Long	Non	Non	Non	
- Const acCmdShowNextStatement = 130 (&H82) As Long				
- Const acCmdShowOnlyWebToolbar = 300 (&H12C) As Long				Non
- Const acCmdShowTable = 185 (&HB9) As Long				
- Const acCmdSingleStep = 88 (&H58) As Long				
- Const acCmdSizeToFit = 59 (&H3B) As Long				
- Const acCmdSizeToFitForm = 69 (&H45) As Long				
- Const acCmdSizeToGrid = 48 (&H30) As Long				
- Const acCmdSizeToNarrowest = 155 (&H9B) As Long				
- Const acCmdSizeToWidest = 156 (&H9C) As Long				
- Const acCmdSnapToGrid = 62 (&H3E) As Long				
- Const acCmdSortAscending = 163 (&HA3) As Long				
- Const acCmdSortDescending = 164 (&HA4) As Long				
- Const acCmdSortingAndGrouping = 51 (&H33) As Long				
- Const acCmdSpeech = 511 (&H1FF) As Long	Non			
- Const acCmdSpelling = 269 (&H10D) As Long				
- Const acCmdSQLView = 184 (&HB8) As Long				
- Const acCmdStackedLayout = 568 (&H238) As Long	Non	Non	Non	
- Const acCmdStartNewWorkflow = 675 (&H2A3) As Long	Non	Non	Non	
- Const acCmdStartupProperties = 224 (&HE0) As Long				
- Const acCmdStepInto = 342 (&H156) As Long				
- Const acCmdStepOut = 311 (&H137) As Long				
- Const acCmdStepOver = 128 (&H80) As Long				
- Const acCmdStepToCursor = 204 (&HCC) As Long				
- Const acCmdStopLoadingPage = 296 (&H128) As Long				Non
- Const acCmdSubdatasheetCollapseAll = 505 (&H1F9) As Long	Non			
- Const acCmdSubdatasheetExpandAll = 504 (&H1F8) As Long	Non			
- Const acCmdSubdatasheetRemove = 506 (&H1FA) As Long	Non			
- Const acCmdSubformDatasheet = 108 (&H6C) As Long				
- Const acCmdSubformDatasheetView = 463 (&H1CF) As Long	Non			
- Const acCmdSubformFormView = 462 (&H1CE) As Long	Non			
- Const acCmdSubformInNewWindow = 495 (&H1EF) As Long	Non			
- Const acCmdSubformPivotChartView = 465 (&H1D1) As Long	Non			
- Const acCmdSubformPivotTableView = 464 (&H1D0) As Long	Non			
- Const acCmdSwitchboardManager = 521 (&H209) As Long	Non			
- Const acCmdSynchronize = 638 (&H27E) As Long	Non	Non	Non	
- Const acCmdSynchronizeNow = 264 (&H108) As Long				
- Const acCmdTabControlPageOrder = 330 (&H14A) As Long				
- Const acCmdTableAddTable = 498 (&H1F2) As Long	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : AcCommand (Type : Enum)</i>	00	02	03	07 *
- Const acCmdTableCustomView = 497 (&H1F1) As Long	Non			
- Const acCmdTableNames = 75 (&H4B) As Long				
- Const acCmdTabOrder = 41 (&H29) As Long				
- Const acCmdTabularLayout = 569 (&H239) As Long	Non	Non	Non	
- Const acCmdTestValidationRules = 196 (&HC4) As Long				
- Const acCmdTileHorizontally = 286 (&H11E) As Long				
- Const acCmdTileVertically = 23 (&H17) As Long				
- Const acCmdToggleBreakpoint = 131 (&H83) As Long				
- Const acCmdToggleCacheListData = 642 (&H282) As Long	Non	Non	Non	
- Const acCmdToggleFilter = 220 (&HDC) As Long				
- Const acCmdToggleOffline = 540 (&H21C) As Long	Non	Non	Non	
- Const acCmdToolbarControlProperties = 301 (&H12D) As Long				
- Const acCmdToolbarsCustomize = 165 (&HA5) As Long				
- Const acCmdTransferSQLDatabase = 515 (&H203) As Long	Non			
- Const acCmdTransparentBackground = 288 (&H120) As Long				
- Const acCmdTransparentBorder = 289 (&H121) As Long				
- Const acCmdUndo = 292 (&H124) As Long				
- Const acCmdUnfreezeAllColumns = 106 (&H6A) As Long				
- Const acCmdUngroupControls = 485 (&H1E5) As Long	Non			
- Const acCmdUnhideColumns = 80 (&H50) As Long				
- Const acCmdUpsizingWizard = 522 (&H20A) As Long	Non			
- Const acCmdUserAndGroupAccounts = 104 (&H68) As Long				
- Const acCmdUserAndGroupPermissions = 103 (&H67) As Long				
- Const acCmdUserLevelSecurityWizard = 276 (&H114) As Long				
- Const acCmdVerticalSpacingDecrease = 161 (&HA1) As Long				
- Const acCmdVerticalSpacingIncrease = 162 (&HA2) As Long				
- Const acCmdVerticalSpacingMakeEqual = 160 (&HA0) As Long				
- Const acCmdViewCode = 170 (&HAA) As Long				
- Const acCmdViewDataAccessPages = 349 (&H15D) As Long				Non
- Const acCmdViewDetails = 210 (&HD2) As Long				
- Const acCmdViewDiagrams = 354 (&H162) As Long				
- Const acCmdViewFieldList = 353 (&H161) As Long				
- Const acCmdViewForms = 112 (&H70) As Long				
- Const acCmdViewFunctions = 395 (&H18B) As Long	Non			
- Const acCmdViewGrid = 63 (&H3F) As Long				
- Const acCmdViewLargelcons = 209 (&HD1) As Long				
- Const acCmdViewList = 212 (&HD4) As Long				
- Const acCmdViewMacros = 114 (&H72) As Long				
- Const acCmdViewModules = 115 (&H73) As Long				
- Const acCmdViewObjectDependencies = 536 (&H218) As Long	Non	Non		
- Const acCmdViewQueries = 111 (&H6F) As Long				
- Const acCmdViewReports = 113 (&H71) As Long				
- Const acCmdViewRuler = 61 (&H3D) As Long				
- Const acCmdViewShowPaneDiagram = 358 (&H166) As Long				
- Const acCmdViewShowPaneGrid = 359 (&H167) As Long				

Classes et membres de la référence ACCESS

Classe de membres : **AcCommand (Type : Enum)**

	00	02	03	07 *
- Const acCmdViewShowPaneSQL = 357 (&H165) As Long				
- Const acCmdViewSmallIcons = 211 (&HD3) As Long				
- Const acCmdViewStoredProcedures = 355 (&H163) As Long				
- Const acCmdViewTableColumnNames = 363 (&H16B) As Long				
- Const acCmdViewTableColumnProperties = 368 (&H170) As Long				
- Const acCmdViewTableKeys = 369 (&H171) As Long				
- Const acCmdViewTableNameOnly = 364 (&H16C) As Long				
- Const acCmdViewTables = 110 (&H6E) As Long				
- Const acCmdViewTableUserView = 370 (&H172) As Long				
- Const acCmdViewToolbox = 85 (&H55) As Long				
- Const acCmdViewVerifySQL = 360 (&H168) As Long				
- Const acCmdViewViews = 356 (&H164) As Long				
- Const acCmdVisualBasicEditor = 525 (&H20D) As Long	Non			
- Const acCmdWebPagePreview = 466 (&H1D2) As Long	Non			Non
- Const acCmdWebPageProperties = 486 (&H1E6) As Long	Non			Non
- Const acCmdWebTheme = 473 (&H1D9) As Long	Non			Non
- Const acCmdWindowArrangeIcons = 24 (&H18) As Long				
- Const acCmdWindowCascade = 22 (&H16) As Long				
- Const acCmdWindowHide = 2 (&H2) As Long				
- Const acCmdWindowSplit = 121 (&H79) As Long				
- Const acCmdWindowUnhide = 1 (&H1) As Long				
- Const acCmdWordMailMerge = 195 (&HC3) As Long				
- Const acCmdWorkflowTasks = 674 (&H2A2) As Long	Non	Non	Non	
- Const acCmdWorkgroupAdministrator = 391 (&H187) As Long	Non			
- Const acCmdZoom10 = 244 (&HF4) As Long				
- Const acCmdZoom100 = 240 (&HF0) As Long				
- Const acCmdZoom1000 = 482 (&H1E2) As Long	Non			
- Const acCmdZoom150 = 239 (&HEF) As Long				
- Const acCmdZoom200 = 238 (&HEE) As Long				
- Const acCmdZoom25 = 243 (&HF3) As Long				
- Const acCmdZoom50 = 242 (&HF2) As Long				
- Const acCmdZoom500 = 481 (&H1E1) As Long	Non			
- Const acCmdZoom75 = 241 (&HF1) As Long				
- Const acCmdZoomBox = 179 (&HB3) As Long				
- Const acCmdZoomSelection = 371 (&H173) As Long				

Classe de membres : **AcControlType (Type : Enum)**

	00	02	03	07 *
- Const acAttachment = 126 (&H7E) As Long	Non	Non	Non	
- Const acBoundObjectFrame = 108 (&H6C) As Long				
- Const acCheckBox = 106 (&H6A) As Long				
- Const acComboBox = 111 (&H6F) As Long				
- Const acCommandButton = 104 (&H68) As Long				
- Const acCustomControl = 119 (&H77) As Long				
- Const acImage = 103 (&H67) As Long				
- Const acLabel = 100 (&H64) As Long				
- Const acLine = 102 (&H66) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcControlType (Type : Enum)</i>	00	02	03	07 *
- Const acListBox = 110 (&H6E) As Long				
- Const acObjectFrame = 114 (&H72) As Long				
- Const acOptionButton = 105 (&H69) As Long				
- Const acOptionGroup = 107 (&H6B) As Long				
- Const acPage = 124 (&H7C) As Long				
- Const acPageBreak = 118 (&H76) As Long				
- Const acRectangle = 101 (&H65) As Long				
- Const acSubform = 112 (&H70) As Long				
- Const acTabCtl = 123 (&H7B) As Long				
- Const acTextBox = 109 (&H6D) As Long				
- Const acToggleButton = 122 (&H7A) As Long				
<i>Classe de membres : AcCurrentView (Type : Enum)</i>	00	02	03	07 *
- Const acCurViewDatasheet = 2 (&H2) As Long	Non			
- Const acCurViewDesign = 0 (&H0) As Long	Non			
- Const acCurViewFormBrowse = 1 (&H1) As Long	Non			
- Const acCurViewLayout = 7 (&H7) As Long	Non	Non	Non	
- Const acCurViewPivotChart = 4 (&H4) As Long	Non			
- Const acCurViewPivotTable = 3 (&H3) As Long	Non			
- Const acCurViewPreview = 5 (&H5) As Long	Non			
- Const acCurViewReportBrowse = 6 (&H6) As Long	Non	Non	Non	
<i>Classe de membres : AcCursorOnHover (Type : Enum)</i>	00	02	03	07 *
- Const acCursorOnHoverDefault = 0 (&H0) As Long	Non	Non	Non	
- Const acCursorOnHoverHyperlinkHand = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : AcDataAccessPageView (Type : Enum)</i>	00	02	03	07 *
- Const acDataAccessPageBrowse = 0 (&H0) As Long				Non
- Const acDataAccessPageDesign = 1 (&H1) As Long				Non
<i>Classe de membres : AcDataObjectType (Type : Enum)</i>	00	02	03	07 *
- Const acActiveDataObject = -1 (&HFFFFFF) As Long				
- Const acDataForm = 2 (&H2) As Long				
- Const acDataFunction = 10 (&HA) As Long	Non			
- Const acDataQuery = 1 (&H1) As Long				
- Const acDataReport = 3 (&H3) As Long	Non	Non	Non	
- Const acDataServerView = 7 (&H7) As Long				
- Const acDataStoredProcedure = 9 (&H9) As Long				
- Const acDataTable = 0 (&H0) As Long				
<i>Classe de membres : AcDataTransferType (Type : Enum)</i>	00	02	03	07 *
- Const acExport = 1 (&H1) As Long				
- Const acImport = 0 (&H0) As Long				
- Const acLink = 2 (&H2) As Long				
<i>Classe de membres : AcDefReportView (Type : Enum)</i>	00	02	03	07 *
- Const acDefViewPreview = 0 (&H0) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : AcDefReportView (Type : Enum)		00	02	03	07 *
- Const acDefViewReportBrowse = 1 (&H1) As Long	Non	Non	Non		
Classe de membres : AcDefView (Type : Enum)		00	02	03	07 *
- Const acDefViewContinuous = 1 (&H1) As Long	Non				
- Const acDefViewDatasheet = 2 (&H2) As Long	Non				
- Const acDefViewPivotChart = 4 (&H4) As Long	Non				
- Const acDefViewPivotTable = 3 (&H3) As Long	Non				
- Const acDefViewSingle = 0 (&H0) As Long	Non				
- Const acDefViewSplitForm = 5 (&H5) As Long	Non	Non	Non		
Classe de membres : AcDisplayAs (Type : Enum)		00	02	03	07 *
- Const acDisplayAsIcon = 1 (&H1) As Long	Non	Non	Non		
- Const acDisplayAsImageIcon = 0 (&H0) As Long	Non	Non	Non		
- Const acDisplayAsPaperclip = 2 (&H2) As Long	Non	Non	Non		
Classe de membres : AcDisplayAsHyperlink (Type : Enum)		00	02	03	07 *
- Const acDisplayAsHyperlinkAlways = 1 (&H1) As Long	Non	Non	Non		
- Const acDisplayAsHyperlinkIfHyperlink = 0 (&H0) As Long	Non	Non	Non		
- Const acDisplayAsHyperlinkOnScreenOnly = 2 (&H2) As Long	Non	Non	Non		
Classe de membres : AcExportQuality (Type : Enum)		00	02	03	07 *
- Const acExportQualityPrint = 0 (&H0) As Long	Non	Non	Non		
- Const acExportQualityScreen = 1 (&H1) As Long	Non	Non	Non		
Classe de membres : AcExportXMLEncoding (Type : Enum)		00	02	03	07 *
- Const acUTF16 = 1 (&H1) As Long	Non				
- Const acUTF8 = 0 (&H0) As Long	Non				
Classe de membres : AcExportXMLObjectType (Type : Enum)		00	02	03	07 *
- Const acExportForm = 2 (&H2) As Long	Non				
- Const acExportFunction = 10 (&HA) As Long	Non				
- Const acExportQuery = 1 (&H1) As Long	Non				
- Const acExportReport = 3 (&H3) As Long	Non				
- Const acExportServerView = 7 (&H7) As Long	Non				
- Const acExportStoredProcedure = 9 (&H9) As Long	Non				
- Const acExportTable = 0 (&H0) As Long	Non				
Classe de membres : AcExportXMLOtherFlags (Type : Enum)		00	02	03	07 *
- Const acEmbedSchema = 1 (&H1) As Long	Non	Non			
- Const acExcludePrimaryKeyAndIndexes = 2 (&H2) As Long	Non	Non			
- Const acExportAllTableAndFieldProperties = 32 (&H20) As Long	Non	Non	Non		
- Const acLiveReportSource = 8 (&H8) As Long	Non	Non			
- Const acPersistReportML = 16 (&H10) As Long	Non	Non			
- Const acRunFromServer = 4 (&H4) As Long	Non	Non			
Classe de membres : AcExportXMLSchemaFormat (Type : Enum)		00	02	03	07 *
- Const acSchemaNone = 0 (&H0) As Long	Non				
- Const acSchemaXSD = 1 (&H1) As Long	Non				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcFileFormat (Type : Enum)</i>	00	02	03	07 *
- Const acFileFormatAccess2 = 2 (&H2) As Long	Non			
- Const acFileFormatAccess2000 = 9 (&H9) As Long	Non			
- Const acFileFormatAccess2002 = 10 (&HA) As Long	Non			
- Const acFileFormatAccess2007 = 12 (&HC) As Long	Non	Non	Non	
- Const acFileFormatAccess95 = 7 (&H7) As Long	Non			
- Const acFileFormatAccess97 = 8 (&H8) As Long	Non			
<i>Classe de membres : AcFilterType (Type : Enum)</i>	00	02	03	07 *
- Const acFilterNormal = 0 (&H0) As Long				
- Const acServerFilter = 1 (&H1) As Long				
<i>Classe de membres : AcFindField (Type : Enum)</i>	00	02	03	07 *
- Const acAll = 0 (&H0) As Long				
- Const acCurrent = -1 (&HFFFFFFF) As Long				
<i>Classe de membres : AcFindMatch (Type : Enum)</i>	00	02	03	07 *
- Const acAnywhere = 0 (&H0) As Long				
- Const acEntire = 1 (&H1) As Long				
- Const acStart = 2 (&H2) As Long				
<i>Classe de membres : AcFormatConditionOperator (Type : Enum)</i>	00	02	03	07 *
- Const acBetween = 0 (&H0) As Long				
- Const acEqual = 2 (&H2) As Long				
- Const acGreaterThan = 4 (&H4) As Long				
- Const acGreaterThanOrEqual = 6 (&H6) As Long				
- Const acLessThan = 5 (&H5) As Long				
- Const acLessThanOrEqual = 7 (&H7) As Long				
- Const acNotBetween = 1 (&H1) As Long				
- Const acNotEqual = 3 (&H3) As Long				
<i>Classe de membres : AcFormatConditionType (Type : Enum)</i>	00	02	03	07 *
- Const acExpression = 1 (&H1) As Long				
- Const acFieldHasFocus = 2 (&H2) As Long				
- Const acFieldValue = 0 (&H0) As Long				
<i>Classe de membres : AcFormOpenDataMode (Type : Enum)</i>	00	02	03	07 *
- Const acFormAdd = 0 (&H0) As Long				
- Const acFormEdit = 1 (&H1) As Long				
- Const acFormPropertySettings = -1 (&HFFFFFFF) As Long				
- Const acFormReadOnly = 2 (&H2) As Long				
<i>Classe de membres : AcFormView (Type : Enum)</i>	00	02	03	07 *
- Const acDesign = 1 (&H1) As Long				
- Const acFormDS = 3 (&H3) As Long				
- Const acFormPivotChart = 5 (&H5) As Long	Non			
- Const acFormPivotTable = 4 (&H4) As Long	Non			
- Const acLayout = 6 (&H6) As Long	Non	Non	Non	
- Const acNormal = 0 (&H0) As Long				

Classes et membres de la référence ACCESS

Classe de membres : AcFormView (Type : Enum)	00	02	03	07 *
- Const acPreview = 2 (&H2) As Long				
Classe de membres : AcHorizontalAnchor (Type : Enum)	00	02	03	07 *
- Const acHorizontalAnchorBoth = 2 (&H2) As Long	Non	Non	Non	
- Const acHorizontalAnchorLeft = 0 (&H0) As Long	Non	Non	Non	
- Const acHorizontalAnchorRight = 1 (&H1) As Long	Non	Non	Non	
Classe de membres : AcHyperlinkPart (Type : Enum)	00	02	03	07 *
- Const acAddress = 2 (&H2) As Long				
- Const acDisplayedValue = 0 (&H0) As Long				
- Const acDisplayText = 1 (&H1) As Long				
- Const acFullAddress = 5 (&H5) As Long				
- Const acScreenTip = 4 (&H4) As Long				
- Const acSubAddress = 3 (&H3) As Long				
Classe de membres : AcImeMode (Type : Enum)	00	02	03	07 *
- Const acImeModeAlpha = 8 (&H8) As Long				
- Const acImeModeAlphaFull = 7 (&H7) As Long				
- Const acImeModeDisable = 3 (&H3) As Long				
- Const acImeModeHangul = 10 (&HA) As Long				
- Const acImeModeHangulFull = 9 (&H9) As Long				
- Const acImeModeHiragana = 4 (&H4) As Long				
- Const acImeModeKatakana = 5 (&H5) As Long				
- Const acImeModeKatakanaHalf = 6 (&H6) As Long				
- Const acImeModeNoControl = 0 (&H0) As Long				
- Const acImeModeOff = 2 (&H2) As Long				
- Const acImeModeOn = 1 (&H1) As Long				
Classe de membres : AcImeSentenceMode (Type : Enum)	00	02	03	07 *
- Const acImeSentenceModeConversation = 2 (&H2) As Long				
- Const acImeSentenceModeNone = 3 (&H3) As Long				
- Const acImeSentenceModePhrasePredict = 0 (&H0) As Long				
- Const acImeSentenceModePluralClause = 1 (&H1) As Long				
Classe de membres : AcImportXMLOption (Type : Enum)	00	02	03	07 *
- Const acAppendData = 2 (&H2) As Long	Non			
- Const acStructureAndData = 1 (&H1) As Long	Non			
- Const acStructureOnly = 0 (&H0) As Long	Non			
Classe de membres : AcLayoutType (Type : Enum)	00	02	03	07 *
- Const acLayoutNone = 0 (&H0) As Long	Non	Non	Non	
- Const acLayoutStacked = 2 (&H2) As Long	Non	Non	Non	
- Const acLayoutTabular = 1 (&H1) As Long	Non	Non	Non	
Classe de membres : AcModuleType (Type : Enum)	00	02	03	07 *
- Const acClassModule = 1 (&H1) As Long				
- Const acStandardModule = 0 (&H0) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcNewDatabaseFormat (Type : Enum)</i>	00	02	03	07 *
- Const acNewDatabaseFormatAccess2000 = 9 (&H9) As Long	Non	Non	Non	
- Const acNewDatabaseFormatAccess2002 = 10 (&HA) As Long	Non	Non	Non	
- Const acNewDatabaseFormatAccess2007 = 12 (&HC) As Long	Non	Non	Non	
- Const acNewDatabaseFormatUserDefault = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : AcObjectType (Type : Enum)</i>	00	02	03	07 *
- Const acDataAccessPage = 6 (&H6) As Long				Non
- Const acDefault = -1 (&HFFFFFF) As Long				
- Const acDiagram = 8 (&H8) As Long				
- Const acForm = 2 (&H2) As Long				
- Const acFunction = 10 (&HA) As Long	Non			
- Const acMacro = 4 (&H4) As Long				
- Const acModule = 5 (&H5) As Long				
- Const acQuery = 1 (&H1) As Long				
- Const acReport = 3 (&H3) As Long				
- Const acServerView = 7 (&H7) As Long				
- Const acStoredProcedure = 9 (&H9) As Long				
- Const acTable = 0 (&H0) As Long				
<i>Classe de membres : AcOpenDataMode (Type : Enum)</i>	00	02	03	07 *
- Const acAdd = 0 (&H0) As Long				
- Const acEdit = 1 (&H1) As Long				
- Const acReadOnly = 2 (&H2) As Long				
<i>Classe de membres : AcOutputObjectType (Type : Enum)</i>	00	02	03	07 *
- Const acOutputDataAccessPage = 6 (&H6) As Long				Non
- Const acOutputForm = 2 (&H2) As Long				
- Const acOutputFunction = 10 (&HA) As Long	Non			
- Const acOutputModule = 5 (&H5) As Long				
- Const acOutputQuery = 1 (&H1) As Long				
- Const acOutputReport = 3 (&H3) As Long				
- Const acOutputServerView = 7 (&H7) As Long				
- Const acOutputStoredProcedure = 9 (&H9) As Long				
- Const acOutputTable = 0 (&H0) As Long				
<i>Classe de membres : AcPictureCaptionArrangement (Type : Enum)</i>	00	02	03	07 *
- Const acBottom = 3 (&H3) As Long	Non	Non	Non	
- Const acGeneral = 1 (&H1) As Long	Non	Non	Non	
- Const acLeft = 4 (&H4) As Long	Non	Non	Non	
- Const acNoPictureCaption = 0 (&H0) As Long	Non	Non	Non	
- Const acRight = 5 (&H5) As Long	Non	Non	Non	
- Const acTop = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : AcPrintColor (Type : Enum)</i>	00	02	03	07 *
- Const acPRCMColor = 2 (&H2) As Long	Non			
- Const acPRCMMonochrome = 1 (&H1) As Long	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : AcPrintDuplex (Type : Enum)</i>	00	02	03	07 *
Const acPRDPHorizontal = 2 (&H2) As Long	Non			
Const acPRDPSimplex = 1 (&H1) As Long	Non			
Const acPRDPVertical = 3 (&H3) As Long	Non			
<i>Classe de membres : AcPrintItemLayout (Type : Enum)</i>	00	02	03	07 *
Const acPRHorizontalColumnLayout = 1953 (&H7A1) As Long	Non			
Const acPRVerticalColumnLayout = 1954 (&H7A2) As Long	Non			
<i>Classe de membres : AcPrintObjQuality (Type : Enum)</i>	00	02	03	07 *
Const acPRPQDraft = -1 (&HFFFFFFF) As Long	Non			
Const acPRPQHigh = -4 (&HFFFFFFFC) As Long	Non			
Const acPRPQLow = -2 (&HFFFFFFFE) As Long	Non			
Const acPRPQMedium = -3 (&HFFFFFFFD) As Long	Non			
<i>Classe de membres : AcPrintOrientation (Type : Enum)</i>	00	02	03	07 *
Const acPRORLandscape = 2 (&H2) As Long	Non			
Const acPRORPortrait = 1 (&H1) As Long	Non			
<i>Classe de membres : AcPrintPaperBin (Type : Enum)</i>	00	02	03	07 *
Const acPRBNAuto = 7 (&H7) As Long	Non			
Const acPRBNCassette = 14 (&HE) As Long	Non			
Const acPRBNEvelope = 5 (&H5) As Long	Non			
Const acPRBNEnvManual = 6 (&H6) As Long	Non			
Const acPRBNFormSource = 15 (&HF) As Long	Non			
Const acPRBNLargeCapacity = 11 (&HB) As Long	Non			
Const acPRBNLargeFmt = 10 (&HA) As Long	Non			
Const acPRBNLower = 2 (&H2) As Long	Non			
Const acPRBNManual = 4 (&H4) As Long	Non			
Const acPRBNMiddle = 3 (&H3) As Long	Non			
Const acPRBNSmallFmt = 9 (&H9) As Long	Non			
Const acPRBNTractor = 8 (&H8) As Long	Non			
Const acPRBNUpper = 1 (&H1) As Long	Non			
<i>Classe de membres : AcPrintPaperSize (Type : Enum)</i>	00	02	03	07 *
Const acPRPS10x14 = 16 (&H10) As Long	Non			
Const acPRPS11x17 = 17 (&H11) As Long	Non			
Const acPRPSA3 = 8 (&H8) As Long	Non			
Const acPRPSA4 = 9 (&H9) As Long	Non			
Const acPRPSA4Small = 10 (&HA) As Long	Non			
Const acPRPSA5 = 11 (&HB) As Long	Non			
Const acPRPSB4 = 12 (&HC) As Long	Non			
Const acPRPSB5 = 13 (&HD) As Long	Non			
Const acPRPSCSheet = 24 (&H18) As Long	Non			
Const acPRPSDSheet = 25 (&H19) As Long	Non			
Const acPRPSEnv10 = 20 (&H14) As Long	Non			
Const acPRPSEnv11 = 21 (&H15) As Long	Non			
Const acPRPSEnv12 = 22 (&H16) As Long	Non			

Classes et membres de la référence ACCESS

Classe de membres : AcPrintPaperSize (Type : Enum)	00	02	03	07 *
- Const acPRPSEnv14 = 23 (&H17) As Long	Non			
- Const acPRPSEnv9 = 19 (&H13) As Long	Non			
- Const acPRPSEnvB4 = 33 (&H21) As Long	Non			
- Const acPRPSEnvB5 = 34 (&H22) As Long	Non			
- Const acPRPSEnvB6 = 35 (&H23) As Long	Non			
- Const acPRPSEnvC3 = 29 (&H1D) As Long	Non			
- Const acPRPSEnvC4 = 30 (&H1E) As Long	Non			
- Const acPRPSEnvC5 = 28 (&H1C) As Long	Non			
- Const acPRPSEnvC6 = 31 (&H1F) As Long	Non			
- Const acPRPSEnvC65 = 32 (&H20) As Long	Non			
- Const acPRPSEnvDL = 27 (&H1B) As Long	Non			
- Const acPRPSEnvItaly = 36 (&H24) As Long	Non			
- Const acPRPSEnvMonarch = 37 (&H25) As Long	Non			
- Const acPRPSEnvPersonal = 38 (&H26) As Long	Non			
- Const acPRPSESheet = 26 (&H1A) As Long	Non			
- Const acPRPSExecutive = 7 (&H7) As Long	Non			
- Const acPRPSFanfoldLglGerman = 41 (&H29) As Long	Non			
- Const acPRPSFanfoldStdGerman = 40 (&H28) As Long	Non			
- Const acPRPSFanfoldUS = 39 (&H27) As Long	Non			
- Const acPRPSFolio = 14 (&HE) As Long	Non			
- Const acPRPSLedger = 4 (&H4) As Long	Non			
- Const acPRPSLegal = 5 (&H5) As Long	Non			
- Const acPRPSLetter = 1 (&H1) As Long	Non			
- Const acPRPSLetterSmall = 2 (&H2) As Long	Non			
- Const acPRPSNote = 18 (&H12) As Long	Non			
- Const acPRPSQuarto = 15 (&HF) As Long	Non			
- Const acPRPSStatement = 6 (&H6) As Long	Non			
- Const acPRPSTabloid = 3 (&H3) As Long	Non			
- Const acPRPSUser = 256 (&H100) As Long	Non			

Classe de membres : AcPrintQuality (Type : Enum)	00	02	03	07 *
- Const acDraft = 3 (&H3) As Long				
- Const acHigh = 0 (&H0) As Long				
- Const acLow = 2 (&H2) As Long				
- Const acMedium = 1 (&H1) As Long				

Classe de membres : AcPrintRange (Type : Enum)	00	02	03	07 *
- Const acPages = 2 (&H2) As Long				
- Const acPrintAll = 0 (&H0) As Long				
- Const acSelection = 1 (&H1) As Long				

Classe de membres : AcProjectType (Type : Enum)	00	02	03	07 *
- Const acADP = 1 (&H1) As Long				
- Const acMDB = 2 (&H2) As Long				
- Const acNull = 0 (&H0) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcProperty (Type : Enum)</i>	00	02	03	07 *
- Const acPropertyBackColor = 8 (&H8) As Long	Non	Non	Non	
- Const acPropertyCaption = 9 (&H9) As Long	Non	Non	Non	
- Const acPropertyEnabled = 0 (&H0) As Long	Non	Non	Non	
- Const acPropertyForeColor = 7 (&H7) As Long	Non	Non	Non	
- Const acPropertyHeight = 6 (&H6) As Long	Non	Non	Non	
- Const acPropertyLeft = 3 (&H3) As Long	Non	Non	Non	
- Const acPropertyLocked = 2 (&H2) As Long	Non	Non	Non	
- Const acPropertyTop = 4 (&H4) As Long	Non	Non	Non	
- Const acPropertyVisible = 1 (&H1) As Long	Non	Non	Non	
- Const acPropertyWidth = 5 (&H5) As Long	Non	Non	Non	
<i>Classe de membres : AcQuitOption (Type : Enum)</i>	00	02	03	07 *
- Const acQuitPrompt = 0 (&H0) As Long				
- Const acQuitSaveAll = 1 (&H1) As Long				
- Const acQuitSaveNone = 2 (&H2) As Long				
<i>Classe de membres : AcRecord (Type : Enum)</i>	00	02	03	07 *
- Const acFirst = 2 (&H2) As Long				
- Const acGoTo = 4 (&H4) As Long				
- Const acLast = 3 (&H3) As Long				
- Const acNewRec = 5 (&H5) As Long				
- Const acNext = 1 (&H1) As Long				
- Const acPrevious = 0 (&H0) As Long				
<i>Classe de membres : AcSearchDirection (Type : Enum)</i>	00	02	03	07 *
- Const acDown = 1 (&H1) As Long				
- Const acSearchAll = 2 (&H2) As Long				
- Const acUp = 0 (&H0) As Long				
<i>Classe de membres : AcSection (Type : Enum)</i>	00	02	03	07 *
- Const acDetail = 0 (&H0) As Long				
- Const acFooter = 2 (&H2) As Long				
- Const acGroupLevel1Footer = 6 (&H6) As Long				
- Const acGroupLevel1Header = 5 (&H5) As Long				
- Const acGroupLevel2Footer = 8 (&H8) As Long				
- Const acGroupLevel2Header = 7 (&H7) As Long				
- Const acHeader = 1 (&H1) As Long				
- Const acPageFooter = 4 (&H4) As Long				
- Const acPageHeader = 3 (&H3) As Long				
<i>Classe de membres : AcSendObjectType (Type : Enum)</i>	00	02	03	07 *
- Const acSendDataAccessPage = 6 (&H6) As Long				Non
- Const acSendForm = 2 (&H2) As Long				
- Const acSendModule = 5 (&H5) As Long				
- Const acSendNoObject = -1 (&HFFFFFF) As Long				
- Const acSendQuery = 1 (&H1) As Long				
- Const acSendReport = 3 (&H3) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcSendObjectType (Type : Enum)</i>	00	02	03	07 *
- Const acSendTable = 0 (&H0) As Long				
<i>Classe de membres : AcSeparatorCharacters (Type : Enum)</i>	00	02	03	07 *
- Const acSeparatorCharactersComma = 3 (&H3) As Long	Non	Non	Non	
- Const acSeparatorCharactersNewLine = 1 (&H1) As Long	Non	Non	Non	
- Const acSeparatorCharactersSemiColon = 2 (&H2) As Long	Non	Non	Non	
- Const acSeparatorCharactersSystemSeparator = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : AcSharePointListTransferType (Type : Enum)</i>	00	02	03	07 *
- Const acImportSharePointList = 0 (&H0) As Long	Non	Non	Non	
- Const acLinkSharePointList = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : AcShowToolbar (Type : Enum)</i>	00	02	03	07 *
- Const acToolbarNo = 2 (&H2) As Long				
- Const acToolbarWhereApprop = 1 (&H1) As Long				
- Const acToolbarYes = 0 (&H0) As Long				
<i>Classe de membres : AcSplitFormDatasheet (Type : Enum)</i>	00	02	03	07 *
- Const acDatasheetAllowEdits = 0 (&H0) As Long	Non	Non	Non	
- Const acDatasheetReadOnly = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : AcSplitFormOrientation (Type : Enum)</i>	00	02	03	07 *
- Const acDatasheetOnBottom = 1 (&H1) As Long	Non	Non	Non	
- Const acDatasheetOnLeft = 2 (&H2) As Long	Non	Non	Non	
- Const acDatasheetOnRight = 3 (&H3) As Long	Non	Non	Non	
- Const acDatasheetOnTop = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : AcSplitFormPrinting (Type : Enum)</i>	00	02	03	07 *
- Const acFormOnly = 0 (&H0) As Long	Non	Non	Non	
- Const acGridOnly = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : AcSpreadSheetType (Type : Enum)</i>	00	02	03	07 *
- Const acSpreadsheetTypeExcel12 = 9 (&H9) As Long	Non	Non	Non	
- Const acSpreadsheetTypeExcel12Xml = 10 (&HA) As Long	Non	Non	Non	
- Const acSpreadsheetTypeExcel3 = 0 (&H0) As Long				
- Const acSpreadsheetTypeExcel4 = 6 (&H6) As Long				
- Const acSpreadsheetTypeExcel5 = 5 (&H5) As Long				
- Const acSpreadsheetTypeExcel7 = 5 (&H5) As Long				
- Const acSpreadsheetTypeExcel8 = 8 (&H8) As Long				
- Const acSpreadsheetTypeExcel9 = 8 (&H8) As Long				
- Const acSpreadsheetTypeLotusWJ2 = 4 (&H4) As Long				
- Const acSpreadsheetTypeLotusWK1 = 2 (&H2) As Long				
- Const acSpreadsheetTypeLotusWK3 = 3 (&H3) As Long				
- Const acSpreadsheetTypeLotusWK4 = 7 (&H7) As Long				
<i>Classe de membres : AcSysCmdAction (Type : Enum)</i>	00	02	03	07 *
- Const acSysCmdAccessDir = 9 (&H9) As Long				
- Const acSysCmdAccessVer = 7 (&H7) As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : AcSysCmdAction (Type : Enum)</i>	00	02	03	07 *
- Const acSysCmdClearHelpTopic = 11 (&HB) As Long				
- Const acSysCmdClearStatus = 5 (&H5) As Long				
- Const acSysCmdGetObjectState = 10 (&HA) As Long				
- Const acSysCmdGetWorkgroupFile = 13 (&HD) As Long				
- Const acSysCmdIniFile = 8 (&H8) As Long				
- Const acSysCmdInitMeter = 1 (&H1) As Long				
- Const acSysCmdProfile = 12 (&HC) As Long				
- Const acSysCmdRemoveMeter = 3 (&H3) As Long				
- Const acSysCmdRuntime = 6 (&H6) As Long				
- Const acSysCmdSetStatus = 4 (&H4) As Long				
- Const acSysCmdUpdateMeter = 2 (&H2) As Long				
<i>Classe de membres : AcTextFormat (Type : Enum)</i>	00	02	03	07 *
- Const acTextFormatHTMLRichText = 1 (&H1) As Long	Non	Non	Non	
- Const acTextFormatPlain = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : AcTextTransferType (Type : Enum)</i>	00	02	03	07 *
- Const acExportDelim = 2 (&H2) As Long				
- Const acExportFixed = 3 (&H3) As Long				
- Const acExportHTML = 8 (&H8) As Long				
- Const acExportMerge = 4 (&H4) As Long				
- Const acImportDelim = 0 (&H0) As Long				
- Const acImportFixed = 1 (&H1) As Long				
- Const acImportHTML = 7 (&H7) As Long				
- Const acLinkDelim = 5 (&H5) As Long				
- Const acLinkFixed = 6 (&H6) As Long				
- Const acLinkHTML = 9 (&H9) As Long				
<i>Classe de membres : AcTransformXMLScriptOption (Type : Enum)</i>	00	02	03	07 *
- Const acDisableScript = 2 (&H2) As Long	Non	Non		
- Const acEnableScript = 0 (&H0) As Long	Non	Non		
- Const acPromptScript = 1 (&H1) As Long	Non	Non		
<i>Classe de membres : AcVerticalAnchor (Type : Enum)</i>	00	02	03	07 *
- Const acVerticalAnchorBoth = 2 (&H2) As Long	Non	Non	Non	
- Const acVerticalAnchorBottom = 1 (&H1) As Long	Non	Non	Non	
- Const acVerticalAnchorTop = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : AcView (Type : Enum)</i>	00	02	03	07 *
- Const acViewDesign = 1 (&H1) As Long				
- Const acViewLayout = 6 (&H6) As Long	Non	Non	Non	
- Const acViewNormal = 0 (&H0) As Long				
- Const acViewPivotChart = 4 (&H4) As Long	Non			
- Const acViewPivotTable = 3 (&H3) As Long	Non			
- Const acViewPreview = 2 (&H2) As Long				
- Const acViewReport = 5 (&H5) As Long	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : AcWindowMode (Type : Enum)</i>	00	02	03	07 *
- Const acDialog = 3 (&H3) As Long				
- Const acHidden = 1 (&H1) As Long				
- Const acIcon = 2 (&H2) As Long				
- Const acWindowNormal = 0 (&H0) As Long				
<i>Classe de membres : AdditionalData (Type : Classe)</i>	00	02	03	07 *
- Function Add (var As String) As AdditionalData	Non	Non		
- Property Get Count As Long	Non	Non		
- Property Get Item (Index As Variant) As AdditionalData	Non	Non		
- Property Get/Let Name As String	Non	Non		
<i>Classe de membres : AllDataAccessPages (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllDatabaseDiagrams (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllForms (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllFunctions (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Count As Long	Non			
- Property Get Item (var As Variant) As AccessObject	Non			
- Property Get Parent As Object	Non			
<i>Classe de membres : AllMacros (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllModules (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				

Classes et membres de la référence ACCESS

<i>Classe de membres : AllObjects (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllQueries (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllReports (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllStoredProcedures (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllTables (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : AllViews (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (var As Variant) As AccessObject				
- Property Get Parent As Object				
<i>Classe de membres : Application (Type : Classe)</i>	00	02	03	07 *
- Function AccessError (ErrorNumber As Variant) As Variant				
- Sub AddToFavorites ()				
- Property Get AnswerWizard As AnswerWizard				
- Property Get Application As Application				
- Property Get Assistance As IAssistance	Non	Non	Non	
- Property Get Assistant As Assistant				
- Property Get AutoCorrect As AutoCorrect	Non	Non		
- Property Get/Let AutomationSecurity As MsoAutomationSecurity	Non	Non		
- Property Get BrokenReference As Boolean	Non			
- Property Get Build As Long	Non			

Classes et membres de la référence ACCESS

Classe de membres : Application (Type : Classe)

	00	02	03	07 *
- Function BuildCriteria (Field As String, FieldType As Integer, Expression As String) As String				
- Sub CloseCurrentDatabase ()				
- Property Get CodeContextObject As Object				
- Property Get CodeData As CodeData				
- Function CodeDb () As Database				
- Property Get CodeProject As CodeProject				
- Function ColumnHistory (TableName As String, ColumnName As String, queryString As String) As String	Non	Non	Non	
- Property Get COMAddIns As COMAddIns				
- Property Get CommandBars As CommandBars				
- Function CompactRepair (SourceFile As String, DestinationFile As String, [LogFile As Boolean = Faux]) As Boolean	Non			
- Sub ConvertAccessProject (SourceFilename As String, DestinationFilename As String, DestinationFileFormat As AcFileFormat)	Non			
- Sub CreateAccessProject (filepath As String, Optional Connect As Variant)				
- Function CreateAdditionalData () As AdditionalData	Non	Non		
- Function CreateControl (FormName As String, ControlType As AcControlType, [Section As AcSection = acDetail], Optional Parent As Variant, Optional ColumnName As Variant, Optional Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant) As Control				
- Function CreateDataAccessPage (FileName As Variant, [CreateNewFile As Boolean = Vrai]) As DataAccessPage		Non	Non	Non
- Function CreateForm (Optional Database As Variant, Optional FormTemplate As Variant) As Form				
- Function CreateGroupLevel (ReportName As String, Expression As String, Header As Integer, Footer As Integer) As Long				
- Sub CreateNewWorkgroupFile ([Path As String = " "], [Name As String = " "], [Company As String = " "], [WorkgroupID As String = " "], [Replace As Boolean = Faux])	Non			Non
- Function CreateReport (Optional Database As Variant, Optional ReportTemplate As Variant) As Report				
- Function CreateReportControl (ReportName As String, ControlType As AcControlType, [Section As AcSection = acDetail], Optional Parent As Variant, Optional ColumnName As Variant, Optional Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant) As Control				
- Property Get CurrentData As CurrentData				
- Function CurrentDb () As Database				
- Property Get CurrentObjectName As String				
- Property Get CurrentObjectType As Long		Non	Non	Non
- Property Get CurrentObjectType As AcObjectType	Non			
- Property Get CurrentProject As CurrentProject				
- Function CurrentUser () As String				
- Property Get DataAccessPages As DataAccessPages				Non
- Function DAvg (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Property Get DBEngine As DBEngine				
- Function DCount (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Sub DDEExecute (ChanNum As Variant, Command As String)				

Classes et membres de la référence ACCESS

Classe de membres : **Application (Type : Classe)**

	00	02	03	07 *
- Function DDEInitiate (Application As String, Topic As String) As Variant				
- Sub DDEPoke (ChanNum As Variant, Item As String, Data As String)				
- Function DDERequest (ChanNum As Variant, Item As String) As String				
- Sub DDETerminate (ChanNum As Variant)				
- Sub DDETerminateAll ()				
- Property Get DefaultWebOptions As DefaultWebOptions				Non
- Function DefaultWorkspaceClone () As Workspace				
- Sub DeleteControl (FormName As String, ControlName As String)				
- Sub DeleteReportControl (ReportName As String, ControlName As String)				
- Function DFirst (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DLast (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DLookup (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DMax (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DMin (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Property Get DoCmd As DoCmd				
- Function DStDev (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DStDevP (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DSum (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DVar (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Function DVarP (Expr As String, Domain As String, Optional Criteria As Variant) As Variant				
- Sub Echo (EchoOn As Integer, [bstrStatusBarText As String])				
- Function EuroConvert (Number As Double, SourceCurrency As String, TargetCurrency As String, Optional FullPrecision As Variant, Optional TriangulationPrecision As Variant) As Double				
- Function Eval (StringExpr As String) As Variant				
- Sub ExportNavigationPane (Path As String)	Non	Non	Non	
- Sub ExportXML (ObjectType As AcExportXMLObjectType, DataSource As String, [DataTarget As String], [SchemaTarget As String], [PresentationTarget As String], [ImageTarget As String], [Encoding As AcExportXMLEncoding = acUTF8], [OtherFlags As Long])	Non		Non	Non
- Sub ExportXML (ObjectType As AcExportXMLObjectType, DataSource As String, [DataTarget As String], [SchemaTarget As String], [PresentationTarget As String], [ImageTarget As String], [Encoding As AcExportXMLEncoding = acUTF8], [OtherFlags As AcExportXMLOtherFlags], [WhereCondition As String], Optional AdditionalData As Variant)	Non	Non		
- Property Get/Let FeatureInstall As MsoFeatureInstall				
- Property Get FileDialog (dialogType As MsoFileDialogType) As FileDialog	Non			
- Property Get FileSearch As FileSearch				Non
- Sub FollowHyperlink (Address As String, [SubAddress As String], [NewWindow As Boolean = Faux], [AddHistory As Boolean = Vrai], ExtraInfo As Variant, [Method As MsoExtraInfoMethod = msoMethodGet], [HeaderInfo As String])				
- Property Get Forms As Forms				
- Function GetHiddenAttribute (ObjectType As AcObjectType, ObjectName As String) As Boolean				
- Function GetOption (OptionName As String) As Variant				
- Function GUIDFromString (String As Variant) As Variant				

Classes et membres de la référence ACCESS

<i>Classe de membres : Application (Type : Classe)</i>	00	02	03	07 *
- Function HtmlEncode (PlainText As Variant, Optional Length As Variant) As String	Non	Non	Non	
- Function hWndAccessApp () As Long				
- Function HyperlinkPart (Hyperlink As Variant, [Part As AcHyperlinkPart = acDisplayedValue]) As String				
- Sub ImportNavigationPane (Path As String, [fAppendOnly As Boolean = Faux])	Non	Non	Non	
- Sub ImportXML (DataSource As String, [ImportOptions As AcImportXMLOption = acStructureAndData])	Non			
- Property Get IsCompiled As Boolean				
- Property Get LanguageSettings As LanguageSettings				
- Sub LoadCustomUI (CustomUIName As String, CustomUIXML As String)	Non	Non	Non	
- Function LoadPicture (FileName As String) As Object				
- Property Get MacroError As MacroError	Non	Non	Non	
- Property Get/Let MenuBar As String				
- Property Get Modules As Modules				
- Property Get Name As String				
- Sub NewAccessProject (filepath As String, Optional Connect As Variant)				
- Sub NewCurrentDatabase (filepath As String)				Non
- Sub NewCurrentDatabase (filepath As String, [FileFormat As AcNewDatabaseFormat = acNewDatabaseFormatUserDefault], Template As Variant, [SiteAddress As String], [ListID As String])	Non	Non	Non	
- Property Get NewFileTaskPane As NewFile	Non			
- Function Nz (Value As Variant, Optional ValuelfNull As Variant) As Variant				
- Sub OpenAccessProject (filepath As String, [Exclusive As Boolean = Faux])				
- Sub OpenCurrentDatabase (filepath As String, [Exclusive As Boolean = Faux])		Non	Non	Non
- Sub OpenCurrentDatabase (filepath As String, [Exclusive As Boolean = Faux], [bstrPassword As String])	Non			
- Property Get Parent As Object				
- Function PlainText (RichText As Variant, Optional Length As Variant) As String	Non	Non	Non	
- Property Get/Let/Set Printer As Printer	Non			
- Property Get Printers As Printers	Non			
- Property Get ProductCode As String				
- Sub Quit ([Option As AcQuitOption = acQuitSaveAll])				
- Property Get References As References				
- Sub RefreshDatabaseWindow ()				
- Sub RefreshTitleBar ()				
- Property Get Reports As Reports				
- Function Run (Procedure As String, Optional Arg1 As Variant, Optional Arg2 As Variant, Optional Arg3 As Variant, Optional Arg4 As Variant, Optional Arg5 As Variant, Optional Arg6 As Variant, Optional Arg7 As Variant, Optional Arg8 As Variant, Optional Arg9 As Variant, Optional Arg10 As Variant, Optional Arg11 As Variant, Optional Arg12 As Variant, Optional Arg13 As Variant, Optional Arg14 As Variant, Optional Arg15 As Variant, Optional Arg16 As Variant, Optional Arg17 As Variant, Optional Arg18 As Variant, Optional Arg19 As Variant, Optional Arg20 As Variant, Optional Arg21 As Variant, Optional Arg22 As Variant, Optional Arg23 As Variant, Optional Arg24 As Variant, Optional Arg25 As Variant, Optional Arg26 As Variant, Optional Arg27 As Variant, Optional Arg28 As Variant, Optional Arg29 As Variant, Optional Arg30 As Variant) As Variant				
- Sub RunCommand (Command As AcCommand)				
- Property Get Screen As Screen				

Classes et membres de la référence ACCESS

<i>Classe de membres : Application (Type : Classe)</i>	00	02	03	07 *
- Sub SetDefaultWorkgroupFile (Path As String)	Non			
- Sub SetHiddenAttribute (ObjectType As AcObjectType, ObjectName As String, fHidden As Boolean)				
- Sub SetOption (OptionName As String, Setting As Variant)				
- Property Get/Let ShortcutMenuBar As String				
- Function StringFromGUID (Guid As Variant) As Variant				
- Function SysCmd (Action As AcSysCmdAction, Optional Argument2 As Variant, Optional Argument3 As Variant) As Variant				
- Property Get TempVars As TempVars	Non	Non	Non	
- Sub TransformXML (DataSource As String, TransformSource As String, OutputTarget As String, [WellFormedXMLOutput As Boolean = Faux], [ScriptOption As AcTransformXMLScriptOption = acPromptScript])	Non	Non		
- Property Get/Let UserControl As Boolean				
- Property Get VBE As VBE				
- Property Get Version As String	Non			
- Property Get/Let Visible As Boolean				
<i>Classe de membres : Attachment (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean	Non	Non	Non	
- Property Get/Let AfterUpdate As String	Non	Non	Non	
- Event AfterUpdate ()	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get AttachmentCount As Long	Non	Non	Non	
- Event AttachmentCurrent ()	Non	Non	Non	
- Property Get/Let AutoLabel As Boolean	Non	Non	Non	
- Sub Back ()	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As Byte	Non	Non	Non	
- Property Get/Let BeforeUpdate As String	Non	Non	Non	
- Event BeforeUpdate (Cancel As Integer)	Non	Non	Non	
- Property Get/Let BorderColor As Long	Non	Non	Non	
- Property Get/Let BorderStyle As Byte	Non	Non	Non	
- Property Get/Let BorderWidth As Byte	Non	Non	Non	
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Property Get/Let ColumnHidden As Boolean	Non	Non	Non	
- Property Get/Let ColumnOrder As Integer	Non	Non	Non	
- Property Get/Let ColumnWidth As Integer	Non	Non	Non	
- Property Get Controls As Children	Non	Non	Non	
- Property Get/Let ControlSource As String	Non	Non	Non	
- Property Get/Let ControlTipText As String	Non	Non	Non	
- Property Get/Let ControlType As Byte	Non	Non	Non	
- Property Get/Let CurrentAttachment As Long	Non	Non	Non	
- Event DblClick (Cancel As Integer)	Non	Non	Non	
- Property Get/Let DefaultPicture As String	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : Attachment (Type : Classe)</i>	00	02	03	07 *
- Event Dirty (Cancel As Integer)	Non	Non	Non	
- Property Get/Let DisplayAs As AcDisplayAs	Non	Non	Non	
- Property Get/Let DisplayWhen As Byte	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Property Get/Let EventProcPrefix As String	Non	Non	Non	
- Event Exit (Cancel As Integer)	Non	Non	Non	
- Property Get FileName (Optional var As Variant) As String	Non	Non	Non	
- Property Get FileType (Optional var As Variant) As String	Non	Non	Non	
- Property Get FileURL (Optional var As Variant) As String	Non	Non	Non	
- Sub Forward ()	Non	Non	Non	
- Event GotFocus ()	Non	Non	Non	
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer	Non	Non	Non	
- Property Get/Let HelpContextId As Long	Non	Non	Non	
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean	Non	Non	Non	
- Event KeyDown (KeyCode As Integer, Shift As Integer)	Non	Non	Non	
- Event KeyPress (KeyAscii As Integer)	Non	Non	Non	
- Event KeyUp (KeyCode As Integer, Shift As Integer)	Non	Non	Non	
- Property Get/Let LabelAlign As Byte	Non	Non	Non	
- Property Get/Let LabelX As Integer	Non	Non	Non	
- Property Get/Let LabelY As Integer	Non	Non	Non	
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer	Non	Non	Non	
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Event LostFocus ()	Non	Non	Non	
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get/Let OldBorderStyle As Byte	Non	Non	Non	
- Property Get OldValue As Variant	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : Attachment (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OnAttachmentCurrent As String	Non	Non	Non	
- Property Get/Let OnChange As String	Non	Non	Non	
- Property Get/Let OnClick As String	Non	Non	Non	
- Property Get/Let OnDbClick As String	Non	Non	Non	
- Property Get/Let OnDirty As String	Non	Non	Non	
- Property Get/Let OnEnter As String	Non	Non	Non	
- Property Get/Let OnExit As String	Non	Non	Non	
- Property Get/Let OnGotFocus As String	Non	Non	Non	
- Property Get/Let OnKeyDown As String	Non	Non	Non	
- Property Get/Let OnKeyPress As String	Non	Non	Non	
- Property Get/Let OnKeyUp As String	Non	Non	Non	
- Property Get/Let OnLostFocus As String	Non	Non	Non	
- Property Get/Let OnMouseDown As String	Non	Non	Non	
- Property Get/Let OnMouseMove As String	Non	Non	Non	
- Property Get/Let OnMouseUp As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let PictureAlignment As Byte	Non	Non	Non	
- Property Get/Let PictureSizeMode As Byte	Non	Non	Non	
- Property Get/Let PictureTiling As Boolean	Non	Non	Non	
- Property Get Properties As Properties	Non	Non	Non	
- Sub Requery ()	Non	Non	Non	
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer	Non	Non	Non	
- Sub SetFocus ()	Non	Non	Non	
- Property Get/Let ShortcutMenuBar As String	Non	Non	Non	
- Sub SizeToFit ()	Non	Non	Non	
- Property Get/Let SpecialEffect As Byte	Non	Non	Non	
- Property Get/Let StatusBarText As String	Non	Non	Non	
- Property Get/Let TabIndex As Integer	Non	Non	Non	
- Property Get/Let TabStop As Boolean	Non	Non	Non	
- Property Get/Let Tag As String	Non	Non	Non	
- Property Get/Let Top As Integer	Non	Non	Non	
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	
- Property Get/Let Width As Integer	Non	Non	Non	

<i>Classe de membres : AutoCorrect (Type : Classe)</i>	00	02	03	07 *
--	----	----	----	------

- Property Get/Let DisplayAutoCorrectOptions As Boolean	Non	Non		
---	-----	-----	--	--

<i>Classe de membres : BoundObjectFrame (Type : Classe)</i>	00	02	03	07 *
---	----	----	----	------

- Property Get/Let Action As Integer				
- Property Get/Let AddColon As Boolean				
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get Application As Application				

Classes et membres de la référence ACCESS

Classe de membres : **BoundObjectFrame** (Type : Classe)

	00	02	03	07 *
- Property Get/Let AutoActivate As Integer				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let Class As String				
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DisplayType As Boolean				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				

Classes et membres de la référence ACCESS

<i>Classe de membres : BoundObjectFrame (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Property Get/Let LpOleObject As Long				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get Object As Object				
- Property Get ObjectVerbs (Index As Long) As String				
- Property Get/Let ObjectVerbsCount As Long				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OLEType As Byte				
- Property Get/Let OLETypeAllowed As Byte				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OnUpdated As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Scaling As Byte				
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let SizeMode As Byte				
- Sub SizeToFit ()				
- Property Get/Let SourceDoc As String				

Classes et membres de la référence ACCESS

Classe de membres : **BoundObjectFrame** (Type : Classe)

	00	02	03	07 *
- Property Get/Let Sourceltem As String				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Event Updated (Code As Integer)				
- Property Get/Let UpdateOptions As Integer				
- Property Get/Let Value As Variant				
- Property Get/Let Verb As Long				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **CheckBox** (Type : Classe)

	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DefaultValue As String				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : </i> CheckBox (Type : Classe)	00	02	03	07 *
- Property Get/Let GridLineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridLineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridLineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- EventMouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OptionValue As Long				

Classes et membres de la référence ACCESS

<i>Classe de membres : CheckBox (Type : Classe)</i>	00	02	03	07 *
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let TripleState As Boolean				
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : Class (Type : Classe)</i>	00	02	03	07 *
- Event Initialize ()	Non		Non	
- Event Terminate ()	Non		Non	

<i>Classe de membres : CodeData (Type : Classe)</i>	00	02	03	07 *
- Property Get AllDatabaseDiagrams As AllDatabaseDiagrams				
- Property Get AllFunctions As AllFunctions	Non			
- Property Get AllQueries As AllQueries				
- Property Get AllStoredProcedures As AllStoredProcedures				
- Property Get AllTables As AllTables				
- Property Get AllViews As AllViews				

<i>Classe de membres : CodeProject (Type : Classe)</i>	00	02	03	07 *
- Property Get AccessConnection As Connection	Non			
- Property Get AllDataAccessPages As AllDataAccessPages				Non
- Property Get AllForms As AllForms				
- Property Get AllMacros As AllMacros				
- Property Get AllModules As AllModules				
- Property Get AllReports As AllReports				
- Property Get Application As Application				
- Property Get BaseConnectionString As String				
- Sub CloseConnection ()				

Classes et membres de la référence ACCESS

<i>Classe de membres : CodeProject (Type : Classe)</i>	00	02	03	07 *
- Property Get Connection As Connection				
- Property Get FileFormat As AcFileFormat	Non			
- Property Get FullName As String				
- Property Get ImportExportSpecifications As ImportExportSpecifications	Non	Non	Non	
- Property Get IsConnected As Boolean				
- Property Get IsTrusted As Boolean	Non	Non	Non	
- Property Get Name As String				
- Sub OpenConnection (Optional BaseConnectionString As Variant, Optional UserID As Variant, Optional Password As Variant)				
- Property Get Parent As Object				
- Property Get Path As String				
- Property Get ProjectType As AcProjectType				
- Property Get Properties As AccessObjectProperties				
- Property Get/Let RemovePersonalInformation As Boolean	Non			
- Sub UpdateDependencyInfo ()	Non	Non		

<i>Classe de membres : ComboBox (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Sub AddItem (Item As String, Optional Index As Variant)	Non			
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get/Let AllowAutoCorrect As Boolean				
- Property Get/Let AllowedText As Byte		Non	Non	Non
- Property Get/Let AllowValueListEdits As Boolean	Non	Non	Non	
- Property Get Application As Application				
- Property Get/Let AutoExpand As Boolean				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomMargin As Integer	Non	Non	Non	
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let BoundColumn As Long				
- Property Get/Let CanGrow As Boolean	Non	Non	Non	
- Property Get/Let CanShrink As Boolean	Non	Non	Non	
- Event Change ()				
- Event Click ()				
- Property Get Column (Index As Long, Optional Row As Variant) As Variant				
- Property Get/Let ColumnCount As Integer				
- Property Get/Let ColumnHeads As Boolean				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				

Classes et membres de la référence ACCESS

Classe de membres : ComboBox (Type : Classe)	00	02	03	07 *
- Property Get/Let ColumnWidth As Integer				
- Property Get/Let ColumnWidths As String				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DecimalPlaces As Byte				
- Property Get/Let DefaultValue As String				
- Event Dirty (Cancel As Integer)	Non			
- Property Get/Let DisplayAsHyperlink As AcDisplayAsHyperlink	Non	Non	Non	
- Property Get/Let DisplayWhen As Byte				
- Sub Dropdown ()				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Property Get/Let Format As String				
- Property Get FormatConditions As FormatConditions				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let IMEHold As Boolean				
- Property Get/Let IMEMode As AclmeMode				
- Property Get/Let IMESentenceMode As AclmeSentenceMode				
- Property Get/Let InheritValueList As Boolean	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : **ComboBox (Type : Classe)**

	00	02	03	07 *
- Property Get/Let InputMask As String				
- Property Get/Let IsHyperlink As Boolean				
- Property Get/Let IsVisible As Boolean				
- Property Get ItemData (Index As Long) As Variant				
- Property Get ItemsSelected As ItemsSelected	Non	Non	Non	
- Property Get/Let KeyboardLanguage As Byte				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftMargin As Integer	Non	Non	Non	
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let LimitToList As Boolean				
- Property Get/Let ListCount As Long				
- Property Get/Let ListIndex As Long				
- Property Get/Let ListItemsEditForm As String	Non	Non	Non	
- Property Get/Let ListRows As Integer				
- Property Get/Let ListWidth As String				
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Event NotInList (NewData As String, Response As Integer)				
- Property Get/Let NumeralShapes As Byte				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnChange As String				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnDirty As String	Non			
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				

Classes et membres de la référence ACCESS

Classe de membres : **ComboBox** (Type : Classe)

	00	02	03	07 *
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OnNotInList As String				
- Property Get/Let OnUndo As String	Non			
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Set Recordset As Object	Non			
- Sub RemoveItem (Index As Variant)	Non			
- Sub Requery ()				
- Property Get/Let RightMargin As Integer	Non	Non	Non	
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let RowSource As String				
- Property Get/Let RowSourceType As String				
- Property Get/Let ScrollBarAlign As Byte				
- Property Get/Let Section As Integer				
- Property Get/Let Selected (IRow As Long) As Long	Non	Non	Non	
- Property Get/Let SelLength As Integer				
- Property Get/Let SelStart As Integer				
- Property Get/Let SelText As String				
- Property Get/Let SeparatorCharacters As AcSeparatorCharacters	Non	Non	Non	
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let ShowOnlyRowSourceValues As Boolean	Non	Non	Non	
- Sub SizeToFit ()				
- Property Get SmartTags As SmartTags	Non	Non		
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Text As String				
- Property Get/Let TextAlign As Byte				
- Property Get/Let Top As Integer				
- Property Get/Let TopMargin As Integer	Non	Non	Non	
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Event Undo (Cancel As Integer)	Non			
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classes et membres de la référence ACCESS

<i>Classe de membres : CommandButton (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get/Let Alignment As Byte	Non	Non	Non	
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let AutoRepeat As Boolean				
- Property Get/Let BackStyle As Byte	Non	Non	Non	
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let Cancel As Boolean				
- Property Get/Let Caption As String				
- Event Click ()				
- Property Get Controls As Children				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Property Get/Let CursorOnHover As AcCursorOnHover	Non	Non	Non	
- Event DbClick (Cancel As Integer)				
- Property Get/Let Default As Boolean				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let HyperlinkAddress As String				
- Property Get/Let HyperlinkSubAddress As String				
- Property Get/Let IsVisible As Boolean				

Classes et membres de la référence ACCESS

<i>Classe de membres : CommandButton (Type : Classe)</i>	00	02	03	07 *
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- EventMouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureCaptionArrangement As AcPictureCaptionArrangement	Non	Non	Non	
- Property Get/Let PictureType As Byte				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				

Classes et membres de la référence ACCESS

Classe de membres : **CommandButton** (Type : Classe) 00 02 03 07 *

	00	02	03	07 *
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let Transparent As Boolean				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **Constants** (Type : Module) 00 02 03 07 *

	00	02	03	07 *
- Const acAltMask = 4 (&H4) As Integer				
- Const acApplyFilter = 1 (&H1) As Integer				
- Const acApplyServerFilter = 3 (&H3) As Integer				
- Const acCloseFilterWindow = 2 (&H2) As Integer				
- Const acCloseServerFilterWindow = 4 (&H4) As Integer				
- Const acCopy = 2 (&H2) As Integer				
- Const acCtrlMask = 2 (&H2) As Integer				
- Const acCut = 1 (&H1) As Integer				
- Const acDataErrAdded = 2 (&H2) As Integer				
- Const acDataErrContinue = 0 (&H0) As Integer				
- Const acDataErrDisplay = 1 (&H1) As Integer				
- Const acDelete = 6 (&H6) As Integer				
- Const acDeleteCancel = 1 (&H1) As Integer				
- Const acDeleteOK = 0 (&H0) As Integer				
- Const acDeleteUserCancel = 2 (&H2) As Integer				
- Const acEditMenu = 1 (&H1) As Integer				
- Const acEffectChisel = 5 (&H5) As Integer				
- Const acEffectEtched = 3 (&H3) As Integer				
- Const acEffectNormal = 0 (&H0) As Integer				
- Const acEffectRaised = 1 (&H1) As Integer				
- Const acEffectShadow = 4 (&H4) As Integer				
- Const acEffectSunken = 2 (&H2) As Integer				
- Const acExit = 2 (&H2) As Integer				
- Const acFile = 0 (&H0) As Integer				
- Const acFilterAdvanced = 1 (&H1) As Integer				
- Const acFilterByForm = 0 (&H0) As Integer				
- Const acFormatASP = "Microsoft Active Server Pages (*.asp)"				Non
- Const acFormatDAP = "Microsoft Access Data Access Page (*.html)"		Non	Non	Non
- Const acFormatDAP = "Microsoft Access Data Access Page (*.htm; *.html)"	Non			Non
- Const acFormatHTML = "HTML (*.html)"				
- Const acFormatIIS = "Microsoft IIS (*.htx; *.idc)"				Non
- Const acFormatPDF = "PDF Format (*.pdf)"	Non	Non	Non	
- Const acFormatRTF = "Rich Text Format (*.rtf)"				
- Const acFormatSNP = "Snapshot Format (*.snp)"				
- Const acFormatTXT = "MS-DOS Text (*.txt)"				
- Const acFormatXLS = "Microsoft Excel (*.xls)"				
- Const acFormatXLSB = "Microsoft Excel Binary Workbook (*.xlsb)"	Non	Non	Non	
- Const acFormatXLSX = "Microsoft Excel Workbook (*.xlsx)"	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : Constants (Type : Module)

	00	02	03	07 *
- Const acFormatXPS = "XPS Format (*.xps)"	Non	Non	Non	
- Const acFormBar = 0 (&H0) As Integer				
- Const acGridlinesBoth = 3 (&H3) As Integer				
- Const acGridlinesBothV2 = -1 (&HFFFF) As Integer				
- Const acGridlinesHoriz = 1 (&H1) As Integer				
- Const acGridlinesNone = 0 (&H0) As Integer				
- Const acGridlinesVert = 2 (&H2) As Integer				
- Const acLBClose = 8 (&H8) As Integer				
- Const acLBEnd = 9 (&H9) As Integer				
- Const acLBGetColumnCount = 4 (&H4) As Integer				
- Const acLBGetColumnWidth = 5 (&H5) As Integer				
- Const acLBGetFormat = 7 (&H7) As Integer				
- Const acLBGetRowCount = 3 (&H3) As Integer				
- Const acLBGetValue = 6 (&H6) As Integer				
- Const acLBInitialize = 0 (&H0) As Integer				
- Const acLBOpen = 1 (&H1) As Integer				
- Const acLeftButton = 1 (&H1) As Integer				
- Const acMenuCheck = 3 (&H3) As Integer				
- Const acMenuGray = 1 (&H1) As Integer				
- Const acMenuUncheck = 2 (&H2) As Integer				
- Const acMenuUngray = 0 (&H0) As Integer				
- Const acMenuVer1X = 11 (&HB) As Integer				
- Const acMenuVer20 = 20 (&H14) As Integer				
- Const acMenuVer70 = 70 (&H46) As Integer				
- Const acMiddleButton = 4 (&H4) As Integer				
- Const acNew = 0 (&H0) As Integer				
- Const acObject = 14 (&HE) As Integer				
- Const acObjectUpdate = 3 (&H3) As Integer				
- Const acObjectVerb = 0 (&H0) As Integer				
- Const acObjStateDirty = 2 (&H2) As Integer				
- Const acObjStateNew = 4 (&H4) As Integer				
- Const acObjStateOpen = 1 (&H1) As Integer				
- Const acOLEActivate = 7 (&H7) As Integer				
- Const acOLEActivateDoubleClick = 2 (&H2) As Integer				
- Const acOLEActivateGetFocus = 1 (&H1) As Integer				
- Const acOLEActivateManual = 0 (&H0) As Integer				
- Const acOLEChanged = 0 (&H0) As Integer				
- Const acOLEClose = 9 (&H9) As Integer				
- Const acOLEClosed = 2 (&H2) As Integer				
- Const acOLECopy = 4 (&H4) As Integer				
- Const acOLECreateEmbed = 0 (&H0) As Integer				
- Const acOLECreateFromFile = 1 (&H1) As Integer				
- Const acOLECreateLink = 1 (&H1) As Integer				
- Const acOLECreateNew = 0 (&H0) As Integer				
- Const acOLEDelete = 10 (&HA) As Integer				

Classes et membres de la référence ACCESS

Classe de membres : Constants (Type : Module)

	00	02	03	07 *
- Const acOLEDisplayContent = 0 (&H0) As Integer				
- Const acOLEDisplaylcon = 1 (&H1) As Integer				
- Const acOLEEITHER = 2 (&H2) As Integer				
- Const acOLEEmbedded = 1 (&H1) As Integer				
- Const acOLEFetchVerbs = 17 (&H11) As Integer				
- Const acOLEInsertObjDlg = 14 (&HE) As Integer				
- Const acOLELinked = 0 (&H0) As Integer				
- Const acOLENone = 3 (&H3) As Integer				
- Const acOLEPaste = 5 (&H5) As Integer				
- Const acOLEPasteSpecialDlg = 15 (&HF) As Integer				
- Const acOLERenamed = 3 (&H3) As Integer				
- Const acOLESaved = 1 (&H1) As Integer				
- Const acOLESizeAutoSize = 2 (&H2) As Integer				
- Const acOLESizeClip = 0 (&H0) As Integer				
- Const acOLESizeStretch = 1 (&H1) As Integer				
- Const acOLESizeZoom = 3 (&H3) As Integer				
- Const acOLEUpdate = 6 (&H6) As Integer				
- Const acOLEUpdateAutomatic = 0 (&H0) As Integer				
- Const acOLEUpdateFrozen = 1 (&H1) As Integer				
- Const acOLEUpdateManual = 2 (&H2) As Integer				
- Const acOLEVerbHide = -3 (&HFFFD) As Integer				
- Const acOLEVerbInPlaceActivate = -5 (&HFFFB) As Integer				
- Const acOLEVerbInPlaceUIActivate = -4 (&HFFFC) As Integer				
- Const acOLEVerbOpen = -2 (&HFFFE) As Integer				
- Const acOLEVerbPrimary = 0 (&H0) As Integer				
- Const acOLEVerbShow = -1 (&HFFFF) As Integer				
- Const acPaste = 3 (&H3) As Integer				
- Const acPrompt = 0 (&H0) As Integer				
- Const acRecordsMenu = 5 (&H5) As Integer				
- Const acRefresh = 5 (&H5) As Integer				
- Const acRightButton = 2 (&H2) As Integer				
- Const acSave = 1 (&H1) As Integer				
- Const acSaveForm = 4 (&H4) As Integer				
- Const acSaveFormAs = 5 (&H5) As Integer				
- Const acSaveRecord = 4 (&H4) As Integer				
- Const acSecFrmRptExecute = 256 (&H100) As Long				
- Const acSecFrmRptReadDef = 4 (&H4) As Long				
- Const acSecFrmRptWriteDef = 65548 (&H1000C) As Long				
- Const acSecMacExecute = 8 (&H8) As Long				
- Const acSecMacReadDef = 10 (&HA) As Long				
- Const acSecMacWriteDef = 65542 (&H10006) As Long				
- Const acSecModReadDef = 2 (&H2) As Long				
- Const acSecModWriteDef = 65542 (&H10006) As Long				
- Const acSelectAllRecords = 9 (&H9) As Integer				
- Const acSelectRecord = 8 (&H8) As Integer				

Classes et membres de la référence ACCESS

Classe de membres : Constants (Type : Module)

00 02 03 07 *

- Const acServerFilterByForm = 2 (&H2) As Integer
- Const acShiftMask = 1 (&H1) As Integer
- Const acShowAllRecords = 0 (&H0) As Integer
- Const acUndo = 0 (&H0) As Integer
- Const vbKey0 = 48 (&H30) As Integer
- Const vbKey1 = 49 (&H31) As Integer
- Const vbKey2 = 50 (&H32) As Integer
- Const vbKey3 = 51 (&H33) As Integer
- Const vbKey4 = 52 (&H34) As Integer
- Const vbKey5 = 53 (&H35) As Integer
- Const vbKey6 = 54 (&H36) As Integer
- Const vbKey7 = 55 (&H37) As Integer
- Const vbKey8 = 56 (&H38) As Integer
- Const vbKey9 = 57 (&H39) As Integer
- Const vbKeyA = 65 (&H41) As Integer
- Const vbKeyAdd = 107 (&H6B) As Integer
- Const vbKeyB = 66 (&H42) As Integer
- Const vbKeyBack = 8 (&H8) As Integer
- Const vbKeyC = 67 (&H43) As Integer
- Const vbKeyCancel = 3 (&H3) As Integer
- Const vbKeyCapital = 20 (&H14) As Integer
- Const vbKeyClear = 12 (&HC) As Integer
- Const vbKeyControl = 17 (&H11) As Integer
- Const vbKeyD = 68 (&H44) As Integer
- Const vbKeyDecimal = 110 (&H6E) As Integer
- Const vbKeyDelete = 46 (&H2E) As Integer
- Const vbKeyDivide = 111 (&H6F) As Integer
- Const vbKeyDown = 40 (&H28) As Integer
- Const vbKeyE = 69 (&H45) As Integer
- Const vbKeyEnd = 35 (&H23) As Integer
- Const vbKeyEscape = 27 (&H1B) As Integer
- Const vbKeyExecute = 43 (&H2B) As Integer
- Const vbKeyF = 70 (&H46) As Integer
- Const vbKeyF1 = 112 (&H70) As Integer
- Const vbKeyF10 = 121 (&H79) As Integer
- Const vbKeyF11 = 122 (&H7A) As Integer
- Const vbKeyF12 = 123 (&H7B) As Integer
- Const vbKeyF13 = 124 (&H7C) As Integer
- Const vbKeyF14 = 125 (&H7D) As Integer
- Const vbKeyF15 = 126 (&H7E) As Integer
- Const vbKeyF16 = 127 (&H7F) As Integer
- Const vbKeyF2 = 113 (&H71) As Integer
- Const vbKeyF3 = 114 (&H72) As Integer
- Const vbKeyF4 = 115 (&H73) As Integer
- Const vbKeyF5 = 116 (&H74) As Integer

Classes et membres de la référence ACCESS

Classe de membres : Constants (Type : Module)

	00	02	03	07 *
- Const vbKeyF6 = 117 (&H75) As Integer				
- Const vbKeyF7 = 118 (&H76) As Integer				
- Const vbKeyF8 = 119 (&H77) As Integer				
- Const vbKeyF9 = 120 (&H78) As Integer				
- Const vbKeyG = 71 (&H47) As Integer				
- Const vbKeyH = 72 (&H48) As Integer				
- Const vbKeyHelp = 47 (&H2F) As Integer				
- Const vbKeyHome = 36 (&H24) As Integer				
- Const vbKeyI = 73 (&H49) As Integer				
- Const vbKeyInsert = 45 (&H2D) As Integer				
- Const vbKeyJ = 74 (&H4A) As Integer				
- Const vbKeyK = 75 (&H4B) As Integer				
- Const vbKeyL = 76 (&H4C) As Integer				
- Const vbKeyLButton = 1 (&H1) As Integer				
- Const vbKeyLeft = 37 (&H25) As Integer				
- Const vbKeyM = 77 (&H4D) As Integer				
- Const vbKeyMButton = 4 (&H4) As Integer				
- Const vbKeyMenu = 18 (&H12) As Integer				
- Const vbKeyMultiply = 106 (&H6A) As Integer				
- Const vbKeyN = 78 (&H4E) As Integer				
- Const vbKeyNumlock = 144 (&H90) As Integer				
- Const vbKeyNumpad0 = 96 (&H60) As Integer				
- Const vbKeyNumpad1 = 97 (&H61) As Integer				
- Const vbKeyNumpad2 = 98 (&H62) As Integer				
- Const vbKeyNumpad3 = 99 (&H63) As Integer				
- Const vbKeyNumpad4 = 100 (&H64) As Integer				
- Const vbKeyNumpad5 = 101 (&H65) As Integer				
- Const vbKeyNumpad6 = 102 (&H66) As Integer				
- Const vbKeyNumpad7 = 103 (&H67) As Integer				
- Const vbKeyNumpad8 = 104 (&H68) As Integer				
- Const vbKeyNumpad9 = 105 (&H69) As Integer				
- Const vbKeyO = 79 (&H4F) As Integer				
- Const vbKeyP = 80 (&H50) As Integer				
- Const vbKeyPageDown = 34 (&H22) As Integer				
- Const vbKeyPageUp = 33 (&H21) As Integer				
- Const vbKeyPause = 19 (&H13) As Integer				
- Const vbKeyPrint = 42 (&H2A) As Integer				
- Const vbKeyQ = 81 (&H51) As Integer				
- Const vbKeyR = 82 (&H52) As Integer				
- Const vbKeyRButton = 2 (&H2) As Integer				
- Const vbKeyReturn = 13 (&HD) As Integer				
- Const vbKeyRight = 39 (&H27) As Integer				
- Const vbKeyS = 83 (&H53) As Integer				
- Const vbKeySelect = 41 (&H29) As Integer				
- Const vbKeySeparator = 108 (&H6C) As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **Constants (Type : Module)**

	00	02	03	07 *
- Const vbKeyShift = 16 (&H10) As Integer				
- Const vbKeySnapshot = 44 (&H2C) As Integer				
- Const vbKeySpace = 32 (&H20) As Integer				
- Const vbKeySubtract = 109 (&H6D) As Integer				
- Const vbKeyT = 84 (&H54) As Integer				
- Const vbKeyTab = 9 (&H9) As Integer				
- Const vbKeyU = 85 (&H55) As Integer				
- Const vbKeyUp = 38 (&H26) As Integer				
- Const vbKeyV = 86 (&H56) As Integer				
- Const vbKeyW = 87 (&H57) As Integer				
- Const vbKeyX = 88 (&H58) As Integer				
- Const vbKeyY = 89 (&H59) As Integer				
- Const vbKeyZ = 90 (&H5A) As Integer				

Classe de membres : **Control (Type : Classe)**

	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get Column (Index As Long, Optional Row As Variant) As Variant				
- Property Get Controls As Children				
- Sub Dropdown ()				
- Property Get Form As Form				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get ItemData (Index As Long) As Variant				
- Property Get ItemsSelected As ItemsSelected				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Object As Object				
- Property Get ObjectVerbs (Index As Long) As String				
- Property Get OldValue As Variant				
- Property Get Pages As Pages				
- Property Get Parent As Object				
- Property Get Properties As Properties				

Classes et membres de la référence ACCESS

Classe de membres : **Control (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Property Get Report As Report				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Selected (IRow As Long) As Long				
- Sub SetFocus ()				
- Sub SizeToFit ()				
- Property Get SmartTags As SmartTags	Non	Non		
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Sub Undo ()				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	

Classe de membres : **Controls (Type : Dispatch)** 00 02 03 07 *

	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Object				
- Property Get Parent As Object				

Classe de membres : **CurrentData (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Property Get AllDatabaseDiagrams As AllDatabaseDiagrams				
- Property Get AllFunctions As AllFunctions	Non			
- Property Get AllQueries As AllQueries				
- Property Get AllStoredProcedures As AllStoredProcedures				
- Property Get AllTables As AllTables				
- Property Get AllViews As AllViews				

Classe de membres : **CurrentProject (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Property Get AccessConnection As Connection	Non			
- Property Get AllDataAccessPages As AllDataAccessPages				Non
- Property Get AllForms As AllForms				
- Property Get AllMacros As AllMacros				
- Property Get AllModules As AllModules				
- Property Get AllReports As AllReports				
- Property Get Application As Application				
- Property Get BaseConnectionString As String				
- Sub CloseConnection ()				
- Property Get Connection As Connection				
- Property Get FileFormat As AcFileFormat	Non			
- Property Get FullName As String				
- Property Get ImportExportSpecifications As ImportExportSpecifications	Non	Non	Non	
- Property Get IsConnected As Boolean				
- Property Get IsTrusted As Boolean	Non	Non	Non	
- Property Get Name As String				
- Sub OpenConnection (Optional BaseConnectionString As Variant, Optional UserID As Variant, Optional Password As Variant)				
- Property Get Parent As Object				
- Property Get Path As String				

Classes et membres de la référence ACCESS

Classe de membres : **CurrentProject (Type : Classe)** 00 02 03 07 *

- Property Get ProjectType As AcProjectType				
- Property Get Properties As AccessObjectProperties				
- Property Get/Let RemovePersonallInformation As Boolean	Non			
- Sub UpdateDependencyInfo ()	Non	Non		

Classe de membres : **CustomControl (Type : Classe)** 00 02 03 07 *

- Property Get/Let About As String				
- Property Get Application As Application				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let Cancel As Boolean				
- Property Get/Let Class As String				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Property Get/Let Custom As String				
- Property Get/Let Default As Boolean				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Event GotFocus ()				
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Left As Integer				
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Property Get/Let LpOleObject As Long				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get Object As Object				
- Property Get ObjectVerbs (Index As Long) As String				
- Property Get/Let ObjectVerbsCount As Long				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OLEClass As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnUpdated As String				

Classes et membres de la référence ACCESS

<i>Classe de membres : CustomControl (Type : Classe)</i>	00	02	03	07 *
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Event Updated (Code As Integer)				
- Property Get/Let Value As Variant				
- Property Get/Let Verb As Long				
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : DataAccessPage (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Sub ApplyTheme (ThemeName As String)				
- Property Get/Let ConnectionString As String				
- Property Get CurrentView As Integer				
- Property Get Document As Object				
- Property Get MailEnvelope As MsoEnvelope	Non			
- Property Get MSODSC As IDataSourceControl	Non		Non	Non
- Property Get MSODSC As Object	Non	Non		
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get/Let RemovePersonallInformation As Boolean	Non			
- Property Get/Let Tag As String		Non	Non	Non
- Property Get/Let Visible As Boolean				
- Property Get WebOptions As WebOptions				Non
- Property Get WindowHeight As Long				
- Property Get WindowWidth As Long				

<i>Classe de membres : DataAccessPages (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				Non
- Property Get Count As Long				Non
- Property Get Item (var As Variant) As DataAccessPage				Non
- Property Get Parent As Object				Non

<i>Classe de membres : DefaultWebOptions (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AlwaysSaveInDefaultEncoding As Boolean				Non
- Property Get Application As Application				
- Property Get/Let CheckIfOfficeIsHTMLEditor As Boolean				Non
- Property Get/Let DownloadComponents As Boolean				Non

Classes et membres de la référence ACCESS

Classe de membres : **DefaultWebOptions** (Type : Classe) 00 02 03 07 *

- Property Get/Let Encoding As MsoEncoding				Non
- Property Get FolderSuffix As String				Non
- Property Get/Let FollowedHyperlinkColor As AcColorIndex				
- Property Get/Let HyperlinkColor As AcColorIndex				
- Property Get/Let LocationOfComponents As String				Non
- Property Get/Let OrganizeInFolder As Boolean				Non
- Property Get Parent As Object				
- Property Get/Let TargetBrowser As MsoTargetBrowser	Non			Non
- Property Get/Let UnderlineHyperlinks As Boolean				
- Property Get/Let UseLongFileNames As Boolean				Non

Classe de membres : **DependencyInfo** (Type : Classe) 00 02 03 07 *

- Property Get Dependants As DependencyObjects	Non	Non		
- Property Get Dependencies As DependencyObjects	Non	Non		
- Property Get InsufficientPermissions As DependencyObjects	Non	Non		
- Property Get OutOfDateObjects As DependencyObjects	Non	Non		
- Property Get Parent As Object	Non	Non		
- Property Get UnsupportedObjects As DependencyObjects	Non	Non		

Classe de membres : **DependencyObjects** (Type : Classe) 00 02 03 07 *

- Property Get Application As Application	Non	Non		
- Property Get Count As Long	Non	Non		
- Property Get Item (Index As Variant) As AccessObject	Non	Non		
- Property Get Parent As Object	Non	Non		

Classe de membres : **DoCmd** (Type : Dispatch) 00 02 03 07 *

- Sub AddMenu (MenuName As Variant, MenuMacroName As Variant, StatusBarText As Variant)				
- Sub ApplyFilter (Optional FilterName As Variant, Optional WhereCondition As Variant)				Non
- Sub ApplyFilter (Optional FilterName As Variant, Optional WhereCondition As Variant, Optional ControlName As Variant)	Non	Non	Non	
- Sub Beep ()				
- Sub CancelEvent ()				
- Sub ClearMacroError ()	Non	Non	Non	
- Sub Close ([ObjectType As AcObjectType = acDefault], ObjectName As Variant, [Save As AcCloseSave = acSavePrompt])				
- Sub CloseDatabase ()	Non	Non	Non	
- Sub CopyDatabaseFile (DatabaseFileName As Variant, Optional OverwriteExistingFile As Variant, Optional DisconnectAllUsers As Variant)	Non			
- Sub CopyObject (DestinationDatabase As Variant, NewName As Variant, [SourceObjectType As AcObjectType = acDefault], Optional SourceObjectName As Variant)				
- Sub DeleteObject ([ObjectType As AcObjectType = acDefault], Optional ObjectName As Variant)				
- Sub DoMenuItem (MenuBar As Variant, MenuName As Variant, Command As Variant, Optional Subcommand As Variant, Optional Version As Variant)				
- Sub Echo (EchoOn As Variant, Optional StatusBarText As Variant)				
- Sub FindNext ()				

Classes et membres de la référence ACCESS

Classe de membres : DoCmd (Type : Dispatch)

	00	02	03	07 *
- Sub FindRecord (FindWhat As Variant, [Match As AcFindMatch = acEntire], MatchCase As Variant, [Search As AcSearchDirection = acSearchAll], SearchAsFormatted As Variant, [OnlyCurrentField As AcFindField = acCurrent], Optional FindFirst As Variant)				
- Sub GoToControl (ControlName As Variant)				
- Sub GoToPage (PageNumber As Variant, Optional Right As Variant, Optional Down As Variant)				
- Sub GoToRecord ([ObjectType As AcDataObjectType = acActiveDataObject], ObjectName As Variant, [Record As AcRecord = acNext], Optional Offset As Variant)				
- Sub Hourglass (HourglassOn As Variant)				
- Sub LockNavigationPane (Lock As Variant)	Non	Non	Non	
- Sub Maximize ()				
- Sub Minimize ()				
- Sub MoveSize (Optional Right As Variant, Optional Down As Variant, Optional Width As Variant, Optional Height As Variant)				
- Sub NavigateTo (Optional Category As Variant, Optional Group As Variant)	Non	Non	Non	
- Sub OpenDataAccessPage (DataAccessPageName As Variant, [View As AcDataAccessPageView = acDataAccessPageBrowse])				
- Sub OpenDiagram (DiagramName As Variant)				
- Sub OpenForm (FormName As Variant, [View As AcFormView = acNormal], FilterName As Variant, WhereCondition As Variant, [DataMode As AcFormOpenDataMode = acFormPropertySettings], [WindowMode As AcWindowMode = acWindowNormal], Optional OpenArgs As Variant)				
- Sub OpenFunction (FunctionName As Variant, [View As AcView = acViewNormal], [DataMode As AcOpenDataMode = acEdit])	Non			
- Sub OpenModule (Optional ModuleName As Variant, Optional ProcedureName As Variant)				
- Sub OpenQuery (QueryName As Variant, [View As AcView = acViewNormal], [DataMode As AcOpenDataMode = acEdit])				
- Sub OpenReport (ReportName As Variant, [View As AcView = acViewNormal], Optional FilterName As Variant, Optional WhereCondition As Variant)		Non	Non	Non
- Sub OpenReport (ReportName As Variant, [View As AcView = acViewNormal], FilterName As Variant, WhereCondition As Variant, [WindowMode As AcWindowMode = acWindowNormal], Optional OpenArgs As Variant)	Non			
- Sub OpenStoredProcedure (ProcedureName As Variant, [View As AcView = acViewNormal], [DataMode As AcOpenDataMode = acEdit])				
- Sub OpenTable (TableName As Variant, [View As AcView = acViewNormal], [DataMode As AcOpenDataMode = acEdit])				
- Sub OpenView (ViewName As Variant, [View As AcView = acViewNormal], [DataMode As AcOpenDataMode = acEdit])				
- Sub OutputTo (ObjectType As AcOutputObjectType, Optional ObjectName As Variant, Optional OutputFormat As Variant, Optional OutputFile As Variant, Optional AutoStart As Variant, Optional TemplateFile As Variant)		Non	Non	Non
- Sub OutputTo (ObjectType As AcOutputObjectType, Optional ObjectName As Variant, Optional OutputFormat As Variant, Optional OutputFile As Variant, Optional AutoStart As Variant, Optional TemplateFile As Variant, Optional Encoding As Variant)	Non			Non
- Sub OutputTo (ObjectType As AcOutputObjectType, ObjectName As Variant, OutputFormat As Variant, OutputFile As Variant, AutoStart As Variant, TemplateFile As Variant, Encoding As Variant, [OutputQuality As AcExportQuality = acExportQualityPrint])	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : DoCmd (Type : Dispatch)

	00	02	03	07 *
- Sub PrintOut ([PrintRange As AcPrintRange = acPrintAll], PageFrom As Variant, PageTo As Variant, [PrintQuality As AcPrintQuality = acHigh], Optional Copies As Variant, Optional CollateCopies As Variant)				
- Sub Quit ([Options As AcQuitOption = acQuitSaveAll])				
- Sub Rename (NewName As Variant, [ObjectType As AcObjectType = acDefault], Optional OldName As Variant)				
- Sub RepaintObject ([ObjectType As AcObjectType = acDefault], Optional ObjectName As Variant)				
- Sub Requery (Optional ControlName As Variant)				
- Sub Restore ()				
- Sub RunCommand (Command As AcCommand)				
- Sub RunMacro (MacroName As Variant, Optional RepeatCount As Variant, Optional RepeatExpression As Variant)				
- Sub RunSavedImportExport (SavedImportExportName As Variant)	Non	Non	Non	
- Sub RunSQL (SQLStatement As Variant, Optional UseTransaction As Variant)				
- Sub Save ([ObjectType As AcObjectType = acDefault], Optional ObjectName As Variant)				
- Sub SearchForRecord ([ObjectType As AcDataObjectType = acActiveDataObject], ObjectName As Variant, [Record As AcRecord = acFirst], Optional WhereCondition As Variant)	Non	Non	Non	
- Sub SelectObject (ObjectType As AcObjectType, Optional ObjectName As Variant, Optional InDatabaseWindow As Variant)				
- Sub SendObject ([ObjectType As AcSendObjectType = acSendNoObject], Optional ObjectName As Variant, Optional OutputFormat As Variant, Optional To As Variant, Optional Cc As Variant, Optional Bcc As Variant, Optional Subject As Variant, Optional MessageText As Variant, Optional EditMessage As Variant, Optional TemplateFile As Variant)				
- Sub SetDisplayedCategories (Show As Variant, Optional Category As Variant)	Non	Non	Non	
- Sub SetMenuItem (MenuItemIndex As Variant, Optional CommandIndex As Variant, Optional SubcommandIndex As Variant, Optional Flag As Variant)				
- Sub SetProperty (ControlName As Variant, [Property As AcProperty = acPropertyEnabled], Optional Value As Variant)	Non	Non	Non	
- Sub SetWarnings (WarningsOn As Variant)				
- Sub ShowAllRecords ()				
- Sub ShowToolbar (ToolbarName As Variant, [Show As AcShowToolbar = acToolbarYes])				
- Sub SingleStep ()	Non	Non	Non	
- Sub TransferDatabase ([TransferType As AcDataTransferType = acImport], DatabaseType As Variant, DatabaseName As Variant, [ObjectType As AcObjectType = acTable], Optional Source As Variant, Optional Destination As Variant, Optional StructureOnly As Variant, Optional StoreLogin As Variant)				
- Sub TransferSharePointList (TransferType As AcSharePointListTransferType, SiteAddress As Variant, ListID As Variant, Optional ViewID As Variant, Optional TableName As Variant, Optional GetLookupDisplayValues As Variant)	Non	Non	Non	
- Sub TransferSpreadsheet ([TransferType As AcDataTransferType = acImport], [SpreadsheetType As AcSpreadSheetType = acSpreadsheetTypeExcel97], Optional TableName As Variant, Optional FileName As Variant, Optional HasFieldNames As Variant, Optional Range As Variant, Optional UseOA As Variant)				Non

Classes et membres de la référence ACCESS

<i>Classe de membres : DoCmd (Type : Dispatch)</i>	00	02	03	07 *
- Sub TransferSpreadsheet ([TransferType As AcDataTransferType = acImport], [SpreadsheetType As AcSpreadSheetType = acSpreadsheetTypeExcel12Xml], Optional TableName As Variant, Optional FileName As Variant, Optional HasFieldNames As Variant, Optional Range As Variant, Optional UseOA As Variant)	Non	Non	Non	
- Sub TransferSQLDatabase (Server As Variant, Database As Variant, Optional UseTrustedConnection As Variant, Optional Login As Variant, Optional Password As Variant, Optional TransferCopyData As Variant)	Non			
- Sub TransferText ([TransferType As AcTextTransferType = acImportDelim], Optional SpecificationName As Variant, Optional TableName As Variant, Optional FileName As Variant, Optional HasFieldNames As Variant, Optional HTMLTableName As Variant, Optional CodePage As Variant)				

<i>Classe de membres : Form (Type : Classe)</i>	00	02	03	07 *
- Event Activate ()				
- Property Get ActiveControl As Control				
- Property Get/Let AfterDelConfirm As String				
- Event AfterDelConfirm (Status As Integer)				
- Property Get/Let AfterFinalRender As String	Non			
- Event AfterFinalRender (drawObject As Object)	Non			
- Property Get/Let AfterInsert As String				
- Event AfterInsert ()				
- Property Get/Let AfterLayout As String	Non			
- Event AfterLayout (drawObject As Object)	Non			
- Property Get/Let AfterRender As String	Non			
- Event AfterRender (drawObject As Object, chartObject As Object)	Non			
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get/Let AllowAdditions As Boolean				
- Property Get/Let AllowDatasheetView As Boolean	Non			
- Property Get/Let AllowDeletions As Boolean				
- Property Get/Let AllowDesignChanges As Boolean				Non
- Property Get/Let AllowEdits As Boolean				
- Property Get/Let AllowFilters As Boolean				
- Property Get/Let AllowFormView As Boolean	Non			
- Property Get/Let AllowLayoutView As Boolean	Non	Non	Non	
- Property Get/Let AllowPivotChartView As Boolean	Non			
- Property Get/Let AllowPivotTableView As Boolean	Non			
- Property Get Application As Application				
- Event ApplyFilter (Cancel As Integer, ApplyType As Integer)				
- Property Get/Let AutoCenter As Boolean				
- Property Get/Let AutoResize As Boolean				
- Property Get/Let BeforeDelConfirm As String				
- Event BeforeDelConfirm (Cancel As Integer, Response As Integer)				
- Property Get/Let BeforeInsert As String				
- Event BeforeInsert (Cancel As Integer)				
- Property Get/Let BeforeQuery As String	Non			
- Event BeforeQuery ()	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : Form (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let BeforeRender As String	Non			
- Event BeforeRender (drawObject As Object, chartObject As Object, Cancel As Object)	Non			
- Property Get/Let BeforeScreenTip As String	Non			
- Event BeforeScreenTip (ScreenTipText As Object, SourceObject As Object)	Non			
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let Bookmark As Variant				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let Caption As String				
- Property Get ChartSpace As ChartSpaceDeprecated	Non		Non	Non
- Property Get ChartSpace As ChartSpace	Non		Non	Non
- Property Get ChartSpace As Object	Non	Non		
- Event Click ()				
- Event Close ()				
- Property Get/Let CloseButton As Boolean				
- Property Get/Let CommandBeforeExecute As String	Non			
- Event CommandBeforeExecute (Command As Variant, Cancel As Object)	Non			
- Property Get/Let CommandChecked As String	Non			
- Event CommandChecked (Command As Variant, Checked As Object)	Non			
- Property Get/Let CommandEnabled As String	Non			
- Event CommandEnabled (Command As Variant, Enabled As Object)	Non			
- Property Get/Let CommandExecute As String	Non			
- Event CommandExecute (Command As Variant)	Non			
- Property Get/Let ControlBox As Boolean				
- Property Get Controls As Controls				
- Property Get/Let Count As Integer				
- Event Current ()				
- Property Get/Let CurrentRecord As Long				
- Property Get/Let CurrentSectionLeft As Integer				
- Property Get/Let CurrentSectionTop As Integer				
- Property Get/Let CurrentView As Integer				
- Property Get/Let Cycle As Byte				
- Property Get/Let DataChange As String	Non			
- Event DataChange (Reason As Long)	Non			
- Property Get/Let DataEntry As Boolean				
- Property Get/Let DataSetChange As String	Non			
- Event DataSetChange ()	Non			
- Property Get/Let DatasheetAlternateBackColor As Long	Non	Non	Non	
- Property Get/Let DatasheetBackColor As Long				
- Property Get/Let DatasheetBorderStyle As Byte	Non			
- Property Get/Let DatasheetCellsEffect As Byte				
- Property Get/Let DatasheetColumnHeaderUnderlineStyle As Byte	Non			
- Property Get/Let DatasheetFontHeight As Integer				
- Property Get/Let DatasheetFontItalic As Boolean				
- Property Get/Let DatasheetFontName As String				

Classes et membres de la référence ACCESS

Classe de membres : **Form (Type : Classe)**

	00	02	03	07 *
- Property Get/Let DatasheetFontUnderline As Boolean				
- Property Get/Let DatasheetFontWeight As Integer				
- Property Get/Let DatasheetForeColor As Long				
- Property Get/Let DatasheetGridlinesBehavior As Byte				
- Property Get/Let DatasheetGridlinesColor As Long				
- Event DblClick (Cancel As Integer)				
- Event Deactivate ()				
- Property Get DefaultControl (ControlType As Long) As Control				
- Property Get/Let DefaultView As Byte				
- Event Delete (Cancel As Integer)				
- Property Get/Let Dirty As Boolean				
- Event Dirty (Cancel As Integer)				
- Property Get/Let DisplayOnSharePointSite As Byte	Non	Non	Non	
- Property Get/Let DividingLines As Boolean				
- Event Error (DataErr As Integer, Response As Integer)				
- Property Get/Let FastLaserPrinting As Boolean				
- Property Get/Let FetchDefaults As Boolean	Non			
- Property Get/Let Filter As String				
- Event Filter (Cancel As Integer, FilterType As Integer)				
- Property Get/Let FilterOn As Boolean				
- Property Get/Let FilterOnLoad As Boolean	Non	Non	Non	
- Property Get/Let FitToScreen As Boolean	Non	Non	Non	
- Property Get Form As Form				
- Property Get/Let FrozenColumns As Integer				
- Event GotFocus ()				
- Sub GoToPage (PageNumber As Long, [Right As Long], [Down As Long])				
- Property Get/Let GridX As Integer				
- Property Get/Let GridY As Integer				
- Property Get/Let HasModule As Boolean				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HelpFile As String				
- Property Get/Let HorizontalDatasheetGridLineStyle As Byte	Non			
- Property Get/Let Hwnd As Long				
- Property Get/Let InputParameters As String				
- Property Get/Let InsideHeight As Long				
- Property Get/Let InsideWidth As Long				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Property Get/Let KeyPreview As Boolean				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LayoutForPrint As Boolean				
- Event Load ()				
- Event LostFocus ()				
- Property Get/Let MaxRecButton As Boolean				
- Property Get/Let MaxRecords As Long				

Classes et membres de la référence ACCESS

Classe de membres : **Form (Type : Classe)**

	00	02	03	07 *
- Property Get/Let MenuBar As String				
- Property Get/Let MinMaxButtons As Byte				
- Property Get/Let Modal As Boolean				
- Property Get Module As Module				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Property Get/Let MouseWheel As String	Non			
- Event MouseWheel (Page As Boolean, Count As Long)	Non			
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Moveable As Boolean	Non			
- Property Get/Let Name As String				
- Property Get/Let NavigationButtons As Boolean				
- Property Get/Let NavigationCaption As String	Non	Non	Non	
- Property Get NewRecord As Integer				
- Property Get/Let OnActivate As String				
- Property Get/Let OnApplyFilter As String				
- Property Get/Let OnClick As String				
- Property Get/Let OnClose As String				
- Property Get/Let OnConnect As String	Non			
- Event OnConnect ()	Non			
- Property Get/Let OnCurrent As String				
- Property Get/Let OnDbfClick As String				
- Property Get/Let OnDeactivate As String				
- Property Get/Let OnDelete As String				
- Property Get/Let OnDirty As String				
- Property Get/Let OnDisconnect As String	Non			
- Event OnDisconnect ()	Non			
- Property Get/Let OnError As String				
- Property Get/Let OnFilter As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLoad As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OnOpen As String				
- Property Get/Let OnResize As String				
- Property Get/Let OnTimer As String				
- Property Get/Let OnUndo As String	Non			
- Property Get/Let OnUnload As String				

Classes et membres de la référence ACCESS

Classe de membres : **Form (Type : Classe)**

	00	02	03	07 *
- Event Open (Cancel As Integer)				
- Property Get/Let OpenArgs As Variant				
- Property Get/Let OrderBy As String				
- Property Get/Let OrderByOn As Boolean				
- Property Get/Let OrderByOnLoad As Boolean	Non	Non	Non	
- Property Get/Let Orientation As Byte				
- Property Get/Let Page As Long				
- Property Get/Let Pages As Integer				
- Property Get/Let Painting As Boolean				
- Property Get/Let PaletteSource As String				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureAlignment As Byte				
- Property Get/Let PictureSizeMode As Byte				
- Property Get/Let PictureTiling As Boolean				
- Property Get/Let PictureType As Byte				
- Property Get PivotTable As PivotTableDeprecated	Non		Non	Non
- Property Get PivotTable As PivotTable	Non		Non	Non
- Property Get PivotTable As Object	Non	Non		
- Property Get/Let PivotTableChange As String	Non			
- Event PivotTableChange (Reason As Long)	Non			
- Property Get/Let PopUp As Boolean				
- Property Get/Let/Set Printer As Printer	Non			
- Property Get Properties As Properties				
- Property Get/Let Query As String	Non			
- Event Query ()	Non			
- Sub Recalc ()				
- Property Get/Let RecordLocks As Byte				
- Property Get/Let RecordSelectors As Boolean				
- Property Get/Set Recordset As Object				
- Property Get RecordsetClone As Object				
- Property Get/Let RecordsetType As Byte				
- Property Get/Let RecordSource As String				
- Property Get/Let RecordSourceQualifier As String	Non			
- Sub Refresh ()				
- Sub Repaint ()				
- Sub Requery ()				
- Event Resize ()				
- Property Get/Let ResyncCommand As String				
- Property Get/Let RibbonName As String	Non	Non	Non	
- Property Get/Let RowHeight As Integer				
- Property Get/Let ScrollBars As Byte				
- Property Get Section (Index As Variant) As Section				
- Property Get/Let SelectionChange As String	Non			
- Event SelectionChange ()	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : Form (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let SelHeight As Long				
- Property Get/Let SelLeft As Long				
- Property Get/Let SelTop As Long				
- Property Get/Let SelWidth As Long				
- Property Get/Let ServerFilter As String				
- Property Get/Let ServerFilterByForm As Boolean				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenu As Boolean				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let SplitFormDatasheet As AcSplitFormDatasheet	Non	Non	Non	
- Property Get/Let SplitFormOrientation As AcSplitFormOrientation	Non	Non	Non	
- Property Get/Let SplitFormPrinting As AcSplitFormPrinting	Non	Non	Non	
- Property Get/Let SplitFormSize As Long	Non	Non	Non	
- Property Get/Let SplitFormSplitterBar As Boolean	Non	Non	Non	
- Property Get/Let SplitFormSplitterBarSave As Boolean	Non	Non	Non	
- Property Get/Let SubdatasheetExpanded As Boolean				
- Property Get/Let SubdatasheetHeight As Integer				
- Property Get/Let Tag As String				
- Event Timer ()				
- Property Get/Let TimerInterval As Long				
- Property Get/Let Toolbar As String				
- Event Undo (Cancel As Integer)	Non			
- Sub Undo ()				
- Property Get/Let UniqueTable As String				
- Event Unload (Cancel As Integer)				
- Property Get/Let UseDefaultPrinter As Boolean	Non			
- Property Get/Let VerticalDdatasheetGridLineStyle As Byte	Non			
- Property Get/Let ViewChange As String	Non			
- Event ViewChange (Reason As Long)	Non			
- Property Get/Let ViewsAllowed As Byte				
- Property Get/Let Visible As Boolean				
- Property Get/Let WhatsThisButton As Boolean				Non
- Property Get/Let Width As Integer				
- Property Get/Let WindowHeight As Integer				
- Property Get WindowLeft As Integer	Non			
- Property Get WindowTop As Integer	Non			
- Property Get/Let WindowWidth As Integer				

<i>Classe de membres : FormatCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let BackColor As Long				
- Sub Delete ()				
- Property Get/Let Enabled As Boolean				
- Property Get Expression1 As String				
- Property Get Expression2 As String				
- Property Get/Let FontBold As Boolean				
- Property Get/Let FontItalic As Boolean				

Classes et membres de la référence ACCESS

<i>Classe de membres : FormatCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let ForeColor As Long				
- Sub Modify (Type As AcFormatConditionType, [Operator As AcFormatConditionOperator = acBetween], Optional Expression1 As Variant, Optional Expression2 As Variant)				
- Property Get Operator As AcFormatConditionOperator				
- Property Get Type As AcFormatConditionType				
<i>Classe de membres : FormatConditions (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Type As AcFormatConditionType, [Operator As AcFormatConditionOperator = acBetween], Optional Expression1 As Variant, Optional Expression2 As Variant) As FormatCondition				
- Property Get Application As Application				
- Property Get Count As Long				
- Sub Delete ()				
- Property Get Item (Index As Variant) As FormatCondition				
- Property Get Parent As Object				
<i>Classe de membres : Forms (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Form				
- Property Get Parent As Object				
<i>Classe de membres : GroupLevel (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let ControlSource As String				
- Property Get/Let GroupFooter As Boolean				
- Property Get/Let GroupHeader As Boolean				
- Property Get/Let GroupInterval As Long				
- Property Get/Let GroupOn As Integer				
- Property Get/Let KeepTogether As Byte				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let SortOrder As Boolean				
<i>Classe de membres : Hyperlink (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Address As String				
- Sub AddToFavorites ()				
- Sub CreateNewDocument (FileName As String, EditNow As Boolean, Overwrite As Boolean)				
- Property Get/Let EmailSubject As String				
- Sub Follow ([NewWindow As Boolean = Faux], [AddHistory As Boolean = Vrai], ExtraInfo As Variant, [Method As MsoExtraInfoMethod = msoMethodGet], [HeaderInfo As String])				
- Property Get/Let ScreenTip As String				
- Property Get/Let SubAddress As String				
- Property Get/Let TextToDisplay As String				

Classes et membres de la référence ACCESS

Classe de membres : **Image (Type : Classe)**

	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Event Click ()				
- Property Get Controls As Children				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridLineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridLineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridLineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridLineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let HyperlinkAddress As String				
- Property Get/Let HyperlinkSubAddress As String				
- Property Get/Let ImageHeight As Long				
- Property Get/Let ImageWidth As Long				
- Property Get/Let IsVisible As Boolean				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				

Classes et membres de la référence ACCESS

<i>Classe de membres : Image (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OnDbClick As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureAlignment As Byte				
- Property Get/Let PictureTiling As Boolean				
- Property Get/Let PictureType As Byte				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let SizeMode As Byte				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				
<i>Classe de membres : ImportExportSpecification (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Description As String	Non	Non	Non	
- Sub Execute (Optional Prompt As Variant)	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	
<i>Classe de membres : ImportExportSpecifications (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Name As String, SpecificationDefinition As String) As ImportExportSpecification	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Property Get Item (Index As Variant) As ImportExportSpecification	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
<i>Classe de membres : Label (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				

Classes et membres de la référence ACCESS

<i>Classe de membres : Label (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomMargin As Integer				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let Caption As String				
- Event Click ()				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DblClick (Cancel As Integer)				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let HyperlinkAddress As String				
- Property Get/Let HyperlinkSubAddress As String				
- Property Get/Let IsVisible As Boolean				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftMargin As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let LineSpacing As Integer				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				

Classes et membres de la référence ACCESS

<i>Classe de membres : Label (Type : Classe)</i>	00	02	03	07 *
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let NumeralShapes As Byte				
- Property Get/Let OldBorderStyle As Byte				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let RightMargin As Integer				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get SmartTags As SmartTags	Non	Non		
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let Tag As String				
- Property Get/Let TextAlign As Byte				
- Property Get/Let Top As Integer				
- Property Get/Let TopMargin As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let Vertical As Boolean				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				
<i>Classe de membres : Line (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let ControlType As Byte				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let Height As Integer				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Left As Integer				
- Property Get/Let LineSlant As Boolean				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				

Classes et membres de la référence ACCESS

<i>Classe de membres : Line (Type : Classe)</i>	00	02	03	07 *
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let Section As Integer				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : ListBox (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Sub AddItem (Item As String, Optional Index As Variant)	Non			
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get/Let AllowValueListEdits As Boolean	Non	Non	Non	
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BackColor As Long				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let BoundColumn As Long				
- Event Click ()				
- Property Get Column (Index As Long, Optional Row As Variant) As Variant				
- Property Get/Let ColumnCount As Integer				
- Property Get/Let ColumnHeads As Boolean				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get/Let ColumnWidths As String				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DblClick (Cancel As Integer)				
- Property Get/Let DefaultValue As String				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				

Classes et membres de la référence ACCESS

Classe de membres : **ListBox (Type : Classe)**

	00	02	03	07 *
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let IMEHold As Boolean				
- Property Get/Let IMEMode As AcImeMode				
- Property Get/Let IMESentenceMode As AcImeSentenceMode				
- Property Get/Let InheritValueList As Boolean	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get ItemData (Index As Long) As Variant				
- Property Get ItemsSelected As ItemsSelected				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let ListCount As Long				
- Property Get/Let ListIndex As Long				
- Property Get/Let ListItemsEditForm As String	Non	Non	Non	
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				

Classes et membres de la référence ACCESS

Classe de membres : **ListBox (Type : Classe)**

	00	02	03	07 *
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let MultiSelect As Byte				
- Property Get/Let Name As String				
- Property Get/Let NumeralShapes As Byte				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Set Recordset As Object	Non			
- Sub RemoveItem (Index As Variant)	Non			
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let RowSource As String				
- Property Get/Let RowSourceType As String				
- Property Get/Let ScrollBarAlign As Byte				
- Property Get/Let Section As Integer				
- Property Get/Let Selected (IRow As Long) As Long				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let ShowOnlyRowSourceValues As Boolean	Non	Non	Non	
- Sub SizeToFit ()				
- Property Get SmartTags As SmartTags	Non	Non		
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let TextAlign As Byte		Non	Non	Non
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	

Classes et membres de la référence ACCESS

Classe de membres : **ListBox (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **MacroError (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Property Get ActionName As String	Non	Non	Non	
- Property Get Arguments As String	Non	Non	Non	
- Property Get Condition As String	Non	Non	Non	
- Property Get Description As String	Non	Non	Non	
- Property Get MacroName As String	Non	Non	Non	
- Property Get Number As Long	Non	Non	Non	

Classe de membres : **Module (Type : Dispatch)** 00 02 03 07 *

	00	02	03	07 *
- Sub AddFromFile (FileName As String)				
- Sub AddFromString (String As String)				
- Property Get Application As Application				
- Property Get CountOfDeclarationLines As Long				
- Property Get CountOfLines As Long				
- Function CreateEventProc (EventName As String, ObjectName As String) As Long				
- Sub DeleteLines (StartLine As Long, Count As Long)				
- Function Find (Target As String, StartLine As Long, StartColumn As Long, EndLine As Long, EndColumn As Long, [WholeWord As Boolean = Faux], [MatchCase As Boolean = Faux], [PatternSearch As Boolean = Faux]) As Boolean				
- Sub InsertLines (Line As Long, String As String)				
- Sub InsertText (Text As String)				
- Property Get Lines (Line As Long, NumLines As Long) As String				
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get ProcBodyLine (ProcName As String, ProcKind As vbext_ProcKind) As Long				
- Property Get ProcCountLines (ProcName As String, ProcKind As vbext_ProcKind) As Long				
- Property Get ProcOfLine (Line As Long, pprockind As vbext_ProcKind) As String				
- Property Get ProcStartLine (ProcName As String, ProcKind As vbext_ProcKind) As Long				
- Sub ReplaceLine (Line As Long, String As String)				
- Property Get Type As AcModuleType				

Classe de membres : **Modules (Type : Dispatch)** 00 02 03 07 *

	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Module				
- Property Get Parent As Object				

Classe de membres : **ObjectFrame (Type : Classe)** 00 02 03 07 *

	00	02	03	07 *
- Property Get/Let Action As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **ObjectFrame** (Type : Classe)

	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let AutoActivate As Integer				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let Class As String				
- Event Click ()				
- Property Get/Let ColumnCount As Integer				
- Property Get/Let ColumnHeads As Boolean				
- Property Get Controls As Children				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DisplayType As Boolean				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Item As String				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let LinkChildFields As String				
- Property Get/Let LinkMasterFields As String				
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				

Classes et membres de la référence ACCESS

Classe de membres : **ObjectFrame** (Type : Classe)

	00	02	03	07 *
- Property Get/Let LpOleObject As Long				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get Object As Object				
- Property Get ObjectVerbs (Index As Long) As String				
- Property Get/Let ObjectVerbsCount As Long				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OLEClass As String				
- Property Get/Let OLEType As Byte				
- Property Get/Let OLETypeAllowed As Byte				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OnUpdated As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let RowSource As String				
- Property Get/Let RowSourceType As String				
- Property Get/Let Scaling As Byte				
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let SizeMode As Byte				
- Sub SizeToFit ()				
- Property Get/Let SourceDoc As String				
- Property Get/Let SourceItem As String				
- Property Get/Let SourceObject As String				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				

Classes et membres de la référence ACCESS

Classe de membres : **ObjectFrame** (Type : Classe) 00 02 03 07 *

	00	02	03	07 *
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Event Updated (Code As Integer)				
- Property Get/Let UpdateMethod As Integer				
- Property Get/Let UpdateOptions As Integer				
- Property Get/Let Verb As Long				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **OldConstants** (Type : Module) 00 02 03 07 *

	00	02	03	07 *
- Const A_ADD = 0 (&H0) As Integer				
- Const A_ALL = 0 (&H0) As Integer				
- Const A_ANYWHERE = 0 (&H0) As Integer				
- Const A_ATTACH = 2 (&H2) As Integer				
- Const A_COPY = 3 (&H3) As Integer				
- Const A_CURRENT = 1 (&H1) As Integer				
- Const A_CUT = 2 (&H2) As Integer				
- Const A_DELETE = 6 (&H6) As Integer				
- Const A_DELETE_V2 = 7 (&H7) As Integer				
- Const A_DESIGN = 1 (&H1) As Integer				
- Const A_DIALOG = 3 (&H3) As Integer				
- Const A_DOWN = 1 (&H1) As Integer				
- Const A_DRAFT = 3 (&H3) As Integer				
- Const A_EDIT = 1 (&H1) As Integer				
- Const A_EDITMENU = 1 (&H1) As Integer				
- Const A_ENTIRE = 1 (&H1) As Integer				
- Const A_EXIT = 2 (&H2) As Integer				
- Const A_EXPORT = 1 (&H1) As Integer				
- Const A_EXPORTDELIM = 2 (&H2) As Integer				
- Const A_EXPORTFIXED = 3 (&H3) As Integer				
- Const A_EXPORTMERGE = 4 (&H4) As Integer				
- Const A_FILE = 0 (&H0) As Integer				
- Const A_FIRST = 2 (&H2) As Integer				
- Const A_FORM = 2 (&H2) As Integer				
- Const A_FORMATRTF = "Rich Text Format (*.rtf)"				
- Const A_FORMATTXT = "MS-DOS Text (*.txt)"				
- Const A_FORMATXLS = "Microsoft Excel (*.xls)"				
- Const A_FORMBAR = 0 (&H0) As Integer				
- Const A_FORMDS = 3 (&H3) As Integer				
- Const A_GOTO = 4 (&H4) As Integer				
- Const A_HIDDEN = 1 (&H1) As Integer				
- Const A_HIGH = 0 (&H0) As Integer				
- Const A_ICON = 2 (&H2) As Integer				
- Const A_IMPORT = 0 (&H0) As Integer				
- Const A_IMPORTDELIM = 0 (&H0) As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **OldConstants (Type : Module)**

	00	02	03	07 *
- Const A_IMPORTFIXED = 1 (&H1) As Integer				
- Const A_LAST = 3 (&H3) As Integer				
- Const A_LOW = 2 (&H2) As Integer				
- Const A_MACRO = 4 (&H4) As Integer				
- Const A_MEDIUM = 1 (&H1) As Integer				
- Const A_MENU_VER1X = 11 (&HB) As Integer				
- Const A_MENU_VER20 = 20 (&H14) As Integer				
- Const A_MODULE = 5 (&H5) As Integer				
- Const A_NEW = 0 (&H0) As Integer				
- Const A_NEWREC = 5 (&H5) As Integer				
- Const A_NEXT = 1 (&H1) As Integer				
- Const A_NORMAL = 0 (&H0) As Integer				
- Const A_OBJECT = 14 (&HE) As Integer				
- Const A_OBJECTUPDATE = 3 (&H3) As Integer				
- Const A_OBJECTVERB = 0 (&H0) As Integer				
- Const A_PAGES = 2 (&H2) As Integer				
- Const A_PASTE = 4 (&H4) As Integer				
- Const A_PREVIEW = 2 (&H2) As Integer				
- Const A_PREVIOUS = 0 (&H0) As Integer				
- Const A_PRINTALL = 0 (&H0) As Integer				
- Const A_PROMPT = 0 (&H0) As Integer				
- Const A_QUERY = 1 (&H1) As Integer				
- Const A_READONLY = 2 (&H2) As Integer				
- Const A_RECORDSMENU = 3 (&H3) As Integer				
- Const A_REFRESH = 2 (&H2) As Integer				
- Const A_REPORT = 3 (&H3) As Integer				
- Const A_SAVE = 1 (&H1) As Integer				
- Const A_SAVEFORM = 2 (&H2) As Integer				
- Const A_SAVEFORMAS = 3 (&H3) As Integer				
- Const A_SAVERECORD = 4 (&H4) As Integer				
- Const A_SELECTALLRECORDS = 8 (&H8) As Integer				
- Const A_SELECTALLRECORDS_V2 = 9 (&H9) As Integer				
- Const A_SELECTION = 1 (&H1) As Integer				
- Const A_SELECTRECORD = 7 (&H7) As Integer				
- Const A_SELECTRECORD_V2 = 8 (&H8) As Integer				
- Const A_START = 2 (&H2) As Integer				
- Const A_TABLE = 0 (&H0) As Integer				
- Const A_TOOLBAR_NO = 2 (&H2) As Integer				
- Const A_TOOLBAR_WHERE_APPROP = 1 (&H1) As Integer				
- Const A_TOOLBAR_YES = 0 (&H0) As Integer				
- Const A_UNDO = 0 (&H0) As Integer				
- Const A_UNDOFIELD = 1 (&H1) As Integer				
- Const A_UP = 0 (&H0) As Integer				
- Const ALT_MASK = 4 (&H4) As Integer				
- Const CTRL_MASK = 2 (&H2) As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **OldConstants (Type : Module)**

00 02 03 07 *

- | - Const DATA_ERRADDED = 2 (&H2) As Integer | | | | |
|--|--|--|--|--|
| - Const DATA_ERRCONTINUE = 0 (&H0) As Integer | | | | |
| - Const DATA_ERRDISPLAY = 1 (&H1) As Integer | | | | |
| - Const DB_APPENDONLY = 8 (&H8) As Long | | | | |
| - Const DB_ATTACHEDODBC = 536870912 (&H20000000) As Long | | | | |
| - Const DB_ATTACHEDTABLE = 1073741824 (&H40000000) As Long | | | | |
| - Const DB_ATTACHEXCLUSIVE = 65536 (&H10000) As Long | | | | |
| - Const DB_ATTACHSAVEPWD = 131072 (&H20000) As Long | | | | |
| - Const DB_AUTOINCRFIELD = 16 (&H10) As Long | | | | |
| - Const DB_BINARY = 9 (&H9) As Integer | | | | |
| - Const DB_BOOLEAN = 1 (&H1) As Long | | | | |
| - Const DB_BYTE = 2 (&H2) As Long | | | | |
| - Const DB_CONSISTENT = 32 (&H20) As Long | | | | |
| - Const DB_CURRENCY = 5 (&H5) As Long | | | | |
| - Const DB_DATE = 8 (&H8) As Long | | | | |
| - Const DB_DECRYPT = 4 (&H4) As Long | | | | |
| - Const DB_DENYREAD = 2 (&H2) As Long | | | | |
| - Const DB_DENYWRITE = 1 (&H1) As Long | | | | |
| - Const DB_DESCENDING = 1 (&H1) As Long | | | | |
| - Const DB_DOUBLE = 7 (&H7) As Long | | | | |
| - Const DB_ENCRYPT = 2 (&H2) As Long | | | | |
| - Const DB_FAILONERROR = 128 (&H80) As Long | | | | |
| - Const DB_FIXEDFIELD = 1 (&H1) As Long | | | | |
| - Const DB_FORWARDONLY = 256 (&H100) As Long | | | | |
| - Const DB_FREELOCKS = 1 (&H1) As Long | | | | |
| - Const DB_HIDDENOBJECT = 1 (&H1) As Long | | | | |
| - Const DB_IGNORENULL = 8 (&H8) As Long | | | | |
| - Const DB_INCONSISTENT = 16 (&H10) As Long | | | | |
| - Const DB_INTEGER = 3 (&H3) As Long | | | | |
| - Const DB_LANG_ARABIC = ";LANGID=0x0401;CP=1256;COUNTRY=0" | | | | |
| - Const DB_LANG_CYRILLIC = ";LANGID=0x0419;CP=1251;COUNTRY=0" | | | | |
| - Const DB_LANG_CZECH = ";LANGID=0x0405;CP=1250;COUNTRY=0" | | | | |
| - Const DB_LANG_DUTCH = ";LANGID=0x0413;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_GENERAL = ";LANGID=0x0409;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_GREEK = ";LANGID=0x0408;CP=1253;COUNTRY=0" | | | | |
| - Const DB_LANG_HEBREW = ";LANGID=0x040D;CP=1255;COUNTRY=0" | | | | |
| - Const DB_LANG_HUNGARIAN = ";LANGID=0x040E;CP=1250;COUNTRY=0" | | | | |
| - Const DB_LANG_ICELANDIC = ";LANGID=0x040F;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_NORDIC = ";LANGID=0x041D;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_NORWDAN = ";LANGID=0x0414;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_POLISH = ";LANGID=0x0415;CP=1250;COUNTRY=0" | | | | |
| - Const DB_LANG_SPANISH = ";LANGID=0x040A;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_SWEDFIN = ";LANGID=0x040B;CP=1252;COUNTRY=0" | | | | |
| - Const DB_LANG_TURKISH = ";LANGID=0x041F;CP=1254;COUNTRY=0" | | | | |
| - Const DB_LONG = 4 (&H4) As Long | | | | |

Classes et membres de la référence ACCESS

Classe de membres : OldConstants (Type : Module)

	00	02	03	07 *
- Const DB_LONGBINARY = 11 (&HB) As Long				
- Const DB_MEMO = 12 (&HC) As Long				
- Const DB_NONULLS = 3 (&H3) As Integer				
- Const DB_OLE = 11 (&HB) As Integer				
- Const DB_OPEN_DYNASET = 2 (&H2) As Long				
- Const DB_OPEN_SNAPSHOT = 4 (&H4) As Long				
- Const DB_OPEN_TABLE = 1 (&H1) As Long				
- Const DB_OPTIONINIPATH = 1 (&H1) As Long				
- Const DB_PRIMARY = 2 (&H2) As Long				
- Const DB_PROHIBITNULL = 4 (&H4) As Long				
- Const DB_QACTION = 240 (&HF0) As Long				
- Const DB_QAPPEND = 64 (&H40) As Long				
- Const DB_QCROSSTAB = 16 (&H10) As Long				
- Const DB_QDDL = 96 (&H60) As Long				
- Const DB_QDELETE = 32 (&H20) As Long				
- Const DB_QMAKETABLE = 80 (&H50) As Long				
- Const DB_QSELECT = 0 (&H0) As Long				
- Const DB_QSETOPERATION = 128 (&H80) As Long				
- Const DB_QSPTBULK = 144 (&H90) As Long				
- Const DB_QSQLPASSTHROUGH = 112 (&H70) As Long				
- Const DB_QUERYDEF = 5 (&H5) As Long				
- Const DB_QUPDATE = 48 (&H30) As Long				
- Const DB_READONLY = 4 (&H4) As Long				
- Const DB_RELATIONDELETECASCADE = 4096 (&H1000) As Long				
- Const DB_RELATIONDONTENFORCE = 2 (&H2) As Long				
- Const DB_RELATIONINHERITED = 4 (&H4) As Long				
- Const DB_RELATIONLEFT = 16777216 (&H1000000) As Long				
- Const DB_RELATIONRIGHT = 33554432 (&H2000000) As Long				
- Const DB_RELATIONUNIQUE = 1 (&H1) As Long				
- Const DB_RELATIONUPDATECASCADE = 256 (&H100) As Long				
- Const DB_SEC_CREATE = 1 (&H1) As Long				
- Const DB_SEC_DBCREATE = 1 (&H1) As Long				
- Const DB_SEC_DBEXCLUSIVE = 4 (&H4) As Long				
- Const DB_SEC_DBOPEN = 2 (&H2) As Long				
- Const DB_SEC_DELETE = 65536 (&H10000) As Long				
- Const DB_SEC_DELETEDATA = 128 (&H80) As Long				
- Const DB_SEC_FRMRPT_EXECUTE = 256 (&H100) As Long				
- Const DB_SEC_FRMRPT_READDEF = 4 (&H4) As Long				
- Const DB_SEC_FRMRPT_WRITEDEF = 65548 (&H1000C) As Long				
- Const DB_SEC_FULLACCESS = 1048575 (&HFFFFF) As Long				
- Const DB_SEC_INSERTDATA = 32 (&H20) As Long				
- Const DB_SEC_MAC_EXECUTE = 8 (&H8) As Long				
- Const DB_SEC_MAC_READDEF = 10 (&HA) As Long				
- Const DB_SEC_MAC_WRITEDEF = 65542 (&H10006) As Long				
- Const DB_SEC_MOD_READDEF = 2 (&H2) As Long				

Classes et membres de la référence ACCESS

Classe de membres : **OldConstants (Type : Module)**

00 02 03 07 *

- Const DB_SEC_MOD_WRITEDEF = 65542 (&H10006) As Long
- Const DB_SEC_NOACCESS = 0 (&H0) As Long
- Const DB_SEC_READDEF = 4 (&H4) As Long
- Const DB_SEC_READSEC = 131072 (&H20000) As Long
- Const DB_SEC_REPLACEDATA = 64 (&H40) As Long
- Const DB_SEC_RETRIEVEDATA = 20 (&H14) As Long
- Const DB_SEC_WRITEDEF = 65548 (&H1000C) As Long
- Const DB_SEC_WRITEOWNER = 524288 (&H80000) As Long
- Const DB_SEC_WRITESEC = 262144 (&H40000) As Long
- Const DB_SINGLE = 6 (&H6) As Long
- Const DB_SORTARABIC = 267 (&H10B) As Long
- Const DB_SORTCYRILLIC = 263 (&H107) As Long
- Const DB_SORTCZECH = 264 (&H108) As Long
- Const DB_SORTDUTCH = 259 (&H103) As Long
- Const DB_SORTGENERAL = 256 (&H100) As Long
- Const DB_SORTGREEK = 269 (&H10D) As Long
- Const DB_SORTHEBREW = 268 (&H10C) As Long
- Const DB_SORTHUNGARIAN = 265 (&H109) As Long
- Const DB_SORTICELANDIC = 262 (&H106) As Long
- Const DB_SORTNORWDAN = 261 (&H105) As Long
- Const DB_SORTPDXINTL = 4096 (&H1000) As Long
- Const DB_SORTPDXNOR = 4098 (&H1002) As Long
- Const DB_SORTPDXSWE = 4097 (&H1001) As Long
- Const DB_SORTPOLISH = 266 (&H10A) As Long
- Const DB_SORTSPANISH = 258 (&H102) As Long
- Const DB_SORTSWEDFIN = 260 (&H104) As Long
- Const DB_SORTTURKISH = 270 (&H10E) As Long
- Const DB_SORTUNDEFINED = -1 (&HFFFFFFF) As Long
- Const DB_SQLPASSTHROUGH = 64 (&H40) As Long
- Const DB_SYSTEMOBJECT = -2147483646 (&H80000002) As Long
- Const DB_TABLE = 1 (&H1) As Long
- Const DB_TEXT = 10 (&HA) As Long
- Const DB_UNIQUE = 1 (&H1) As Long
- Const DB_UPDATABLEFIELD = 32 (&H20) As Long
- Const DB_VARIABLEFIELD = 2 (&H2) As Long
- Const DB_VERSION10 = 1 (&H1) As Long
- Const DB_VERSION11 = 8 (&H8) As Long
- Const DB_VERSION20 = 16 (&H10) As Long
- Const DELETE_CANCEL = 1 (&H1) As Integer
- Const DELETE_OK = 0 (&H0) As Integer
- Const DELETE_USER_CANCEL = 2 (&H2) As Integer
- Const LB_CLOSE = 8 (&H8) As Integer
- Const LB_END = 9 (&H9) As Integer
- Const LB_GETCOLUMNCOUNT = 4 (&H4) As Integer
- Const LB_GETCOLUMNWIDTH = 5 (&H5) As Integer

Classes et membres de la référence ACCESS

Classe de membres : **OldConstants (Type : Module)**

00 02 03 07 *

- Const LB_GETFORMAT = 7 (&H7) As Integer
- Const LB_GETROWCOUNT = 3 (&H3) As Integer
- Const LB_GETVALUE = 6 (&H6) As Integer
- Const LB_INITIALIZE = 0 (&H0) As Integer
- Const LB_OPEN = 1 (&H1) As Integer
- Const LEFT_BUTTON = 1 (&H1) As Integer
- Const MIDDLE_BUTTON = 4 (&H4) As Integer
- Const OBJSTATE_DIRTY = 2 (&H2) As Integer
- Const OBJSTATE_NEW = 4 (&H4) As Integer
- Const OBJSTATE_OPEN = 1 (&H1) As Integer
- Const OLE_CHANGED = 0 (&H0) As Integer
- Const OLE_CLOSED = 2 (&H2) As Integer
- Const OLE_RELEASE = 5 (&H5) As Integer
- Const OLE_RENAMED = 3 (&H3) As Integer
- Const OLE_SAVED = 1 (&H1) As Integer
- Const RIGHT_BUTTON = 2 (&H2) As Integer
- Const SHIFT_MASK = 1 (&H1) As Integer
- Const SYSCMD_ACCESSDIR = 9 (&H9) As Integer
- Const SYSCMD_ACCESSVER = 7 (&H7) As Integer
- Const SYSCMD_CLEARHELPTOPIC = 11 (&HB) As Integer
- Const SYSCMD_CLEARSTATUS = 5 (&H5) As Integer
- Const SYSCMD_GETOBJECTSTATE = 10 (&HA) As Integer
- Const SYSCMD_INIFILE = 8 (&H8) As Integer
- Const SYSCMD_INITMETER = 1 (&H1) As Integer
- Const SYSCMD_REMOVEMETER = 3 (&H3) As Integer
- Const SYSCMD_RUNTIME = 6 (&H6) As Integer
- Const SYSCMD_SETSTATUS = 4 (&H4) As Integer
- Const SYSCMD_UPDATEMETER = 2 (&H2) As Integer
- Const V_CURRENCY = 6 (&H6) As Integer
- Const V_DATE = 7 (&H7) As Integer
- Const V_DOUBLE = 5 (&H5) As Integer
- Const V_EMPTY = 0 (&H0) As Integer
- Const V_INTEGER = 2 (&H2) As Integer
- Const V_LONG = 3 (&H3) As Integer
- Const V_NULL = 1 (&H1) As Integer
- Const V_SINGLE = 4 (&H4) As Integer
- Const V_STRING = 8 (&H8) As Integer

Classe de membres : **OptionButton (Type : Classe)**

00 02 03 07 *

- Property Get/Let AddColon As Boolean
- Property Get/Let AfterUpdate As String
- Event AfterUpdate ()
- Property Get Application As Application
- Property Get/Let AutoLabel As Boolean
- Property Get/Let BeforeUpdate As String
- Event BeforeUpdate (Cancel As Integer)

Classes et membres de la référence ACCESS

Classe de membres : **OptionButton** (Type : Classe)

	00	02	03	07 *
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DefaultValue As String				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let Locked As Boolean				

Classes et membres de la référence ACCESS

Classe de membres : **OptionButton** (Type : Classe)

	00	02	03	07 *
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OptionValue As Long				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let TripleState As Boolean				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **OptionGroup (Type : Classe)**

	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DefaultValue As String				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get/Let Left As Integer				
- Property Get/Let Locked As Boolean				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				

Classes et membres de la référence ACCESS

Classe de membres : **OptionGroup (Type : Classe)**

	00	02	03	07 *
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **Page (Type : Classe)**

	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let Caption As String				
- Event Click ()				
- Property Get Controls As Children				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let Enabled As Boolean				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Left As Integer				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				

Classes et membres de la référence ACCESS

<i>Classe de membres : Page (Type : Classe)</i>	00	02	03	07 *
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let PageIndex As Integer				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureType As Byte				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Sub SetTabOrder ()	Non	Non	Non	
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let StatusBarText As String				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : PageBreak (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let ControlType As Byte				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Left As Integer				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let Section As Integer				
- Sub SizeToFit ()				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let Visible As Boolean				

<i>Classe de membres : Pages (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Optional Before As Variant) As Page				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Page				

Classes et membres de la référence ACCESS

<i>Classe de membres : Pages (Type : Dispatch)</i>	00	02	03	07 *
- Sub Remove (Optional Item As Variant)				
<i>Classe de membres : PaletteButton (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean	Non		Non	
- Property Get/Let AfterUpdate As String	Non		Non	
- Event AfterUpdate ()	Non		Non	
- Property Get Application As Application	Non		Non	
- Property Get/Let AutoLabel As Boolean	Non		Non	
- Property Get/Let BackColor As Long	Non		Non	
- Property Get/Let BackStyle As Byte	Non		Non	
- Property Get/Let BeforeUpdate As String	Non		Non	
- Event BeforeUpdate (Cancel As Integer)	Non		Non	
- Event Click ()	Non		Non	
- Property Get/Let ColumnHidden As Boolean	Non		Non	
- Property Get/Let ColumnOrder As Integer	Non		Non	
- Property Get/Let ColumnWidth As Integer	Non		Non	
- Property Get Controls As Children	Non		Non	
- Property Get/Let ControlSource As String	Non		Non	
- Property Get/Let ControlTipText As String	Non		Non	
- Property Get/Let ControlType As Byte	Non		Non	
- Event DblClick (Cancel As Integer)	Non		Non	
- Property Get/Let DefaultValue As String	Non		Non	
- Property Get/Let DisplayWhen As Byte	Non		Non	
- Property Get/Let Enabled As Boolean	Non		Non	
- Event Enter ()	Non		Non	
- Property Get/Let EventProcPrefix As String	Non		Non	
- Event Exit (Cancel As Integer)	Non		Non	
- Event GotFocus ()	Non		Non	
- Property Get/Let Height As Integer	Non		Non	
- Property Get/Let HelpContextId As Long	Non		Non	
- Property Get/Let HideDuplicates As Boolean	Non		Non	
- Property Get/Let IsVisible As Boolean	Non		Non	
- Event KeyDown (KeyCode As Integer, Shift As Integer)	Non		Non	
- Event KeyPress (KeyAscii As Integer)	Non		Non	
- Event KeyUp (KeyCode As Integer, Shift As Integer)	Non		Non	
- Property Get/Let LabelAlign As Byte	Non		Non	
- Property Get/Let LabelX As Integer	Non		Non	
- Property Get/Let LabelY As Integer	Non		Non	
- Property Get/Let Left As Integer	Non		Non	
- Property Get/Let Locked As Boolean	Non		Non	
- Event LostFocus ()	Non		Non	
- EventMouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non		Non	
- EventMouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non		Non	
- EventMouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non		Non	
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non		Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : PaletteButton (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Name As String	Non		Non	
- Property Get OldValue As Variant	Non		Non	
- Property Get/Let OnClick As String	Non		Non	
- Property Get/Let OnDbfClick As String	Non		Non	
- Property Get/Let OnEnter As String	Non		Non	
- Property Get/Let OnExit As String	Non		Non	
- Property Get/Let OnGotFocus As String	Non		Non	
- Property Get/Let OnKeyDown As String	Non		Non	
- Property Get/Let OnKeyPress As String	Non		Non	
- Property Get/Let OnKeyUp As String	Non		Non	
- Property Get/Let OnLostFocus As String	Non		Non	
- Property Get/Let OnMouseDown As String	Non		Non	
- Property Get/Let OnMouseMove As String	Non		Non	
- Property Get/Let OnMouseUp As String	Non		Non	
- Property Get/Let OptionValue As Long	Non		Non	
- Property Get Parent As Object	Non		Non	
- Property Get Properties As Properties	Non		Non	
- Sub Requery ()	Non		Non	
- Property Get/Let Section As Integer	Non		Non	
- Sub SetFocus ()	Non		Non	
- Property Get/Let ShortcutMenuBar As String	Non		Non	
- Sub SizeToFit ()	Non		Non	
- Property Get/Let StatusBarText As String	Non		Non	
- Property Get/Let TabIndex As Integer	Non		Non	
- Property Get/Let TabStop As Boolean	Non		Non	
- Property Get/Let Tag As String	Non		Non	
- Property Get/Let Top As Integer	Non		Non	
- Property Get/Let TripleState As Boolean	Non		Non	
- Property Get/Let ValidationRule As String	Non		Non	
- Property Get/Let ValidationText As String	Non		Non	
- Property Get/Let Value As Variant	Non		Non	
- Property Get/Let Visible As Boolean	Non		Non	
- Property Get/Let Width As Integer	Non		Non	

<i>Classe de membres : Printer (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let BottomMargin As Long	Non			
- Property Get/Let ColorMode As AcPrintColor	Non			
- Property Get/Let ColumnSpacing As Long	Non			
- Property Get/Let Copies As Long	Non			
- Property Get/Let DataOnly As Boolean	Non			
- Property Get/Let DefaultSize As Boolean	Non			
- Property Get DeviceName As String	Non			
- Property Get DriverName As String	Non			
- Property Get/Let Duplex As AcPrintDuplex	Non			
- Property Get/Let ItemLayout As AcPrintItemLayout	Non			
- Property Get/Let ItemsAcross As Long	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : Printer (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let ItemSizeHeight As Long	Non			
- Property Get/Let ItemSizeWidth As Long	Non			
- Property Get/Let LeftMargin As Long	Non			
- Property Get/Let Orientation As AcPrintOrientation	Non			
- Property Get/Let PaperBin As AcPrintPaperBin	Non			
- Property Get/Let PaperSize As AcPrintPaperSize	Non			
- Property Get Port As String	Non			
- Property Get/Let PrintQuality As AcPrintObjQuality	Non			
- Property Get/Let RightMargin As Long	Non			
- Property Get/Let RowSpacing As Long	Non			
- Property Get/Let TopMargin As Long	Non			
<i>Classe de membres : Printers (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Count As Long	Non			
- Property Get Item (Index As Variant) As Printer	Non			
- Property Get Parent As Object	Non			
<i>Classe de membres : Properties (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Object				
- Property Get Parent As Object				
<i>Classe de membres : Rectangle (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Event Click ()				
- Property Get/Let ControlType As Byte				
- Event DblClick (Cancel As Integer)				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let Height As Integer				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get/Let Left As Integer				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				

Classes et membres de la référence ACCESS

<i>Classe de membres : Rectangle (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OldBorderStyle As Byte				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let Section As Integer				
- Sub SizeToFit ()				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : Reference (Type : Dispatch)</i>	00	02	03	07 *
- Property Get BuiltIn As Boolean				
- Property Get Collection As References				
- Property Get FullPath As String				
- Property Get Guid As String				
- Property Get IsBroken As Boolean				
- Property Get Kind As vbext_RefKind				
- Property Get Major As Long				
- Property Get Minor As Long				
- Property Get Name As String				

<i>Classe de membres : References (Type : Classe)</i>	00	02	03	07 *
- Function AddFromFile (FileName As String) As Reference				
- Function AddFromGuid (Guid As String, Major As Long, Minor As Long) As Reference				
- Property Get Count As Long				
- Function Item (var As Variant) As Reference				
- Event ItemAdded (Reference As Reference)				
- Event ItemRemoved (Reference As Reference)				
- Property Get Parent As Object				
- Sub Remove (Reference As Reference)				

<i>Classe de membres : Report (Type : Classe)</i>	00	02	03	07 *
- Event Activate ()				
- Property Get ActiveControl As Control				
- Property Get/Let AllowLayoutView As Boolean	Non	Non	Non	
- Property Get/Let AllowReportView As Boolean	Non	Non	Non	
- Property Get Application As Application				
- Event ApplyFilter (Cancel As Integer, ApplyType As Integer)	Non	Non	Non	
- Property Get/Let AutoCenter As Boolean	Non			

Classes et membres de la référence ACCESS

<i>Classe de membres : Report (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AutoResize As Boolean	Non			
- Property Get/Let BorderStyle As Byte	Non			
- Property Get/Let Caption As String				
- Sub Circle (flags As Integer, X As Single, Y As Single, radius As Single, color As Long, start As Single, end As Single, aspect As Single)				
- Event Click ()	Non	Non	Non	
- Event Close ()				
- Property Get/Let CloseButton As Boolean	Non			
- Property Get/Let ControlBox As Boolean	Non			
- Property Get Controls As Controls				
- Property Get/Let Count As Integer				
- Event Current ()	Non	Non	Non	
- Property Get/Let CurrentRecord As Long				
- Property Get/Let CurrentView As Integer	Non	Non	Non	
- Property Get/Let CurrentX As Single				
- Property Get/Let CurrentY As Single				
- Property Get/Let Cycle As Byte	Non	Non	Non	
- Property Get/Let DateGrouping As Byte				
- Event DbClick (Cancel As Integer)	Non	Non	Non	
- Event Deactivate ()				
- Property Get DefaultControl (ControlType As Long) As Control				
- Property Get/Let DefaultView As Byte	Non	Non	Non	
- Property Get/Let Dirty As Boolean				
- Property Get/Let DisplayOnSharePointSite As Byte	Non	Non	Non	
- Property Get/Let DrawMode As Integer				
- Property Get/Let DrawStyle As Integer				
- Property Get/Let DrawWidth As Integer				
- Event Error (DataErr As Integer, Response As Integer)				
- Property Get/Let FastLaserPrinting As Boolean				
- Property Get/Let FillColor As Long				
- Property Get/Let FillStyle As Integer				
- Property Get/Let Filter As String				
- Event Filter (Cancel As Integer, FilterType As Integer)	Non	Non	Non	
- Property Get/Let FilterOn As Boolean				
- Property Get/Let FilterOnLoad As Boolean	Non	Non	Non	
- Property Get/Let FitToPage As Boolean	Non	Non	Non	
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Integer				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Integer				
- Property Get/Let ForeColor As Long				
- Property Get/Let FormatCount As Integer				
- Event GotFocus ()	Non	Non	Non	
- Property Get/Let GridX As Integer				

Classes et membres de la référence ACCESS

Classe de membres : Report (Type : Classe)

	00	02	03	07 *
- Property Get/Let GridY As Integer				
- Property Get GroupLevel (Index As Long) As GroupLevel				
- Property Get/Let GrpKeepTogether As Byte				
- Property Get/Let HasData As Long				
- Property Get/Let HasModule As Boolean				
- Property Get/Let Height As Long				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HelpFile As String				
- Property Get/Let Hwnd As Long				
- Property Get/Let InputParameters As String				
- Event KeyDown (KeyCode As Integer, Shift As Integer)	Non	Non	Non	
- Event KeyPress (KeyAscii As Integer)	Non	Non	Non	
- Property Get/Let KeyPreview As Boolean	Non	Non	Non	
- Event KeyUp (KeyCode As Integer, Shift As Integer)	Non	Non	Non	
- Property Get/Let LayoutForPrint As Boolean				
- Property Get/Let Left As Long				
- Sub Line (flags As Integer, x1 As Single, y1 As Single, x2 As Single, y2 As Single, color As Long)				
- Event Load ()	Non	Non	Non	
- Event LostFocus ()	Non	Non	Non	
- Property Get/Let MenuBar As String				
- Property Get/Let MinMaxButtons As Byte	Non			
- Property Get/Let Modal As Boolean	Non			
- Property Get Module As Module				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseWheel As String	Non	Non	Non	
- Event MouseWheel (Page As Boolean, Count As Long)	Non	Non	Non	
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Moveable As Boolean	Non			
- Property Get/Let MoveLayout As Boolean				
- Property Get/Let Name As String				
- Property Get/Let NextRecord As Boolean				
- Event NoData (Cancel As Integer)				
- Property Get/Let OnActivate As String				
- Property Get/Let OnApplyFilter As String	Non	Non	Non	
- Property Get/Let OnClick As String	Non	Non	Non	
- Property Get/Let OnClose As String				
- Property Get/Let OnCurrent As String	Non	Non	Non	
- Property Get/Let OnDbClick As String	Non	Non	Non	
- Property Get/Let OnDeactivate As String				
- Property Get/Let OnError As String				
- Property Get/Let OnFilter As String	Non	Non	Non	
- Property Get/Let OnGotFocus As String	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : Report (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OnKeyDown As String	Non	Non	Non	
- Property Get/Let OnKeyPress As String	Non	Non	Non	
- Property Get/Let OnKeyUp As String	Non	Non	Non	
- Property Get/Let OnLoad As String	Non	Non	Non	
- Property Get/Let OnLostFocus As String	Non	Non	Non	
- Property Get/Let OnMouseDown As String	Non	Non	Non	
- Property Get/Let OnMouseMove As String	Non	Non	Non	
- Property Get/Let OnMouseUp As String	Non	Non	Non	
- Property Get/Let OnNoData As String				
- Property Get/Let OnOpen As String				
- Property Get/Let OnPage As String				
- Property Get/Let OnResize As String	Non	Non	Non	
- Property Get/Let OnTimer As String	Non	Non	Non	
- Property Get/Let OnUnload As String	Non	Non	Non	
- Event Open (Cancel As Integer)				
- Property Get/Let OpenArgs As Variant	Non			
- Property Get/Let OrderBy As String				
- Property Get/Let OrderByOn As Boolean				
- Property Get/Let OrderByOnLoad As Boolean	Non	Non	Non	
- Property Get/Let Orientation As Byte				
- Property Get/Let Page As Long				
- Event Page ()				
- Property Get/Let PageFooter As Byte				
- Property Get/Let PageHeader As Byte				
- Property Get/Let Pages As Integer				
- Property Get/Let Painting As Boolean				
- Property Get/Let PaletteSource As String				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureAlignment As Byte				
- Property Get/Let PicturePages As Byte				
- Property Get/Let PictureSizeMode As Byte				
- Property Get/Let PictureTiling As Boolean				
- Property Get/Let PictureType As Byte				
- Property Get/Let PopUp As Boolean	Non			
- Sub Print (Expr As String)				
- Property Get/Let PrintCount As Integer				
- Property Get/Let/Set Printer As Printer	Non			
- Property Get/Let PrintSection As Boolean				
- Property Get Properties As Properties				
- Sub PSet (flags As Integer, X As Single, Y As Single, color As Long)				
- Property Get/Let RecordLocks As Byte				
- Property Get/Set Recordset As Object	Non			
- Property Get/Let RecordSource As String				
- Property Get/Let RecordSourceQualifier As String	Non			

Classes et membres de la référence ACCESS

Classe de membres : Report (Type : Classe)	00	02	03	07 *
- Property Get Report As Report				
- Sub Requery ()	Non	Non	Non	
- Event Resize ()	Non	Non	Non	
- Property Get/Let RibbonName As String	Non	Non	Non	
- Sub Scale (flags As Integer, x1 As Single, y1 As Single, x2 As Single, y2 As Single)				
- Property Get/Let ScaleHeight As Single				
- Property Get/Let ScaleLeft As Single				
- Property Get/Let ScaleMode As Integer				
- Property Get/Let ScaleTop As Single				
- Property Get/Let ScaleWidth As Single				
- Property Get/Let ScrollBars As Byte	Non	Non	Non	
- Property Get Section (Index As Variant) As Section				
- Property Get/Let ServerFilter As String				
- Property Get Shape As String	Non			
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let ShowPageMargins As Boolean	Non	Non	Non	
- Property Get/Let Tag As String				
- Function TextHeight (Expr As String) As Single				
- Function TextWidth (Expr As String) As Single				
- Event Timer ()	Non	Non	Non	
- Property Get/Let TimerInterval As Long	Non	Non	Non	
- Property Get/Let Toolbar As String				
- Property Get/Let Top As Long				
- Event Unload (Cancel As Integer)	Non	Non	Non	
- Property Get/Let UseDefaultPrinter As Boolean	Non			
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				
- Property Get/Let WindowHeight As Integer	Non			
- Property Get WindowLeft As Integer	Non			
- Property Get WindowTop As Integer	Non			
- Property Get/Let WindowWidth As Integer	Non			

Classe de membres : Reports (Type : Dispatch)	00	02	03	07 *
- Property Get Application As Application				
- Property Get Count As Long				
- Property Get Item (Index As Variant) As Report				
- Property Get Parent As Object				

Classe de membres : Screen (Type : Dispatch)	00	02	03	07 *
- Property Get ActiveControl As Control				
- Property Get ActiveDataAccessPage As DataAccessPage				Non
- Property Get ActiveDatasheet As Form				
- Property Get ActiveForm As Form				
- Property Get ActiveReport As Report				
- Property Get Application As Application				
- Property Get/Let MousePointer As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **Screen (Type : Dispatch)** 00 02 03 07 *

- Property Get Parent As Object
- Property Get PreviousControl As Control

Classe de membres : **Section (Type : Classe)** 00 02 03 07 *

- | - Property Get/Let AlternateBackColor As Long | Non | Non | Non | |
|---|-----|-----|-----|--|
| - Property Get Application As Application | | | | |
| - Property Get/Let AutoHeight As Boolean | Non | Non | Non | |
| - Property Get/Let BackColor As Long | | | | |
| - Property Get/Let CanGrow As Boolean | | | | |
| - Property Get/Let CanShrink As Boolean | | | | |
| - Event Click () | | | | |
| - Property Get Controls As Children | | | | |
| - Event DblClick (Cancel As Integer) | | | | |
| - Property Get/Let DisplayWhen As Byte | | | | |
| - Property Get/Let EventProcPrefix As String | | | | |
| - Property Get/Let ForceNewPage As Byte | | | | |
| - Property Get/Let HasContinued As Boolean | | | | |
| - Property Get/Let Height As Integer | | | | |
| - Property Get/Let KeepTogether As Boolean | | | | |
| - Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single) | | | | |
| - Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single) | | | | |
| - Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single) | | | | |
| - Property Get/Let Name As String | | | | |
| - Property Get/Let NewRowOrCol As Byte | | | | |
| - Property Get/Let OnClick As String | | | | |
| - Property Get/Let OnDblClick As String | | | | |
| - Property Get/Let OnFormat As String | | | | |
| - Property Get/Let OnMouseDown As String | | | | |
| - Property Get/Let OnMouseMove As String | | | | |
| - Property Get/Let OnMouseUp As String | | | | |
| - Property Get/Let OnPaint As String | Non | Non | Non | |
| - Property Get/Let OnPrint As String | | | | |
| - Property Get/Let OnRetreat As String | | | | |
| - Event Paint () | Non | Non | Non | |
| - Property Get Parent As Object | | | | |
| - Property Get Properties As Properties | | | | |
| - Property Get/Let RepeatSection As Boolean | | | | |
| - Sub SetTabOrder () | Non | Non | Non | |
| - Property Get/Let SpecialEffect As Byte | | | | |
| - Property Get/Let Tag As String | | | | |
| - Property Get/Let Visible As Boolean | | | | |
| - Property Get/Let WillContinue As Boolean | | | | |

Classe de membres : **SmartTag (Type : Classe)** 00 02 03 07 *

- | | | | | |
|---|-----|-----|--|--|
| - Property Get Application As Application | Non | Non | | |
| - Sub Delete () | Non | Non | | |

Classes et membres de la référence ACCESS

<i>Classe de membres : SmartTag (Type : Classe)</i>	00	02	03	07 *
- Property Get IsMissing As Boolean	Non	Non		
- Property Get Name As String	Non	Non		
- Property Get Parent As Object	Non	Non		
- Property Get Properties As SmartTagProperties	Non	Non		
- Property Get SmartTagActions As SmartTagActions	Non	Non		
- Property Get XML As String	Non	Non		
<i>Classe de membres : SmartTagAction (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non		
- Sub Execute ()	Non	Non		
- Property Get Name As String	Non	Non		
- Property Get Parent As Object	Non	Non		
<i>Classe de membres : SmartTagActions (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non		
- Property Get Count As Long	Non	Non		
- Property Get Item (Index As Variant) As SmartTagAction	Non	Non		
- Property Get Parent As Object	Non	Non		
<i>Classe de membres : SmartTagProperties (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String, Value As Variant) As SmartTagProperty	Non	Non		
- Property Get Application As Application	Non	Non		
- Property Get Count As Long	Non	Non		
- Property Get Item (Index As Variant) As SmartTagProperty	Non	Non		
- Property Get Parent As Object	Non	Non		
<i>Classe de membres : SmartTagProperty (Type : Classe)</i>	00	02	03	07 *
- Sub Delete ()	Non	Non		
- Property Get/Let Name As String	Non	Non		
- Property Get/Let Value As String	Non	Non		
<i>Classe de membres : SmartTags (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String) As SmartTag	Non	Non		
- Property Get Application As Application	Non	Non		
- Property Get Count As Long	Non	Non		
- Property Get Item (Index As Variant) As SmartTag	Non	Non		
- Property Get Parent As Object	Non	Non		
<i>Classe de membres : SubForm (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let CanGrow As Boolean				

Classes et membres de la référence ACCESS

Classe de membres : **SubForm (Type : Classe)**

	00	02	03	07 *
- Property Get/Let CanShrink As Boolean				
- Property Get Controls As Controls				
- Property Get/Let ControlType As Byte				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let FilterOnEmptyMaster As Boolean	Non	Non	Non	
- Property Get Form As Form				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let LinkChildFields As String				
- Property Get/Let LinkMasterFields As String				
- Property Get/Let Locked As Boolean				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let OldBorderStyle As Byte				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get Report As Report				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				

Classes et membres de la référence ACCESS

Classe de membres : **SubForm (Type : Classe)** 00 02 03 07 *

- Sub SizeToFit ()				
- Property Get/Let SourceObject As String				
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **SubReport (Type : Classe)** 00 02 03 07 *

- Property Get Application As Application				
- Event Enter ()				
- Event Exit (Cancel As Integer)				
- Property Get Form As Form				
- Property Get Parent As Object				
- Property Get Report As Report				

Classe de membres : **TabControl (Type : Classe)** 00 02 03 07 *

- Property Get Application As Application				
- Property Get/Let BackStyle As Byte				
- Event Change ()				
- Event Click ()				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Property Get/Let EventProcPrefix As String				
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let Left As Integer				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				

Classes et membres de la référence ACCESS

<i>Classe de membres : TabControl (Type : Classe)</i>	00	02	03	07 *
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let MultiRow As Boolean				
- Property Get/Let Name As String				
- Property Get OldValue As Variant				
- Property Get/Let OnChange As String				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get Pages As Pages				
- Property Get Parent As Object				
- Property Get Properties As Properties				
- Property Get/Let Section As Integer				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let StatusBarText As String				
- Property Get/Let Style As Byte				
- Property Get/Let TabFixedHeight As Integer				
- Property Get/Let TabFixedWidth As Integer				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : TempVar (Type : Classe)</i>	00	02	03	07 *
- Property Get Name As String	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	

<i>Classe de membres : TempVars (Type : Classe)</i>	00	02	03	07 *
- Sub Add (Name As String, Value As Variant)	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Property Get Item (Index As Variant) As TempVar	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (var As Variant)	Non	Non	Non	

Classes et membres de la référence ACCESS

<i>Classe de membres : TempVars (Type : Classe)</i>	00	02	03	07 *
- Sub RemoveAll ()	Non	Non	Non	
<i>Classe de membres : TextBox (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get/Let AllowAutoCorrect As Boolean				
- Property Get/Let AllowedText As Byte		Non	Non	Non
- Property Get Application As Application				
- Property Get/Let AsianLineBreak As Boolean	Non			
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let AutoTab As Boolean				
- Property Get/Let BackColor As Long				
- Property Get/Let BackStyle As Byte				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BorderColor As Long				
- Property Get/Let BorderStyle As Byte				
- Property Get/Let BorderWidth As Byte				
- Property Get/Let BottomMargin As Integer				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let CanGrow As Boolean				
- Property Get/Let CanShrink As Boolean				
- Event Change ()				
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DecimalPlaces As Byte				
- Property Get/Let DefaultValue As String				
- Event Dirty (Cancel As Integer)	Non			
- Property Get/Let DisplayAsHyperlink As AcDisplayAsHyperlink	Non	Non	Non	
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EnterKeyBehavior As Boolean				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let FELineBreak As Boolean		Non	Non	Non
- Property Get/Let FilterLookup As Byte				
- Property Get/Let FontBold As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **TextBox (Type : Classe)**

	00	02	03	07 *
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Property Get/Let Format As String				
- Property Get FormatConditions As FormatConditions				
- Property Get/Let FuriganaControl As String				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get Hyperlink As Hyperlink				
- Property Get/Let IMEHold As Boolean				
- Property Get/Let IMEMode As AclmeMode				
- Property Get/Let IMESentenceMode As AclmeSentenceMode				
- Property Get/Let InputMask As String				
- Property Get/Let IsHyperlink As Boolean				
- Property Get/Let IsVisible As Boolean				
- Property Get/Let KeyboardLanguage As Byte				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftMargin As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let LineSpacing As Integer				
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				

Classes et membres de la référence ACCESS

Classe de membres : **TextBox (Type : Classe)**

	00	02	03	07 *
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get/Let NumeralShapes As Byte				
- Property Get/Let OldBorderStyle As Byte				
- Property Get OldValue As Variant				
- Property Get/Let OnChange As String				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnDirty As String	Non			
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OnUndo As String	Non			
- Property Get Parent As Object				
- Property Get/Let PostalAddress As String				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightMargin As Integer				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let RunningSum As Byte				
- Property Get/Let ScrollBarAlign As Byte				
- Property Get/Let ScrollBars As Byte				
- Property Get/Let Section As Integer				
- Property Get/Let SelLength As Integer				
- Property Get/Let SelStart As Integer				
- Property Get/Let SelText As String				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Property Get/Let ShowDatePicker As Integer	Non	Non	Non	
- Sub SizeToFit ()				
- Property Get SmartTags As SmartTags	Non	Non		
- Property Get/Let SpecialEffect As Byte				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				

Classes et membres de la référence ACCESS

Classe de membres : **TextBox (Type : Classe)**

	00	02	03	07 *
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Text As String				
- Property Get/Let TextAlign As Byte				
- Property Get/Let TextFormat As AcTextFormat	Non	Non	Non	
- Property Get/Let Top As Integer				
- Property Get/Let TopMargin As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Event Undo (Cancel As Integer)	Non			
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let Vertical As Boolean				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

Classe de membres : **ToggleButton (Type : Classe)**

	00	02	03	07 *
- Property Get/Let AddColon As Boolean				
- Property Get/Let AfterUpdate As String				
- Event AfterUpdate ()				
- Property Get Application As Application				
- Property Get/Let AutoLabel As Boolean				
- Property Get/Let BeforeUpdate As String				
- Event BeforeUpdate (Cancel As Integer)				
- Property Get/Let BottomPadding As Integer	Non	Non	Non	
- Property Get/Let Caption As String				
- Event Click ()				
- Property Get/Let ColumnHidden As Boolean				
- Property Get/Let ColumnOrder As Integer				
- Property Get/Let ColumnWidth As Integer				
- Property Get Controls As Children				
- Property Get/Let ControlSource As String				
- Property Get/Let ControlTipText As String				
- Property Get/Let ControlType As Byte				
- Event DbClick (Cancel As Integer)				
- Property Get/Let DefaultValue As String				
- Property Get/Let DisplayWhen As Byte				
- Property Get/Let Enabled As Boolean				
- Event Enter ()				
- Property Get/Let EventProcPrefix As String				
- Event Exit (Cancel As Integer)				
- Property Get/Let FontBold As Integer				
- Property Get/Let FontItalic As Boolean				
- Property Get/Let FontName As String				

Classes et membres de la référence ACCESS

Classe de membres : **ToggleButton** (Type : Classe)

	00	02	03	07 *
- Property Get/Let FontSize As Integer				
- Property Get/Let FontUnderline As Boolean				
- Property Get/Let FontWeight As Integer				
- Property Get/Let ForeColor As Long				
- Event GotFocus ()				
- Property Get/Let GridlineColor As Long	Non	Non	Non	
- Property Get/Let GridlineStyleBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleRight As Byte	Non	Non	Non	
- Property Get/Let GridlineStyleTop As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthBottom As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthLeft As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthRight As Byte	Non	Non	Non	
- Property Get/Let GridlineWidthTop As Byte	Non	Non	Non	
- Property Get/Let Height As Integer				
- Property Get/Let HelpContextId As Long				
- Property Get/Let HideDuplicates As Boolean				
- Property Get/Let HorizontalAnchor As AcHorizontalAnchor	Non	Non	Non	
- Property Get/Let IsVisible As Boolean				
- Event KeyDown (KeyCode As Integer, Shift As Integer)				
- Event KeyPress (KeyAscii As Integer)				
- Event KeyUp (KeyCode As Integer, Shift As Integer)				
- Property Get/Let LabelAlign As Byte				
- Property Get/Let LabelX As Integer				
- Property Get/Let LabelY As Integer				
- Property Get Layout As AcLayoutType	Non	Non	Non	
- Property Get LayoutID As Long	Non	Non	Non	
- Property Get/Let Left As Integer				
- Property Get/Let LeftPadding As Integer	Non	Non	Non	
- Property Get/Let Locked As Boolean				
- Event LostFocus ()				
- Event MouseDown (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseMove (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Event MouseUp (Button As Integer, Shift As Integer, X As Single, Y As Single)				
- Sub Move (Left As Variant, Optional Top As Variant, Optional Width As Variant, Optional Height As Variant)	Non			
- Property Get/Let Name As String				
- Property Get OldValue As Variant				
- Property Get/Let OnClick As String				
- Property Get/Let OnDbClick As String				
- Property Get/Let OnEnter As String				
- Property Get/Let OnExit As String				
- Property Get/Let OnGotFocus As String				
- Property Get/Let OnKeyDown As String				
- Property Get/Let OnKeyPress As String				

Classes et membres de la référence ACCESS

<i>Classe de membres : ToggleButton (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OnKeyUp As String				
- Property Get/Let OnLostFocus As String				
- Property Get/Let OnMouseDown As String				
- Property Get/Let OnMouseMove As String				
- Property Get/Let OnMouseUp As String				
- Property Get/Let OptionValue As Long				
- Property Get Parent As Object				
- Property Get/Let Picture As String				
- Property Get/Let PictureType As Byte				
- Property Get Properties As Properties				
- Sub Requery ()				
- Property Get/Let RightPadding As Integer	Non	Non	Non	
- Property Get/Let Section As Integer				
- Sub SetFocus ()				
- Property Get/Let ShortcutMenuBar As String				
- Sub SizeToFit ()				
- Property Get/Let StatusBarText As String				
- Property Get/Let TabIndex As Integer				
- Property Get/Let TabStop As Boolean				
- Property Get/Let Tag As String				
- Property Get/Let Top As Integer				
- Property Get/Let TopPadding As Integer	Non	Non	Non	
- Property Get/Let TripleState As Boolean				
- Sub Undo ()				
- Property Get/Let ValidationRule As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				
- Property Get/Let VerticalAnchor As AcVerticalAnchor	Non	Non	Non	
- Property Get/Let Visible As Boolean				
- Property Get/Let Width As Integer				

<i>Classe de membres : WebOptions (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let DownloadComponents As Boolean				
- Property Get/Let Encoding As MsoEncoding				
- Property Get FolderSuffix As String				
- Property Get/Let LocationOfComponents As String				
- Property Get/Let OrganizeInFolder As Boolean				
- Property Get Parent As Object				
- Property Get/Let TargetBrowser As MsoTargetBrowser	Non			
- Sub UseDefaultFolderSuffix ()				
- Property Get/Let UseLongFileNames As Boolean				

Classes et membres de la référence ACCESS

* *Un membre marqué 'Non' est :*

- *soit absent de la référence;*
- *soit masqué;*
- *soit différent.*

Une classe de membres absente pour une version est indiquée par un n° de version rouge sur fond gris.