

---

*Classes et membres de la référence*

# *OUTLOOK*

---

## **Microsoft Outlook X.X Object Library**

**GUID** : {00062FFF-0000-0000-C000-000000000046}

**Source** : **Projet collaboratif d'étude des références de Microsoft ACCESS**

**Origine** : WWW.DEVELOPPEZ.COM

**Forum** : ACCESS -> Contribuez

**Auteur** : [PhilBen]

**Membres** : [Kikof], [Dolphy35], [Starec], [Jean-Paul LePetit], [Boulap]

**Remerciements** : [Cafeine], [Papy Turbo], [Tofalu]

**Version PDF** : 1.0 ext

## Les versions étudiées de la référence OUTLOOK

*Fichier* : **MSOUTL9.OLB**  
*Version ext.* : **9.0**                      *Version int.* : **9.0**  
*Fichier d'Aide* : **VBAOUTL9.CHM**  
*Version Office* : **2000 [00]**

---

*Nb de classes* : **113**                      *Nb de Membres* : **1927**

*Fichier* : **MSOUTL.OLB**  
*Version ext.* : **10.0**                      *Version int.* : **9.1**  
*Fichier d'Aide* : **VBAOL10.CHM**  
*Version Office* : **2002 [02]**

---

*Nb de classes* : **130**                      *Nb de Membres* : **2211**

*Fichier* : **MSOUTL.OLB**  
*Version ext.* : **11.0**                      *Version int.* : **9.2**  
*Fichier d'Aide* : **VBAOL11.CHM**  
*Version Office* : **2003 [03]**

---

*Nb de classes* : **136**                      *Nb de Membres* : **2323**

*Fichier* : **MSOUTL.OLB**  
*Versions ext.* : **12.0**                      *Versions int.* : **9.3**  
*Fichier d'Aide* : **VBAOL11.CHM**  
*Version Office* : **2007 [07]**

---

*Nb de classes* : **317**                      *Nb de Membres* : **4653**

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Account (Type : Classe)</i>	00	02	03	07 *
- Property Get AccountType As OIAccountType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get DisplayName As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get SmtAddress As String	Non	Non	Non	
- Property Get UserName As String	Non	Non	Non	

<i>Classe de membres : AccountRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Account As Account	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : Accounts (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Item (Index As Variant) As Account	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : Action (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get/Let CopyLike As OIActionCopyLike				
- Sub Delete ()				
- Property Get/Let Enabled As Boolean				
- Function Execute () As Object				
- Property Get/Let MessageClass As String				
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get/Let Prefix As String				
- Property Get/Let ReplyStyle As OIActionReplyStyle				
- Property Get/Let ResponseStyle As OIActionResponseStyle				
- Property Get Session As NameSpace				
- Property Get/Let ShowOn As OIActionShowOn				

<i>Classe de membres : Actions (Type : Dispatch)</i>	00	02	03	07 *
- Function Add () As Action				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Actions (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Count As Long				
- Function Item (Index As Variant) As Action				
- Property Get Parent As Object				
- Sub Remove (Index As Long)				
- Property Get Session As NameSpace				

<i>Classe de membres : AddressEntries (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Type As String, Optional Name As Variant, Optional Address As Variant) As AddressEntry				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function GetFirst () As AddressEntry				
- Function GetLast () As AddressEntry				
- Function GetNext () As AddressEntry				
- Function GetPrevious () As AddressEntry				
- Function Item (Index As Variant) As AddressEntry				
- Property Get Parent As Object				
- Property Get RawTable As Unknown	Mask	Mask	Mask	Mask
- Property Get Session As NameSpace				
- Sub Sort (Optional Property As Variant, Optional Order As Variant)				

<i>Classe de membres : AddressEntry (Type : Dispatch)</i>	00	02	03	07 *
- Property Get/Let Address As String				
- Property Get AddressEntryUserType As OIAddressEntryUserType	Non	Non	Non	
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Sub Delete ()				
- Sub Details (Optional HWnd As Variant)				
- Property Get DisplayType As OIDisplayType				
- Function GetContact () As ContactItem	Non	Non	Non	
- Function GetExchangeDistributionList () As ExchangeDistributionList	Non	Non	Non	
- Function GetExchangeUser () As ExchangeUser	Non	Non	Non	
- Function GetFreeBusy (Start As Date, MinPerChar As Long, Optional CompleteFormat As Variant) As String				
- Property Get ID As String				
- Property Get Manager As AddressEntry				Mask
- Property Get/Let MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get Members As AddressEntries				Mask
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace				
- Property Get/Let Type As String				
- Sub Update (Optional MakePermanent As Variant, Optional Refresh As Variant)				
- Sub UpdateFreeBusy ()	Mask	Mask	Mask	Mask

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : AddressList (Type : Dispatch)</i>	00	02	03	07 *
- Property Get AddressEntries As AddressEntries				
- Property Get AddressListType As OIAddressListType	Non	Non	Non	
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Function GetContactsFolder () As MAPIFolder	Non	Non	Non	
- Property Get ID As String				
- Property Get Index As Long				
- Property Get IsInitialAddressList As Boolean	Non	Non	Non	
- Property Get IsReadOnly As Boolean				
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get ResolutionOrder As Long	Non	Non	Non	
- Property Get Session As NameSpace				
<i>Classe de membres : AddressLists (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As AddressList				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : AddressRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Address As Variant	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : Application (Type : Classe)</i>	00	02	03	07 *
- Function ActiveExplorer () As Explorer				
- Function ActiveInspector () As Inspector				
- Function ActiveWindow () As Object				
- Function AdvancedSearch (Scope As String, Optional Filter As Variant, Optional SearchSubFolders As Variant, Optional Tag As Variant) As Search	Non			
- Event AdvancedSearchComplete (SearchObject As Search)	Non			
- Event AdvancedSearchStopped (SearchObject As Search)	Non			
- Property Get AnswerWizard As AnswerWizard				Mask
- Property Get Application As Application				
- Property Get Assistance As IAssistance	Non	Non	Non	
- Property Get Assistant As Assistant				Mask
- Event AttachmentContextMenuDisplay (CommandBar As CommandBar, Attachments As AttachmentSelection)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Application (Type : Classe)</i>	00	02	03	07 *
- Event BeforeFolderSharingDialog (FolderToShare As MAPIFolder, Cancel As Boolean)	Non	Non	Non	
- Property Get Class As OIObjectClass				
- Property Get COMAddIns As COMAddIns				
- Event ContextMenuClose (ContextMenu As OIContextMenu)	Non	Non	Non	
- Function CopyFile (FilePath As String, DestFolderPath As String) As Object	Non			
- Function CreateItem (ItemType As OIItemType) As Object				
- Function CreateItemFromTemplate (TemplatePath As String, Optional InFolder As Variant) As Object				
- Function CreateObject (ObjectName As String) As Object				
- Property Get DefaultProfileName As String	Non	Non	Non	
- Property Get Explorers As Explorers				
- Property Get/Let FeatureInstall As MsoFeatureInstall	Mask	Mask	Mask	Mask
- Event FolderContextMenuDisplay (CommandBar As CommandBar, Folder As Folder)	Non	Non	Non	
- Function GetNamespace (Type As String) As NameSpace				
- Sub GetNewNickNames (pvar As Variant)	Non	Mask	Mask	Mask
- Function GetObjectReference (Item As Object, ReferenceType As OIReferenceType) As Object	Non	Non	Non	
- Property Get Inspectors As Inspectors				
- Function IsSearchSynchronous (LookInFolders As String) As Boolean	Non			
- Property Get IsTrusted As Boolean	Non	Non	Non	
- Event ItemContextMenuDisplay (CommandBar As CommandBar, Selection As Selection)	Non	Non	Non	
- Event ItemLoad (Item As Object)	Non	Non	Non	
- Event ItemSend (Item As Object, Cancel As Boolean)				
- Property Get LanguageSettings As LanguageSettings				
- Event MAPILogonComplete ()	Non			
- Property Get Name As String				
- Event NewMail ()				
- Event NewMailEx (EntryIDCollection As String)	Non	Non		
- Event OptionsPagesAdd (Pages As PropertyPages)				
- Property Get Parent As Object				
- Property Get ProductCode As String				
- Event Quit ()				
- Sub Quit ()				
- Event Reminder (Item As Object)				
- Property Get Reminders As Reminders	Non			
- Property Get Session As NameSpace				
- Event ShortcutContextMenuDisplay (CommandBar As CommandBar, Shortcut As OutlookBarShortcut)	Non	Non	Non	
- Event Startup ()				
- Event StoreContextMenuDisplay (CommandBar As CommandBar, Store As Store)	Non	Non	Non	
- Property Get TimeZones As TimeZones	Non	Non	Non	
- Property Get Version As String				
- Event ViewContextMenuDisplay (CommandBar As CommandBar, View As View)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ApplicationEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event ItemSend (Item As Object, Cancel As Boolean)		Non	Non	Non
- Sub ItemSend (Item As Object, Cancel As Boolean)	Non			
- Event NewMail ()		Non	Non	Non
- Sub NewMail ()	Non			
- Event OptionsPagesAdd (Pages As PropertyPages)		Non	Non	Non
- Sub OptionsPagesAdd (Pages As PropertyPages)	Non			
- Event Quit ()		Non	Non	Non
- Sub Quit ()	Non			
- Event Reminder (Item As Object)		Non	Non	Non
- Sub Reminder (Item As Object)	Non			
- Event Startup ()		Non	Non	Non
- Sub Startup ()	Non			

<i>Classe de membres : AppointmentItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get/Let AllDayEvent As Boolean				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let BusyStatus As OIBusyStatus				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Sub ClearRecurrencePattern ()				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get/Let ConferenceServerAllowExternal As Boolean				Mask
- Property Get/Let ConferenceServerPassword As String				Mask
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : AppointmentItem (Type : Classe)</i>	00	02	03	07 *
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get/Let Duration As Long				
- Property Get/Let End As Date				
- Property Get/Let EndInEndTimeZone As Date	Non	Non	Non	
- Property Get/Let EndTimeZone As TimeZone	Non	Non	Non	
- Property Get/Let EndUTC As Date	Non	Non	Non	
- Property Get EntryID As String				
- Property Get/Let ForceUpdateToAllAttendees As Boolean	Non	Non	Non	
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function ForwardAsVcal () As MailItem				
- Property Get GetInspector As Inspector				
- Function GetRecurrencePattern () As RecurrencePattern				
- Property Get GlobalAppointmentID As String	Non	Non	Non	
- Property Get/Let Importance As OIImportance				
- Property Get/Let InternetCodepage As Long	Non			
- Property Get IsConflict As Boolean	Non			
- Property Get/Let IsOnlineMeeting As Boolean				Mask
- Property Get IsRecurring As Boolean				
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get/Let Location As String				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MeetingStatus As OIMeetingStatus				
- Property Get MeetingWorkspaceURL As String	Non	Non		
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NetMeetingAutoStart As Boolean				Mask
- Property Get/Let NetMeetingDocPathName As String				Mask
- Property Get/Let NetMeetingOrganizerAlias As String				Mask
- Property Get/Let NetMeetingServer As String				Mask
- Property Get/Let NetMeetingType As OINetMeetingType				Mask
- Property Get/Let NetShowURL As String				Mask
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get/Let OptionalAttendees As String				
- Property Get Organizer As String				



## Classes et membres de la référence OUTLOOK

<i>Classe de membres : AppointmentItem (Type : Classe)</i>	00	02	03	07 *
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Property Get Recipients As Recipients				
- Property Get RecurrenceState As OIRecurrenceState				
- Property Get/Let ReminderMinutesBeforeStart As Long				
- Property Get/Let ReminderOverrideDefault As Boolean				
- Property Get/Let ReminderPlaySound As Boolean				
- Property Get/Let ReminderSet As Boolean				
- Property Get/Let ReminderSoundFile As String				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Property Get/Let ReplyTime As Date				
- Property Get/Let RequiredAttendees As String				
- Property Get/Let Resources As String				
- Function Respond (Response As OIMeetingResponse, Optional fNoUI As Variant, Optional fAdditionalTextDialog As Variant) As MeetingItem				
- Property Get/Let ResponseRequested As Boolean				
- Property Get ResponseStatus As OIResponseStatus				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Sub Send ()				
- Property Get/Let SendUsingAccount As Account	Non	Non	Non	
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Start As Date				
- Property Get/Let StartInStartTimeZone As Date	Non	Non	Non	
- Property Get/Let StartTimeZone As TimeZone	Non	Non	Non	
- Property Get/Let StartUTC As Date	Non	Non	Non	
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				
<i>Classe de membres : AssignToCategoryRuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

### *Classe de membres : AssignToCategoryRuleAction (Type : Classe)*

	00	02	03	07 *
- Property Get/Let Categories As Variant	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

### *Classe de membres : Attachment (Type : Dispatch)*

	00	02	03	07 *
- Property Get Application As Application				
- Property Get BlockLevel As OIAttachmentBlockLevel	Non	Non	Non	
- Property Get Class As OIObjectClass				
- Sub Delete ()				
- Property Get/Let DisplayName As String				
- Property Get FileName As String				
- Property Get Index As Long				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get Parent As Object				
- Property Get PathName As String				
- Property Get/Let Position As Long				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Sub SaveAsFile (Path As String)				
- Property Get Session As NameSpace				
- Property Get Size As Long	Non	Non	Non	
- Property Get Type As OIAttachmentType				

### *Classe de membres : Attachments (Type : Dispatch)*

	00	02	03	07 *
- Function Add (Source As Variant, Optional Type As Variant, Optional Position As Variant, Optional DisplayName As Variant) As Attachment				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Attachment				
- Property Get Parent As Object				
- Sub Remove (Index As Long)				
- Property Get Session As NameSpace				

### *Classe de membres : AttachmentSelection (Type : Classe)*

	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Item (Index As Variant) As Attachment	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

### *Classe de membres : AutoFormatRule (Type : Classe)*

	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : AutoFormatRule (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Filter As String	Non	Non	Non	
- Property Get/Let Font As ViewFont	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	

<i>Classe de membres : AutoFormatRules (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String) As AutoFormatRule	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Insert (Name As String, Index As Variant) As AutoFormatRule	Non	Non	Non	
- Function Item (Index As Variant) As AutoFormatRule	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Sub RemoveAll ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : BusinessCardView (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Sub Apply ()	Non	Non	Non	
- Property Get/Let CardSize As Long	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get HeadingsFont As ViewFont	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get SortFields As OrderFields	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	

<i>Classe de membres : CalendarModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : CalendarModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	
<i>Classe de membres : CalendarSharing (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get/Let CalendarDetail As OICalendarDetail	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let EndDate As Date	Non	Non	Non	
- Property Get Folder As MAPIFolder	Non	Non	Non	
- Function ForwardAslCal (MailFormat As OICalendarMailFormat) As MailItem	Non	Non	Non	
- Property Get/Let IncludeAttachments As Boolean	Non	Non	Non	
- Property Get/Let IncludePrivateDetails As Boolean	Non	Non	Non	
- Property Get/Let IncludeWholeCalendar As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let RestrictToWorkingHours As Boolean	Non	Non	Non	
- Sub SaveAslCal (Path As String)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let StartDate As Date	Non	Non	Non	
<i>Classe de membres : CalendarView (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Sub Apply ()	Non	Non	Non	
- Property Get AutoFormatRules As AutoFormatRules	Non	Non	Non	
- Property Get/Let BoldDatesWithItems As Boolean	Non	Non	Non	
- Property Get/Let BoldSubjects As Boolean	Non	Non	Non	
- Property Get/Let CalendarViewMode As OICalendarViewMode	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Property Get/Let DaysInMultiDayMode As Long	Non	Non	Non	
- Property Get DayWeekFont As ViewFont	Non	Non	Non	
- Property Get DayWeekTimeFont As ViewFont	Non	Non	Non	
- Property Get/Let DayWeekTimeScale As OIDayWeekTimeScale	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get DisplayedDates As Variant	Non	Non	Non	
- Property Get/Let EndField As String	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get MonthFont As ViewFont	Non	Non	Non	
- Property Get/Let MonthShowEndTime As Boolean	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : CalendarView (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get/Let StartField As String	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	

<i>Classe de membres : CardView (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AllowInCellEditing As Boolean	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Sub Apply ()	Non	Non	Non	
- Property Get AutoFormatRules As AutoFormatRules	Non	Non	Non	
- Property Get BodyFont As ViewFont	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get HeadingsFont As ViewFont	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get/Let MultiLineFieldHeight As Long	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let ShowEmptyFields As Boolean	Non	Non	Non	
- Property Get SortFields As OrderFields	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get ViewFields As ViewFields	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	
- Property Get/Let Width As Long	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	

<i>Classe de membres : Categories (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String, Optional Color As Variant, Optional ShortcutKey As Variant) As Category	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : Categories (Type : Classe)</i>	00	02	03	07 *
- Function Item (Index As Variant) As Category	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : Category (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get CategoryBorderColor As Long	Non	Non	Non	
- Property Get CategoryGradientBottomColor As Long	Non	Non	Non	
- Property Get CategoryGradientTopColor As Long	Non	Non	Non	
- Property Get CategoryID As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Color As OICategoryColor	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let ShortcutKey As OICategoryShortcutKey	Non	Non	Non	
<i>Classe de membres : CategoryRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get/Let Categories As Variant	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : Column (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : ColumnFormat (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Align As OIAlign	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let FieldFormat As Long	Non	Non	Non	
- Property Get FieldType As OIUserPropertyType	Non	Non	Non	
- Property Get/Let Label As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Width As Long	Non	Non	Non	
<i>Classe de membres : Columns (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String) As Column	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Columns (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Item (Index As Variant) As Column	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Sub RemoveAll ()	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : Conflict (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non		
- Property Get Class As OIObjectClass	Non	Non		
- Property Get Item As Object	Non	Non		
- Property Get Name As String	Non	Non		
- Property Get Parent As Object	Non	Non		
- Property Get Session As NameSpace	Non	Non		
- Property Get Type As OIObjectClass	Non	Non		

<i>Classe de membres : Conflicts (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non		
- Property Get Class As OIObjectClass	Non	Non		
- Property Get Count As Long	Non	Non		
- Function GetFirst () As Conflict	Non	Non		
- Function GetLast () As Conflict	Non	Non		
- Function GetNext () As Conflict	Non	Non		
- Function GetPrevious () As Conflict	Non	Non		
- Function Item (Index As Variant) As Conflict	Non	Non		
- Property Get Parent As Object	Non	Non		
- Property Get Session As NameSpace	Non	Non		

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Account As String				
- Property Get Actions As Actions				
- Sub AddBusinessCardLogoPicture (Path As String)	Non	Non	Non	
- Sub AddPicture (Path As String)	Non	Non		
- Property Get/Let Anniversary As Date				
- Property Get Application As Application				
- Property Get/Let AssistantName As String				
- Property Get/Let AssistantTelephoneNumber As String				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Birthday As Date				
- Property Get/Let Body As String				
- Property Get/Let Business2TelephoneNumber As String				
- Property Get/Let BusinessAddress As String				
- Property Get/Let BusinessAddressCity As String				
- Property Get/Let BusinessAddressCountry As String				
- Property Get/Let BusinessAddressPostalCode As String				
- Property Get/Let BusinessAddressPostOfficeBox As String				
- Property Get/Let BusinessAddressState As String				
- Property Get/Let BusinessAddressStreet As String				
- Property Get/Let BusinessCardLayoutXml As String	Non	Non	Non	
- Property Get BusinessCardType As OIBusinessCardType	Non	Non	Non	
- Property Get/Let BusinessFaxNumber As String				
- Property Get/Let BusinessHomePage As String				
- Property Get/Let BusinessTelephoneNumber As String				
- Property Get/Let CallbackTelephoneNumber As String				
- Property Get/Let CarTelephoneNumber As String				
- Property Get/Let Categories As String				
- Property Get/Let Children As String				
- Property Get Class As OIObjectClass				
- Sub ClearTaskFlag ()	Non	Non	Non	
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get CompanyAndFullName As String				
- Property Get CompanyLastFirstNoSpace As String				
- Property Get CompanyLastFirstSpaceOnly As String				
- Property Get/Let CompanyMainTelephoneNumber As String				
- Property Get/Let CompanyName As String				
- Property Get/Let ComputerNetworkName As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Property Get/Let CustomerID As String				



## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Property Get/Let Department As String				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get/Let Email1Address As String				
- Property Get/Let Email1AddressType As String				
- Property Get Email1DisplayName As String		Non	Non	Non
- Property Get/Let Email1DisplayName As String	Non			
- Property Get Email1EntryID As String				
- Property Get/Let Email2Address As String				
- Property Get/Let Email2AddressType As String				
- Property Get Email2DisplayName As String		Non	Non	Non
- Property Get/Let Email2DisplayName As String	Non			
- Property Get Email2EntryID As String				
- Property Get/Let Email3Address As String				
- Property Get/Let Email3AddressType As String				
- Property Get Email3DisplayName As String		Non	Non	Non
- Property Get/Let Email3DisplayName As String	Non			
- Property Get Email3EntryID As String				
- Property Get EntryID As String				
- Property Get/Let FileAs As String				
- Property Get/Let FirstName As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function ForwardAsBusinessCard () As MailItem	Non	Non	Non	
- Function ForwardAsVcard () As MailItem				
- Property Get/Let FTPSite As String				
- Property Get/Let FullName As String				
- Property Get FullNameAndCompany As String				
- Property Get/Let Gender As OIGender				
- Property Get GetInspector As Inspector				
- Property Get/Let GovernmentIDNumber As String				
- Property Get HasPicture As Boolean	Non	Non		
- Property Get/Let Hobby As String				
- Property Get/Let Home2TelephoneNumber As String				
- Property Get/Let HomeAddress As String				
- Property Get/Let HomeAddressCity As String				
- Property Get/Let HomeAddressCountry As String				
- Property Get/Let HomeAddressPostalCode As String				
- Property Get/Let HomeAddressPostOfficeBox As String				
- Property Get/Let HomeAddressState As String				
- Property Get/Let HomeAddressStreet As String				
- Property Get/Let HomeFaxNumber As String				
- Property Get/Let HomeTelephoneNumber As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let IMAddress As String	Non			
- Property Get/Let Importance As OIImportance				
- Property Get/Let Initials As String				
- Property Get/Let InternetFreeBusyAddress As String				
- Property Get IsConflict As Boolean	Non			
- Property Get/Let ISDNNumber As String				
- Property Get IsMarkedAsTask As Boolean	Non	Non	Non	
- Property Get ItemProperties As ItemProperties	Non			
- Property Get/Let JobTitle As String				
- Property Get/Let Journal As Boolean				
- Property Get/Let Language As String				
- Property Get LastFirstAndSuffix As String				
- Property Get LastFirstNoSpace As String				
- Property Get LastFirstNoSpaceAndSuffix As String	Non			
- Property Get LastFirstNoSpaceCompany As String				
- Property Get LastFirstSpaceOnly As String				
- Property Get LastFirstSpaceOnlyCompany As String				
- Property Get LastModificationTime As Date				
- Property Get/Let LastName As String				
- Property Get LastNameAndFirstName As String				
- Property Get Links As Links				
- Property Get/Let MailingAddress As String				
- Property Get/Let MailingAddressCity As String				
- Property Get/Let MailingAddressCountry As String				
- Property Get/Let MailingAddressPostalCode As String				
- Property Get/Let MailingAddressPostOfficeBox As String				
- Property Get/Let MailingAddressState As String				
- Property Get/Let MailingAddressStreet As String				
- Property Get/Let ManagerName As String				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Sub MarkAsTask (MarkInterval As OIMarkInterval)	Non	Non	Non	
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let MiddleName As String				
- Property Get/Let Mileage As String				
- Property Get/Let MobileTelephoneNumber As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NetMeetingAlias As String				
- Property Get/Let NetMeetingServer As String				
- Property Get/Let NickName As String				
- Property Get/Let NoAging As Boolean				
- Property Get/Let OfficeLocation As String				
- Event Open (Cancel As Boolean)				
- Property Get/Let OrganizationalIDNumber As String				
- Property Get/Let OtherAddress As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let OtherAddressCity As String				
- Property Get/Let OtherAddressCountry As String				
- Property Get/Let OtherAddressPostalCode As String				
- Property Get/Let OtherAddressPostOfficeBox As String				
- Property Get/Let OtherAddressState As String				
- Property Get/Let OtherAddressStreet As String				
- Property Get/Let OtherFaxNumber As String				
- Property Get/Let OtherTelephoneNumber As String				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get/Let PagerNumber As String				
- Property Get Parent As Object				
- Property Get/Let PersonalHomePage As String				
- Property Get/Let PrimaryTelephoneNumber As String				
- Sub PrintOut ()				
- Property Get/Let Profession As String				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Property Get/Let RadioTelephoneNumber As String				
- Event Read ()				
- Property Get/Let ReferredBy As String				
- Property Get/Let ReminderOverrideDefault As Boolean	Non	Non	Non	
- Property Get/Let ReminderPlaySound As Boolean	Non	Non	Non	
- Property Get/Let ReminderSet As Boolean	Non	Non	Non	
- Property Get/Let ReminderSoundFile As String	Non	Non	Non	
- Property Get/Let ReminderTime As Date	Non	Non	Non	
- Sub RemovePicture ()	Non	Non		
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub ResetBusinessCard ()	Non	Non	Non	
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Sub SaveBusinessCardImage (Path As String)	Non	Non	Non	
- Property Get Saved As Boolean				
- Property Get/Let SelectedMailingAddress As OIMailingAddress				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowBusinessCardEditor ()	Non	Non	Non	
- Sub ShowCategoriesDialog ()	Non			
- Sub ShowCheckPhoneDialog (PhoneNumber As OIContactPhoneNumber)	Non	Non	Non	
- Property Get Size As Long				
- Property Get/Let Spouse As String				
- Property Get/Let Subject As String				
- Property Get/Let Suffix As String				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : ContactItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let TaskCompletedDate As Date	Non	Non	Non	
- Property Get/Let TaskDueDate As Date	Non	Non	Non	
- Property Get/Let TaskStartDate As Date	Non	Non	Non	
- Property Get/Let TaskSubject As String	Non	Non	Non	
- Property Get/Let TelexNumber As String				
- Property Get/Let Title As String				
- Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
- Property Get/Let TTYTDDTelephoneNumber As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get/Let User1 As String				
- Property Get/Let User2 As String				
- Property Get/Let User3 As String				
- Property Get/Let User4 As String				
- Property Get/Let UserCertificate As String				Mask
- Property Get UserProperties As UserProperties				
- Property Get/Let WebPage As String				
- Event Write (Cancel As Boolean)				
- Property Get/Let YomiCompanyName As String				
- Property Get/Let YomiFirstName As String				
- Property Get/Let YomiLastName As String				

<i>Classe de membres : ContactsModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	

<i>Classe de membres : DataSourceObject (Type : Classe)</i>	00	02	03	07 *
- OutlookItem As Object	Non		Non	Non

<i>Classe de membres : DDataSourceObject (Type : Dispatch)</i>	00	02	03	07 *
- OutlookItem As Object	Non		Non	Non

<i>Classe de membres : DistListItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Sub AddMember (Recipient As Recipient)	Non			
- Sub AddMembers (Recipients As Recipients)				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : DistListItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get CheckSum As Long	Mask	Mask	Mask	Mask
- Property Get Class As OIObjectClass				
- Sub ClearTaskFlag ()	Non	Non	Non	
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get/Let DLName As String				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Property Get GetInspector As Inspector				
- Function GetMember (Index As Long) As Recipient				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get IsMarkedAsTask As Boolean	Non	Non	Non	
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Sub MarkAsTask (MarkInterval As OIMarkInterval)	Non	Non	Non	
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : DistListItem (Type : Classe)</i>	00	02	03	07 *
Property Get MemberCount As Long				
Property Get/Let Members As Variant	Mask	Mask	Mask	Mask
Property Get/Let MessageClass As String				
Property Get/Let Mileage As String				
Function Move (DestFldr As MAPIFolder) As Object				
Property Get/Let NoAging As Boolean				
Property Get/Let OneOffMembers As Variant	Mask	Mask	Mask	Mask
Event Open (Cancel As Boolean)				
Property Get OutlookInternalVersion As Long				
Property Get OutlookVersion As String				
Property Get Parent As Object				
Sub PrintOut ()				
Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
Event PropertyChange (Name As String)				
Event Read ()				
Property Get/Let ReminderOverrideDefault As Boolean	Non	Non	Non	
Property Get/Let ReminderPlaySound As Boolean	Non	Non	Non	
Property Get/Let ReminderSet As Boolean	Non	Non	Non	
Property Get/Let ReminderSoundFile As String	Non	Non	Non	
Property Get/Let ReminderTime As Date	Non	Non	Non	
Sub RemoveMember (Recipient As Recipient)	Non			
Sub RemoveMembers (Recipients As Recipients)				
Event Reply (Response As Object, Cancel As Boolean)				
Event ReplyAll (Response As Object, Cancel As Boolean)				
Sub Save ()				
Sub SaveAs (Path As String, Optional Type As Variant)				
Property Get Saved As Boolean				
Event Send (Cancel As Boolean)				
Property Get/Let Sensitivity As OISensitivity				
Property Get Session As NameSpace				
Sub ShowCategoriesDialog ()	Non			
Property Get Size As Long				
Property Get/Let Subject As String				
Property Get/Let TaskCompletedDate As Date	Non	Non	Non	
Property Get/Let TaskDueDate As Date	Non	Non	Non	
Property Get/Let TaskStartDate As Date	Non	Non	Non	
Property Get/Let TaskSubject As String	Non	Non	Non	
Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
Event Unload ()	Non	Non	Non	
Property Get/Let UnRead As Boolean				
Property Get UserProperties As UserProperties				
Event Write (Cancel As Boolean)				
<i>Classe de membres : DocumentItem (Type : Classe)</i>	00	02	03	07 *
Property Get Actions As Actions				
Property Get Application As Application				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : DocumentItem (Type : Classe)</i>	00	02	03	07 *
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : DocumentItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				
<i>Classe de membres : Exception (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get AppointmentItem As AppointmentItem				
- Property Get Class As OIObjectClass				
- Property Get Deleted As Boolean				
- Property Get ItemProperties As ItemProperties	Non			
- Property Get OriginalDate As Date				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : Exceptions (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Exception				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : ExchangeDistributionList (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Address As String	Non	Non	Non	
- Property Get AddressEntryUserType As OIAddressEntryUserType	Non	Non	Non	



## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ExchangeDistributionList (Type : Classe)</i>	00	02	03	07 *
- Property Get Alias As String	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Comments As String	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Sub Details (Optional HWnd As Variant)	Non	Non	Non	
- Property Get DisplayType As OIDisplayType	Non	Non	Non	
- Function GetContact () As ContactItem	Non	Non	Non	
- Function GetExchangeDistributionList () As ExchangeDistributionList	Non	Non	Non	
- Function GetExchangeDistributionListMembers () As AddressEntries	Non	Non	Non	
- Function GetExchangeUser () As ExchangeUser	Non	Non	Non	
- Function GetFreeBusy (Start As Date, MinPerChar As Long, Optional CompleteFormat As Variant) As String	Non	Non	Non	
- Function GetMemberOfList () As AddressEntries	Non	Non	Non	
- Function GetOwners () As AddressEntries	Non	Non	Non	
- Property Get ID As String	Non	Non	Non	
- Property Get Manager As AddressEntry	Non	Non	Non	Mask
- Property Get/Let MAPIOBJECT As Unknown	Non	Non	Non	Mask
- Property Get Members As AddressEntries	Non	Non	Non	Mask
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get PrimarySmtpAddress As String	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Type As String	Non	Non	Non	
- Sub Update (Optional MakePermanent As Variant, Optional Refresh As Variant)	Non	Non	Non	
- Sub UpdateFreeBusy ()	Non	Non	Non	Mask
<i>Classe de membres : ExchangeUser (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Address As String	Non	Non	Non	
- Property Get AddressEntryUserType As OIAddressEntryUserType	Non	Non	Non	
- Property Get Alias As String	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get/Let AssistantName As String	Non	Non	Non	
- Property Get/Let BusinessTelephoneNumber As String	Non	Non	Non	
- Property Get/Let City As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Comments As String	Non	Non	Non	
- Property Get/Let CompanyName As String	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Department As String	Non	Non	Non	
- Sub Details (Optional HWnd As Variant)	Non	Non	Non	
- Property Get DisplayType As OIDisplayType	Non	Non	Non	
- Property Get/Let FirstName As String	Non	Non	Non	
- Function GetContact () As ContactItem	Non	Non	Non	
- Function GetDirectReports () As AddressEntries	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : ExchangeUser (Type : Classe)</i>	00	02	03	07 *
- Function GetExchangeDistributionList () As ExchangeDistributionList	Non	Non	Non	
- Function GetExchangeUser () As ExchangeUser	Non	Non	Non	
- Function GetExchangeUserManager () As ExchangeUser	Non	Non	Non	
- Function GetFreeBusy (Start As Date, MinPerChar As Long, Optional CompleteFormat As Variant) As String	Non	Non	Non	
- Function GetMemberOfList () As AddressEntries	Non	Non	Non	
- Property Get ID As String	Non	Non	Non	
- Property Get/Let JobTitle As String	Non	Non	Non	
- Property Get/Let LastName As String	Non	Non	Non	
- Property Get Manager As AddressEntry	Non	Non	Non	Mask
- Property Get/Let MAPIOBJECT As Unknown	Non	Non	Non	Mask
- Property Get Members As AddressEntries	Non	Non	Non	Mask
- Property Get/Let MobileTelephoneNumber As String	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get/Let OfficeLocation As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let PostalCode As String	Non	Non	Non	
- Property Get PrimarySmtpAddress As String	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let StateOrProvince As String	Non	Non	Non	
- Property Get/Let StreetAddress As String	Non	Non	Non	
- Property Get/Let Type As String	Non	Non	Non	
- Sub Update (Optional MakePermanent As Variant, Optional Refresh As Variant)	Non	Non	Non	
- Sub UpdateFreeBusy ()	Non	Non	Non	Mask
- Property Get/Let YomiCompanyName As String	Non	Non	Non	
- Property Get/Let YomiDepartment As String	Non	Non	Non	
- Property Get/Let YomiDisplayName As String	Non	Non	Non	
- Property Get/Let YomiFirstName As String	Non	Non	Non	
- Property Get/Let YomiLastName As String	Non	Non	Non	

<i>Classe de membres : Explorer (Type : Classe)</i>	00	02	03	07 *
- Event Activate ()				
- Sub Activate ()				
- Property Get Application As Application				
- Event BeforeFolderSwitch (NewFolder As Object, Cancel As Boolean)				
- Event BeforeItemCopy (Cancel As Boolean)	Non			
- Event BeforeItemCut (Cancel As Boolean)	Non			
- Event BeforeItemPaste (ClipboardContent As Variant, Target As MAPIFolder, Cancel As Boolean)	Non			
- Event BeforeMaximize (Cancel As Boolean)	Non			
- Event BeforeMinimize (Cancel As Boolean)	Non			
- Event BeforeMove (Cancel As Boolean)	Non			
- Event BeforeSize (Cancel As Boolean)	Non			
- Event BeforeViewSwitch (NewView As Variant, Cancel As Boolean)				
- Property Get Caption As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Explorer (Type : Classe)</i>	00	02	03	07 *
- Property Get Class As OIObjectClass				
- Sub ClearSearch ()	Non	Non	Non	
- Event Close ()				
- Sub Close ()				
- Property Get CommandBars As CommandBars				
- Property Get/Set CurrentFolder As MAPIFolder				
- Property Get/Let CurrentView As Variant				
- Event Deactivate ()				
- Sub DeselectFolder (Folder As MAPIFolder)	Non	Non		Mask
- Sub Display ()				
- Event FolderSwitch ()				
- Property Get/Let Height As Long				
- Property Get HTMLDocument As Object	Non			
- Function IsFolderSelected (Folder As MAPIFolder) As Boolean	Non	Non		Mask
- Function IsPaneVisible (Pane As OIPane) As Boolean				
- Property Get/Let Left As Long				
- Property Get NavigationPane As NavigationPane	Non	Non	Non	
- Property Get Panes As Panes				
- Property Get Parent As Object				
- Sub Search (Query As String, SearchScope As OISearchScope)	Non	Non	Non	
- Sub SelectFolder (Folder As MAPIFolder)	Non	Non		Mask
- Property Get Selection As Selection				
- Event SelectionChange ()				
- Property Get Session As NameSpace				
- Sub ShowPane (Pane As OIPane, Visible As Boolean)				
- Property Get/Let Top As Long				
- Property Get Views As Object	Mask	Mask	Mask	Mask
- Event ViewSwitch ()				
- Property Get/Let Width As Long				
- Property Get/Let WindowState As OIWindowState				

<i>Classe de membres : ExplorerEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event Activate ()		Non	Non	Non
- Sub Activate ()	Non			
- Event BeforeFolderSwitch (NewFolder As Object, Cancel As Boolean)		Non	Non	Non
- Sub BeforeFolderSwitch (NewFolder As Object, Cancel As Boolean)	Non			
- Event BeforeViewSwitch (NewView As Variant, Cancel As Boolean)		Non	Non	Non
- Sub BeforeViewSwitch (NewView As Variant, Cancel As Boolean)	Non			
- Event Close ()		Non	Non	Non
- Sub Close ()	Non			
- Event Deactivate ()		Non	Non	Non
- Sub Deactivate ()	Non			
- Event FolderSwitch ()		Non	Non	Non
- Sub FolderSwitch ()	Non			
- Event SelectionChange ()		Non	Non	Non
- Sub SelectionChange ()	Non			

## *Classes et membres de la référence OUTLOOK*

### *Classe de membres : ExplorerEvents (Type : Dispatch)*

	00	02	03	07 *
- Event ViewSwitch ()		Non	Non	Non
- Sub ViewSwitch ()	Non			

### *Classe de membres : Explorers (Type : Classe)*

	00	02	03	07 *
- Function Add (Folder As Variant, DisplayMode As OIFolderDisplayMode) As Explorer				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Explorer				
- Event NewExplorer (Explorer As Explorer)				
- Property Get Parent As Object				
- Property Get Session As NameSpace				

### *Classe de membres : ExplorersEvents (Type : Dispatch)*

	00	02	03	07 *
- Event NewExplorer (Explorer As Explorer)				

### *Classe de membres : Folder (Type : Classe)*

	00	02	03	07 *
- Property Get/Let AddressBookName As String	Non	Non	Non	
- Sub AddToFavorites (Optional fNoUI As Variant, Optional Name As Variant)	Non	Non	Non	Mask
- Sub AddToPFFavorites ()	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Event BeforeFolderMove (MoveTo As MAPIFolder, Cancel As Boolean)	Non	Non	Non	
- Event BeforeItemMove (Item As Object, MoveTo As MAPIFolder, Cancel As Boolean)	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function CopyTo (DestinationFolder As MAPIFolder) As MAPIFolder	Non	Non	Non	
- Property Get CurrentView As View	Non	Non	Non	
- Property Get/Let CustomViewsOnly As Boolean	Non	Non	Non	
- Property Get DefaultItemType As OIItemType	Non	Non	Non	
- Property Get DefaultMessageClass As String	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Description As String	Non	Non	Non	
- Sub Display ()	Non	Non	Non	
- Property Get EntryID As String	Non	Non	Non	
- Property Get FolderPath As String	Non	Non	Non	
- Property Get Folders As Folders	Non	Non	Non	
- Property Get FullFolderPath As String	Non	Non	Non	Mask
- Function GetCalendarExporter () As CalendarSharing	Non	Non	Non	
- Function GetExplorer (Optional DisplayMode As Variant) As Explorer	Non	Non	Non	
- Function GetStorage (StorageIdentifier As String, StorageIdentifierType As OIStorageIdentifierType) As StorageItem	Non	Non	Non	
- Function GetTable (Optional Filter As Variant, Optional TableContents As Variant) As Table	Non	Non	Non	
- Property Get/Let InAppFolderSyncObject As Boolean	Non	Non	Non	
- Property Get IsSharePointFolder As Boolean	Non	Non	Non	
- Property Get Items As Items	Non	Non	Non	
- Property Get MAPIOBJECT As Unknown	Non	Non	Non	Mask
- Sub MoveTo (DestinationFolder As MAPIFolder)	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : Folder (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let ShowAsOutlookAB As Boolean	Non	Non	Non	
- Property Get/Let ShowItemCount As OIShowItemCount	Non	Non	Non	
- Property Get Store As Store	Non	Non	Non	
- Property Get StoreID As String	Non	Non	Non	
- Property Get UnReadItemCount As Long	Non	Non	Non	
- Property Get UserDefinedProperties As UserDefinedProperties	Non	Non	Non	
- Property Get UserPermissions As Object	Non	Non	Non	Mask
- Property Get Views As Views	Non	Non	Non	
- Property Get/Let WebViewAllowNavigation As Boolean	Non	Non	Non	Mask
- Property Get/Let WebViewOn As Boolean	Non	Non	Non	
- Property Get/Let WebViewURL As String	Non	Non	Non	

<i>Classe de membres : Folders (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String, Optional Type As Variant) As MAPIFolder				
- Property Get Application As Application				
- Property Get Class As IOObjectClass				
- Property Get Count As Long				
- Event FolderAdd (Folder As MAPIFolder)				
- Event FolderChange (Folder As MAPIFolder)				
- Event FolderRemove ()				
- Function GetFirst () As MAPIFolder				
- Function GetLast () As MAPIFolder				
- Function GetNext () As MAPIFolder				
- Function GetPrevious () As MAPIFolder				
- Function Item (Index As Variant) As MAPIFolder				
- Property Get Parent As Object				
- Property Get RawTable As Unknown	Mask	Mask	Mask	Mask
- Sub Remove (Index As Long)				
- Property Get Session As NameSpace				

<i>Classe de membres : FoldersEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event FolderAdd (Folder As MAPIFolder)				
- Event FolderChange (Folder As MAPIFolder)				
- Event FolderRemove ()				

<i>Classe de membres : FormDescription (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get/Let Category As String				
- Property Get/Let CategorySub As String				
- Property Get Class As IOObjectClass				
- Property Get/Let Comment As String				
- Property Get/Let ContactName As String				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : FormDescription (Type : Dispatch)</i>	00	02	03	07 *
- Property Get/Let DisplayName As String				
- Property Get/Let Hidden As Boolean				
- Property Get/Let Icon As String				
- Property Get/Let Locked As Boolean				
- Property Get MessageClass As String				
- Property Get/Let Minicon As String				
- Property Get/Let Name As String				
- Property Get/Let Number As String				
- Property Get/Let OneOff As Boolean				
- Property Get Parent As Object				
- Property Get/Let Password As String				Mask
- Sub PublishForm (Registry As OIFormRegistry, Optional Folder As Variant)				
- Property Get ScriptText As String				
- Property Get Session As NameSpace				
- Property Get/Let Template As String				
- Property Get/Let UseWordMail As Boolean				
- Property Get/Let Version As String				

<i>Classe de membres : FormNameRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let FormName As Variant	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : FormRegion (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Event Close ()	Non	Non	Non	
- Property Get/Let Detail As String	Non	Non	Non	
- Property Get DisplayName As String	Non	Non	Non	
- Property Get/Let EnableAutoLayout As Boolean	Non	Non	Non	
- Event Expanded (Expand As Boolean)	Non	Non	Non	
- Property Get Form As Object	Non	Non	Non	
- Property Get FormRegionMode As OIFormRegionMode	Non	Non	Non	
- Property Get Inspector As Inspector	Non	Non	Non	
- Property Get InternalName As String	Non	Non	Non	
- Property Get IsExpanded As Boolean	Non	Non	Non	
- Property Get Item As Object	Non	Non	Non	
- Property Get Language As Long	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reflow ()	Non	Non	Non	
- Sub Select ()	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : FormRegion (Type : Classe)</i>	00	02	03	07 *
- Sub SetControllItemProperty (Control As Object, PropertyName As String)	Non	Non	Non	
- Property Get/Let SuppressControlReplacement As Boolean	Non	Non	Non	
<i>Classe de membres : FormRegionEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event Close ()	Non	Non	Non	
- Event Expanded (Expand As Boolean)	Non	Non	Non	
<i>Classe de membres : FormRegionStartup (Type : Classe)</i>	00	02	03	07 *
- Sub BeforeFormRegionShow (FormRegion As FormRegion)	Non	Non	Non	
- Function GetFormRegionIcon (FormRegionName As String, LCID As Long, Icon As OIFormRegionIcon) As Variant	Non	Non	Non	
- Function GetFormRegionManifest (FormRegionName As String, LCID As Long) As Variant	Non	Non	Non	
- Function GetFormRegionStorage (FormRegionName As String, Item As Object, LCID As Long, FormRegionMode As OIFormRegionMode, FormRegionSize As OIFormRegionSize) As Variant	Non	Non	Non	
<i>Classe de membres : FromRssFeedRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let FromRssFeed As Variant	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : IconView (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Sub Apply ()	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get/Let IconPlacement As OIIconViewPlacement	Non	Non	Non	
- Property Get/Let IconViewType As OIIconViewType	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get SortFields As OrderFields	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : IconView (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let XML As String	Non	Non	Non	
<i>Classe de membres : ImportanceRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let Importance As OIImportance	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : Inspector (Type : Classe)</i>	00	02	03	07 *
- Event Activate ()				
- Sub Activate ()				
- Property Get Application As Application				
- Event BeforeMaximize (Cancel As Boolean)	Non			
- Event BeforeMinimize (Cancel As Boolean)	Non			
- Event BeforeMove (Cancel As Boolean)	Non			
- Event BeforeSize (Cancel As Boolean)	Non			
- Property Get Caption As String				
- Property Get Class As OIObjectClass				
- Event Close ()				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get CommandBars As CommandBars				
- Property Get CurrentItem As Object				
- Event Deactivate ()				
- Sub Display (Optional Modal As Variant)				
- Property Get EditorType As OIEditorType				
- Property Get/Let Height As Long				
- Sub HideFormPage (PageName As String)				
- Property Get HTMLEditor As Object				Mask
- Function IsWordMail () As Boolean				
- Property Get/Let Left As Long				
- Property Get ModifiedFormPages As Object				
- Function NewFormRegion () As Object	Non	Non	Non	
- Function OpenFormRegion (Path As String) As Object	Non	Non	Non	
- Event PageChange (ActivePageName As String)	Non	Non	Non	
- Property Get Parent As Object				
- Sub SaveFormRegion (Page As Object, FileName As String)	Non	Non	Non	
- Property Get Session As NameSpace				
- Sub SetControllItemProperty (Control As Object, PropertyName As String)	Non	Non		
- Sub SetCurrentFormPage (PageName As String)				
- Sub ShowFormPage (PageName As String)				
- Property Get/Let Top As Long				
- Property Get/Let Width As Long				
- Property Get/Let WindowState As OIWindowState				



## Classes et membres de la référence OUTLOOK

### Classe de membres : Inspector (Type : Classe)

	00	02	03	07 *
- Property Get WordEditor As Object				

### Classe de membres : InspectorEvents (Type : Dispatch)

	00	02	03	07 *
- Event Activate ()		Non	Non	Non
- Sub Activate ()	Non			
- Event Close ()		Non	Non	Non
- Sub Close ()	Non			
- Event Deactivate ()		Non	Non	Non
- Sub Deactivate ()	Non			

### Classe de membres : Inspectors (Type : Classe)

	00	02	03	07 *
- Function Add (Item As Object) As Inspector				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Inspector				
- Event NewInspector (Inspector As Inspector)				
- Property Get Parent As Object				
- Property Get Session As NameSpace				

### Classe de membres : InspectorsEvents (Type : Dispatch)

	00	02	03	07 *
- Event NewInspector (Inspector As Inspector)				

### Classe de membres : ItemEvents (Type : Dispatch)

	00	02	03	07 *
- Event AttachmentAdd (Attachment As Attachment)		Non	Non	Non
- Sub AttachmentAdd (Attachment As Attachment)	Non			
- Event AttachmentRead (Attachment As Attachment)		Non	Non	Non
- Sub AttachmentRead (Attachment As Attachment)	Non			
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)		Non	Non	Non
- Sub BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)	Non			
- Event BeforeCheckNames (Cancel As Boolean)		Non	Non	Non
- Sub BeforeCheckNames (Cancel As Boolean)	Non			
- Event Close (Cancel As Boolean)		Non	Non	Non
- Sub Close (Cancel As Boolean)	Non			
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)		Non	Non	Non
- Sub CustomAction (Action As Object, Response As Object, Cancel As Boolean)	Non			
- Event CustomPropertyChange (Name As String)		Non	Non	Non
- Sub CustomPropertyChange (Name As String)	Non			
- Event Forward (Forward As Object, Cancel As Boolean)		Non	Non	Non
- Sub Forward (Forward As Object, Cancel As Boolean)	Non			
- Event Open (Cancel As Boolean)		Non	Non	Non
- Sub Open (Cancel As Boolean)	Non			
- Event PropertyChange (Name As String)		Non	Non	Non
- Sub PropertyChange (Name As String)	Non			
- Event Read ()		Non	Non	Non
- Sub Read ()	Non			
- Event Reply (Response As Object, Cancel As Boolean)		Non	Non	Non

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : ItemEvents (Type : Dispatch)</i>	00	02	03	07 *
- Sub Reply (Response As Object, Cancel As Boolean)	Non			
- Event ReplyAll (Response As Object, Cancel As Boolean)		Non	Non	Non
- Sub ReplyAll (Response As Object, Cancel As Boolean)	Non			
- Event Send (Cancel As Boolean)		Non	Non	Non
- Sub Send (Cancel As Boolean)	Non			
- Event Write (Cancel As Boolean)		Non	Non	Non
- Sub Write (Cancel As Boolean)	Non			

<i>Classe de membres : ItemProperties (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Name As String, Type As OIUserPropertyType, Optional AddToFolderFields As Variant, Optional DisplayFormat As Variant) As ItemProperty	Non			
- Property Get Application As Application	Non			
- Property Get Class As OIObjectClass	Non			
- Property Get Count As Long	Non			
- Function Item (Index As Variant) As ItemProperty	Non			
- Function _NewEnum () As Unknown	Non	Mask	Mask	Mask
- Property Get Parent As Object	Non			
- Sub Remove (Index As Long)	Non			
- Property Get Session As NameSpace	Non			

<i>Classe de membres : ItemProperty (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Class As OIObjectClass	Non			
- Sub Delete ()	Non	Mask	Mask	Mask
- Property Get/Let Formula As String	Non	Mask	Mask	Mask
- Property Get IsUserProperty As Boolean	Non			
- Property Get Name As String	Non			
- Property Get Parent As Object	Non			
- Property Get Session As NameSpace	Non			
- Property Get Type As OIUserPropertyType	Non			
- Property Get/Let ValidationFormula As String	Non	Mask	Mask	Mask
- Property Get/Let ValidationText As String	Non	Mask	Mask	Mask
- Property Get/Let Value As Variant	Non			

<i>Classe de membres : Items (Type : Classe)</i>	00	02	03	07 *
- Function Add (Optional Type As Variant) As Object				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Find (Filter As String) As Object				
- Function FindNext () As Object				
- Function GetFirst () As Object				
- Function GetLast () As Object				
- Function GetNext () As Object				
- Function GetPrevious () As Object				
- Property Get/Let IncludeRecurrences As Boolean				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Items (Type : Classe)</i>	00	02	03	07 *
- Function Item (Index As Variant) As Object				
- Event ItemAdd (Item As Object)				
- Event ItemChange (Item As Object)				
- Event ItemRemove ()				
- Property Get Parent As Object				
- Property Get RawTable As Unknown	Mask	Mask	Mask	Mask
- Sub Remove (Index As Long)				
- Sub ResetColumns ()				
- Function Restrict (Filter As String) As Items				
- Property Get Session As NameSpace				
- Sub SetColumns (Columns As String)				
- Sub Sort (Property As String, Optional Descending As Variant)				

<i>Classe de membres : ItemsEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event ItemAdd (Item As Object)				
- Event ItemChange (Item As Object)				
- Event ItemRemove ()				

<i>Classe de membres : JournalItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get/Let ContactNames As String				
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : JournalItem (Type : Classe)</i>	00	02	03	07 *
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get/Let DocPosted As Boolean				
- Property Get/Let DocPrinted As Boolean				
- Property Get/Let DocRouted As Boolean				
- Property Get/Let DocSaved As Boolean				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get/Let Duration As Long				
- Property Get/Let End As Date				
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function Forward () As MailItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Property Get Recipients As Recipients				
- Event Reply (Response As Object, Cancel As Boolean)				
- Function Reply () As MailItem				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Function ReplyAll () As MailItem				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : JournalItem (Type : Classe)</i>	00	02	03	07 *
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Start As Date				
- Sub StartTimer ()				
- Sub StopTimer ()				
- Property Get/Let Subject As String				
- Property Get/Let Type As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : JournalModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	

<i>Classe de membres : Link (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Item As Object				
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
- Property Get Type As OIObjectClass				

<i>Classe de membres : Links (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Item As Object) As Link				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Link				
- Property Get Parent As Object				
- Sub Remove (Index As Variant)				
- Property Get Session As NameSpace				

<i>Classe de membres : MailItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : MailItem (Type : Classe)</i>	00	02	03	07 *
- Sub AddBusinessCard (contact As ContactItem)	Non	Non	Non	
- Property Get/Let AlternateRecipientAllowed As Boolean				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get/Let AutoForwarded As Boolean				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Property Get/Let BCC As String				
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let BodyFormat As OIBodyFormat	Non			
- Property Get/Let Categories As String				
- Property Get/Let CC As String				
- Property Get Class As IOBJECTCLASS				
- Sub ClearConversationIndex ()				
- Sub ClearTaskFlag ()	Non	Non	Non	
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Property Get/Let DeferredDeliveryTime As Date				
- Sub Delete ()				
- Property Get/Let DeleteAfterSubmit As Boolean				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get/Let EnableSharedAttachments As Boolean	Non	Non	Mask	Mask
- Property Get EntryID As String				
- Property Get/Let ExpiryTime As Date				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : MailItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let FlagDueBy As Date				Mask
- Property Get/Let FlagIcon As OIFlagIcon	Non	Non		Mask
- Property Get/Let FlagRequest As String				
- Property Get/Let FlagStatus As OIFlagStatus				Mask
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function Forward () As MailItem				
- Property Get GetInspector As Inspector				
- Property Get/Let HasCoverSheet As Boolean	Non	Non	Mask	Mask
- Property Get/Let HTMLBody As String				
- Property Get/Let Importance As OIImportance				
- Property Get/Let InternetCodepage As Long	Non			
- Property Get IsConflict As Boolean	Non			
- Property Get/Let IsIPFax As Boolean	Non	Non	Mask	Mask
- Property Get IsMarkedAsTask As Boolean	Non	Non	Non	
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Sub MarkAsTask (MarkInterval As OIMarkInterval)	Non	Non	Non	
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get/Let OriginatorDeliveryReportRequested As Boolean				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Property Get/Let Permission As OIPermission	Non	Non		
- Property Get/Let PermissionService As OIPermissionService	Non	Non		
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Property Get/Let ReadReceiptRequested As Boolean				
- Property Get ReceivedByEntryID As String				
- Property Get ReceivedByName As String				
- Property Get ReceivedOnBehalfOfEntryID As String				
- Property Get ReceivedOnBehalfOfName As String				
- Property Get ReceivedTime As Date				
- Property Get/Let RecipientReassignmentProhibited As Boolean				
- Property Get Recipients As Recipients				
- Property Get/Let ReminderOverrideDefault As Boolean				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : MailItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let ReminderPlaySound As Boolean				
- Property Get/Let ReminderSet As Boolean				
- Property Get/Let ReminderSoundFile As String				
- Property Get/Let ReminderTime As Date				
- Property Get/Let RemoteStatus As OIRemoteStatus				
- Event Reply (Response As Object, Cancel As Boolean)				
- Function Reply () As MailItem				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Function ReplyAll () As MailItem				
- Property Get ReplyRecipientNames As String				
- Property Get ReplyRecipients As Recipients				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Property Get/Set SaveSentMessageFolder As MAPIFolder				
- Event Send (Cancel As Boolean)				
- Sub Send ()				
- Property Get SenderEmailAddress As String	Non	Non		
- Property Get SenderEmailType As String	Non	Non		
- Property Get SenderName As String				
- Property Get/Let SendUsingAccount As Account	Non	Non	Non	
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Sent As Boolean				
- Property Get SentOn As Date				
- Property Get/Let SentOnBehalfOfName As String				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Property Get Submitted As Boolean				
- Property Get/Let TaskCompletedDate As Date	Non	Non	Non	
- Property Get/Let TaskDueDate As Date	Non	Non	Non	
- Property Get/Let TaskStartDate As Date	Non	Non	Non	
- Property Get/Let TaskSubject As String	Non	Non	Non	
- Property Get/Let To As String				
- Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Property Get/Let VotingOptions As String				
- Property Get/Let VotingResponse As String				
- Event Write (Cancel As Boolean)				
<i>Classe de membres : MailModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As IOObjectClass	Non	Non	Non	



## Classes et membres de la référence OUTLOOK

<i>Classe de membres : MailModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	

<i>Classe de membres : MAPIFolder (Type : Dispatch)</i>	00	02	03	07 *
- Property Get/Let AddressBookName As String	Non			
- Sub AddToFavorites (Optional fNoUI As Variant, Optional Name As Variant)	Non			Mask
- Sub AddToPFFavorites ()	Mask			
- Property Get Application As Application				
- Property Get Class As IOObjectClass				
- Function CopyTo (DestinationFolder As MAPIFolder) As MAPIFolder				
- Property Get CurrentView As View	Non			
- Property Get/Let CustomViewsOnly As Boolean	Non			
- Property Get DefaultItemType As OIItemtype				
- Property Get DefaultMessageClass As String				
- Sub Delete ()				
- Property Get/Let Description As String				
- Sub Display ()				
- Property Get EntryID As String				
- Property Get FolderPath As String	Non			
- Property Get Folders As Folders				
- Property Get FullFolderPath As String	Non	Mask	Mask	Mask
- Function GetCalendarExporter () As CalendarSharing	Non	Non	Non	
- Function GetExplorer (Optional DisplayMode As Variant) As Explorer				
- Function GetStorage (StorageIdentifier As String, StorageIdentifierType As OIStorageIdentifierType) As StorageItem	Non	Non	Non	
- Function GetTable (Optional Filter As Variant, Optional TableContents As Variant) As Table	Non	Non	Non	
- Property Get/Let InAppFolderSyncObject As Boolean	Non			
- Property Get IsSharePointFolder As Boolean	Non	Non		
- Property Get Items As Items				
- Property Get MAPIOBJECT As Unknown	Non	Mask	Mask	Mask
- Sub MoveTo (DestinationFolder As MAPIFolder)				
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace				
- Property Get/Let ShowAsOutlookAB As Boolean	Non			
- Property Get/Let ShowItemCount As OIShowItemCount	Non	Non		
- Property Get Store As Store	Non	Non	Non	
- Property Get StoreID As String				
- Property Get UnReadItemCount As Long				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : MAPIFolder (Type : Dispatch)</i>	00	02	03	07 *
- Property Get UserDefinedProperties As UserDefinedProperties	Non	Non	Non	
- Property Get UserPermissions As Object	Mask	Mask	Mask	Mask
- Property Get Views As Views	Non			
- Property Get/Let WebViewAllowNavigation As Boolean		Mask	Mask	Mask
- Property Get/Let WebViewOn As Boolean				
- Property Get/Let WebViewURL As String				

<i>Classe de membres : MAPIFolderEvents_12 (Type : Dispatch)</i>	00	02	03	07 *
- Event BeforeFolderMove (MoveTo As MAPIFolder, Cancel As Boolean)	Non	Non	Non	
- Event BeforeItemMove (Item As Object, MoveTo As MAPIFolder, Cancel As Boolean)	Non	Non	Non	

<i>Classe de membres : MarkAsTaskRuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let FlagTo As String	Non	Non	Non	
- Property Get/Let MarkInterval As OIMarkInterval	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : MeetingItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get/Let AutoForwarded As Boolean				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : MeetingItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Property Get/Let DeferredDeliveryTime As Date				
- Sub Delete ()				
- Property Get/Let DeleteAfterSubmit As Boolean				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get/Let ExpiryTime As Date				
- Property Get/Let FlagDueBy As Date				Mask
- Property Get/Let FlagIcon As OIFlagIcon	Non	Non		Mask
- Property Get/Let FlagRequest As String				Mask
- Property Get/Let FlagStatus As OIFlagStatus				Mask
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function Forward () As MeetingItem				
- Function GetAssociatedAppointment (AddToCalendar As Boolean) As AppointmentItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get MeetingWorkspaceURL As String	Non	Non		
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get/Let OriginatorDeliveryReportRequested As Boolean				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : MeetingItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let ReceivedTime As Date				
- Property Get Recipients As Recipients				
- Property Get/Let ReminderSet As Boolean				
- Property Get/Let ReminderTime As Date				
- Event Reply (Response As Object, Cancel As Boolean)				
- Function Reply () As MailItem				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Function ReplyAll () As MailItem				
- Property Get ReplyRecipients As Recipients				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Property Get/Set SaveSentMessageFolder As MAPIFolder				
- Event Send (Cancel As Boolean)				
- Sub Send ()				
- Property Get SenderEmailAddress As String	Non	Non		
- Property Get SenderEmailType As String	Non	Non		
- Property Get SenderName As String				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Sent As Boolean				
- Property Get SentOn As Date				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Property Get Submitted As Boolean				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : MoveOrCopyRuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let Folder As MAPIFolder	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : NameSpace (Type : Classe)</i>	00	02	03	07 *
- Property Get Accounts As Accounts	Non	Non	Non	
- Property Get AddressLists As AddressLists				
- Sub AddStore (Store As Variant)				
- Sub AddStoreEx (Store As Variant, Type As OIStoreType)	Non	Non		
- Property Get Application As Application				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Namespace (Type : Classe)</i>	00	02	03	07 *
- Event AutoDiscoverComplete ()	Non	Non	Non	
- Property Get AutoDiscoverConnectionMode As OIAutoDiscoverConnectionMode	Non	Non	Non	
- Property Get AutoDiscoverXml As String	Non	Non	Non	
- Property Get Categories As Categories	Non	Non	Non	
- Property Get Class As OIObjectClass				
- Function CompareEntryIDs (FirstEntryID As String, SecondEntryID As String) As Boolean	Non	Non	Non	
- Function CreateRecipient (RecipientName As String) As Recipient				
- Function CreateSharingItem (Context As Variant, Optional Provider As Variant) As SharingItem	Non	Non	Non	
- Property Get CurrentProfileName As String	Non	Non	Non	
- Property Get CurrentUser As Recipient				
- Property Get DefaultStore As Store	Non	Non	Non	
- Sub Dial (Optional ContactItem As Variant)	Non			
- Property Get ExchangeConnectionMode As OIExchangeConnectionMode	Non	Non		
- Property Get ExchangeMailboxServerName As String	Non	Non	Non	
- Property Get ExchangeMailboxServerVersion As String	Non	Non	Non	
- Property Get Folders As Folders				
- Function GetAddressEntryFromID (ID As String) As AddressEntry	Non	Non	Non	
- Function GetDefaultFolder (FolderType As OIDefaultFolders) As MAPIFolder				
- Function GetFolderFromID (EntryIDFolder As String, Optional EntryIDStore As Variant) As MAPIFolder				
- Function GetGlobalAddressList () As AddressList	Non	Non	Non	
- Function GetItemFromID (EntryIDItem As String, Optional EntryIDStore As Variant) As Object				
- Function GetRecipientFromID (EntryID As String) As Recipient				
- Function GetSelectNamesDialog () As SelectNamesDialog	Non	Non	Non	
- Function GetSharedDefaultFolder (Recipient As Recipient, FolderType As OIDefaultFolders) As MAPIFolder				
- Function GetStoreFromID (ID As String) As Store	Non	Non	Non	
- Sub Logoff ()				
- Sub Logon (Optional Profile As Variant, Optional Password As Variant, Optional ShowDialog As Variant, Optional NewSession As Variant)				
- Property Get MAPIOBJECT As Unknown	Non	Mask	Mask	Mask
- Property Get Offline As Boolean	Non			
- Function OpenSharedFolder (Path As String, Optional Name As Variant, Optional DownloadAttachments As Variant, Optional UseTTL As Variant) As MAPIFolder	Non	Non	Non	
- Function OpenSharedItem (Path As String) As Object	Non	Non	Non	
- Event OptionsPagesAdd (Pages As PropertyPages, Folder As MAPIFolder)				
- Property Get Parent As Object				
- Function PickFolder () As MAPIFolder				
- Sub RefreshRemoteHeaders ()	Mask	Mask	Mask	Mask
- Sub RemoveStore (Folder As MAPIFolder)	Mask			
- Sub SendAndReceive (showProgressDialog As Boolean)	Non	Non	Non	
- Property Get Session As NameSpace				
- Property Get Stores As Stores	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Namespace (Type : Classe)</i>	00	02	03	07 *
- Property Get SyncObjects As SyncObjects				
- Property Get Type As String				
<i>Classe de membres : NamespaceEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event AutoDiscoverComplete ()	Non	Non	Non	
- Event OptionsPagesAdd (Pages As PropertyPages, Folder As MAPIFolder)				
<i>Classe de membres : NavigationFolder (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get DisplayName As String	Non	Non	Non	
- Property Get Folder As MAPIFolder	Non	Non	Non	
- Property Get IsRemovable As Boolean	Non	Non	Non	
- Property Get/Let IsSelected As Boolean	Non	Non	Non	
- Property Get/Let IsSideBySide As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : NavigationFolders (Type : Classe)</i>	00	02	03	07 *
- Function Add (Folder As MAPIFolder) As NavigationFolder	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Item (Index As Variant) As NavigationFolder	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (RemovableFolder As NavigationFolder)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : NavigationGroup (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get GroupType As OIGroupType	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get NavigationFolders As NavigationFolders	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : NavigationGroups (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Create (GroupDisplayName As String) As NavigationGroup	Non	Non	Non	
- Sub Delete (Group As NavigationGroup)	Non	Non	Non	
- Function GetDefaultNavigationGroup (DefaultFolderGroup As OIGroupType) As NavigationGroup	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : NavigationGroups (Type : Classe)</i>	00	02	03	07 *
- Function Item (Index As Variant) As NavigationGroup	Non	Non	Non	
- Event NavigationFolderAdd (NavigationFolder As NavigationFolder)	Non	Non	Non	
- Event NavigationFolderRemove ()	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Event SelectedChange (NavigationFolder As NavigationFolder)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : NavigationModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	
<i>Classe de membres : NavigationModules (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function GetNavigationModule (ModuleType As OINavigationModuleType) As NavigationModule	Non	Non	Non	
- Function Item (Index As Variant) As NavigationModule	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : NavigationPane (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Set CurrentModule As NavigationModule	Non	Non	Non	
- Property Get/Let DisplayedModuleCount As Long	Non	Non	Non	
- Property Get/Let IsCollapsed As Boolean	Non	Non	Non	
- Property Get Modules As NavigationModules	Non	Non	Non	
- Event ModuleSwitch (CurrentModule As NavigationModule)	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres :NewItemAlertRuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Text As String	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : NoteItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Color As OINoteColor				Mask
- Property Get Conflicts As Conflicts	Non	Non		
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get GetInspector As Inspector				
- Property Get/Let Height As Long				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get/Let Left As Long				
- Property Get Links As Links				
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Property Get Session As NameSpace				
- Property Get Size As Long				
- Property Get Subject As String				
- Property Get/Let Top As Long				
- Property Get/Let Width As Long				
<i>Classe de membres : NotesModule (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	



## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : <b>OIAccountType (Type : Enum)</b></i>	00	02	03	07 *
- Const olExchange = 0 (&H0) As Long	Non	Non	Non	
- Const olHttp = 3 (&H3) As Long	Non	Non	Non	
- Const olImap = 1 (&H1) As Long	Non	Non	Non	
- Const olOtherAccount = 5 (&H5) As Long	Non	Non	Non	
- Const olPop3 = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : <b>OIActionCopyLike (Type : Enum)</b></i>	00	02	03	07 *
- Const olForward = 2 (&H2) As Long				
- Const olReply = 0 (&H0) As Long				
- Const olReplyAll = 1 (&H1) As Long				
- Const olReplyFolder = 3 (&H3) As Long				
- Const olRespond = 4 (&H4) As Long				
<i>Classe de membres : <b>OIActionReplyStyle (Type : Enum)</b></i>	00	02	03	07 *
- Const olEmbedOriginalItem = 1 (&H1) As Long				
- Const olIncludeOriginalText = 2 (&H2) As Long				
- Const olIndentOriginalText = 3 (&H3) As Long				
- Const olLinkOriginalItem = 4 (&H4) As Long				
- Const olOmitOriginalText = 0 (&H0) As Long				
- Const olReplyTickOriginalText = 1000 (&H3E8) As Long				
- Const olUserPreference = 5 (&H5) As Long				
<i>Classe de membres : <b>OIActionResponseStyle (Type : Enum)</b></i>	00	02	03	07 *
- Const olOpen = 0 (&H0) As Long				
- Const olPrompt = 2 (&H2) As Long				
- Const olSend = 1 (&H1) As Long				
<i>Classe de membres : <b>OIActionShowOn (Type : Enum)</b></i>	00	02	03	07 *
- Const olDontShow = 0 (&H0) As Long				
- Const olMenu = 1 (&H1) As Long				
- Const olMenuAndToolbar = 2 (&H2) As Long				
<i>Classe de membres : <b>OIAddressEntryUserType (Type : Enum)</b></i>	00	02	03	07 *
- Const olExchangeAgentAddressEntry = 3 (&H3) As Long	Non	Non	Non	
- Const olExchangeDistributionListAddressEntry = 1 (&H1) As Long	Non	Non	Non	
- Const olExchangeOrganizationAddressEntry = 4 (&H4) As Long	Non	Non	Non	
- Const olExchangePublicFolderAddressEntry = 2 (&H2) As Long	Non	Non	Non	
- Const olExchangeRemoteUserAddressEntry = 5 (&H5) As Long	Non	Non	Non	
- Const olExchangeUserAddressEntry = 0 (&H0) As Long	Non	Non	Non	
- Const olLdapAddressEntry = 20 (&H14) As Long	Non	Non	Non	
- Const olOtherAddressEntry = 40 (&H28) As Long	Non	Non	Non	
- Const olOutlookContactAddressEntry = 10 (&HA) As Long	Non	Non	Non	
- Const olOutlookDistributionListAddressEntry = 11 (&HB) As Long	Non	Non	Non	
- Const olSmtppAddressEntry = 30 (&H1E) As Long	Non	Non	Non	
<i>Classe de membres : <b>OIAddressListType (Type : Enum)</b></i>	00	02	03	07 *
- Const olCustomAddressList = 4 (&H4) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : OIAddressListType (Type : Enum)</i>	00	02	03	07 *
Const olExchangeContainer = 1 (&H1) As Long	Non	Non	Non	
Const olExchangeGlobalAddressList = 0 (&H0) As Long	Non	Non	Non	
Const olOutlookAddressList = 2 (&H2) As Long	Non	Non	Non	
Const olOutlookLdapAddressList = 3 (&H3) As Long	Non	Non	Non	
<i>Classe de membres : OIAlign (Type : Enum)</i>	00	02	03	07 *
Const olAlignCenter = 1 (&H1) As Long	Non	Non	Non	
Const olAlignLeft = 0 (&H0) As Long	Non	Non	Non	
Const olAlignRight = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OIAlignment (Type : Enum)</i>	00	02	03	07 *
Const olAlignmentLeft = 0 (&H0) As Long	Non	Non	Non	
Const olAlignmentRight = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIAppointmentTimeField (Type : Enum)</i>	00	02	03	07 *
Const olAppointmentTimeFieldEnd = 3 (&H3) As Long	Non	Non	Non	
Const olAppointmentTimeFieldNone = 1 (&H1) As Long	Non	Non	Non	
Const olAppointmentTimeFieldStart = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OIAttachmentBlockLevel (Type : Enum)</i>	00	02	03	07 *
Const olAttachmentBlockLevelNone = 0 (&H0) As Long	Non	Non	Non	
Const olAttachmentBlockLevelOpen = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIAttachmentType (Type : Enum)</i>	00	02	03	07 *
Const olByReference = 4 (&H4) As Long				
Const olByValue = 1 (&H1) As Long				
Const olEmbeddeditem = 5 (&H5) As Long				
Const olOLE = 6 (&H6) As Long				
<i>Classe de membres : OIAutoDiscoverConnectionMode (Type : Enum)</i>	00	02	03	07 *
Const olAutoDiscoverConnectionExternal = 1 (&H1) As Long	Non	Non	Non	
Const olAutoDiscoverConnectionInternal = 2 (&H2) As Long	Non	Non	Non	
Const olAutoDiscoverConnectionInternalDomain = 3 (&H3) As Long	Non	Non	Non	
Const olAutoDiscoverConnectionUnknown = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OIAutoPreview (Type : Enum)</i>	00	02	03	07 *
Const olAutoPreviewAll = 0 (&H0) As Long	Non	Non	Non	
Const olAutoPreviewNone = 2 (&H2) As Long	Non	Non	Non	
Const olAutoPreviewUnread = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIBackStyle (Type : Enum)</i>	00	02	03	07 *
Const olBackStyleOpaque = 1 (&H1) As Long	Non	Non	Non	
Const olBackStyleTransparent = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OIBodyFormat (Type : Enum)</i>	00	02	03	07 *
Const olFormatHTML = 2 (&H2) As Long	Non			
Const olFormatPlain = 1 (&H1) As Long	Non			
Const olFormatRichText = 3 (&H3) As Long	Non			

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OIBodyFormat (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olFormatUnspecified = 0 (&H0) As Long	Non			
<b>Classe de membres : OIBorderStyle (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olBorderStyleNone = 0 (&H0) As Long	Non	Non	Non	
- Const olBorderStyleSingle = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OIBusinessCardType (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olBusinessCardTypeInterConnect = 1 (&H1) As Long	Non	Non	Non	
- Const olBusinessCardTypeOutlook = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OIBusyStatus (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olBusy = 2 (&H2) As Long				
- Const olFree = 0 (&H0) As Long				
- Const olOutOfOffice = 3 (&H3) As Long				
- Const olTentative = 1 (&H1) As Long				
<b>Classe de membres : OICalendarDetail (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olFreeBusyAndSubject = 1 (&H1) As Long	Non	Non	Non	
- Const olFreeBusyOnly = 0 (&H0) As Long	Non	Non	Non	
- Const olFullDetails = 2 (&H2) As Long	Non	Non	Non	
<b>Classe de membres : OICalendarMailFormat (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olCalendarMailFormatDailySchedule = 0 (&H0) As Long	Non	Non	Non	
- Const olCalendarMailFormatEventList = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OICalendarViewMode (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olCalendarView5DayWeek = 4 (&H4) As Long	Non	Non	Non	
- Const olCalendarViewDay = 0 (&H0) As Long	Non	Non	Non	
- Const olCalendarViewMonth = 2 (&H2) As Long	Non	Non	Non	
- Const olCalendarViewMultiDay = 3 (&H3) As Long	Non	Non	Non	
- Const olCalendarViewWeek = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OICategoryColor (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olCategoryColorBlack = 15 (&HF) As Long	Non	Non	Non	
- Const olCategoryColorBlue = 8 (&H8) As Long	Non	Non	Non	
- Const olCategoryColorDarkBlue = 23 (&H17) As Long	Non	Non	Non	
- Const olCategoryColorDarkGray = 14 (&HE) As Long	Non	Non	Non	
- Const olCategoryColorDarkGreen = 20 (&H14) As Long	Non	Non	Non	
- Const olCategoryColorDarkMaroon = 25 (&H19) As Long	Non	Non	Non	
- Const olCategoryColorDarkOlive = 22 (&H16) As Long	Non	Non	Non	
- Const olCategoryColorDarkOrange = 17 (&H11) As Long	Non	Non	Non	
- Const olCategoryColorDarkPeach = 18 (&H12) As Long	Non	Non	Non	
- Const olCategoryColorDarkPurple = 24 (&H18) As Long	Non	Non	Non	
- Const olCategoryColorDarkRed = 16 (&H10) As Long	Non	Non	Non	
- Const olCategoryColorDarkSteel = 12 (&HC) As Long	Non	Non	Non	
- Const olCategoryColorDarkTeal = 21 (&H15) As Long	Non	Non	Non	
- Const olCategoryColorDarkYellow = 19 (&H13) As Long	Non	Non	Non	
- Const olCategoryColorGray = 13 (&HD) As Long	Non	Non	Non	

## Classes et membres de la référence *OUTLOOK*

<i>Classe de membres : OI</i> CategoryColor (Type : Enum)	00	02	03	07 *
- Const olCategoryColorGreen = 5 (&H5) As Long	Non	Non	Non	
- Const olCategoryColorMaroon = 10 (&HA) As Long	Non	Non	Non	
- Const olCategoryColorNone = 0 (&H0) As Long	Non	Non	Non	
- Const olCategoryColorOlive = 7 (&H7) As Long	Non	Non	Non	
- Const olCategoryColorOrange = 2 (&H2) As Long	Non	Non	Non	
- Const olCategoryColorPeach = 3 (&H3) As Long	Non	Non	Non	
- Const olCategoryColorPurple = 9 (&H9) As Long	Non	Non	Non	
- Const olCategoryColorRed = 1 (&H1) As Long	Non	Non	Non	
- Const olCategoryColorSteel = 11 (&HB) As Long	Non	Non	Non	
- Const olCategoryColorTeal = 6 (&H6) As Long	Non	Non	Non	
- Const olCategoryColorYellow = 4 (&H4) As Long	Non	Non	Non	

<i>Classe de membres : OI</i> CategoryShortcutKey (Type : Enum)	00	02	03	07 *
- Const olCategoryShortcutKeyCtrlF10 = 9 (&H9) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF11 = 10 (&HA) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF12 = 11 (&HB) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF2 = 1 (&H1) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF3 = 2 (&H2) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF4 = 3 (&H3) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF5 = 4 (&H4) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF6 = 5 (&H5) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF7 = 6 (&H6) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF8 = 7 (&H7) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyCtrlF9 = 8 (&H8) As Long	Non	Non	Non	
- Const olCategoryShortcutKeyNone = 0 (&H0) As Long	Non	Non	Non	

<i>Classe de membres : OI</i> Color (Type : Enum)	00	02	03	07 *
- Const olAutoColor = 0 (&H0) As Long	Non	Non	Non	
- Const olColorAqua = 15 (&HF) As Long	Non	Non	Non	
- Const olColorBlack = 1 (&H1) As Long	Non	Non	Non	
- Const olColorBlue = 13 (&HD) As Long	Non	Non	Non	
- Const olColorFuchsia = 14 (&HE) As Long	Non	Non	Non	
- Const olColorGray = 8 (&H8) As Long	Non	Non	Non	
- Const olColorGreen = 3 (&H3) As Long	Non	Non	Non	
- Const olColorLime = 11 (&HB) As Long	Non	Non	Non	
- Const olColorMaroon = 2 (&H2) As Long	Non	Non	Non	
- Const olColorNavy = 5 (&H5) As Long	Non	Non	Non	
- Const olColorOlive = 4 (&H4) As Long	Non	Non	Non	
- Const olColorPurple = 6 (&H6) As Long	Non	Non	Non	
- Const olColorRed = 10 (&HA) As Long	Non	Non	Non	
- Const olColorSilver = 9 (&H9) As Long	Non	Non	Non	
- Const olColorTeal = 7 (&H7) As Long	Non	Non	Non	
- Const olColorWhite = 16 (&H10) As Long	Non	Non	Non	
- Const olColorYellow = 12 (&HC) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

### Classe de membres : **OlComboBoxStyle (Type : Enum)** 00 02 03 07 \*

	00	02	03	07 *
- Const olComboBoxStyleCombo = 0 (&H0) As Long	Non	Non	Non	
- Const olComboBoxStyleList = 2 (&H2) As Long	Non	Non	Non	

### Classe de membres : **OlContactPhoneNumber (Type : Enum)** 00 02 03 07 \*

	00	02	03	07 *
- Const olContactPhoneAssistant = 0 (&H0) As Long	Non	Non	Non	
- Const olContactPhoneBusiness = 1 (&H1) As Long	Non	Non	Non	
- Const olContactPhoneBusiness2 = 2 (&H2) As Long	Non	Non	Non	
- Const olContactPhoneBusinessFax = 3 (&H3) As Long	Non	Non	Non	
- Const olContactPhoneCallback = 4 (&H4) As Long	Non	Non	Non	
- Const olContactPhoneCar = 5 (&H5) As Long	Non	Non	Non	
- Const olContactPhoneCompany = 6 (&H6) As Long	Non	Non	Non	
- Const olContactPhoneHome = 7 (&H7) As Long	Non	Non	Non	
- Const olContactPhoneHome2 = 8 (&H8) As Long	Non	Non	Non	
- Const olContactPhoneHomeFax = 9 (&H9) As Long	Non	Non	Non	
- Const olContactPhoneISDN = 10 (&HA) As Long	Non	Non	Non	
- Const olContactPhoneMobile = 11 (&HB) As Long	Non	Non	Non	
- Const olContactPhoneOther = 12 (&HC) As Long	Non	Non	Non	
- Const olContactPhoneOtherFax = 13 (&HD) As Long	Non	Non	Non	
- Const olContactPhonePager = 14 (&HE) As Long	Non	Non	Non	
- Const olContactPhonePrimary = 15 (&HF) As Long	Non	Non	Non	
- Const olContactPhoneRadio = 16 (&H10) As Long	Non	Non	Non	
- Const olContactPhoneTelex = 17 (&H11) As Long	Non	Non	Non	
- Const olContactPhoneTTYTTD = 18 (&H12) As Long	Non	Non	Non	

### Classe de membres : **OlContextMenu (Type : Enum)** 00 02 03 07 \*

	00	02	03	07 *
- Const olAttachmentContextMenu = 3 (&H3) As Long	Non	Non	Non	
- Const olFolderContextMenu = 2 (&H2) As Long	Non	Non	Non	
- Const olItemContextMenu = 0 (&H0) As Long	Non	Non	Non	
- Const olShortcutContextMenu = 5 (&H5) As Long	Non	Non	Non	
- Const olStoreContextMenu = 4 (&H4) As Long	Non	Non	Non	
- Const olViewContextMenu = 1 (&H1) As Long	Non	Non	Non	

### Classe de membres : **OlDaysOfWeek (Type : Enum)** 00 02 03 07 \*

	00	02	03	07 *
- Const olFriday = 32 (&H20) As Long				
- Const olMonday = 2 (&H2) As Long				
- Const olSaturday = 64 (&H40) As Long				
- Const olSunday = 1 (&H1) As Long				
- Const olThursday = 16 (&H10) As Long				
- Const olTuesday = 4 (&H4) As Long				
- Const olWednesday = 8 (&H8) As Long				

### Classe de membres : **OlDayWeekTimeScale (Type : Enum)** 00 02 03 07 \*

	00	02	03	07 *
- Const olTimeScale10Minutes = 2 (&H2) As Long	Non	Non	Non	
- Const olTimeScale15Minutes = 3 (&H3) As Long	Non	Non	Non	
- Const olTimeScale30Minutes = 4 (&H4) As Long	Non	Non	Non	
- Const olTimeScale5Minutes = 0 (&H0) As Long	Non	Non	Non	
- Const olTimeScale60Minutes = 5 (&H5) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : <b>OlDayWeekTimeScale</b> (Type : Enum)</i>	00	02	03	07 *
- Const olTimeScale6Minutes = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlDefaultExpandCollapseSetting</b> (Type : Enum)</i>	00	02	03	07 *
- Const olAllCollapsed = 1 (&H1) As Long	Non	Non	Non	
- Const olAllExpanded = 0 (&H0) As Long	Non	Non	Non	
- Const olLastViewed = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlDefaultFolders</b> (Type : Enum)</i>	00	02	03	07 *
- Const olFolderCalendar = 9 (&H9) As Long				
- Const olFolderConflicts = 19 (&H13) As Long	Non	Non		
- Const olFolderContacts = 10 (&HA) As Long				
- Const olFolderDeletedItems = 3 (&H3) As Long				
- Const olFolderDrafts = 16 (&H10) As Long				
- Const olFolderInbox = 6 (&H6) As Long				
- Const olFolderJournal = 11 (&HB) As Long				
- Const olFolderJunk = 23 (&H17) As Long	Non	Non		
- Const olFolderLocalFailures = 21 (&H15) As Long	Non	Non		
- Const olFolderManagedEmail = 29 (&H1D) As Long	Non	Non	Non	
- Const olFolderNotes = 12 (&HC) As Long				
- Const olFolderOutbox = 4 (&H4) As Long				
- Const olFolderRssFeeds = 25 (&H19) As Long	Non	Non	Non	
- Const olFolderSentMail = 5 (&H5) As Long				
- Const olFolderServerFailures = 22 (&H16) As Long	Non	Non		
- Const olFolderSyncIssues = 20 (&H14) As Long	Non	Non		
- Const olFolderTasks = 13 (&HD) As Long				
- Const olFolderToDo = 28 (&H1C) As Long	Non	Non	Non	
- Const olPublicFoldersAllPublicFolders = 18 (&H12) As Long	Non			
<i>Classe de membres : <b>OlDefaultSelectNamesDisplayMode</b> (Type : Enum)</i>	00	02	03	07 *
- Const olDefaultDelegates = 6 (&H6) As Long	Non	Non	Non	
- Const olDefaultMail = 1 (&H1) As Long	Non	Non	Non	
- Const olDefaultMeeting = 2 (&H2) As Long	Non	Non	Non	
- Const olDefaultMembers = 5 (&H5) As Long	Non	Non	Non	
- Const olDefaultPickRooms = 8 (&H8) As Long	Non	Non	Non	
- Const olDefaultSharingRequest = 4 (&H4) As Long	Non	Non	Non	
- Const olDefaultSingleName = 7 (&H7) As Long	Non	Non	Non	
- Const olDefaultTask = 3 (&H3) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlDisplayType</b> (Type : Enum)</i>	00	02	03	07 *
- Const olAgent = 3 (&H3) As Long				
- Const olDistList = 1 (&H1) As Long				
- Const olForum = 2 (&H2) As Long				
- Const olOrganization = 4 (&H4) As Long				
- Const olPrivateDistList = 5 (&H5) As Long				
- Const olRemoteUser = 6 (&H6) As Long				
- Const olUser = 0 (&H0) As Long				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : <b>OlDownloadState</b> (Type : Enum)</i>	00	02	03	07 *
- Const olFullItem = 1 (&H1) As Long	Non			
- Const olHeaderOnly = 0 (&H0) As Long	Non			
<i>Classe de membres : <b>OlDragBehavior</b> (Type : Enum)</i>	00	02	03	07 *
- Const olDragBehaviorDisabled = 0 (&H0) As Long	Non	Non	Non	
- Const olDragBehaviorEnabled = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlEditorType</b> (Type : Enum)</i>	00	02	03	07 *
- Const olEditorHTML = 2 (&H2) As Long				
- Const olEditorRTF = 3 (&H3) As Long				
- Const olEditorText = 1 (&H1) As Long				
- Const olEditorWord = 4 (&H4) As Long				
<i>Classe de membres : <b>OlEnterFieldBehavior</b> (Type : Enum)</i>	00	02	03	07 *
- Const olEnterFieldBehaviorRecallSelection = 1 (&H1) As Long	Non	Non	Non	
- Const olEnterFieldBehaviorSelectAll = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlExchangeConnectionMode</b> (Type : Enum)</i>	00	02	03	07 *
- Const olCachedConnectedDrizzle = 600 (&H258) As Long	Non	Non		
- Const olCachedConnectedFull = 700 (&H2BC) As Long	Non	Non		
- Const olCachedConnectedHeaders = 500 (&H1F4) As Long	Non	Non		
- Const olCachedDisconnected = 400 (&H190) As Long	Non	Non		
- Const olCachedOffline = 200 (&HC8) As Long	Non	Non		
- Const olDisconnected = 300 (&H12C) As Long	Non	Non		
- Const olNoExchange = 0 (&H0) As Long	Non	Non		
- Const olOffline = 100 (&H64) As Long	Non	Non		
- Const olOnline = 800 (&H320) As Long	Non	Non		
<i>Classe de membres : <b>OlExchangeStoreType</b> (Type : Enum)</i>	00	02	03	07 *
- Const olExchangeMailbox = 1 (&H1) As Long	Non	Non	Non	
- Const olExchangePublicFolder = 2 (&H2) As Long	Non	Non	Non	
- Const olNotExchange = 3 (&H3) As Long	Non	Non	Non	
- Const olPrimaryExchangeMailbox = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlFlagIcon</b> (Type : Enum)</i>	00	02	03	07 *
- Const olBlueFlagIcon = 5 (&H5) As Long	Non	Non		
- Const olGreenFlagIcon = 3 (&H3) As Long	Non	Non		
- Const olNoFlagIcon = 0 (&H0) As Long	Non	Non		
- Const olOrangeFlagIcon = 2 (&H2) As Long	Non	Non		
- Const olPurpleFlagIcon = 1 (&H1) As Long	Non	Non		
- Const olRedFlagIcon = 6 (&H6) As Long	Non	Non		
- Const olYellowFlagIcon = 4 (&H4) As Long	Non	Non		
<i>Classe de membres : <b>OlFlagStatus</b> (Type : Enum)</i>	00	02	03	07 *
- Const olFlagComplete = 1 (&H1) As Long				
- Const olFlagMarked = 2 (&H2) As Long				
- Const olNoFlag = 0 (&H0) As Long				

## Classes et membres de la référence OUTLOOK

### Classe de membres : OIFolderDisplayMode (Type : Enum)

	00	02	03	07 *
- Const olFolderDisplayFolderOnly = 1 (&H1) As Long				
- Const olFolderDisplayNoNavigation = 2 (&H2) As Long				
- Const olFolderDisplayNormal = 0 (&H0) As Long				

### Classe de membres : OIFormatCurrency (Type : Enum)

	00	02	03	07 *
- Const olFormatCurrencyDecimal = 1 (&H1) As Long	Non	Non	Non	
- Const olFormatCurrencyNonDecimal = 2 (&H2) As Long	Non	Non	Non	

### Classe de membres : OIFormatDateTime (Type : Enum)

	00	02	03	07 *
- Const olFormatDateTimeBestFit = 17 (&H11) As Long	Non	Non	Non	
- Const olFormatDateTimeLongDate = 6 (&H6) As Long	Non	Non	Non	
- Const olFormatDateTimeLongDateReversed = 7 (&H7) As Long	Non	Non	Non	
- Const OIFormatDateTimeLongDayDate = 5 (&H5) As Long	Non	Non	Non	
- Const olFormatDateTimeLongDayDateTime = 1 (&H1) As Long	Non	Non	Non	
- Const olFormatDateTimeLongTime = 15 (&HF) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDate = 8 (&H8) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDateNumOnly = 9 (&H9) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDateTime = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDayDate = 13 (&HD) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDayDateTime = 3 (&H3) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDayMonth = 10 (&HA) As Long	Non	Non	Non	
- Const olFormatDateTimeShortDayMonthDateTime = 4 (&H4) As Long	Non	Non	Non	
- Const olFormatDateTimeShortMonthYear = 11 (&HB) As Long	Non	Non	Non	
- Const olFormatDateTimeShortMonthYearNumOnly = 12 (&HC) As Long	Non	Non	Non	
- Const olFormatDateTimeShortTime = 16 (&H10) As Long	Non	Non	Non	

### Classe de membres : OIFormatDuration (Type : Enum)

	00	02	03	07 *
- Const olFormatDurationLong = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatDurationLongBusiness = 4 (&H4) As Long	Non	Non	Non	
- Const olFormatDurationShort = 1 (&H1) As Long	Non	Non	Non	
- Const olFormatDurationShortBusiness = 3 (&H3) As Long	Non	Non	Non	

### Classe de membres : OIFormatEnumeration (Type : Enum)

	00	02	03	07 *
- Const olFormatEnumBitmap = 1 (&H1) As Long	Non	Non	Non	
- Const olFormatEnumText = 2 (&H2) As Long	Non	Non	Non	

### Classe de membres : OIFormatInteger (Type : Enum)

	00	02	03	07 *
- Const olFormatIntegerComputer1 = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatIntegerComputer2 = 3 (&H3) As Long	Non	Non	Non	
- Const olFormatIntegerComputer3 = 4 (&H4) As Long	Non	Non	Non	
- Const olFormatIntegerPlain = 1 (&H1) As Long	Non	Non	Non	

### Classe de membres : OIFormatKeywords (Type : Enum)

	00	02	03	07 *
- Const olFormatKeywordsText = 1 (&H1) As Long	Non	Non	Non	

### Classe de membres : OIFormatNumber (Type : Enum)

	00	02	03	07 *
- Const olFormatNumber1Decimal = 3 (&H3) As Long	Non	Non	Non	
- Const olFormatNumber2Decimal = 4 (&H4) As Long	Non	Non	Non	



## Classes et membres de la référence OUTLOOK

<i>Classe de membres : OIFormatNumber (Type : Enum)</i>	00	02	03	07 *
- Const olFormatNumberAllDigits = 1 (&H1) As Long	Non	Non	Non	
- Const olFormatNumberComputer1 = 6 (&H6) As Long	Non	Non	Non	
- Const olFormatNumberComputer2 = 7 (&H7) As Long	Non	Non	Non	
- Const olFormatNumberComputer3 = 8 (&H8) As Long	Non	Non	Non	
- Const olFormatNumberRaw = 9 (&H9) As Long	Non	Non	Non	
- Const olFormatNumberScientific = 5 (&H5) As Long	Non	Non	Non	
- Const olFormatNumberTruncated = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OIFormatPercent (Type : Enum)</i>	00	02	03	07 *
- Const olFormatPercent1Decimal = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatPercent2Decimal = 3 (&H3) As Long	Non	Non	Non	
- Const olFormatPercentAllDigits = 4 (&H4) As Long	Non	Non	Non	
- Const olFormatPercentRounded = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIFormatSmartFrom (Type : Enum)</i>	00	02	03	07 *
- Const olFormatSmartFromFromOnly = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatSmartFromFromTo = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIFormatText (Type : Enum)</i>	00	02	03	07 *
- Const olFormatTextText = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIFormatYesNo (Type : Enum)</i>	00	02	03	07 *
- Const olFormatYesNoIcon = 4 (&H4) As Long	Non	Non	Non	
- Const olFormatYesNoOnOff = 2 (&H2) As Long	Non	Non	Non	
- Const olFormatYesNoTrueFalse = 3 (&H3) As Long	Non	Non	Non	
- Const olFormatYesNoYesNo = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIFormRegionIcon (Type : Enum)</i>	00	02	03	07 *
- Const olFormRegionIconDefault = 1 (&H1) As Long	Non	Non	Non	
- Const olFormRegionIconEncrypted = 9 (&H9) As Long	Non	Non	Non	
- Const olFormRegionIconForwarded = 5 (&H5) As Long	Non	Non	Non	
- Const olFormRegionIconPage = 11 (&HB) As Long	Non	Non	Non	
- Const olFormRegionIconRead = 3 (&H3) As Long	Non	Non	Non	
- Const olFormRegionIconRecurring = 12 (&HC) As Long	Non	Non	Non	
- Const olFormRegionIconReplied = 4 (&H4) As Long	Non	Non	Non	
- Const olFormRegionIconSigned = 8 (&H8) As Long	Non	Non	Non	
- Const olFormRegionIconSubmitted = 7 (&H7) As Long	Non	Non	Non	
- Const olFormRegionIconUnread = 2 (&H2) As Long	Non	Non	Non	
- Const olFormRegionIconUnsent = 6 (&H6) As Long	Non	Non	Non	
- Const olFormRegionIconWindow = 10 (&HA) As Long	Non	Non	Non	
<i>Classe de membres : OIFormRegionMode (Type : Enum)</i>	00	02	03	07 *
- Const olFormRegionCompose = 1 (&H1) As Long	Non	Non	Non	
- Const olFormRegionPreview = 2 (&H2) As Long	Non	Non	Non	
- Const olFormRegionRead = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OIFormRegionSize (Type : Enum)</i>	00	02	03	07 *
- Const olFormRegionTypeAdjoining = 1 (&H1) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OIFormRegionSize (Type : Enum)</b>	00	02	03	07 *
- Const olFormRegionTypeSeparate = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OIFormRegistry (Type : Enum)</b>	00	02	03	07 *
- Const olDefaultRegistry = 0 (&H0) As Long				
- Const olFolderRegistry = 3 (&H3) As Long				
- Const olOrganizationRegistry = 4 (&H4) As Long				
- Const olPersonalRegistry = 2 (&H2) As Long				
<b>Classe de membres : OIGender (Type : Enum)</b>	00	02	03	07 *
- Const olFemale = 1 (&H1) As Long				
- Const olMale = 2 (&H2) As Long				
- Const olUnspecified = 0 (&H0) As Long				
<b>Classe de membres : OIGridLineStyle (Type : Enum)</b>	00	02	03	07 *
- Const olGridLineDashes = 3 (&H3) As Long	Non	Non	Non	
- Const olGridLineLargeDots = 2 (&H2) As Long	Non	Non	Non	
- Const olGridLineNone = 0 (&H0) As Long	Non	Non	Non	
- Const olGridLineSmallDots = 1 (&H1) As Long	Non	Non	Non	
- Const olGridLineSolid = 4 (&H4) As Long	Non	Non	Non	
<b>Classe de membres : OIGroupType (Type : Enum)</b>	00	02	03	07 *
- Const olCustomFoldersGroup = 0 (&H0) As Long	Non	Non	Non	
- Const olFavoriteFoldersGroup = 4 (&H4) As Long	Non	Non	Non	
- Const olMyFoldersGroup = 1 (&H1) As Long	Non	Non	Non	
- Const olOtherFoldersGroup = 3 (&H3) As Long	Non	Non	Non	
- Const olPeopleFoldersGroup = 2 (&H2) As Long	Non	Non	Non	
<b>Classe de membres : OIHorizontalLayout (Type : Enum)</b>	00	02	03	07 *
- Const olHorizontalLayoutAlignCenter = 1 (&H1) As Long	Non	Non	Non	
- Const olHorizontalLayoutAlignLeft = 0 (&H0) As Long	Non	Non	Non	
- Const olHorizontalLayoutAlignRight = 2 (&H2) As Long	Non	Non	Non	
- Const olHorizontalLayoutGrow = 3 (&H3) As Long	Non	Non	Non	
<b>Classe de membres : OIIconViewPlacement (Type : Enum)</b>	00	02	03	07 *
- Const ollconAutoArrange = 2 (&H2) As Long	Non	Non	Non	
- Const ollconDoNotArrange = 0 (&H0) As Long	Non	Non	Non	
- Const ollconLineUp = 1 (&H1) As Long	Non	Non	Non	
- Const ollconSortAndAutoArrange = 3 (&H3) As Long	Non	Non	Non	
<b>Classe de membres : OIIconViewType (Type : Enum)</b>	00	02	03	07 *
- Const ollconViewLarge = 0 (&H0) As Long	Non	Non	Non	
- Const ollconViewList = 2 (&H2) As Long	Non	Non	Non	
- Const ollconViewSmall = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OIImportance (Type : Enum)</b>	00	02	03	07 *
- Const ollImportanceHigh = 2 (&H2) As Long				
- Const ollImportanceLow = 0 (&H0) As Long				
- Const ollImportanceNormal = 1 (&H1) As Long				

## Classes et membres de la référence OUTLOOK

### Classe de membres : OInspectorClose (Type : Enum)

	00	02	03	07 *
- Const olDiscard = 1 (&H1) As Long				
- Const olPromptForSave = 2 (&H2) As Long				
- Const olSave = 0 (&H0) As Long				

### Classe de membres : OItemType (Type : Enum)

	00	02	03	07 *
- Const olAppointmentItem = 1 (&H1) As Long				
- Const olContactItem = 2 (&H2) As Long				
- Const olDistributionListItem = 7 (&H7) As Long				
- Const olJournalItem = 4 (&H4) As Long				
- Const olMailItem = 0 (&H0) As Long				
- Const olNoteItem = 5 (&H5) As Long				
- Const olPostItem = 6 (&H6) As Long				
- Const olTaskItem = 3 (&H3) As Long				

### Classe de membres : OJournalRecipientType (Type : Enum)

	00	02	03	07 *
- Const olAssociatedContact = 1 (&H1) As Long				

### Classe de membres : OlkBusinessCardControl (Type : Classe)

	00	02	03	07 *
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

### Classe de membres : OlkBusinessCardControlEvents (Type : Dispatch)

	00	02	03	07 *
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

### Classe de membres : OlkCategory (Type : Classe)

	00	02	03	07 *
- Property Get/Let AutoSize As Boolean	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : OlkCategory (Type : Classe)</i>	00	02	03	07 *
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : OlkCategoryEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : OlkCheckBox (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Accelerator As String	Non	Non	Non	
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let Alignment As OIAlignment	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let Caption As String	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>OlkCheckBox (Type : Classe)</b></i>	00	02	03	07 *
. Event KeyPress (KeyAscii As Long)	Non	Non	Non	
. Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let MouseIcon As Picture	Non	Non	Non	
. Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
. Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let TripleState As Boolean	Non	Non	Non	
. Property Get/Let Value As Variant	Non	Non	Non	
. Property Get/Let WordWrap As Boolean	Non	Non	Non	

<i>Classe de membres : <b>OlkCheckBoxEvents (Type : Dispatch)</b></i>	00	02	03	07 *
. Event AfterUpdate ()	Non	Non	Non	
. Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
. Event Change ()	Non	Non	Non	
. Event Click ()	Non	Non	Non	
. Event DoubleClick ()	Non	Non	Non	
. Event Enter ()	Non	Non	Non	
. Event Exit (Cancel As Boolean)	Non	Non	Non	
. Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event KeyPress (KeyAscii As Long)	Non	Non	Non	
. Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : <b>OlkComboBox (Type : Classe)</b></i>	00	02	03	07 *
. Sub AddItem (ItemText As String, Optional Index As Variant)	Non	Non	Non	
. Event AfterUpdate ()	Non	Non	Non	
. Property Get/Let AutoSize As Boolean	Non	Non	Non	
. Property Get/Let AutoTab As Boolean	Non	Non	Non	
. Property Get/Let AutoWordSelect As Boolean	Non	Non	Non	
. Property Get/Let BackColor As Long	Non	Non	Non	
. Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
. Property Get/Let BorderStyle As OIBorderStyle	Non	Non	Non	
. Event Change ()	Non	Non	Non	
. Sub Clear ()	Non	Non	Non	
. Event Click ()	Non	Non	Non	
. Sub Copy ()	Non	Non	Non	
. Sub Cut ()	Non	Non	Non	
. Event DoubleClick ()	Non	Non	Non	

## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : <b>OlkComboBox</b> (Type : Classe)</i>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get/Let DragBehavior As OI DragBehavior	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Sub DropDown ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Property Get/Let EnterFieldBehavior As OI EnterFieldBehavior	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Function GetItem (Index As Long) As String	Non	Non	Non	
- Property Get/Let HideSelection As Boolean	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OI ShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OI ShiftState)	Non	Non	Non	
- Property Get ListCount As Long	Non	Non	Non	
- Property Get/Let ListIndex As Long	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Property Get/Let MaxLength As Long	Non	Non	Non	
- Event MouseDown (Button As OI MouseButton, Shift As OI ShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OI MouseButton, Shift As OI ShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OI MousePointer	Non	Non	Non	
- Event MouseUp (Button As OI MouseButton, Shift As OI ShiftState, X As Single, Y As Single)	Non	Non	Non	
- Sub Paste ()	Non	Non	Non	
- Sub RemoveItem (Index As Long)	Non	Non	Non	
- Property Get/Let SelectionMargin As Boolean	Non	Non	Non	
- Property Get/Let SelLength As Long	Non	Non	Non	
- Property Get/Let SelStart As Long	Non	Non	Non	
- Property Get SelText As String	Non	Non	Non	
- Sub SetItem (Index As Long, Item As String)	Non	Non	Non	
- Property Get/Let Style As OI ComboBoxStyle	Non	Non	Non	
- Property Get/Let Text As String	Non	Non	Non	
- Property Get/Let TextAlign As OI TextAlign	Non	Non	Non	
- Property Get/Let TopIndex As Long	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	
<i>Classe de membres : <b>OlkComboBoxEvents</b> (Type : Dispatch)</i>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Event AfterUpdate ()	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>OlkComboBoxEvents</b> (Type : Dispatch)</i>	00	02	03	07 *
· Event Enter ()	Non	Non	Non	
· Event Exit (Cancel As Boolean)	Non	Non	Non	
· Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event KeyPress (KeyAscii As Long)	Non	Non	Non	
· Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : <b>OlkCommandButton</b> (Type : Classe)</i>	00	02	03	07 *
· Property Get/Let Accelerator As String	Non	Non	Non	
· Event AfterUpdate ()	Non	Non	Non	
· Property Get/Let AutoSize As Boolean	Non	Non	Non	
· Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
· Property Get/Let Caption As String	Non	Non	Non	
· Event Click ()	Non	Non	Non	
· Property Get/Let DisplayDropArrow As Boolean	Non	Non	Non	
· Event DoubleClick ()	Non	Non	Non	
· Property Get/Let Enabled As Boolean	Non	Non	Non	
· Event Enter ()	Non	Non	Non	
· Event Exit (Cancel As Boolean)	Non	Non	Non	
· Property Get Font As Font	Non	Non	Non	
· Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event KeyPress (KeyAscii As Long)	Non	Non	Non	
· Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Property Get/Let MouseIcon As Picture	Non	Non	Non	
· Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
· Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Property Get/Let Picture As Picture	Non	Non	Non	
· Property Get/Let PictureAlignment As OIPictureAlignment	Non	Non	Non	
· Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
· Property Get/Let WordWrap As Boolean	Non	Non	Non	

<i>Classe de membres : <b>OlkCommandButtonEvents</b> (Type : Dispatch)</i>	00	02	03	07 *
· Event AfterUpdate ()	Non	Non	Non	
· Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
· Event Click ()	Non	Non	Non	
· Event DoubleClick ()	Non	Non	Non	
· Event Enter ()	Non	Non	Non	

## Classes et membres de la référence **OUTLOOK**

<b>Classe de membres : <b>OlkCommandButtonEvents</b> (Type : Dispatch)</b>	00	02	03	07 *
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
<b>Classe de membres : <b>OlkContactPhoto</b> (Type : Classe)</b>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
<b>Classe de membres : <b>OlkContactPhotoEvents</b> (Type : Dispatch)</b>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
<b>Classe de membres : <b>OlkControl</b> (Type : Dispatch)</b>	00	02	03	07 *
- Property Get/Let ControlProperty As String	Non	Non	Non	



## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>OlkControl (Type : Dispatch)</b></i>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get/Let EnableAutoLayout As Boolean	Non	Non	Non	
- Property Get/Let Format As Long	Non	Non	Non	
- Property Get/Let HorizontalLayout As OIHorizontalLayout	Non	Non	Non	
- Property Get/Let ItemProperty As String	Non	Non	Non	
- Property Get/Let MinimumHeight As Long	Non	Non	Non	
- Property Get/Let MinimumWidth As Long	Non	Non	Non	
- Property Get/Let PossibleValues As String	Non	Non	Non	
- Property Get/Let VerticalLayout As OIVerticalLayout	Non	Non	Non	
<i>Classe de membres : <b>OlkDateControl (Type : Classe)</b></i>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let AutoSize As Boolean	Non	Non	Non	
- Property Get/Let AutoWordSelect As Boolean	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Property Get/Let Date As Date	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Sub DropDown ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Property Get/Let EnterFieldBehavior As OIEnterFieldBehavior	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Property Get/Let HideSelection As Boolean	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let ShowNoneButton As Boolean	Non	Non	Non	
- Property Get/Let Text As String	Non	Non	Non	
- Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>OlkDateControlEvents (Type : Dispatch)</b></i>	00	02	03	07 *
· Event AfterUpdate ()	Non	Non	Non	
· Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
· Event Change ()	Non	Non	Non	
· Event Click ()	Non	Non	Non	
· Event DoubleClick ()	Non	Non	Non	
· Event DropButtonClick ()	Non	Non	Non	
· Event Enter ()	Non	Non	Non	
· Event Exit (Cancel As Boolean)	Non	Non	Non	
· Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event KeyPress (KeyAscii As Long)	Non	Non	Non	
· Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
· Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : <b>OlkFrameHeader (Type : Classe)</b></i>	00	02	03	07 *
· Property Get/Let Alignment As OIAlignment	Non	Non	Non	
· Property Get/Let Caption As String	Non	Non	Non	
· Property Get/Let Enabled As Boolean	Non	Non	Non	
· Property Get Font As Font	Non	Non	Non	
· Property Get/Let ForeColor As Long	Non	Non	Non	
· Property Get/Let MouseIcon As Picture	Non	Non	Non	
· Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	

<i>Classe de membres : <b>OlkInfoBar (Type : Classe)</b></i>	00	02	03	07 *
· Event Click ()	Non	Non	Non	
· Event DoubleClick ()	Non	Non	Non	
· Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Property Get/Let MouseIcon As Picture	Non	Non	Non	
· Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
· Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : <b>OlkInfoBarEvents (Type : Dispatch)</b></i>	00	02	03	07 *
· Event Click ()	Non	Non	Non	
· Event DoubleClick ()	Non	Non	Non	
· Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
· Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : OlkLabel (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Accelerator As String	Non	Non	Non	
- Property Get/Let AutoSize As Boolean	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Property Get/Let BorderStyle As OIBorderStyle	Non	Non	Non	
- Property Get/Let Caption As String	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
- Property Get/Let UseHeaderColor As Boolean	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	Mask
- Property Get/Let WordWrap As Boolean	Non	Non	Non	

<i>Classe de membres : OlkLabelEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

<i>Classe de membres : OlkListBox (Type : Classe)</i>	00	02	03	07 *
- Sub AddItem (ItemText As String, Optional Index As Variant)	Non	Non	Non	
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let BorderStyle As OIBorderStyle	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Sub Clear ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Sub Copy ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : OlkListBox (Type : Classe)</i>	00	02	03	07 *
. Event Exit (Cancel As Boolean)	Non	Non	Non	
. Property Get Font As Font	Non	Non	Non	
. Property Get/Let ForeColor As Long	Non	Non	Non	
. Function GetItem (Index As Long) As String	Non	Non	Non	
. Function GetSelected (Index As Long) As Boolean	Non	Non	Non	
. Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event KeyPress (KeyAscii As Long)	Non	Non	Non	
. Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Property Get ListCount As Long	Non	Non	Non	
. Property Get/Let ListIndex As Long	Non	Non	Non	
. Property Get/Let Locked As Boolean	Non	Non	Non	
. Property Get/Let MatchEntry As OIMatchEntry	Non	Non	Non	
. Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let MouseIcon As Picture	Non	Non	Non	
. Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
. Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Property Get/Let MultiSelect As OIMultiSelect	Non	Non	Non	
. Sub RemoveItem (Index As Long)	Non	Non	Non	
. Sub SetItem (Index As Long, Item As String)	Non	Non	Non	
. Sub SetSelected (Index As Long, Selected As Boolean)	Non	Non	Non	
. Property Get/Let Text As String	Non	Non	Non	
. Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
. Property Get/Let TopIndex As Long	Non	Non	Non	
. Property Get/Let Value As Variant	Non	Non	Non	
<i>Classe de membres : OlkListBoxEvents (Type : Dispatch)</i>	00	02	03	07 *
. Event AfterUpdate ()	Non	Non	Non	
. Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
. Event Change ()	Non	Non	Non	
. Event Click ()	Non	Non	Non	
. Event DoubleClick ()	Non	Non	Non	
. Event Enter ()	Non	Non	Non	
. Event Exit (Cancel As Boolean)	Non	Non	Non	
. Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event KeyPress (KeyAscii As Long)	Non	Non	Non	
. Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
. Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
. Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>OlkOptionButton</b> (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Accelerator As String	Non	Non	Non	
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let Alignment As OIAlignment	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let Caption As String	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Property Get/Let GroupName As String	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- EventKeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	
- Property Get/Let WordWrap As Boolean	Non	Non	Non	
<i>Classe de membres : <b>OlkOptionButtonEvents</b> (Type : Dispatch)</i>	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- EventKeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : <b>OlkPageControl (Type : Classe)</b></i>	00	02	03	07 *
- Property Get/Let Page As OlPageType	Non	Non	Non	
<i>Classe de membres : <b>OlkSenderPhoto (Type : Classe)</b></i>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event MouseDown (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OlMousePointer	Non	Non	Non	
- Event MouseUp (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get PreferredHeight As Long	Non	Non	Non	
- Property Get PreferredWidth As Long	Non	Non	Non	
<i>Classe de membres : <b>OlkSenderPhotoEvents (Type : Dispatch)</b></i>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event MouseDown (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
<i>Classe de membres : <b>OlkTextBox (Type : Classe)</b></i>	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let AutoSize As Boolean	Non	Non	Non	
- Property Get/Let AutoTab As Boolean	Non	Non	Non	
- Property Get/Let AutoWordSelect As Boolean	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let BorderStyle As OlBorderStyle	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Sub Clear ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Sub Copy ()	Non	Non	Non	
- Sub Cut ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Property Get/Let DragBehavior As OlDragBehavior	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Property Get/Let EnterFieldBehavior As OlEnterFieldBehavior	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : OlkTextBox (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let EnterKeyBehavior As Boolean	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Property Get/Let HideSelection As Boolean	Non	Non	Non	
- Property Get/Let IntegralHeight As Boolean	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Property Get/Let MaxLength As Long	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MultiLine As Boolean	Non	Non	Non	
- Property Get/Let PasswordChar As String	Non	Non	Non	
- Sub Paste ()	Non	Non	Non	
- Property Get/Let Scrollbars As OIScrollBars	Non	Non	Non	
- Property Get/Let SelectionMargin As Boolean	Non	Non	Non	
- Property Get/Let SelLength As Long	Non	Non	Non	
- Property Get/Let SelStart As Long	Non	Non	Non	
- Property Get SelText As String	Non	Non	Non	
- Property Get/Let TabKeyBehavior As Boolean	Non	Non	Non	
- Property Get/Let Text As String	Non	Non	Non	
- Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	
- Property Get/Let WordWrap As Boolean	Non	Non	Non	

<i>Classe de membres : OlkTextBoxEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

### *Classe de membres : OlkTextBoxEvents (Type : Dispatch)*

	00	02	03	07 *
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

### *Classe de membres : OlkTimeControl (Type : Classe)*

	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let AutoSize As Boolean	Non	Non	Non	
- Property Get/Let AutoWordSelect As Boolean	Non	Non	Non	
- Property Get/Let BackColor As Long	Non	Non	Non	
- Property Get/Let BackStyle As OIBackStyle	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Sub DropDown ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Property Get/Let EnterFieldBehavior As OIEnterFieldBehavior	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Property Get Font As Font	Non	Non	Non	
- Property Get/Let ForeColor As Long	Non	Non	Non	
- Property Get/Let HideSelection As Boolean	Non	Non	Non	
- Property Get/Let IntervalTime As Date	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let ReferenceTime As Date	Non	Non	Non	
- Property Get/Let Style As OITimeStyle	Non	Non	Non	
- Property Get/Let Text As String	Non	Non	Non	
- Property Get/Let TextAlign As OITextAlign	Non	Non	Non	
- Property Get/Let Time As Date	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	

### *Classe de membres : OlkTimeControlEvents (Type : Dispatch)*

	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	



## *Classes et membres de la référence OUTLOOK*

Classe de membres : <b>OlkTimeControlEvents (Type : Dispatch)</b>	00	02	03	07 *
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	

Classe de membres : <b>OlkTimeZoneControl (Type : Classe)</b>	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Property Get/Let AppointmentTimeField As OIAppointmentTimeField	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	
- Property Get/Let BorderStyle As OIBorderStyle	Non	Non	Non	
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Sub DropDown ()	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OIShiftState)	Non	Non	Non	
- Property Get/Let Locked As Boolean	Non	Non	Non	
- Event MouseDown (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MouseIcon As Picture	Non	Non	Non	
- Event MouseMove (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let MousePointer As OIMousePointer	Non	Non	Non	
- Event MouseUp (Button As OIMouseButton, Shift As OIShiftState, X As Single, Y As Single)	Non	Non	Non	
- Property Get/Let SelectedTimeZoneIndex As Long	Non	Non	Non	
- Property Get/Let Value As Variant	Non	Non	Non	

Classe de membres : <b>OlkTimeZoneControlEvents (Type : Dispatch)</b>	00	02	03	07 *
- Event AfterUpdate ()	Non	Non	Non	
- Event BeforeUpdate (Cancel As Boolean)	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OlkTimeZoneControlEvents (Type : Dispatch)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Event Change ()	Non	Non	Non	
- Event Click ()	Non	Non	Non	
- Event DoubleClick ()	Non	Non	Non	
- Event DropButtonClick ()	Non	Non	Non	
- Event Enter ()	Non	Non	Non	
- Event Exit (Cancel As Boolean)	Non	Non	Non	
- Event KeyDown (KeyCode As Long, Shift As OlShiftState)	Non	Non	Non	
- Event KeyPress (KeyAscii As Long)	Non	Non	Non	
- Event KeyUp (KeyCode As Long, Shift As OlShiftState)	Non	Non	Non	
- Event MouseDown (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseMove (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
- Event MouseUp (Button As OlMouseButton, Shift As OlShiftState, X As Single, Y As Single)	Non	Non	Non	
<b>Classe de membres : OlMailingAddress (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olBusiness = 2 (&H2) As Long				
- Const olHome = 1 (&H1) As Long				
- Const olNone = 0 (&H0) As Long				
- Const olOther = 3 (&H3) As Long				
<b>Classe de membres : OlMailRecipientType (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olBCC = 3 (&H3) As Long				
- Const olCC = 2 (&H2) As Long				
- Const olOriginator = 0 (&H0) As Long				
- Const olTo = 1 (&H1) As Long				
<b>Classe de membres : OlMarkInterval (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olMarkNextWeek = 3 (&H3) As Long	Non	Non	Non	
- Const olMarkNoDate = 4 (&H4) As Long	Non	Non	Non	
- Const olMarkThisWeek = 2 (&H2) As Long	Non	Non	Non	
- Const olMarkToday = 0 (&H0) As Long	Non	Non	Non	
- Const olMarkTomorrow = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OlMatchEntry (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olMatchEntryComplete = 1 (&H1) As Long	Non	Non	Non	
- Const olMatchEntryFirstLetter = 0 (&H0) As Long	Non	Non	Non	
- Const olMatchEntryNone = 2 (&H2) As Long	Non	Non	Non	
<b>Classe de membres : OlMeetingRecipientType (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olOptional = 2 (&H2) As Long				
- Const olOrganizer = 0 (&H0) As Long				
- Const olRequired = 1 (&H1) As Long				
- Const olResource = 3 (&H3) As Long				
<b>Classe de membres : OlMeetingResponse (Type : Enum)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Const olMeetingAccepted = 3 (&H3) As Long				

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OIMeetingResponse (Type : Enum)</b>	00	02	03	07 *
- Const olMeetingDeclined = 4 (&H4) As Long				
- Const olMeetingTentative = 2 (&H2) As Long				
<b>Classe de membres : OIMeetingStatus (Type : Enum)</b>	00	02	03	07 *
- Const olMeeting = 1 (&H1) As Long				
- Const olMeetingCanceled = 5 (&H5) As Long				
- Const olMeetingReceived = 3 (&H3) As Long				
- Const olMeetingReceivedAndCanceled = 7 (&H7) As Long	Non	Non	Non	
- Const olNonMeeting = 0 (&H0) As Long				
<b>Classe de membres : OIMouseButton (Type : Enum)</b>	00	02	03	07 *
- Const olMouseButtonLeft = 1 (&H1) As Long	Non	Non	Non	
- Const olMouseButtonMiddle = 4 (&H4) As Long	Non	Non	Non	
- Const olMouseButtonRight = 2 (&H2) As Long	Non	Non	Non	
<b>Classe de membres : OIMousePointer (Type : Enum)</b>	00	02	03	07 *
- Const olMousePointerAppStarting = 13 (&HD) As Long	Non	Non	Non	
- Const olMousePointerArrow = 1 (&H1) As Long	Non	Non	Non	
- Const olMousePointerCross = 2 (&H2) As Long	Non	Non	Non	
- Const olMousePointerCustom = 99 (&H63) As Long	Non	Non	Non	
- Const olMousePointerDefault = 0 (&H0) As Long	Non	Non	Non	
- Const olMousePointerHelp = 14 (&HE) As Long	Non	Non	Non	
- Const olMousePointerHourGlass = 11 (&HB) As Long	Non	Non	Non	
- Const olMousePointerIBeam = 3 (&H3) As Long	Non	Non	Non	
- Const olMousePointerNoDrop = 12 (&HC) As Long	Non	Non	Non	
- Const olMousePointerSizeAll = 15 (&HF) As Long	Non	Non	Non	
- Const olMousePointerSizeNESW = 6 (&H6) As Long	Non	Non	Non	
- Const olMousePointerSizeNS = 7 (&H7) As Long	Non	Non	Non	
- Const olMousePointerSizeNWSE = 8 (&H8) As Long	Non	Non	Non	
- Const olMousePointerSizeWE = 9 (&H9) As Long	Non	Non	Non	
- Const olMousePointerUpArrow = 10 (&HA) As Long	Non	Non	Non	
<b>Classe de membres : OIMultiLine (Type : Enum)</b>	00	02	03	07 *
- Const olAlwaysMultiLine = 2 (&H2) As Long	Non	Non	Non	
- Const olAlwaysSingleLine = 1 (&H1) As Long	Non	Non	Non	
- Const olWidthMultiLine = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OIMultiSelect (Type : Enum)</b>	00	02	03	07 *
- Const olMultiSelectExtended = 2 (&H2) As Long	Non	Non	Non	
- Const olMultiSelectMulti = 1 (&H1) As Long	Non	Non	Non	
- Const olMultiSelectSingle = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OINavigationModuleType (Type : Enum)</b>	00	02	03	07 *
- Const olModuleCalendar = 1 (&H1) As Long	Non	Non	Non	
- Const olModuleContacts = 2 (&H2) As Long	Non	Non	Non	
- Const olModuleFolderList = 6 (&H6) As Long	Non	Non	Non	
- Const olModuleJournal = 4 (&H4) As Long	Non	Non	Non	

## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : <b>OlNavigationModuleType (Type : Enum)</b></i>	00	02	03	07 *
- Const olModuleMail = 0 (&H0) As Long	Non	Non	Non	
- Const olModuleNotes = 5 (&H5) As Long	Non	Non	Non	
- Const olModuleShortcuts = 7 (&H7) As Long	Non	Non	Non	
- Const olModuleTasks = 3 (&H3) As Long	Non	Non	Non	
<i>Classe de membres : <b>OlNetMeetingType (Type : Enum)</b></i>	00	02	03	07 *
- Const olChat = 2 (&H2) As Long		Non	Non	Non
- Const olExchangeConferencing = 2 (&H2) As Long	Non			
- Const olNetMeeting = 0 (&H0) As Long				
- Const olNetShow = 1 (&H1) As Long				
<i>Classe de membres : <b>OlNoteColor (Type : Enum)</b></i>	00	02	03	07 *
- Const olBlue = 0 (&H0) As Long				
- Const olGreen = 1 (&H1) As Long				
- Const olPink = 2 (&H2) As Long				
- Const olWhite = 4 (&H4) As Long				
- Const olYellow = 3 (&H3) As Long				
<i>Classe de membres : <b>OlObjectClass (Type : Enum)</b></i>	00	02	03	07 *
- Const olAccount = 105 (&H69) As Long	Non	Non	Non	
- Const olAccountRuleCondition = 135 (&H87) As Long	Non	Non	Non	
- Const olAccounts = 106 (&H6A) As Long	Non	Non	Non	
- Const olAction = 32 (&H20) As Long				
- Const olActions = 33 (&H21) As Long				
- Const olAddressEntries = 21 (&H15) As Long				
- Const olAddressEntry = 8 (&H8) As Long				
- Const olAddressList = 7 (&H7) As Long				
- Const olAddressLists = 20 (&H14) As Long				
- Const olAddressRuleCondition = 170 (&HAA) As Long	Non	Non	Non	
- Const olApplication = 0 (&H0) As Long				
- Const olAppointment = 26 (&H1A) As Long				
- Const olAssignToCategoryRuleAction = 122 (&H7A) As Long	Non	Non	Non	
- Const olAttachment = 5 (&H5) As Long				
- Const olAttachments = 18 (&H12) As Long				
- Const olAttachmentSelection = 169 (&HA9) As Long	Non	Non	Non	
- Const olAutoFormatRule = 147 (&H93) As Long	Non	Non	Non	
- Const olAutoFormatRules = 148 (&H94) As Long	Non	Non	Non	
- Const olCalendarModule = 159 (&H9F) As Long	Non	Non	Non	
- Const olCalendarSharing = 151 (&H97) As Long	Non	Non	Non	
- Const olCategories = 153 (&H99) As Long	Non	Non	Non	
- Const olCategory = 152 (&H98) As Long	Non	Non	Non	
- Const olCategoryRuleCondition = 130 (&H82) As Long	Non	Non	Non	
- Const olClassBusinessCardView = 168 (&HA8) As Long	Non	Non	Non	
- Const olClassCalendarView = 139 (&H8B) As Long	Non	Non	Non	
- Const olClassCardView = 138 (&H8A) As Long	Non	Non	Non	
- Const olClassIconView = 137 (&H89) As Long	Non	Non	Non	

## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : OObjectClass (Type : Enum)</i>	00	02	03	07 *
- Const olClassNavigationPane = 155 (&H9B) As Long	Non	Non	Non	
- Const olClassTableView = 136 (&H88) As Long	Non	Non	Non	
- Const olClassTimeLineView = 140 (&H8C) As Long	Non	Non	Non	
- Const olClassTimeZone = 174 (&HAE) As Long	Non	Non	Non	
- Const olClassTimeZones = 175 (&HAF) As Long	Non	Non	Non	
- Const olColumn = 154 (&H9A) As Long	Non	Non	Non	
- Const olColumnFormat = 149 (&H95) As Long	Non	Non	Non	
- Const olColumns = 150 (&H96) As Long	Non	Non	Non	
- Const olConflict = 102 (&H66) As Long	Non	Non		
- Const olConflicts = 103 (&H67) As Long	Non	Non		
- Const olContact = 40 (&H28) As Long				
- Const olContactsModule = 160 (&HA0) As Long	Non	Non	Non	
- Const olDistributionList = 69 (&H45) As Long				
- Const olDocument = 41 (&H29) As Long				
- Const olException = 30 (&H1E) As Long				
- Const olExceptions = 29 (&H1D) As Long				
- Const olExchangeDistributionList = 111 (&H6F) As Long	Non	Non	Non	
- Const olExchangeUser = 110 (&H6E) As Long	Non	Non	Non	
- Const olExplorer = 34 (&H22) As Long				
- Const olExplorers = 60 (&H3C) As Long				
- Const olFolder = 2 (&H2) As Long				
- Const olFolders = 15 (&HF) As Long				
- Const olFormDescription = 37 (&H25) As Long				
- Const olFormNameRuleCondition = 131 (&H83) As Long	Non	Non	Non	
- Const olFormRegion = 129 (&H81) As Long	Non	Non	Non	
- Const olFromRssFeedRuleCondition = 173 (&HAD) As Long	Non	Non	Non	
- Const olFromRuleCondition = 132 (&H84) As Long	Non	Non	Non	
- Const olImportanceRuleCondition = 128 (&H80) As Long	Non	Non	Non	
- Const olInspector = 35 (&H23) As Long				
- Const olInspectors = 61 (&H3D) As Long				
- Const olItemProperties = 98 (&H62) As Long	Non			
- Const olItemProperty = 99 (&H63) As Long	Non			
- Const olItems = 16 (&H10) As Long				
- Const olJournal = 42 (&H2A) As Long				
- Const olJournalModule = 162 (&HA2) As Long	Non	Non	Non	
- Const olLink = 75 (&H4B) As Long				
- Const olLinks = 76 (&H4C) As Long				
- Const olMail = 43 (&H2B) As Long				
- Const olMailModule = 158 (&H9E) As Long	Non	Non	Non	
- Const olMarkAsTaskRuleAction = 124 (&H7C) As Long	Non	Non	Non	
- Const olMeetingCancellation = 54 (&H36) As Long				
- Const olMeetingRequest = 53 (&H35) As Long				
- Const olMeetingResponseNegative = 55 (&H37) As Long				
- Const olMeetingResponsePositive = 56 (&H38) As Long				
- Const olMeetingResponseTentative = 57 (&H39) As Long				

## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres</i> : <b>OObjectClass (Type : Enum)</b>	00	02	03	07 *
- Const olMoveOrCopyRuleAction = 118 (&H76) As Long	Non	Non	Non	
- Const olNamespace = 1 (&H1) As Long				
- Const olNavigationFolder = 167 (&HA7) As Long	Non	Non	Non	
- Const olNavigationFolders = 166 (&HA6) As Long	Non	Non	Non	
- Const olNavigationGroup = 165 (&HA5) As Long	Non	Non	Non	
- Const olNavigationGroups = 164 (&HA4) As Long	Non	Non	Non	
- Const olNavigationModule = 157 (&H9D) As Long	Non	Non	Non	
- Const olNavigationModules = 156 (&H9C) As Long	Non	Non	Non	
- Const olNewItemAlertRuleAction = 125 (&H7D) As Long	Non	Non	Non	
- Const olNote = 44 (&H2C) As Long				
- Const olNotesModule = 163 (&HA3) As Long	Non	Non	Non	
- Const olOrderField = 144 (&H90) As Long	Non	Non	Non	
- Const olOrderFields = 145 (&H91) As Long	Non	Non	Non	
- Const olOutlookBarGroup = 66 (&H42) As Long				
- Const olOutlookBarGroups = 65 (&H41) As Long				
- Const olOutlookBarPane = 63 (&H3F) As Long				
- Const olOutlookBarShortcut = 68 (&H44) As Long				
- Const olOutlookBarShortcuts = 67 (&H43) As Long				
- Const olOutlookBarStorage = 64 (&H40) As Long				
- Const olPages = 36 (&H24) As Long				
- Const olPanels = 62 (&H3E) As Long				
- Const olPlaySoundRuleAction = 123 (&H7B) As Long	Non	Non	Non	
- Const olPost = 45 (&H2D) As Long				
- Const olPropertyAccessor = 112 (&H70) As Long	Non	Non	Non	
- Const olPropertyPages = 71 (&H47) As Long				
- Const olPropertyPageSite = 70 (&H46) As Long				
- Const olRecipient = 4 (&H4) As Long				
- Const olRecipients = 17 (&H11) As Long				
- Const olRecurrencePattern = 28 (&H1C) As Long				
- Const olReminder = 101 (&H65) As Long	Non			
- Const olReminders = 100 (&H64) As Long	Non			
- Const olRemote = 47 (&H2F) As Long				
- Const olReport = 46 (&H2E) As Long				
- Const olResults = 78 (&H4E) As Long	Non			
- Const olRow = 121 (&H79) As Long	Non	Non	Non	
- Const olRule = 115 (&H73) As Long	Non	Non	Non	
- Const olRuleAction = 117 (&H75) As Long	Non	Non	Non	
- Const olRuleActions = 116 (&H74) As Long	Non	Non	Non	
- Const olRuleCondition = 127 (&H7F) As Long	Non	Non	Non	
- Const olRuleConditions = 126 (&H7E) As Long	Non	Non	Non	
- Const olRules = 114 (&H72) As Long	Non	Non	Non	
- Const olSearch = 77 (&H4D) As Long	Non			
- Const olSelection = 74 (&H4A) As Long				
- Const olSelectNamesDialog = 109 (&H6D) As Long	Non	Non	Non	
- Const olSenderInAddressListRuleCondition = 133 (&H85) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OObjectClass (Type : Enum)</b>	00	02	03	07 *
- Const olSendRuleAction = 119 (&H77) As Long	Non	Non	Non	
- Const olSharing = 104 (&H68) As Long	Non	Non	Non	
- Const olStorageItem = 113 (&H71) As Long	Non	Non	Non	
- Const olStore = 107 (&H6B) As Long	Non	Non	Non	
- Const olStores = 108 (&H6C) As Long	Non	Non	Non	
- Const olSyncObject = 72 (&H48) As Long				
- Const olSyncObjects = 73 (&H49) As Long				
- Const olTable = 120 (&H78) As Long	Non	Non	Non	
- Const olTask = 48 (&H30) As Long				
- Const olTaskRequest = 49 (&H31) As Long				
- Const olTaskRequestAccept = 51 (&H33) As Long				
- Const olTaskRequestDecline = 52 (&H34) As Long				
- Const olTaskRequestUpdate = 50 (&H32) As Long				
- Const olTasksModule = 161 (&HA1) As Long	Non	Non	Non	
- Const olTextRuleCondition = 134 (&H86) As Long	Non	Non	Non	
- Const olUserDefinedProperties = 172 (&HAC) As Long	Non	Non	Non	
- Const olUserDefinedProperty = 171 (&HAB) As Long	Non	Non	Non	
- Const olUserProperties = 38 (&H26) As Long				
- Const olUserProperty = 39 (&H27) As Long				
- Const olView = 80 (&H50) As Long	Non			
- Const olViewField = 142 (&H8E) As Long	Non	Non	Non	
- Const olViewFields = 141 (&H8D) As Long	Non	Non	Non	
- Const olViewFont = 146 (&H92) As Long	Non	Non	Non	
- Const olViews = 79 (&H4F) As Long	Non			
<b>Classe de membres : OOfficeDocItemsType (Type : Enum)</b>	00	02	03	07 *
- Const olExcelWorksheetItem = 8 (&H8) As Long	Non			
- Const olPowerPointShowItem = 10 (&HA) As Long	Non			
- Const olWordDocumentItem = 9 (&H9) As Long	Non			
<b>Classe de membres : OOutlookBarViewType (Type : Enum)</b>	00	02	03	07 *
- Const olLargeIcon = 0 (&H0) As Long				
- Const olSmallIcon = 1 (&H1) As Long				
<b>Classe de membres : OPageType (Type : Enum)</b>	00	02	03	07 *
- Const olPageTypePlanner = 0 (&H0) As Long	Non	Non	Non	
- Const olPageTypeTracker = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OPane (Type : Enum)</b>	00	02	03	07 *
- Const olFolderList = 2 (&H2) As Long				
- Const olNavigationPane = 4 (&H4) As Long	Non	Non		
- Const olOutlookBar = 1 (&H1) As Long				
- Const olPreview = 3 (&H3) As Long				
- Const olToDoBar = 5 (&H5) As Long	Non	Non	Non	
<b>Classe de membres : OPermission (Type : Enum)</b>	00	02	03	07 *
- Const olDoNotForward = 1 (&H1) As Long	Non	Non		

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : OIPermission (Type : Enum)</i>	00	02	03	07 *
- Const olPermissionTemplate = 2 (&H2) As Long	Non	Non		
- Const olUnrestricted = 0 (&H0) As Long	Non	Non		
<i>Classe de membres : OIPermissionService (Type : Enum)</i>	00	02	03	07 *
- Const olPassport = 2 (&H2) As Long	Non	Non		
- Const olUnknown = 0 (&H0) As Long	Non	Non		
- Const olWindows = 1 (&H1) As Long	Non	Non		
<i>Classe de membres : OIPictureAlignment (Type : Enum)</i>	00	02	03	07 *
- Const olPictureAlignmentLeft = 0 (&H0) As Long	Non	Non	Non	
- Const olPictureAlignmentTop = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIRecipientSelectors (Type : Enum)</i>	00	02	03	07 *
- Const olShowNone = 0 (&H0) As Long	Non	Non	Non	
- Const olShowTo = 1 (&H1) As Long	Non	Non	Non	
- Const olShowToCc = 2 (&H2) As Long	Non	Non	Non	
- Const olShowToCcBcc = 3 (&H3) As Long	Non	Non	Non	
<i>Classe de membres : OIRecurrenceState (Type : Enum)</i>	00	02	03	07 *
- Const olApptException = 3 (&H3) As Long				
- Const olApptMaster = 1 (&H1) As Long				
- Const olApptNotRecurring = 0 (&H0) As Long				
- Const olApptOccurrence = 2 (&H2) As Long				
<i>Classe de membres : OIRecurrenceType (Type : Enum)</i>	00	02	03	07 *
- Const olRecursDaily = 0 (&H0) As Long				
- Const olRecursMonthly = 2 (&H2) As Long				
- Const olRecursMonthNth = 3 (&H3) As Long				
- Const olRecursWeekly = 1 (&H1) As Long				
- Const olRecursYearly = 5 (&H5) As Long				
- Const olRecursYearNth = 6 (&H6) As Long				
<i>Classe de membres : OIReferenceType (Type : Enum)</i>	00	02	03	07 *
- Const olStrong = 1 (&H1) As Long	Non	Non	Non	
- Const olWeak = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OIRemoteStatus (Type : Enum)</i>	00	02	03	07 *
- Const olMarkedForCopy = 3 (&H3) As Long				
- Const olMarkedForDelete = 4 (&H4) As Long				
- Const olMarkedForDownload = 2 (&H2) As Long				
- Const olRemoteStatusNone = 0 (&H0) As Long				
- Const olUnMarked = 1 (&H1) As Long				
<i>Classe de membres : OIResponseStatus (Type : Enum)</i>	00	02	03	07 *
- Const olResponseAccepted = 3 (&H3) As Long				
- Const olResponseDeclined = 4 (&H4) As Long				
- Const olResponseNone = 0 (&H0) As Long				
- Const olResponseNotResponded = 5 (&H5) As Long				



## Classes et membres de la référence OUTLOOK

### Classe de membres : **OIResponseStatus (Type : Enum)** 00 02 03 07 \*

- Const olResponseOrganized = 1 (&H1) As Long
- Const olResponseTentative = 2 (&H2) As Long

### Classe de membres : **OIRuleActionType (Type : Enum)** 00 02 03 07 \*

- |  | 00  | 02  | 03  | 07 * |
|--|-----|-----|-----|------|
| - Const olRuleActionAssignToCategory = 2 (&H2) As Long     | Non | Non | Non |      |
| - Const olRuleActionCcMessage = 27 (&H1B) As Long          | Non | Non | Non |      |
| - Const olRuleActionClearCategories = 30 (&H1E) As Long    | Non | Non | Non |      |
| - Const olRuleActionCopyToFolder = 5 (&H5) As Long         | Non | Non | Non |      |
| - Const olRuleActionCustomAction = 22 (&H16) As Long       | Non | Non | Non |      |
| - Const olRuleActionDefer = 28 (&H1C) As Long              | Non | Non | Non |      |
| - Const olRuleActionDelete = 3 (&H3) As Long               | Non | Non | Non |      |
| - Const olRuleActionDeletePermanently = 4 (&H4) As Long    | Non | Non | Non |      |
| - Const olRuleActionDesktopAlert = 24 (&H18) As Long       | Non | Non | Non |      |
| - Const olRuleActionFlagClear = 13 (&HD) As Long           | Non | Non | Non |      |
| - Const olRuleActionFlagColor = 12 (&HC) As Long           | Non | Non | Non |      |
| - Const olRuleActionFlagForActionInDays = 11 (&HB) As Long | Non | Non | Non |      |
| - Const olRuleActionForward = 6 (&H6) As Long              | Non | Non | Non |      |
| - Const olRuleActionForwardAsAttachment = 7 (&H7) As Long  | Non | Non | Non |      |
| - Const olRuleActionImportance = 14 (&HE) As Long          | Non | Non | Non |      |
| - Const olRuleActionMarkAsTask = 29 (&H1D) As Long         | Non | Non | Non |      |
| - Const olRuleActionMarkRead = 19 (&H13) As Long           | Non | Non | Non |      |
| - Const olRuleActionMoveToFolder = 1 (&H1) As Long         | Non | Non | Non |      |
| - Const olRuleActionNewItemAlert = 23 (&H17) As Long       | Non | Non | Non |      |
| - Const olRuleActionNotifyDelivery = 26 (&H1A) As Long     | Non | Non | Non |      |
| - Const olRuleActionNotifyRead = 25 (&H19) As Long         | Non | Non | Non |      |
| - Const olRuleActionPlaySound = 17 (&H11) As Long          | Non | Non | Non |      |
| - Const olRuleActionPrint = 16 (&H10) As Long              | Non | Non | Non |      |
| - Const olRuleActionRedirect = 8 (&H8) As Long             | Non | Non | Non |      |
| - Const olRuleActionRunScript = 20 (&H14) As Long          | Non | Non | Non |      |
| - Const olRuleActionSensitivity = 15 (&HF) As Long         | Non | Non | Non |      |
| - Const olRuleActionServerReply = 9 (&H9) As Long          | Non | Non | Non |      |
| - Const olRuleActionStartApplication = 18 (&H12) As Long   | Non | Non | Non |      |
| - Const olRuleActionStop = 21 (&H15) As Long               | Non | Non | Non |      |
| - Const olRuleActionTemplate = 10 (&HA) As Long            | Non | Non | Non |      |
| - Const olRuleActionUnknown = 0 (&H0) As Long              | Non | Non | Non |      |

### Classe de membres : **OIRuleConditionType (Type : Enum)** 00 02 03 07 \*

- |   | 00  | 02  | 03  | 07 * |
|---|-----|-----|-----|------|
| - Const olConditionAccount = 3 (&H3) As Long          | Non | Non | Non |      |
| - Const olConditionAnyCategory = 29 (&H1D) As Long    | Non | Non | Non |      |
| - Const olConditionBody = 13 (&HD) As Long            | Non | Non | Non |      |
| - Const olConditionBodyOrSubject = 14 (&HE) As Long   | Non | Non | Non |      |
| - Const olConditionCategory = 18 (&H12) As Long       | Non | Non | Non |      |
| - Const olConditionCc = 9 (&H9) As Long               | Non | Non | Non |      |
| - Const olConditionDateRange = 22 (&H16) As Long      | Non | Non | Non |      |
| - Const olConditionFlaggedForAction = 8 (&H8) As Long | Non | Non | Non |      |
| - Const olConditionFormName = 23 (&H17) As Long       | Non | Non | Non |      |

## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : OIRuleConditionType (Type : Enum)</i>	00	02	03	07 *
- Const olConditionFrom = 1 (&H1) As Long	Non	Non	Non	
- Const olConditionFromAnyRssFeed = 31 (&H1F) As Long	Non	Non	Non	
- Const olConditionFromRssFeed = 30 (&H1E) As Long	Non	Non	Non	
- Const olConditionHasAttachment = 20 (&H14) As Long	Non	Non	Non	
- Const olConditionImportance = 6 (&H6) As Long	Non	Non	Non	
- Const olConditionLocalMachineOnly = 27 (&H1B) As Long	Non	Non	Non	
- Const olConditionMeetingInviteOrUpdate = 26 (&H1A) As Long	Non	Non	Non	
- Const olConditionMessageHeader = 15 (&HF) As Long	Non	Non	Non	
- Const olConditionNotTo = 11 (&HB) As Long	Non	Non	Non	
- Const olConditionOnlyToMe = 4 (&H4) As Long	Non	Non	Non	
- Const olConditionOOO = 19 (&H13) As Long	Non	Non	Non	
- Const olConditionOtherMachine = 28 (&H1C) As Long	Non	Non	Non	
- Const olConditionProperty = 24 (&H18) As Long	Non	Non	Non	
- Const olConditionRecipientAddress = 16 (&H10) As Long	Non	Non	Non	
- Const olConditionSenderAddress = 17 (&H11) As Long	Non	Non	Non	
- Const olConditionSenderInAddressBook = 25 (&H19) As Long	Non	Non	Non	
- Const olConditionSensitivity = 7 (&H7) As Long	Non	Non	Non	
- Const olConditionSentTo = 12 (&HC) As Long	Non	Non	Non	
- Const olConditionSizeRange = 21 (&H15) As Long	Non	Non	Non	
- Const olConditionSubject = 2 (&H2) As Long	Non	Non	Non	
- Const olConditionTo = 5 (&H5) As Long	Non	Non	Non	
- Const olConditionToOrCc = 10 (&HA) As Long	Non	Non	Non	
- Const olConditionUnknown = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OIRuleExecuteOption (Type : Enum)</i>	00	02	03	07 *
- Const olRuleExecuteAllMessages = 0 (&H0) As Long	Non	Non	Non	
- Const olRuleExecuteReadMessages = 1 (&H1) As Long	Non	Non	Non	
- Const olRuleExecuteUnreadMessages = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OIRuleType (Type : Enum)</i>	00	02	03	07 *
- Const olRuleReceive = 0 (&H0) As Long	Non	Non	Non	
- Const olRuleSend = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OISaveAsType (Type : Enum)</i>	00	02	03	07 *
- Const olDoc = 4 (&H4) As Long				
- Const olHTML = 5 (&H5) As Long				
- Const olIcal = 8 (&H8) As Long	Non			
- Const olMHTML = 10 (&HA) As Long	Non	Non	Non	
- Const olMSG = 3 (&H3) As Long				
- Const olMSGUnicode = 9 (&H9) As Long	Non	Non		
- Const olRTF = 1 (&H1) As Long				
- Const olTemplate = 2 (&H2) As Long				
- Const olTXT = 0 (&H0) As Long				
- Const olVCal = 7 (&H7) As Long				
- Const olVCard = 6 (&H6) As Long				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : OIScrollBars (Type : Enum)</i>	00	02	03	07 *
- Const olScrollBarsBoth = 3 (&H3) As Long	Non	Non	Non	
- Const olScrollBarsHorizontal = 1 (&H1) As Long	Non	Non	Non	
- Const olScrollBarsNone = 0 (&H0) As Long	Non	Non	Non	
- Const olScrollBarsVertical = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OISearchScope (Type : Enum)</i>	00	02	03	07 *
- Const olSearchScopeAllFolders = 1 (&H1) As Long	Non	Non	Non	
- Const olSearchScopeCurrentFolder = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OISensitivity (Type : Enum)</i>	00	02	03	07 *
- Const olConfidential = 3 (&H3) As Long				
- Const olNormal = 0 (&H0) As Long				
- Const olPersonal = 1 (&H1) As Long				
- Const olPrivate = 2 (&H2) As Long				
<i>Classe de membres : OISharingMsgType (Type : Enum)</i>	00	02	03	07 *
- Const olSharingMsgTypeInvite = 2 (&H2) As Long	Non	Non	Non	
- Const olSharingMsgTypeInviteAndRequest = 3 (&H3) As Long	Non	Non	Non	
- Const olSharingMsgTypeRequest = 1 (&H1) As Long	Non	Non	Non	
- Const olSharingMsgTypeResponseAllow = 4 (&H4) As Long	Non	Non	Non	
- Const olSharingMsgTypeResponseDeny = 5 (&H5) As Long	Non	Non	Non	
- Const olSharingMsgTypeUnknown = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OISharingProvider (Type : Enum)</i>	00	02	03	07 *
- Const olProviderExchange = 1 (&H1) As Long	Non	Non	Non	
- Const olProviderlCal = 4 (&H4) As Long	Non	Non	Non	
- Const olProviderPubCal = 3 (&H3) As Long	Non	Non	Non	
- Const olProviderRSS = 6 (&H6) As Long	Non	Non	Non	
- Const olProviderSharePoint = 5 (&H5) As Long	Non	Non	Non	
- Const olProviderUnknown = 0 (&H0) As Long	Non	Non	Non	
- Const olProviderWebCal = 2 (&H2) As Long	Non	Non	Non	
<i>Classe de membres : OIShiftState (Type : Enum)</i>	00	02	03	07 *
- Const olShiftStateAltMask = 4 (&H4) As Long	Non	Non	Non	
- Const olShiftStateCtrlMask = 2 (&H2) As Long	Non	Non	Non	
- Const olShiftStateShiftMask = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OIShowItemCount (Type : Enum)</i>	00	02	03	07 *
- Const olNoItemCount = 0 (&H0) As Long	Non	Non		
- Const olShowTotalItemCount = 2 (&H2) As Long	Non	Non		
- Const olShowUnreadItemCount = 1 (&H1) As Long	Non	Non		
<i>Classe de membres : OISortOrder (Type : Enum)</i>	00	02	03	07 *
- Const olAscending = 1 (&H1) As Long				
- Const olDescending = 2 (&H2) As Long				
- Const olSortNone = 0 (&H0) As Long				

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : OISpecialFolders (Type : Enum)</b>	00	02	03	07 *
- Const olSpecialFolderAllTasks = 0 (&H0) As Long	Non	Non	Non	
- Const olSpecialFolderReminders = 1 (&H1) As Long	Non	Non	Non	
<b>Classe de membres : OIStorageIdentifierType (Type : Enum)</b>	00	02	03	07 *
- Const olIdentifyByEntryID = 1 (&H1) As Long	Non	Non	Non	
- Const olIdentifyByMessageClass = 2 (&H2) As Long	Non	Non	Non	
- Const olIdentifyBySubject = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OIStoreType (Type : Enum)</b>	00	02	03	07 *
- Const olStoreANSI = 3 (&H3) As Long	Non	Non		
- Const olStoreDefault = 1 (&H1) As Long	Non	Non		
- Const olStoreUnicode = 2 (&H2) As Long	Non	Non		
<b>Classe de membres : OISyncState (Type : Enum)</b>	00	02	03	07 *
- Const olSyncStarted = 1 (&H1) As Long				
- Const olSyncStopped = 0 (&H0) As Long				
<b>Classe de membres : OITableContents (Type : Enum)</b>	00	02	03	07 *
- Const olHiddenItems = 1 (&H1) As Long	Non	Non	Non	
- Const olUserItems = 0 (&H0) As Long	Non	Non	Non	
<b>Classe de membres : OITaskDelegationState (Type : Enum)</b>	00	02	03	07 *
- Const olTaskDelegationAccepted = 2 (&H2) As Long				
- Const olTaskDelegationDeclined = 3 (&H3) As Long				
- Const olTaskDelegationUnknown = 1 (&H1) As Long				
- Const olTaskNotDelegated = 0 (&H0) As Long				
<b>Classe de membres : OITaskOwnership (Type : Enum)</b>	00	02	03	07 *
- Const olDelegatedTask = 1 (&H1) As Long				
- Const olNewTask = 0 (&H0) As Long				
- Const olOwnTask = 2 (&H2) As Long				
<b>Classe de membres : OITaskRecipientType (Type : Enum)</b>	00	02	03	07 *
- Const olFinalStatus = 3 (&H3) As Long				
- Const olUpdate = 2 (&H2) As Long				
<b>Classe de membres : OITaskResponse (Type : Enum)</b>	00	02	03	07 *
- Const olTaskAccept = 2 (&H2) As Long				
- Const olTaskAssign = 1 (&H1) As Long				
- Const olTaskDecline = 3 (&H3) As Long				
- Const olTaskSimple = 0 (&H0) As Long				
<b>Classe de membres : OITaskStatus (Type : Enum)</b>	00	02	03	07 *
- Const olTaskComplete = 2 (&H2) As Long				
- Const olTaskDeferred = 4 (&H4) As Long				
- Const olTaskInProgress = 1 (&H1) As Long				
- Const olTaskNotStarted = 0 (&H0) As Long				
- Const olTaskWaiting = 3 (&H3) As Long				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : OITextAlign (Type : Enum)</i>	00	02	03	07 *
Const olTextAlignCenter = 2 (&H2) As Long	Non	Non	Non	
Const olTextAlignLeft = 1 (&H1) As Long	Non	Non	Non	
Const olTextAlignRight = 3 (&H3) As Long	Non	Non	Non	
<i>Classe de membres : OITimelineViewMode (Type : Enum)</i>	00	02	03	07 *
Const olTimelineViewDay = 0 (&H0) As Long	Non	Non	Non	
Const olTimelineViewMonth = 2 (&H2) As Long	Non	Non	Non	
Const olTimelineViewWeek = 1 (&H1) As Long	Non	Non	Non	
<i>Classe de membres : OITimeStyle (Type : Enum)</i>	00	02	03	07 *
Const olTimeStyleShortDuration = 4 (&H4) As Long	Non	Non	Non	
Const olTimeStyleTimeDuration = 1 (&H1) As Long	Non	Non	Non	
Const olTimeStyleTimeOnly = 0 (&H0) As Long	Non	Non	Non	
<i>Classe de membres : OITrackingStatus (Type : Enum)</i>	00	02	03	07 *
Const olTrackingDelivered = 1 (&H1) As Long				
Const olTrackingNone = 0 (&H0) As Long				
Const olTrackingNotDelivered = 2 (&H2) As Long				
Const olTrackingNotRead = 3 (&H3) As Long				
Const olTrackingRead = 6 (&H6) As Long				
Const olTrackingRecallFailure = 4 (&H4) As Long				
Const olTrackingRecallSuccess = 5 (&H5) As Long				
Const olTrackingReplied = 7 (&H7) As Long				
<i>Classe de membres : OIUserPropertyType (Type : Enum)</i>	00	02	03	07 *
Const olCombination = 19 (&H13) As Long				
Const olCurrency = 14 (&HE) As Long				
Const olDateTime = 5 (&H5) As Long				
Const olDuration = 7 (&H7) As Long				
Const olEnumeration = 21 (&H15) As Long	Non	Non	Non	
Const olFormula = 18 (&H12) As Long				
Const olInteger = 20 (&H14) As Long	Non	Non	Non	
Const olKeywords = 11 (&HB) As Long				
Const olNumber = 3 (&H3) As Long				
Const olOutlookInternal = 0 (&H0) As Long	Non			
Const olPercent = 12 (&HC) As Long				
Const olSmartFrom = 22 (&H16) As Long	Non	Non	Non	
Const olText = 1 (&H1) As Long				
Const olYesNo = 6 (&H6) As Long				
<i>Classe de membres : OIVerticalLayout (Type : Enum)</i>	00	02	03	07 *
Const olVerticalLayoutAlignBottom = 2 (&H2) As Long	Non	Non	Non	
Const olVerticalLayoutAlignMiddle = 1 (&H1) As Long	Non	Non	Non	
Const olVerticalLayoutAlignTop = 0 (&H0) As Long	Non	Non	Non	
Const olVerticalLayoutGrow = 3 (&H3) As Long	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : <b>OlViewSaveOption (Type : Enum)</b></i>	00	02	03	07 *
- Const olViewSaveOptionAllFoldersOfType = 2 (&H2) As Long	Non			
- Const olViewSaveOptionThisFolderEveryone = 0 (&H0) As Long	Non			
- Const olViewSaveOptionThisFolderOnlyMe = 1 (&H1) As Long	Non			
<i>Classe de membres : <b>OlViewType (Type : Enum)</b></i>	00	02	03	07 *
- Const olBusinessCardView = 5 (&H5) As Long	Non	Non	Non	
- Const olCalendarView = 2 (&H2) As Long	Non			
- Const olCardView = 1 (&H1) As Long	Non			
- Const olDailyTaskListView = 6 (&H6) As Long	Non	Non	Non	
- Const olIconView = 3 (&H3) As Long	Non			
- Const olTableView = 0 (&H0) As Long	Non			
- Const olTimelineView = 4 (&H4) As Long	Non			
<i>Classe de membres : <b>OlWindowState (Type : Enum)</b></i>	00	02	03	07 *
- Const olMaximized = 0 (&H0) As Long				
- Const olMinimized = 1 (&H1) As Long				
- Const olNormalWindow = 2 (&H2) As Long				
<i>Classe de membres : <b>OrderField (Type : Classe)</b></i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let IsDescending As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get ViewXMLSchemaName As String	Non	Non	Non	
<i>Classe de membres : <b>OrderFields (Type : Classe)</b></i>	00	02	03	07 *
- Function Add (PropertyName As String, Optional IsDescending As Variant) As OrderField	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Insert (PropertyName As String, Index As Variant, Optional IsDescending As Variant) As OrderField	Non	Non	Non	
- Function Item (Index As Variant) As OrderField	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Sub RemoveAll ()	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : <b>OutlookBarGroup (Type : Dispatch)</b></i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
- Property Get Shortcuts As OutlookBarShortcuts				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres</i> : OutlookBarGroup (Type : Dispatch)	00	02	03	07 *
- Property Get/Let ViewType As OIOutlookBarViewType				
<i>Classe de membres</i> : OutlookBarGroups (Type : Classe)	00	02	03	07 *
- Function Add (Name As String, Optional Index As Variant) As OutlookBarGroup				
- Property Get Application As Application				
- Event BeforeGroupAdd (Cancel As Boolean)				
- Event BeforeGroupRemove (Group As OutlookBarGroup, Cancel As Boolean)				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Event GroupAdd (NewGroup As OutlookBarGroup)				
- Function Item (Index As Variant) As OutlookBarGroup				
- Property Get Parent As Object				
- Sub Remove (Index As Variant)				
- Property Get Session As NameSpace				
<i>Classe de membres</i> : OutlookBarGroupsEvents (Type : Dispatch)	00	02	03	07 *
- Event BeforeGroupAdd (Cancel As Boolean)				
- Event BeforeGroupRemove (Group As OutlookBarGroup, Cancel As Boolean)				
- Event GroupAdd (NewGroup As OutlookBarGroup)				
<i>Classe de membres</i> : OutlookBarPane (Type : Classe)	00	02	03	07 *
- Property Get Application As Application				
- Event BeforeGroupSwitch (ToGroup As OutlookBarGroup, Cancel As Boolean)				Mask
- Event BeforeNavigate (Shortcut As OutlookBarShortcut, Cancel As Boolean)				
- Property Get Class As OIObjectClass				
- Property Get Contents As OutlookBarStorage				
- Property Get/Set CurrentGroup As OutlookBarGroup				Mask
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
- Property Get/Let Visible As Boolean				
<i>Classe de membres</i> : OutlookBarPaneEvents (Type : Dispatch)	00	02	03	07 *
- Event BeforeGroupSwitch (ToGroup As OutlookBarGroup, Cancel As Boolean)				Mask
- Event BeforeNavigate (Shortcut As OutlookBarShortcut, Cancel As Boolean)				
<i>Classe de membres</i> : OutlookBarShortcut (Type : Dispatch)	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get/Let Name As String				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
- Sub SetIcon (Icon As Variant)	Non			
- Property Get Target As Variant				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : OutlookBarShortcuts (Type : Classe)</i>	00	02	03	07 *
- Function Add (Target As Variant, Name As String, Optional Index As Variant) As OutlookBarShortcut				
- Property Get Application As Application				
- Event BeforeShortcutAdd (Cancel As Boolean)				
- Event BeforeShortcutRemove (Shortcut As OutlookBarShortcut, Cancel As Boolean)				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As OutlookBarShortcut				
- Property Get Parent As Object				
- Sub Remove (Index As Variant)				
- Property Get Session As NameSpace				
- Event ShortcutAdd (NewShortcut As OutlookBarShortcut)				
<i>Classe de membres : OutlookBarShortcutsEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event BeforeShortcutAdd (Cancel As Boolean)				
- Event BeforeShortcutRemove (Shortcut As OutlookBarShortcut, Cancel As Boolean)				
- Event ShortcutAdd (NewShortcut As OutlookBarShortcut)				
<i>Classe de membres : OutlookBarStorage (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Groups As OutlookBarGroups				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : Pages (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Optional Name As Variant) As Object				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Object				
- Property Get Parent As Object				
- Sub Remove (Index As Long)				
- Property Get Session As NameSpace				
<i>Classe de membres : Panes (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Object				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : PlaySoundRuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	



## Classes et membres de la référence **OUTLOOK**

<i>Classe de membres : <b>PlaySoundRuleAction</b> (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get/Let FilePath As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : <b>PostItem</b> (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let BodyFormat As OIBodyFormat	Non			
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Sub ClearConversationIndex ()				
- Sub ClearTaskFlag ()	Non	Non	Non	
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get/Let ExpiryTime As Date				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : PostItem (Type : Classe)</i>	00	02	03	07 *
- Function Forward () As MailItem				
- Property Get GetInspector As Inspector				
- Property Get/Let HTMLBody As String				
- Property Get/Let Importance As OIImportance				
- Property Get/Let InternetCodepage As Long	Non			
- Property Get IsConflict As Boolean	Non			
- Property Get IsMarkedAsTask As Boolean	Non	Non	Non	
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Sub MarkAsTask (MarkInterval As OIMarkInterval)	Non	Non	Non	
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub Post ()				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Property Get ReceivedTime As Date				
- Property Get/Let ReminderOverrideDefault As Boolean	Non	Non	Non	
- Property Get/Let ReminderPlaySound As Boolean	Non	Non	Non	
- Property Get/Let ReminderSet As Boolean	Non	Non	Non	
- Property Get/Let ReminderSoundFile As String	Non	Non	Non	
- Property Get/Let ReminderTime As Date	Non	Non	Non	
- Event Reply (Response As Object, Cancel As Boolean)				
- Function Reply () As MailItem				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get SenderEmailAddress As String	Non	Non		
- Property Get SenderEmailType As String	Non	Non		
- Property Get SenderName As String				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get SentOn As Date				
- Property Get Session As NameSpace				

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : PostItem (Type : Classe)</i>	00	02	03	07 *
- Function SetACLs () As Boolean	Non	Mask	Mask	Mask
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Property Get/Let TaskCompletedDate As Date	Non	Non	Non	
- Property Get/Let TaskDueDate As Date	Non	Non	Non	
- Property Get/Let TaskStartDate As Date	Non	Non	Non	
- Property Get/Let TaskSubject As String	Non	Non	Non	
- Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : PropertyAccessor (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Function BinaryToString (Value As Variant) As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function DeleteProperties (SchemaNames As Variant) As Variant	Non	Non	Non	
- Sub DeleteProperty (SchemaName As String)	Non	Non	Non	
- Function GetProperties (SchemaNames As Variant) As Variant	Non	Non	Non	
- Function GetProperty (SchemaName As String) As Variant	Non	Non	Non	
- Function LocalTimeToUTC (Value As Date) As Date	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Function SetProperty (SchemaNames As Variant, Values As Variant) As Variant	Non	Non	Non	
- Sub SetProperty (SchemaName As String, Value As Variant)	Non	Non	Non	
- Function StringToBinary (Value As String) As Variant	Non	Non	Non	
- Function UTCToLocalTime (Value As Date) As Date	Non	Non	Non	

<i>Classe de membres : PropertyPages (Type : Dispatch)</i>	00	02	03	07 *
- Sub Add (Page As Variant, Title As String)				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Object				
- Property Get Parent As Object				
- Sub Remove (Index As Variant)				
- Property Get Session As NameSpace				

<i>Classe de membres : PropertyPageSite (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Sub OnStatusChange ()				
- Property Get Parent As Object				
- Property Get Session As NameSpace				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres</i> : <b>Recipient (Type : Dispatch)</b>	00	02	03	07 *
- Property Get Address As String				
- Property Get/Set AddressEntry As AddressEntry				
- Property Get Application As Application				
- Property Get/Let AutoResponse As String				
- Property Get Class As OIObjectClass				
- Sub Delete ()				
- Property Get DisplayType As OIDisplayType				
- Property Get EntryID As String				
- Function FreeBusy (Start As Date, MinPerChar As Long, Optional CompleteFormat As Variant) As String				
- Property Get Index As Long				
- Property Get MeetingResponseStatus As OIResponseStatus				
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Function Resolve () As Boolean				
- Property Get Resolved As Boolean				
- Property Get Session As NameSpace				
- Property Get/Let TrackingStatus As OITrackingStatus				
- Property Get/Let TrackingStatusTime As Date				
- Property Get/Let Type As Long				
<i>Classe de membres</i> : <b>Recipients (Type : Dispatch)</b>	00	02	03	07 *
- Function Add (Name As String) As Recipient				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Recipient				
- Property Get Parent As Object				
- Sub Remove (Index As Long)				
- Function ResolveAll () As Boolean				
- Property Get Session As NameSpace				
<i>Classe de membres</i> : <b>RecurrencePattern (Type : Dispatch)</b>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get/Let DayOfMonth As Long				
- Property Get/Let DayOfWeekMask As OIDaysOfWeek				
- Property Get/Let Duration As Long				
- Property Get/Let EndTime As Date				
- Property Get Exceptions As Exceptions				
- Function GetOccurrence (StartDate As Date) As AppointmentItem				
- Property Get/Let Instance As Long				
- Property Get/Let Interval As Long				
- Property Get/Let MonthOfYear As Long				
- Property Get/Let NoEndDate As Boolean				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : RecurrencePattern (Type : Dispatch)</i>	00	02	03	07 *
- Property Get/Let Occurrences As Long				
- Property Get Parent As Object				
- Property Get/Let PatternEndDate As Date				
- Property Get/Let PatternStartDate As Date				
- Property Get/Let RecurrenceType As OIRecurrenceType				
- Property Get/Let Regenerate As Boolean				
- Property Get Session As NameSpace				
- Property Get/Let StartTime As Date				
<i>Classe de membres : Reminder (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Caption As String	Non			
- Property Get Class As OIObjectClass	Non			
- Sub Dismiss ()	Non			
- Property Get IsVisible As Boolean	Non			
- Property Get Item As Object	Non			
- Property Get NextReminderDate As Date	Non			
- Property Get OriginalReminderDate As Date	Non			
- Property Get Parent As Object	Non			
- Property Get Session As NameSpace	Non			
- Sub Snooze (Optional SnoozeTime As Variant)	Non			
<i>Classe de membres : ReminderCollectionEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event BeforeReminderShow (Cancel As Boolean)	Non			
- Event ReminderAdd (ReminderObject As Reminder)	Non			
- Event ReminderChange (ReminderObject As Reminder)	Non			
- Event ReminderFire (ReminderObject As Reminder)	Non			
- Event ReminderRemove ()	Non			
- Event Snooze (ReminderObject As Reminder)	Non			
<i>Classe de membres : Reminders (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Event BeforeReminderShow (Cancel As Boolean)	Non			
- Property Get Class As OIObjectClass	Non			
- Property Get Count As Long	Non			
- Function Item (Index As Variant) As Reminder	Non			
- Function _NewEnum () As Unknown	Non	Mask	Mask	Mask
- Property Get Parent As Object	Non			
- Event ReminderAdd (ReminderObject As Reminder)	Non			
- Event ReminderChange (ReminderObject As Reminder)	Non			
- Event ReminderFire (ReminderObject As Reminder)	Non			
- Event ReminderRemove ()	Non			
- Sub Remove (Index As Variant)	Non			
- Property Get Session As NameSpace	Non			
- Event Snooze (ReminderObject As Reminder)	Non			

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : RemoteItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Property Get GetInspector As Inspector				
- Property Get HasAttachment As Boolean				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : RemoteItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChanged (Name As String)				
- Event Read ()				
- Property Get RemoteMessageClass As String				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Property Get TransferSize As Long				
- Property Get TransferTime As Long				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : ReportItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ReportItem (Type : Classe)</i>	00	02	03	07 *
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				



## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : ReportItem (Type : Classe)</i>	00	02	03	07 *
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : Results (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Class As OIObjectClass	Non			
- Property Get Count As Long	Non			
- Property Get/Let DefaultItemType As OIItem Type	Non			
- Function GetFirst () As Object	Non			
- Function GetLast () As Object	Non			
- Function GetNext () As Object	Non			
- Function GetPrevious () As Object	Non			
- Function Item (Index As Variant) As Object	Non			
- Event ItemAdd (Item As Object)	Non			
- Event ItemChange (Item As Object)	Non			
- Event ItemRemove ()	Non			
- Property Get Parent As Object	Non			
- Property Get RawTable As Unknown	Non	Mask	Mask	Mask
- Sub ResetColumns ()	Non			
- Property Get Session As NameSpace	Non			
- Sub SetColumns (Columns As String)	Non			
- Sub Sort (Property As String, Optional Descending As Variant)	Non			

<i>Classe de membres : ResultsEvents (Type : Dispatch)</i>	00	02	03	07 *
- Event ItemAdd (Item As Object)	Non			
- Event ItemChange (Item As Object)	Non			
- Event ItemRemove ()	Non			

<i>Classe de membres : Row (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Function BinaryToString (Index As Variant) As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function GetValues () As Variant	Non	Non	Non	
- Function Item (Index As Variant) As Variant	Non	Non	Non	
- Function LocalTimeToUTC (Index As Variant) As Date	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : Row (Type : Classe)</i>	00	02	03	07 *
- Property Get Session As NameSpace	Non	Non	Non	
- Function UTCToLocalTime (Index As Variant) As Date	Non	Non	Non	
<i>Classe de membres : Rule (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As RuleActions	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Conditions As RuleConditions	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Exceptions As RuleConditions	Non	Non	Non	
- Sub Execute (Optional ShowProgress As Variant, Optional Folder As Variant, Optional IncludeSubfolders As Variant, Optional RuleExecuteOption As Variant)	Non	Non	Non	
- Property Get/Let ExecutionOrder As Long	Non	Non	Non	
- Property Get IsLocalRule As Boolean	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get RuleType As OIRuleType	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : RuleAction (Type : Classe)</i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : RuleActions (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get AssignToCategory As AssignToCategoryRuleAction	Non	Non	Non	
- Property Get CC As SendRuleAction	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ClearCategories As RuleAction	Non	Non	Non	
- Property Get CopyToFolder As MoveOrCopyRuleAction	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Property Get Delete As RuleAction	Non	Non	Non	
- Property Get DeletePermanently As RuleAction	Non	Non	Non	
- Property Get DesktopAlert As RuleAction	Non	Non	Non	
- Property Get Forward As SendRuleAction	Non	Non	Non	
- Property Get ForwardAsAttachment As SendRuleAction	Non	Non	Non	
- Function Item (Index As Long) As RuleAction	Non	Non	Non	
- Property Get MarkAsTask As MarkAsTaskRuleAction	Non	Non	Non	
- Property Get MoveToFolder As MoveOrCopyRuleAction	Non	Non	Non	
- Property Get NewItemAlert As NewItemAlertRuleAction	Non	Non	Non	
- Property Get NotifyDelivery As RuleAction	Non	Non	Non	
- Property Get NotifyRead As RuleAction	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : RuleActions (Type : Classe)</i>	00	02	03	07 *
- Property Get Parent As Object	Non	Non	Non	
- Property Get PlaySound As PlaySoundRuleAction	Non	Non	Non	
- Property Get Redirect As SendRuleAction	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Stop As RuleAction	Non	Non	Non	
<i>Classe de membres : RuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : RuleConditions (Type : Classe)</i>	00	02	03	07 *
- Property Get Account As AccountRuleCondition	Non	Non	Non	
- Property Get AnyCategory As RuleCondition	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Body As TextRuleCondition	Non	Non	Non	
- Property Get BodyOrSubject As TextRuleCondition	Non	Non	Non	
- Property Get Category As CategoryRuleCondition	Non	Non	Non	
- Property Get CC As RuleCondition	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Property Get FormName As FormNameRuleCondition	Non	Non	Non	
- Property Get From As ToOrFromRuleCondition	Non	Non	Non	
- Property Get FromAnyRSSFeed As RuleCondition	Non	Non	Non	
- Property Get FromRssFeed As FromRssFeedRuleCondition	Non	Non	Non	
- Property Get HasAttachment As RuleCondition	Non	Non	Non	
- Property Get Importance As ImportanceRuleCondition	Non	Non	Non	
- Function Item (Index As Long) As RuleCondition	Non	Non	Non	
- Property Get MeetingInviteOrUpdate As RuleCondition	Non	Non	Non	
- Property Get MessageHeader As TextRuleCondition	Non	Non	Non	
- Property Get NotTo As RuleCondition	Non	Non	Non	
- Property Get OnLocalMachine As RuleCondition	Non	Non	Non	
- Property Get OnlyToMe As RuleCondition	Non	Non	Non	
- Property Get OnOtherMachine As RuleCondition	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get RecipientAddress As AddressRuleCondition	Non	Non	Non	
- Property Get SenderAddress As AddressRuleCondition	Non	Non	Non	
- Property Get SenderInAddressList As SenderInAddressListRuleCondition	Non	Non	Non	
- Property Get SentTo As ToOrFromRuleCondition	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Subject As TextRuleCondition	Non	Non	Non	
- Property Get ToMe As RuleCondition	Non	Non	Non	
- Property Get ToOrCc As RuleCondition	Non	Non	Non	

## Classes et membres de la référence OUTLOOK

<i>Classe de membres : Rules (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Create (Name As String, RuleType As OIRuleType) As Rule	Non	Non	Non	
- Property Get/Let IsRssRulesProcessingEnabled As Boolean	Non	Non	Non	
- Function Item (Index As Variant) As Rule	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Sub Save (Optional ShowProgress As Variant)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : Search (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Property Get Class As OIObjectClass	Non			
- Property Get Filter As String	Non			
- Function GetTable () As Table	Non	Non	Non	
- Property Get IsSynchronous As Boolean	Non			
- Property Get Parent As Object	Non			
- Property Get Results As Results	Non			
- Function Save (Name As String) As MAPIFolder	Non	Non		
- Property Get Scope As String	Non			
- Property Get SearchSubFolders As Boolean	Non			
- Property Get Session As NameSpace	Non			
- Sub Stop ()	Non			
- Property Get Tag As String	Non			
<i>Classe de membres : Selection (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As Object				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
<i>Classe de membres : SelectNamesDialog (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let AllowMultipleSelection As Boolean	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get/Let BccLabel As String	Non	Non	Non	
- Property Get/Let Caption As String	Non	Non	Non	
- Property Get/Let CcLabel As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Display () As Boolean	Non	Non	Non	
- Property Get/Let ForceResolution As Boolean	Non	Non	Non	
- Property Get/Let InitialAddressList As AddressList	Non	Non	Non	
- Property Get/Let NumberOfRecipientSelectors As OIRecipientSelectors	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : <b>SelectNamesDialog (Type : Classe)</b></i>	00	02	03	07 *
- Property Get/Let Recipients As Recipients	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Sub SetDefaultDisplayMode (defaultMode As OIDefaultSelectNamesDisplayMode)	Non	Non	Non	
- Property Get/Let ShowOnlyInitialAddressList As Boolean	Non	Non	Non	
- Property Get/Let ToLabel As String	Non	Non	Non	
<i>Classe de membres : <b>SenderInAddressListRuleCondition (Type : Classe)</b></i>	00	02	03	07 *
- Property Get/Let AddressList As AddressList	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : <b>SendRuleAction (Type : Classe)</b></i>	00	02	03	07 *
- Property Get ActionType As OIRuleActionType	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Recipients As Recipients	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
<i>Classe de membres : <b>SharingItem (Type : Classe)</b></i>	00	02	03	07 *
- Property Get Actions As Actions	Non	Non	Non	
- Sub AddBusinessCard (contact As ContactItem)	Non	Non	Non	
- Sub Allow ()	Non	Non	Non	
- Property Get/Let AllowWriteAccess As Boolean	Non	Non	Non	
- Property Get/Let AlternateRecipientAllowed As Boolean	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Event AttachmentAdd (Attachment As Attachment)	Non	Non	Non	
- Event AttachmentRead (Attachment As Attachment)	Non	Non	Non	
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments	Non	Non	Non	
- Property Get/Let AutoForwarded As Boolean	Non	Non	Non	
- Property Get/Let BCC As String	Non	Non	Non	
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)	Non	Non	Non	
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : SharingItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let BillingInformation As String	Non	Non	Non	
- Property Get/Let Body As String	Non	Non	Non	
- Property Get/Let BodyFormat As OIBodyFormat	Non	Non	Non	
- Property Get/Let Categories As String	Non	Non	Non	
- Property Get/Let CC As String	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Sub ClearConversationIndex ()	Non	Non	Non	
- Sub ClearTaskFlag ()	Non	Non	Non	
- Event Close (Cancel As Boolean)	Non	Non	Non	
- Sub Close (SaveMode As OIInspectorClose)	Non	Non	Non	
- Property Get/Let Companies As String	Non	Non	Non	
- Property Get Conflicts As Conflicts	Non	Non	Non	
- Property Get ConversationIndex As String	Non	Non	Non	
- Property Get ConversationTopic As String	Non	Non	Non	
- Function Copy () As Object	Non	Non	Non	
- Property Get CreationTime As Date	Non	Non	Non	
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)	Non	Non	Non	
- Event CustomPropertyChange (Name As String)	Non	Non	Non	
- Property Get/Let DeferredDeliveryTime As Date	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let DeleteAfterSubmit As Boolean	Non	Non	Non	
- Function Deny () As SharingItem	Non	Non	Non	
- Sub Display (Optional Modal As Variant)	Non	Non	Non	
- Property Get DownloadState As OIDownloadState	Non	Non	Non	
- Property Get/Let EnableSharedAttachments As Boolean	Non	Non	Non	Mask
- Property Get EntryID As String	Non	Non	Non	
- Property Get/Let ExpiryTime As Date	Non	Non	Non	Mask
- Property Get/Let FlagDueBy As Date	Non	Non	Non	Mask
- Property Get/Let FlagIcon As OIFlagIcon	Non	Non	Non	Mask
- Property Get/Let FlagRequest As String	Non	Non	Non	
- Property Get/Let FlagStatus As OIFlagStatus	Non	Non	Non	Mask
- Property Get FormDescription As FormDescription	Non	Non	Non	
- Event Forward (Forward As Object, Cancel As Boolean)	Non	Non	Non	
- Function Forward () As SharingItem	Non	Non	Non	
- Property Get GetInspector As Inspector	Non	Non	Non	
- Property Get/Let HTMLBody As String	Non	Non	Non	
- Property Get/Let Importance As OIImportance	Non	Non	Non	
- Property Get/Let InternetCodepage As Long	Non	Non	Non	
- Property Get IsConflict As Boolean	Non	Non	Non	
- Property Get IsMarkedAsTask As Boolean	Non	Non	Non	
- Property Get ItemProperties As ItemProperties	Non	Non	Non	
- Property Get LastModificationTime As Date	Non	Non	Non	
- Property Get MAPIOBJECT As Unknown	Non	Non	Non	Mask
- Sub MarkAsTask (MarkInterval As OIMarkInterval)	Non	Non	Non	
- Property Get/Let MarkForDownload As OIRemoteStatus	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : SharingItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let MessageClass As String	Non	Non	Non	
- Property Get/Let Mileage As String	Non	Non	Non	
- Function Move (DestFldr As MAPIFolder) As Object	Non	Non	Non	
- Property Get/Let NoAging As Boolean	Non	Non	Non	
- Event Open (Cancel As Boolean)	Non	Non	Non	
- Function OpenSharedFolder () As MAPIFolder	Non	Non	Non	
- Property Get/Let OriginatorDeliveryReportRequested As Boolean	Non	Non	Non	
- Property Get OutlookInternalVersion As Long	Non	Non	Non	
- Property Get OutlookVersion As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Permission As OIPermission	Non	Non	Non	
- Property Get/Let PermissionService As OIPermissionService	Non	Non	Non	
- Sub PrintOut ()	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)	Non	Non	Non	
- Event Read ()	Non	Non	Non	
- Property Get/Let ReadReceiptRequested As Boolean	Non	Non	Non	
- Property Get ReceivedByEntryID As String	Non	Non	Non	
- Property Get ReceivedByName As String	Non	Non	Non	
- Property Get ReceivedOnBehalfOfEntryID As String	Non	Non	Non	
- Property Get ReceivedOnBehalfOfName As String	Non	Non	Non	
- Property Get ReceivedTime As Date	Non	Non	Non	
- Property Get/Let RecipientReassignmentProhibited As Boolean	Non	Non	Non	
- Property Get Recipients As Recipients	Non	Non	Non	
- Property Get/Let ReminderOverrideDefault As Boolean	Non	Non	Non	
- Property Get/Let ReminderPlaySound As Boolean	Non	Non	Non	
- Property Get/Let ReminderSet As Boolean	Non	Non	Non	
- Property Get/Let ReminderSoundFile As String	Non	Non	Non	
- Property Get/Let ReminderTime As Date	Non	Non	Non	
- Property Get RemoteID As String	Non	Non	Non	
- Property Get RemoteName As String	Non	Non	Non	
- Property Get RemotePath As String	Non	Non	Non	
- Property Get/Let RemoteStatus As OIRemoteStatus	Non	Non	Non	
- Event Reply (Response As Object, Cancel As Boolean)	Non	Non	Non	
- Function Reply () As MailItem	Non	Non	Non	
- Event ReplyAll (Response As Object, Cancel As Boolean)	Non	Non	Non	
- Function ReplyAll () As MailItem	Non	Non	Non	
- Property Get ReplyRecipientNames As String	Non	Non	Non	
- Property Get ReplyRecipients As Recipients	Non	Non	Non	
- Property Get RequestedFolder As OIDefaultFolders	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Sub SaveAs (Path As String, Optional Type As Variant)	Non	Non	Non	
- Property Get Saved As Boolean	Non	Non	Non	
- Property Get/Set SaveSentMessageFolder As MAPIFolder	Non	Non	Non	
- Event Send (Cancel As Boolean)	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : SharingItem (Type : Classe)</i>	00	02	03	07 *
- Sub Send ()	Non	Non	Non	
- Property Get SenderEmailAddress As String	Non	Non	Non	
- Property Get SenderEmailType As String	Non	Non	Non	
- Property Get SenderName As String	Non	Non	Non	
- Property Get/Let SendUsingAccount As Account	Non	Non	Non	
- Property Get/Let Sensitivity As OISensitivity	Non	Non	Non	
- Property Get Sent As Boolean	Non	Non	Non	
- Property Get SentOn As Date	Non	Non	Non	
- Property Get/Let SentOnBehalfOfName As String	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get SharingProvider As OISharingProvider	Non	Non	Non	
- Property Get SharingProviderGuid As String	Non	Non	Non	
- Sub ShowCategoriesDialog ()	Non	Non	Non	
- Property Get Size As Long	Non	Non	Non	
- Property Get/Let Subject As String	Non	Non	Non	
- Property Get Submitted As Boolean	Non	Non	Non	
- Property Get/Let TaskCompletedDate As Date	Non	Non	Non	
- Property Get/Let TaskDueDate As Date	Non	Non	Non	
- Property Get/Let TaskStartDate As Date	Non	Non	Non	
- Property Get/Let TaskSubject As String	Non	Non	Non	
- Property Get/Let To As String	Non	Non	Non	
- Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
- Property Get/Let Type As OISharingMsgType	Non	Non	Non	
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean	Non	Non	Non	
- Property Get UserProperties As UserProperties	Non	Non	Non	
- Event Write (Cancel As Boolean)	Non	Non	Non	
<i>Classe de membres : StorageItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Attachments As Attachments	Non	Non	Non	
- Property Get/Let Body As String	Non	Non	Non	
- Property Get Class As IOObjectClass	Non	Non	Non	
- Property Get CreationTime As Date	Non	Non	Non	
- Property Get/Let Creator As String	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get EntryID As String	Non	Non	Non	
- Property Get LastModificationTime As Date	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Size As Long	Non	Non	Non	
- Property Get/Let Subject As String	Non	Non	Non	
- Property Get UserProperties As UserProperties	Non	Non	Non	



## Classes et membres de la référence OUTLOOK

<b>Classe de membres : Store (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get DisplayName As String	Non	Non	Non	
- Property Get ExchangeStoreType As OIExchangeStoreType	Non	Non	Non	
- Property Get FilePath As String	Non	Non	Non	
- Function GetRootFolder () As MAPIFolder	Non	Non	Non	
- Function GetRules () As Rules	Non	Non	Non	
- Function GetSearchFolders () As Folders	Non	Non	Non	
- Function GetSpecialFolder (FolderType As OISpecialFolders) As MAPIFolder	Non	Non	Non	
- Property Get IsCachedExchange As Boolean	Non	Non	Non	
- Property Get IsDataFileStore As Boolean	Non	Non	Non	
- Property Get IsInstantSearchEnabled As Boolean	Non	Non	Non	
- Property Get IsOpen As Boolean	Non	Non	Non	
- Property Get MAPIOBJECT As Unknown	Non	Non	Non	Mask
- Property Get Parent As Object	Non	Non	Non	
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get StoreID As String	Non	Non	Non	

<b>Classe de membres : Stores (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application	Non	Non	Non	
- Event BeforeStoreRemove (Store As Store, Cancel As Boolean)	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Item (Index As Variant) As Store	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Event StoreAdd (Store As Store)	Non	Non	Non	

<b>Classe de membres : SyncObject (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Name As String				
- Event OnError (Code As Long, Description As String)				
- Property Get Parent As Object				
- Event Progress (State As OISyncState, Description As String, Value As Long, Max As Long)				
- Property Get Session As NameSpace				
- Sub Start ()				
- Sub Stop ()				
- Event SyncEnd ()				
- Event SyncStart ()				

<b>Classe de membres : SyncObjectEvents (Type : Dispatch)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Event OnError (Code As Long, Description As String)				
- Event Progress (State As OISyncState, Description As String, Value As Long, Max As Long)				

## *Classes et membres de la référence OUTLOOK*

### *Classe de membres : SyncObjectEvents (Type : Dispatch)* 00 02 03 07 \*

- Event SyncEnd ()				
- Event SyncStart ()				

### *Classe de membres : SyncObjects (Type : Dispatch)* 00 02 03 07 \*

- Property Get AppFolders As SyncObject	Non			
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Property Get Count As Long				
- Function Item (Index As Variant) As SyncObject				
- Property Get Parent As Object				
- Property Get Session As NameSpace				

### *Classe de membres : Table (Type : Classe)* 00 02 03 07 \*

- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Columns As Columns	Non	Non	Non	
- Property Get EndOfTable As Boolean	Non	Non	Non	
- Function FindNextRow () As Row	Non	Non	Non	
- Function FindRow (Filter As String) As Row	Non	Non	Non	
- Function GetArray (MaxRows As Long) As Variant	Non	Non	Non	
- Function GetNextRow () As Row	Non	Non	Non	
- Function GetRowCount () As Long	Non	Non	Non	
- Sub MoveToStart ()	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Function Restrict (Filter As String) As Table	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Sub Sort (SortProperty As String, Optional Descending As Variant)	Non	Non	Non	

### *Classe de membres : TableView (Type : Classe)* 00 02 03 07 \*

- Property Get/Let AllowInCellEditing As Boolean	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Sub Apply ()	Non	Non	Non	
- Property Get AutoFormatRules As AutoFormatRules	Non	Non	Non	
- Property Get/Let AutomaticColumnSizing As Boolean	Non	Non	Non	
- Property Get/Let AutomaticGrouping As Boolean	Non	Non	Non	
- Property Get/Let AutoPreview As OIAutoPreview	Non	Non	Non	
- Property Get AutoPreviewFont As ViewFont	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ColumnFont As ViewFont	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Property Get/Let DefaultExpandCollapseSetting As OIDefaultExpandCollapseSetting	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get/Let GridLineStyle As OIGridLineStyle	Non	Non	Non	
- Property Get GroupByFields As OrderFields	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TableView (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let HideReadingPaneHeaderInfo As Boolean	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get/Let MaxLinesInMultiLineView As Long	Non	Non	Non	
- Property Get/Let MultiLine As OIMultiLine	Non	Non	Non	
- Property Get/Let MultiLineWidth As Long	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Property Get RowFont As ViewFont	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let ShowItemsInGroups As Boolean	Non	Non	Non	
- Property Get/Let ShowNewItemRow As Boolean	Non	Non	Non	
- Property Get/Let ShowReadingPane As Boolean	Non	Non	Non	
- Property Get/Let ShowUnreadAndFlaggedMessages As Boolean	Non	Non	Non	
- Property Get SortFields As OrderFields	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get ViewFields As ViewFields	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	

<i>Classe de membres : TaskItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get/Let ActualWork As Long				
- Property Get Application As Application				
- Function Assign () As TaskItem				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Sub CancelResponseState ()				
- Property Get/Let CardData As String				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskItem (Type : Classe)</i>	00	02	03	07 *
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Sub ClearRecurrencePattern ()				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get/Let Complete As Boolean				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get/Let ContactNames As String				
- Property Get/Let Contacts As String		Mask	Mask	Mask
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Property Get/Let DateCompleted As Date				
- Property Get DelegationState As OITaskDelegationState				
- Property Get Delegator As String				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get/Let DueDate As Date				
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Property Get GetInspector As Inspector				
- Function GetRecurrencePattern () As RecurrencePattern				
- Property Get/Let Importance As OIImportance				
- Property Get/Let InternetCodepage As Long	Non			
- Property Get IsConflict As Boolean	Non			
- Property Get IsRecurring As Boolean				
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Sub MarkComplete ()				
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get/Let Ordinal As Long				
- Property Get OutlookInternalVersion As Long				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskItem (Type : Classe)</i>	00	02	03	07 *
- Property Get OutlookVersion As String				
- Property Get/Let Owner As String				
- Property Get Ownership As OITaskOwnership				
- Property Get Parent As Object				
- Property Get/Let PercentComplete As Long				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Property Get Recipients As Recipients				
- Property Get/Let ReminderOverrideDefault As Boolean				
- Property Get/Let ReminderPlaySound As Boolean				
- Property Get/Let ReminderSet As Boolean				
- Property Get/Let ReminderSoundFile As String				
- Property Get/Let ReminderTime As Date				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Function Respond (Response As OITaskResponse, fNoUI As Variant, fAdditionalTextDialog As Variant) As TaskItem				
- Property Get ResponseState As OITaskResponse				
- Property Get/Let Role As String				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Property Get/Let SchedulePlusPriority As String				
- Event Send (Cancel As Boolean)				
- Sub Send ()				
- Property Get/Let SendUsingAccount As Account	Non	Non	Non	
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Function SkipRecurrence () As Boolean				
- Property Get/Let StartDate As Date				
- Property Get/Let Status As OITaskStatus				
- Property Get/Let StatusOnCompletionRecipients As String				
- Function StatusReport () As Object				
- Property Get/Let StatusUpdateRecipients As String				
- Property Get/Let Subject As String				
- Property Get/Let TeamTask As Boolean				
- Property Get/Let ToDoTaskOrdinal As Date	Non	Non	Non	
- Property Get/Let TotalWork As Long				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskItem (Type : Classe)</i>	00	02	03	07 *
- Event Write (Cancel As Boolean)				
<i>Classe de membres : TaskRequestAcceptItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function GetAssociatedTask (AddToTaskList As Boolean) As TaskItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskRequestAcceptItem (Type : Classe)</i>	00	02	03	07 *
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : TaskRequestDeclineItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskRequestDeclineItem (Type : Classe)</i>	00	02	03	07 *
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function GetAssociatedTask (AddToTaskList As Boolean) As TaskItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				



## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskRequestDeclineItem (Type : Classe)</i>	00	02	03	07 *
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<i>Classe de membres : TaskRequestItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskRequestItem (Type : Classe)</i>	00	02	03	07 *
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function GetAssociatedTask (AddToTaskList As Boolean) As TaskItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChange (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				
<i>Classe de membres : TaskRequestUpdateItem (Type : Classe)</i>	00	02	03	07 *
- Property Get Actions As Actions				
- Property Get Application As Application				
- Event AttachmentAdd (Attachment As Attachment)				
- Event AttachmentRead (Attachment As Attachment)				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TaskRequestUpdateItem (Type : Classe)</i>	00	02	03	07 *
- Event AttachmentRemove (Attachment As Attachment)	Non	Non	Non	
- Property Get Attachments As Attachments				
- Property Get AutoResolvedWinner As Boolean	Non	Non		
- Event BeforeAttachmentAdd (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentPreview (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentRead (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAttachmentSave (Attachment As Attachment, Cancel As Boolean)				
- Event BeforeAttachmentWriteToTempFile (Attachment As Attachment, Cancel As Boolean)	Non	Non	Non	
- Event BeforeAutoSave (Cancel As Boolean)	Non	Non	Non	
- Event BeforeCheckNames (Cancel As Boolean)				
- Event BeforeDelete (Item As Object, Cancel As Boolean)	Non			
- Property Get/Let BillingInformation As String				
- Property Get/Let Body As String				
- Property Get/Let Categories As String				
- Property Get Class As OIObjectClass				
- Event Close (Cancel As Boolean)				
- Sub Close (SaveMode As OIInspectorClose)				
- Property Get/Let Companies As String				
- Property Get Conflicts As Conflicts	Non	Non		
- Property Get ConversationIndex As String				
- Property Get ConversationTopic As String				
- Function Copy () As Object				
- Property Get CreationTime As Date				
- Event CustomAction (Action As Object, Response As Object, Cancel As Boolean)				
- Event CustomPropertyChange (Name As String)				
- Sub Delete ()				
- Sub Display (Optional Modal As Variant)				
- Property Get DownloadState As OIDownloadState	Non			
- Property Get EntryID As String				
- Property Get FormDescription As FormDescription				
- Event Forward (Forward As Object, Cancel As Boolean)				
- Function GetAssociatedTask (AddToTaskList As Boolean) As TaskItem				
- Property Get GetInspector As Inspector				
- Property Get/Let Importance As OIImportance				
- Property Get IsConflict As Boolean	Non			
- Property Get ItemProperties As ItemProperties	Non			
- Property Get LastModificationTime As Date				
- Property Get Links As Links				
- Property Get MAPIOBJECT As Unknown	Mask	Mask	Mask	Mask
- Property Get/Let MarkForDownload As OIRemoteStatus	Non			
- Property Get/Let MessageClass As String				
- Property Get/Let Mileage As String				
- Function Move (DestFldr As MAPIFolder) As Object				
- Property Get/Let NoAging As Boolean				

## Classes et membres de la référence OUTLOOK

<b>Classe de membres : TaskRequestUpdateItem (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Event Open (Cancel As Boolean)				
- Property Get OutlookInternalVersion As Long				
- Property Get OutlookVersion As String				
- Property Get Parent As Object				
- Sub PrintOut ()				
- Property Get PropertyAccessor As PropertyAccessor	Non	Non	Non	
- Event PropertyChanged (Name As String)				
- Event Read ()				
- Event Reply (Response As Object, Cancel As Boolean)				
- Event ReplyAll (Response As Object, Cancel As Boolean)				
- Sub Save ()				
- Sub SaveAs (Path As String, Optional Type As Variant)				
- Property Get Saved As Boolean				
- Event Send (Cancel As Boolean)				
- Property Get/Let Sensitivity As OISensitivity				
- Property Get Session As NameSpace				
- Sub ShowCategoriesDialog ()	Non			
- Property Get Size As Long				
- Property Get/Let Subject As String				
- Event Unload ()	Non	Non	Non	
- Property Get/Let UnRead As Boolean				
- Property Get UserProperties As UserProperties				
- Event Write (Cancel As Boolean)				

<b>Classe de membres : TasksModule (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get NavigationGroups As NavigationGroups	Non	Non	Non	
- Property Get NavigationModuleType As OINavigationModuleType	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get/Let Position As Long	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Visible As Boolean	Non	Non	Non	

<b>Classe de membres : TextRuleCondition (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Text As Variant	Non	Non	Non	

<b>Classe de membres : TimelineView (Type : Classe)</b>	<b>00</b>	<b>02</b>	<b>03</b>	<b>07 *</b>
- Property Get Application As Application	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TimelineView (Type : Classe)</i>	00	02	03	07 *
- Sub Apply ()	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non	Non	Non	
- Property Get/Let DefaultExpandCollapseSetting As OIDefaultExpandCollapseSetting	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get/Let EndField As String	Non	Non	Non	
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Non	Non	
- Property Get GroupByFields As OrderFields	Non	Non	Non	
- Property Get ItemFont As ViewFont	Non	Non	Non	
- Property Get/Let Language As String	Non	Non	Non	
- Property Get/Let LockUserChanges As Boolean	Non	Non	Non	
- Property Get LowerScaleFont As ViewFont	Non	Non	Non	
- Property Get/Let MaxLabelWidth As Long	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Reset ()	Non	Non	Non	
- Sub Save ()	Non	Non	Non	
- Property Get SaveOption As OIViewSaveOption	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let ShowLabelWhenViewingByMonth As Boolean	Non	Non	Non	
- Property Get/Let ShowWeekNumbers As Boolean	Non	Non	Non	
- Property Get Standard As Boolean	Non	Non	Non	
- Property Get/Let StartField As String	Non	Non	Non	
- Property Get/Let TimelineViewMode As OITimelineViewMode	Non	Non	Non	
- Property Get UpperScaleFont As ViewFont	Non	Non	Non	
- Property Get ViewType As OIViewType	Non	Non	Non	
- Property Get/Let XML As String	Non	Non	Non	
<i>Classe de membres : TimeZone (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Bias As Long	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get DaylightBias As Long	Non	Non	Non	
- Property Get DaylightDate As Date	Non	Non	Non	
- Property Get DaylightDesignation As String	Non	Non	Non	
- Property Get ID As String	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get StandardBias As Long	Non	Non	Non	
- Property Get StandardDate As Date	Non	Non	Non	
- Property Get StandardDesignation As String	Non	Non	Non	
<i>Classe de membres : TimeZones (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : TimeZones (Type : Classe)</i>	00	02	03	07 *
- Property Get Class As OIObjectClass	Non	Non	Non	
- Function ConvertTime (SourceDateTime As Date, SourceTimeZone As TimeZone, DestinationTimeZone As TimeZone) As Date	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Property Get CurrentTimeZone As TimeZone	Non	Non	Non	
- Function Item (Index As Variant) As TimeZone	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : ToOrFromRuleCondition (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ConditionType As OIRuleConditionType	Non	Non	Non	
- Property Get/Let Enabled As Boolean	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Recipients As Recipients	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : UserDefinedProperties (Type : Classe)</i>	00	02	03	07 *
- Function Add (Name As String, Type As OIUserPropertyType, Optional DisplayFormat As Variant, Optional Formula As Variant) As UserDefinedProperty	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Find (Name As String) As UserDefinedProperty	Non	Non	Non	
- Function Item (Index As Variant) As UserDefinedProperty	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Refresh ()	Non	Non	Non	
- Sub Remove (Index As Long)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

<i>Classe de membres : UserDefinedProperty (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Sub Delete ()	Non	Non	Non	
- Property Get DisplayFormat As Long	Non	Non	Non	
- Property Get Formula As String	Non	Non	Non	
- Property Get Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get Type As OIUserPropertyType	Non	Non	Non	

<i>Classe de membres : UserProperties (Type : Dispatch)</i>	00	02	03	07 *
- Function Add (Name As String, Type As OIUserPropertyType, Optional AddToFolderFields As Variant, Optional DisplayFormat As Variant) As UserProperty				
- Property Get Application As Application				
- Property Get Class As OIObjectClass				

## *Classes et membres de la référence OUTLOOK*

<i>Classe de membres : UserProperties (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Count As Long				
- Function Find (Name As String, Optional Custom As Variant) As UserProperty				
- Function Item (Index As Variant) As UserProperty				
- Property Get Parent As Object				
- Sub Remove (Index As Long)				
- Property Get Session As NameSpace				

<i>Classe de membres : UserProperty (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application				
- Property Get Class As OIObjectClass				
- Sub Delete ()				
- Property Get/Let Formula As String				
- Property Get IsUserProperty As Boolean	Non	Mask	Mask	Mask
- Property Get Name As String				
- Property Get Parent As Object				
- Property Get Session As NameSpace				
- Property Get Type As OIUserPropertyType				
- Property Get/Let ValidationFormula As String				
- Property Get/Let ValidationText As String				
- Property Get/Let Value As Variant				

<i>Classe de membres : View (Type : Dispatch)</i>	00	02	03	07 *
- Property Get Application As Application	Non			
- Sub Apply ()	Non			
- Property Get Class As OIObjectClass	Non			
- Function Copy (Name As String, SaveOption As OIViewSaveOption) As View	Non			
- Sub Delete ()	Non			
- Property Get/Let Filter As String	Non	Non	Non	
- Sub GoToDate (Date As Date)	Non	Mask	Mask	
- Property Get/Let Language As String	Non			
- Property Get/Let LockUserChanges As Boolean	Non			
- Property Get/Let Name As String	Non			
- Property Get Parent As Object	Non			
- Sub Reset ()	Non			
- Sub Save ()	Non			
- Property Get SaveOption As OIViewSaveOption	Non			
- Property Get Session As NameSpace	Non			
- Property Get Standard As Boolean	Non			
- Property Get ViewType As OIViewType	Non			
- Property Get/Let XML As String	Non			

<i>Classe de membres : ViewField (Type : Classe)</i>	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get ColumnFormat As ColumnFormat	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	

## *Classes et membres de la référence OUTLOOK*

### *Classe de membres : ViewField (Type : Classe)*

	00	02	03	07 *
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get ViewXMLSchemaName As String	Non	Non	Non	

### *Classe de membres : ViewFields (Type : Classe)*

	00	02	03	07 *
- Function Add (PropertyName As String) As ViewField	Non	Non	Non	
- Property Get Application As Application	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get Count As Long	Non	Non	Non	
- Function Insert (PropertyName As String, Index As Variant) As ViewField	Non	Non	Non	
- Function Item (Index As Variant) As ViewField	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Sub Remove (Index As Variant)	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	

### *Classe de membres : ViewFont (Type : Classe)*

	00	02	03	07 *
- Property Get Application As Application	Non	Non	Non	
- Property Get/Let Bold As Boolean	Non	Non	Non	
- Property Get Class As OIObjectClass	Non	Non	Non	
- Property Get/Let Color As OIColor	Non	Non	Non	
- Property Get/Let Italic As Boolean	Non	Non	Non	
- Property Get/Let Name As String	Non	Non	Non	
- Property Get Parent As Object	Non	Non	Non	
- Property Get Session As NameSpace	Non	Non	Non	
- Property Get/Let Size As Long	Non	Non	Non	
- Property Get/Let Strikethrough As Boolean	Non	Non	Non	
- Property Get/Let Underline As Boolean	Non	Non	Non	

### *Classe de membres : Views (Type : Classe)*

	00	02	03	07 *
- Function Add (Name As String, ViewType As OIViewType, SaveOption As OIViewSaveOption) As View	Non			
- Property Get Application As Application	Non			
- Property Get Class As OIObjectClass	Non			
- Property Get Count As Long	Non			
- Function Item (Index As Variant) As View	Non			
- Function _NewEnum () As Unknown	Non	Mask	Mask	Mask
- Property Get Parent As Object	Non			
- Sub Remove (Index As Variant)	Non			
- Property Get Session As NameSpace	Non			
- Event ViewAdd (View As View)	Non			
- Event ViewRemove (View As View)	Non			



## *Classes et membres de la référence OUTLOOK*

### \* Légendes

<b>xx.x</b>	Classe de membres présente et non masquée	<b>Mask</b>	Membre masqué
<b>xx.x</b>	Classe de membres masquée	<b>Non</b>	Membre absent
<b>xx.x</b>	Classe de membres absente		